

**Samuel Santos**  
csamuelssm@alu.ufc.br

*UFC*  
*Universidade Federal do Ceará*

December 2024

# Restricting infections on graphs

*Immunization problems*

*Supervised by Ana Karolinnna Maia and Carlos Vinícius G. C. Lima*

Several phenomena happen in a **contagion-like manner**.

- Viruses or bacteria;
- Innovation, (mis-)information, and memes. (Ryan and Gross 1950; Coleman, Katz, and Menzel 1957)


# Modeling Contagion on Graphs: Threshold Model

---

- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.


# Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.




# Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.



# Modeling Contagion on Graphs: Threshold Model


- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:

- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;






# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .
- The diffusion happens in **discrete time steps**.



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .
- The diffusion happens in **discrete time steps**.



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:

- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .
- The diffusion happens in **discrete time steps**.
- Once a vertex is infected, it **stays infected** – we call it a  $t$ -**irreversible process**.




Several computational problems arise from the Threshold Model.

- **Influence Maximization** (IM) (Kempe, Kleinberg, and Tardos 2003). NP-complete.
- **Target Set Selection** (TSS) (Dreyer and Roberts 2009). NP-complete.
- Variations:
  - Directed version;
  - Majority version:  $t(v) = \lceil \frac{d(v)}{2} \rceil \quad \forall v \in V(G)$ ;
  - TSS with maximum activation time (Keiler et al. 2023; Flocchini et al. 2003; Marcilon and Sampaio 2018);
  - TSS with activation time equal to 1 (Araújo and Sampaio 2023);

# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model

Immunization problems:

- Firefighter;






# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model


## Immunization problems:

- Firefighter;
- Influence Immunization Bounding (IIB);
  - A generalization of Firefighter?




First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;
- **Option 2: make the vertex invisible – remove it.**



First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;
- **Option 2: make the vertex invisible – remove it.**




## Remark (Option 2)

In this option, immunized vertices do not infect nor get infected.

# Influence Immunization Bounding

Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;




# Influence Immunization Bounding

Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;

## Remark

Notice that  $S = \{a, e, h\}$  is a *target set* for this graph.




Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;

## Remark

Notice that  $S = \{a, e, h\}$  is a *target set* for this graph.






Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;


## Remark

Notice that  $S = \{a, e, h\}$  is a *target set* for this graph.



Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;
- Naturals  $k$  and  $l$ .




# Influence Immunization Bounding

Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;
- Naturals  $k$  and  $l$ . **Let**  $k = 3$  **and**  $l = 2$ .

We want to find a immunizing set  $Y \subseteq V(G)$  such that:

- $|Y| \leq l$ ; and



Given:


- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;
- Naturals  $k$  and  $l$ . **Let**  $k = 3$  **and**  $l = 2$ .

We want to find a immunizing set  $Y \subseteq V(G)$  such that:

- $|Y| \leq l$ ; and
- By immunizing  $Y$  at time  $\tau = 0$ , the **infection gets restricted to at most  $k$  vertices**.

## Remark

Notice that we must have  $k \geq |S|$ .



*But before we proceed...*

A little of **Parameterized Complexity**.

## Definition

A *parameterized problem* is a pair  $(P, \kappa)$ , such that  $P$  is a decision problem and  $\kappa$  is a parameter for  $P$ .

**p-INDEPENDENT-SET**

*Input:* A graph  $G$  and  $k \in \mathbb{N}$ .

*Question:* Decide whether  $G$  has an independent set of cardinality  $k$ .

**Parameter:**  $k$ .

**Parameters of the problem matter for its tractability.**

Let  $x \in \Sigma^*$  be an instance of a parameterized problem  $(P, \kappa)$ .

## Definition (XP)

$(P, \kappa)$  is **slicewise polynomial** if it admits an algorithm which running time is

$$O(|x|^{\kappa(x)})$$

- **CLIQUE** is in XP parameterized by  $k$ : enumerate all subsets of  $k$  vertices and check if they form a clique.

Let  $x \in \Sigma^*$  be an instance of a parameterized problem  $(P, \kappa)$ .

## Definition (XP)

$(P, \kappa)$  is **slicewise polynomial** if it admits an algorithm which running time is

$$O(|x|^{\kappa(x)})$$

## Definition (FPT)

$(P, \kappa)$  is **fixed-parameter tractable** if it admits an algorithm which running time is

$$O(f(\kappa(x)) \cdot \text{poly}(|x|))$$

- VERTEX COVER is in FPT parameterized by  $k$ .



- The class FPT is the parameterized analogous to the class P;
- The class para-NP is the parameterized analogous to the class NP;

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- ›  $k$ -CLIQUE is the parameterized analogous to 3-SAT;
  - › No one has managed to find a FPT algorithm;
  - › **Hypothesis:  $k$ -Clique is not in FPT.**

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- ›  $k$ -CLIQUE is the parameterized analogous to 3-SAT;
  - ›› No one has managed to find a FPT algorithm;
  - ›› **Hypothesis:  $k$ -Clique is not in FPT.**
- › The  $W[t]$ -hardness is the parameterized analogous of NP-hardness.
  - ››  $k$ -CLIQUE is  $W[1]$ -hard;
  - ›› HITTING SET and DOMINATING SET are  $W[2]$ -hard;
  - ›› We can show other problems are  $W[t]$ -hard by using FPT-reductions.

# Influence Immunization Bounding (cont.)

Gennaro Cordasco, Luisa Gargano, and Adele A. Rescigno (Apr. 2023). “Immunization in the Threshold Model: A Parameterized Complexity Study”. In: *Algorithmica* 85.11, pp. 3376–3405. ISSN: 1432-0541. DOI: 10.1007/s00453-023-01118-y

Parameter	Hardness
$k$	W[1]-hard $t(v) = 1 \quad \forall v$
$l$	W[1]-hard $t(v) = 1 \quad \forall v$
$k + l$	FPT
$ S  + l$	W[2]-hard Bipartite graphs
$k +  S $	FPT
$\Delta(G) + l$	W[2]-hard $t(v) \leq 2 \quad \forall v$
$tw(G)$	W[1]-hard
$nd(G)$	W[1]-hard
$k + nd(G)$	FPT
$l + nd(G)$	FPT
$\min(\Delta(G), k) + tw(G) + l$	FPT

# Influence Immunization Bounding (cont.)

Let  $G = (V, E)$  be a graph with thresholds  $t : V(G) \rightarrow \mathbb{N}$  and seed set  $S \subseteq V(G)$ .

## Definition

Let  $Y \subseteq V(G)$ . If, by immunizing the vertices of  $Y$ , the infection in  $(G, t)$  is restricted to **at most**  $k$  vertices, we say that  $Y$  is a  **$k$ -restricting set**.

## Definition

The  **$k$ -restricting number of**  $(G, t)$ , denoted by

$$\mathfrak{R}(G, t, k)$$

, is size of a **minimum  $k$ -restricting set** of  $(G, t)$ .


## Influence Immunization Bounding (cont.)

Consider the graph on the right.

### Example

$Y = \{c, h\}$  is a 3-restricting set of  $(G, t)$ .

$\mathfrak{R}(G, t, k = 3) = 2$ .



## Influence Immunization Bounding (cont.)

Consider the graph on the right.

### Example

$Y = \{c, h\}$  is a 3-restricting set of  $(G, t)$ .


$$\mathfrak{R}(G, t, k = 3) = 2.$$

### Definition

If  $k = |S|$ , then we say that  $\mathfrak{R}(G, t, k = |S|)$  is the **total restricting number of**  $(G, t)$ , and denote it by  $\mathfrak{R}_T(G, t)$ .

### Example

$$\mathfrak{R}_T(G, t) = \mathfrak{R}(G, t, k = 3) = 2.$$



# Influence Immunization Bounding (cont.)

Consider the graph on the right.

## Example

$Y = \{c, h\}$  is a 3-restricting set of  $(G, t)$ .

$$\mathfrak{R}(G, t, k = 3) = 2.$$

## Definition

If  $k = |S|$ , then we say that  $\mathfrak{R}(G, t, k = |S|)$  is the **total restricting number** of  $(G, t)$ , and denote it by  $\mathfrak{R}_T(G, t)$ .


## Example

$$\mathfrak{R}_T(G, t) = \mathfrak{R}(G, t, k = 3) = 2.$$

## Remark

For any suitable  $k$ , we have that

$$\mathfrak{R}(G, t, k) \leq \mathfrak{R}_T(G, t)$$





- › Fedor V. Fomin, Petr A. Golovach, and Janne H. Korhonen (2013). “On the Parameterized Complexity of Cutting a Few Vertices from a Graph”. In: *Mathematical Foundations of Computer Science 2013*. Ed. by Krishnendu Chatterjee and Jirí Sgall. Berlin, Heidelberg: Springer Berlin Heidelberg, pp. 421–432. ISBN: 978-3-642-40313-2
- › Ara Hayrapetyan et al. (2005). “Unbalanced Graph Cuts”. In: *Algorithms – ESA 2005*. Springer Berlin Heidelberg, pp. 191–202. ISBN: 9783540319511. DOI: 10.1007/11561071\_19. URL: [http://dx.doi.org/10.1007/11561071\\_19](http://dx.doi.org/10.1007/11561071_19)
- › Hermish Mehta and Daniel Reichman (2022). *Local treewidth of random and noisy graphs with applications to stopping contagion in networks*. eprint: [arXiv:2204.07827](https://arxiv.org/abs/2204.07827)


- Firefighter is very conceptually related (Anshelevich et al. 2010);
- Game theoretical approach (Aspnes, Chang, and Yampolskiy 2006; P.-A. Chen, David, and Kempe 2010; Moscibroda, Schmid, and Wattenhofer 2006; Meier et al. 2014);
- Spectral graph theory (Ahmad et al. 2020; C. Chen et al. 2016; Chakrabarti et al. 2008; Tariq et al. 2017).





# Our Results

## Definition


Let  $G = (V, E)$  be a graph and  $S \subseteq V(G)$  a seed set of  $G$ . Then  $P = v_1 v_2 \dots v_k$  is a  **$S$ -alternating path** of  $G$  if  $P$  is a path of  $G$  with *at least 3 vertices* and the vertices of  $P$  alternate with respect to their membership in  $S$ .



- **Main observation:** for each  $S$ -alternating path of length 4, we need only one vertex to inhibit the infection.



**Figure:** When the  $S$ -alternating path has length 4, we can inhibit the infection by immunizing only one vertex.




- (a) The infection stops by immunizing any vertex. The immunized vertex is shown in blue.



- (b) When the  $S$ -alternating path has length 3 and starts with a uninfected vertex, the infection does not spread.

- We can split the path into  $S$ -alternating paths of length 4.



**Figure:** Splitting a bigger  $S$ -alternating path into pieces of length 4 starting with infected vertices.

## Proposition

Let  $G = P_n$  with  $t(v) = 2$  for all  $v \in V(G)$ . Then, for any  $k \in \mathbb{N}$ ,



$$Im(G, t, k) \leq In(G, t) \leq \lceil \frac{n}{4} \rceil$$

# Complete graphs with $t(v) = c$

## Proposition


Let  $G \cong K_n$  be a complete graph on  $n$  vertices with thresholds  $t(v) = c$  for all  $v \in V(G)$ ,  $S \subseteq V(G)$  a seed set of  $G$ , and  $k \in \mathbb{N}$ . Then:

$$Im(G, t, k) = \begin{cases} \min\{|S| - c + 1, n - k\}, & \text{if } |S| \geq c \\ 0, & \text{otherwise.} \end{cases}$$



## Definition

A graph  $G$  is *chordal* if every cycle  $C$  of length at least 4 in  $G$  has a *chord*: an edge between non-consecutive vertices of  $C$ .



Chordal graphs are a superclass of several important graph classes:

- Trees;
- Split Graphs;
- Interval Graphs.




## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .



➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .

f

➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Theorem (Dirac 1961)

*A graph  $G$  is chordal if and only if  $G$  has a perfect elimination ordering.*

## Theorem (Dirac 1961)


*Let  $G$  be a graph. If  $G$  is chordal and not complete, then  $G$  has two non-adjacent simplicial vertices.*

## Theorem (Dirac 1961)

*If a graph  $G$  is chordal, then any induced subgraph of  $G$  is chordal.*

## Definition

Given a graph  $G$ , a set  $D \subseteq V(G)$  is a *dominating set* if every vertex from  $V(G) \setminus D$  has at least one neighbor in  $D$ .




$k$ -DOMINATING SET is:

- $W[1]$ -hard for chordal graphs parameterized by  $k$  (Liu and Song 2009);
- NP-hard for split graphs (Bertossi 1984).



## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \emptyset$ ;
- $U = \emptyset$ ;

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b\};$
- $U = \{a\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b, d, e\};$
- $U = \{a, c\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b, d, e\};$
- $U = \{a, c, f\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b, d, e\};$
- $U = \{a, c, f\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

- $G$  has a dominating set of size  $\leq k$  if and only if  $(G, t, S)$  has a  $|S|$ -immunizing set of size  $l \leq k$ .




- IIB is  $W[1]$ -hard for chordal graphs parameterized by  $l$ , and NP-complete for split graphs.

# Hardness for Bipartite Graphs

Cordasco, Gargano, and Rescigno 2023 showed that IIB is  $W[2]$ -hard parameterized by  $|S| + I$  even on bipartite graphs.

## Proposition

*IIB is NP-complete on bipartite graphs even if  $A$  is entirely susceptible and  $B$  is entirely infected.*



➤ Reduction from SET COVER.


- Universe set  $\mathcal{U} = \{a_1, a_2, \dots, a_n\}$ ;
- $\mathcal{S} = \{S_1, S_2, \dots, S_m\}$ ;
- Parameter  $c \in \mathbb{N}$ .

- 1 Create a bipartite graph  $G$  such that  $V(G) = \mathcal{U} \cup \mathcal{S}$  and  $E(G) = \{a_i S_j \mid a_i \in S_j\}$ ;
- 2 Define  $k = |\mathcal{S}|$ ,  $l = c$ , and set the seed set  $S = \mathcal{S}$ ;
- 3 Set  $t(a_i) = d_G(a_i)$ , for all  $i \in [n]$ .



**Example**

- $\mathcal{U} = \{1, 2, 3, 4, 5\}$ ;
- $\mathcal{S} = \{S_1 = \{1, 2, 3\}, S_2 = \{2, 4\}, S_3 = \{3, 4\}, S_4 = \{4, 5\}\}$ ; and
- $c = 2$ .



# Hardness for Bipartite Graphs


## Example

- $\mathcal{U} = \{1, 2, 3, 4, 5\}$ ;
- $\mathcal{S} = \{S_1 = \{1, 2, 3\}, S_2 = \{2, 4\}, S_3 = \{3, 4\}, S_4 = \{4, 5\}\}$ ; and
- $c = 2$ .

## Proposition

$(\mathcal{U}, \mathcal{S})$  has a set cover of size  $\leq c$  if and only if  $(G, t)$  has a  $|\mathcal{S}|$ -immunizing set of size  $\leq c$ .

- The problem remains hard even on this restricted instance for bipartite graphs.



## Definition

A graph  $G$  is planar if it can be drawn on the plane without crossing edges.

## Theorem (Wagner 1937)

*A graph  $G$  is planar if and only if  $G$  does not have a  $K_5$  minor nor a  $K_{3,3}$  minor.*

- › In RESTRICTED 3-SAT, we are given a 3-Sat CNF formula in which every variable **occurs exactly 3 times**: twice as positive and once as negative.
  - ›› R-3-SAT is NP-complete (Dahlhaus et al. 1994).

## Example

$$\varphi = (u \vee v \vee \overline{w}) \wedge (\overline{u} \vee v \vee x) \wedge (u \vee \overline{x} \vee \overline{y}) \wedge (\overline{v} \vee w \vee x) \wedge (w \vee z \vee y) \wedge (y \vee \overline{z}) \wedge (z)$$

# Hardness for Planar Bipartite Subcubic Graphs

- In RESTRICTED 3-SAT, we are given a 3-Sat CNF formula in which every variable **occurs exactly 3 times**: twice as positive and once as negative.
  - R-3-SAT is NP-complete (Dahlhaus et al. 1994).

## Example


$$\varphi = (u \vee v \vee \overline{w}) \wedge (\overline{u} \vee v \vee x) \wedge (u \vee \overline{x} \vee \overline{y}) \wedge (\overline{v} \vee w \vee x) \wedge (w \vee z \vee y) \wedge (y \vee \overline{z}) \wedge (z)$$

## Proposition

$\text{R-3-SAT} \leq_P (\text{Planar Bipartite Subcubic}) \text{ IIB.}$

# Hardness for Planar Bipartite Subcubic Graphs

- Given a R-3-SAT formula  $\varphi$ , let:
  - $V(\varphi)$  the set of variables of  $\varphi$ ;
  - $C(\varphi)$  the set of clauses of  $\varphi$ .
- Let's create a graph  $G_\varphi$  with thresholds  $t_\varphi$ . For each variable  $x \in V(\varphi)$ , we are going to add the following gadget to  $G_\varphi$ :




# Hardness for Planar Bipartite Subcubic Graphs

- For each clause  $C \in \mathcal{C}(\varphi)$ , we are going to add a vertex in  $G_\varphi$  and connect it to its literals, setting  $t_\varphi(C) = |C|$ .


## Example

$$C = (u \vee v \vee \overline{w}).$$



# Hardness for Planar Bipartite Subcubic Graphs

- Example of  $G_\varphi$  for the R-3-SAT formula  
 $\varphi = (u \vee v \vee \bar{w}) \wedge (\bar{u} \vee v \vee x) \wedge (u \vee \bar{x} \vee \bar{y}) \wedge$   
 $(\bar{v} \vee w \vee x) \wedge (w \vee z \vee y) \wedge (y \vee \bar{z}) \wedge (z).$





- Suppose  $\varphi$  has a satisfying assignment  $\mathcal{S} : V(\varphi) \rightarrow \{\text{TRUE}, \text{FALSE}\}$ .

## Proposition

$Y = (\{x \mid \mathcal{S}(x) = \text{TRUE}\} \cup \{\bar{x} \mid \mathcal{S}(x) = \text{FALSE}\})$  is a  $(2|V(\varphi)|)$ -immunizing set for  $(G_\varphi, t_\varphi)$  and  $|Y| \leq |V(\varphi)|$ .

# Hardness for Planar Bipartite Subcubic Graphs

- Suppose  $\varphi$  has a satisfying assignment  $\mathcal{S} : V(\varphi) \rightarrow \{\text{TRUE}, \text{FALSE}\}$ .

## Proposition

$Y = (\{x \mid \mathcal{S}(x) = \text{TRUE}\} \cup \{\bar{x} \mid \mathcal{S}(x) = \text{FALSE}\})$  is a  $(2|V(\varphi)|)$ -immunizing set for  $(G_\varphi, t_\varphi)$  and  $|Y| \leq |V(\varphi)|$ .

- Now, suppose  $Y$  is a  $(2|V(\varphi)|)$ -immunizing set for  $(G_\varphi, t_\varphi)$  and  $|Y| \leq |V(\varphi)|$ .

## Proposition

For every  $x \in V(\varphi)$ , either  $x \in Y$  or  $\bar{x} \in Y$ .

- Thus, we can build a satisfying assignment for  $\varphi$  from  $Y$ .

## Proposition

$G_\varphi$  is planar bipartite subcubic.

- Clause vertices have degree at most 3, positive literals vertices have degree 3, negative literals vertices have degree 2, and auxiliary vertices have degree 2.

## Proposition

$G_\varphi$  is planar bipartite subcubic.

- Clause vertices have degree at most 3, positive literals vertices have degree 3, negative literals vertices have degree 2, and auxiliary vertices have degree 2.
- Let  $A$  be the set of auxiliary vertices. Then we have the partition  $(X, Y)$  of  $V(G_\varphi)$  such that  $X = A \cup \mathcal{C}(\varphi)$  and  $Y = \{x, \bar{x} \mid x \in V(\varphi)\}$ .

## Proposition

$G_\varphi$  is planar bipartite subcubic.






- Clause vertices have degree at most 3, positive literals vertices have degree 3, negative literals vertices have degree 2, and auxiliary vertices have degree 2.
- Let  $A$  be the set of auxiliary vertices. Then we have the partition  $(X, Y)$  of  $V(G_\varphi)$  such that  $X = A \cup \mathcal{C}(\varphi)$  and  $Y = \{x, \bar{x} \mid x \in V(\varphi)\}$ .
- Since  $G_\varphi$  is subcubic, it cannot have a  $K_5$  minor.
- In order to have a  $K_{3,3}$  minor, we should have 3 clauses connected with 3 equal positive literals. Since each positive literal appears only twice,  $G_\varphi$  is planar.






## Section 8: **Conclusion and Future Work**







Obrigado.





-  Ahmad, Muhammad et al. (May 2020). “Combinatorial trace method for network immunization”. In: *Information Sciences* 519, pp. 215–228. ISSN: 0020-0255. DOI: 10.1016/j.ins.2020.01.037. URL: <http://dx.doi.org/10.1016/j.ins.2020.01.037>.
-  Anshelevich, Elliot et al. (Dec. 2010). “Approximability of the Firefighter Problem: Computing Cuts over Time”. In: *Algorithmica* 62.1–2, pp. 520–536. ISSN: 1432-0541. DOI: 10.1007/s00453-010-9469-y. URL: <http://dx.doi.org/10.1007/s00453-010-9469-y>.
-  Araújo, Rafael and Rudini Sampaio (May 2023). “Domination and convexity problems in the target set selection model”. In: *Discrete Applied Mathematics* 330, pp. 14–23. ISSN: 0166-218X. DOI: 10.1016/j.dam.2022.12.021. URL: <http://dx.doi.org/10.1016/j.dam.2022.12.021>.
-  Aspnes, James, Kevin Chang, and Aleksandr Yampolskiy (Sept. 2006). “Inoculation strategies for victims of viruses and the sum-of-squares partition problem”. In: *Journal of Computer and System Sciences* 72.6, pp. 1077–1093. ISSN: 0022-0000. DOI: 10.1016/j.jcss.2006.02.003. URL: <http://dx.doi.org/10.1016/j.jcss.2006.02.003>.
-  Bertossi, Alan A (July 1984). “Dominating sets for split and bipartite graphs”. en. In: *Inf. Process. Lett.* 19.1, pp. 37–40.


- 
- Chakrabarti, Deepayan et al. (Jan. 2008). “Epidemic thresholds in real networks”. In: *ACM Transactions on Information and System Security* 10.4, pp. 1–26. ISSN: 1557-7406. DOI: 10.1145/1284680.1284681. URL: <http://dx.doi.org/10.1145/1284680.1284681>.
- 
- Chen, Po-An, Mary David, and David Kempe (June 2010). “Better vaccination strategies for better people”. In: *Proceedings of the 11th ACM conference on Electronic commerce. EC '10*. ACM, pp. 179–188. DOI: 10.1145/1807342.1807370. URL: <http://dx.doi.org/10.1145/1807342.1807370>.
- 
- Chen, Chen et al. (Jan. 2016). “Node Immunization on Large Graphs: Theory and Algorithms”. In: *IEEE Transactions on Knowledge and Data Engineering* 28.1, pp. 113–126. ISSN: 1041-4347. DOI: 10.1109/tkde.2015.2465378. URL: <http://dx.doi.org/10.1109/TKDE.2015.2465378>.
- 
- Coleman, James, Elihu Katz, and Herbert Menzel (Dec. 1957). “The diffusion of an innovation among physicians”. In: *Sociometry* 20.4, p. 253.
- 
- Cordasco, Gennaro, Luisa Gargano, and Adele A. Rescigno (Apr. 2023). “Immunization in the Threshold Model: A Parameterized Complexity Study”. In: *Algorithmica* 85.11, pp. 3376–3405. ISSN: 1432-0541. DOI: 10.1007/s00453-023-01118-y.


-  Dahlhaus, E. et al. (Aug. 1994). "The Complexity of Multiterminal Cuts". In: *SIAM Journal on Computing* 23.4, pp. 864–894. ISSN: 1095-7111. DOI: 10.1137/s0097539792225297. URL: <http://dx.doi.org/10.1137/s0097539792225297>.
-  Dirac, G A (Apr. 1961). "On rigid circuit graphs". en. In: *Abh. Math. Semin. Univ. Hambg.* 25.1-2, pp. 71–76.
-  Dreyer, Paul A. and Fred S. Roberts (2009). "Irreversible k-threshold processes: Graph-theoretical threshold models of the spread of disease and of opinion". In: *Discrete Applied Mathematics* 157.7, pp. 1615–1627. ISSN: 0166-218X. DOI: <https://doi.org/10.1016/j.dam.2008.09.012>. URL: <https://www.sciencedirect.com/science/article/pii/S0166218X08004393>.
-  Flocchini, Paola et al. (Apr. 2003). "On time versus size for monotone dynamic monopolies in regular topologies". In: *Journal of Discrete Algorithms* 1.2, pp. 129–150. ISSN: 1570-8667. DOI: 10.1016/s1570-8667(03)00022-4. URL: [http://dx.doi.org/10.1016/S1570-8667\(03\)00022-4](http://dx.doi.org/10.1016/S1570-8667(03)00022-4).







- 
- Fomin, Fedor V., Petr A. Golovach, and Janne H. Korhonen (2013). “On the Parameterized Complexity of Cutting a Few Vertices from a Graph”. In:
- Mathematical Foundations of Computer Science 2013*
- . Ed. by Krishnendu Chatterjee and Jirí Sgall. Berlin, Heidelberg: Springer Berlin Heidelberg, pp. 421–432. ISBN: 978-3-642-40313-2.


- 
- Hayrapetyan, Ara et al. (2005). “Unbalanced Graph Cuts”. In:
- Algorithms – ESA 2005*
- . Springer Berlin Heidelberg, pp. 191–202. ISBN: 9783540319511. DOI: 10.1007/11561071\_19. URL:
- [http://dx.doi.org/10.1007/11561071\\_19](http://dx.doi.org/10.1007/11561071_19)
- .

- 
- Keiler, Lucas et al. (Oct. 2023). “Target set selection with maximum activation time”. In:
- Discrete Applied Mathematics*
- 338, pp. 199–217. ISSN: 0166-218X. DOI: 10.1016/j.dam.2023.06.004. URL:
- <http://dx.doi.org/10.1016/j.dam.2023.06.004>
- .

- 
- Kempe, David, Jon Kleinberg, and Éva Tardos (2003). “Maximizing the spread of influence through a social network”. In:
- Proceedings of the Ninth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*
- . KDD '03. Washington, D.C.: Association for Computing Machinery, pp. 137–146. ISBN: 1581137370. DOI: 10.1145/956750.956769. URL:
- <https://doi.org/10.1145/956750.956769>
- .

- 
- Liu, Chunmei and Yinglei Song (July 2009). “Parameterized dominating set problem in chordal graphs: complexity and lower bound”. In:
- J. Comb. Optim.*
- 18.1, pp. 87–97.

- 
- Marcilon, Thiago and Rudini Sampaio (Jan. 2018). “The maximum time of 2-neighbor bootstrap percolation: Complexity results”. In:
- Theoretical Computer Science*
- 708, pp. 1–17. ISSN: 0304-3975. DOI: 10.1016/j.tcs.2017.10.014. URL:
- <http://dx.doi.org/10.1016/j.tcs.2017.10.014>
- .
- 
- 
- Mehta, Hermish and Daniel Reichman (2022).
- Local treewidth of random and noisy graphs with applications to stopping contagion in networks*
- . eprint:
- [arXiv:2204.07827](https://arxiv.org/abs/2204.07827)
- .
- 
- 
- Meier, Dominic et al. (Apr. 2014). “On the Windfall and price of friendship: Inoculation strategies on social networks”. In:
- Computer Networks*
- 62, pp. 221–236. ISSN: 1389-1286. DOI: 10.1016/j.bjp.2013.12.004. URL:
- <http://dx.doi.org/10.1016/j.bjp.2013.12.004>
- .
- 
- 
- Moscibroda, Thomas, Stefan Schmid, and Rogert Wattenhofer (July 2006). “When selfish meets evil: byzantine players in a virus inoculation game”. In:
- Proceedings of the twenty-fifth annual ACM symposium on Principles of distributed computing*
- . PODC06. ACM, pp. 35–44. DOI: 10.1145/1146381.1146391. URL:
- <http://dx.doi.org/10.1145/1146381.1146391>
- .
- 
- 
- Ryan, Bryce and Neal Gross (1950).
- Acceptance and diffusion of hybrid corn seed in two Iowa communities*
- .
- 
- 
- Tariq, Juvaria et al. (2017).
- Scalable Approximation Algorithm for Network Immunization*
- . DOI: 10.48550/ARXIV.1711.00784. URL:
- <https://arxiv.org/abs/1711.00784>
- .

-  Wagner, K (Dec. 1937). “Über eine Eigenschaft der ebenen Komplexe”. de. In: *Math. Ann.* 114.1, pp. 570–590.