

Samuel Santos
csamuelssm@alu.ufc.br

UFC
Universidade Federal do Ceará

December 2024

Restricting infections on graph classes

Supervised by Ana Karolinnna Maia de Oliveira and Carlos Vinícius Gomes Costa Lima

Several phenomena happen in a **contagion-like manner**.

- Spreading of pathogens, like viruses or bacteria;

Several phenomena happen in a **contagion-like manner**.

- Spreading of pathogens, like viruses or bacteria;
- The diffusion of innovation, (mis-)information, and memes.



Information

Studies found that most people adopt innovative ideas based on the experience of their neighbors or community.

- » The adoption of hybrid seed corn among farmers (Ryan and Gross 1950);
- » The adoption of tetracycline by physicians (Coleman, Katz, and Menzel 1957).

Several phenomena happen in a **contagion-like manner**.

- Spreading of pathogens, like viruses or bacteria;
- The diffusion of innovation, (mis-)information, and memes.
- Even bedbugs seem to spread from hotel to hotel via travelers (Barabási and Pósfai 2016).


The early models built to study such phenomena are the so-called *compartmental models*.

- Compartments are states;
- Each agent/individual belongs to one state.

The early models built to study such phenomena are the so-called *compartmental models*.

- Compartments are states;
- Each agent/individual belongs to one state.

Example (SIR)



The early models built to study such phenomena are the so-called *compartmental models*.

- Compartments are states;
- Each agent/individual belongs to one state.

Definition (Homogeneous Mixing Hypothesis)

The assumption that every individual from one compartment has the same chance of interacting with an individual from another compartment.

The early models built to study such phenomena are the so-called *compartmental models*.

- Compartments are states;
- Each agent/individual belongs to one state.

Definition (Homogeneous Mixing Hypothesis)

The assumption that every individual from one compartment has the same chance of interacting with an individual from another compartment.

- The homogeneous mixing hypothesis is **false**.

The early models built to study such phenomena are the so-called *compartmental models*.

- › Compartments are states;
- › Each agent/individual belongs to one state.

Definition (Homogeneous Mixing Hypothesis)

The assumption that every individual from one compartment has the same chance of interacting with an individual from another compartment.

- › The homogeneous mixing hypothesis is **false**.
- › The **structure of the contact network** is what facilitates the contagion.



Information


Studies have shown that the airport mobility network provides reliable information for the prediction and control of airborne epidemics like H1N1 (Soriano-Paños et al. 2022).

Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
 - A vertex is either **active (infected)** or **inactive (susceptible)**.


Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
 - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.
 - A threshold value represents **how susceptible** an individual is to the contagious agent.
 - Smaller thresholds: early adopters / low immunity;




Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
 - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.
 - A threshold value represents **how susceptible** an individual is to the contagious agent.
 - Smaller thresholds: early adopters / low immunity;



Modeling Contagion on Graphs: Threshold Model


- Let's consider each vertex as an individual.
 - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.
 - A threshold value represents **how susceptible** an individual is to the contagious agent.
 - Smaller thresholds: early adopters / low immunity;
 - Bigger thresholds: laggards / greater resistance.



Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph** $G = (V, E)$;



Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph** $G = (V, E)$;
- A **threshold function** $t : V(G) \rightarrow \mathbb{N}$;



Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph** $G = (V, E)$;
- A **threshold function** $t : V(G) \rightarrow \mathbb{N}$;
- A set of **initial infected vertices** – the *seed set* $S \subseteq V(G)$.



Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph** $G = (V, E)$;
- A **threshold function** $t : V(G) \rightarrow \mathbb{N}$;
- A set of **initial infected vertices** – the *seed set* $S \subseteq V(G)$.
- The diffusion happens in **discrete time steps**.



Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph** $G = (V, E)$;
- A **threshold function** $t : V(G) \rightarrow \mathbb{N}$;
- A set of **initial infected vertices** – the *seed set* $S \subseteq V(G)$.
- The diffusion happens in **discrete time steps**.



Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:

- A **graph** $G = (V, E)$;
- A **threshold function** $t : V(G) \rightarrow \mathbb{N}$;
- A set of **initial infected vertices** – the *seed set* $S \subseteq V(G)$.
- The diffusion happens in **discrete time steps**.
- Once a vertex is infected, it **stays infected** – we call it a t -**irreversible process**.



Problems arising from the Threshold Model

Several computational problems arise from the Threshold Model.

- **Influence Maximization** (IM) (Kempe, Kleinberg, and Tardos 2003): find a seed set of bounded cardinality that maximizes the number of infected vertices.

Several computational problems arise from the Threshold Model.

- **Influence Maximization** (IM) (Kempe, Kleinberg, and Tardos 2003): find a seed set of bounded cardinality that maximizes the number of infected vertices.
 - Decision version is NP-complete even for bipartite graphs.

Several computational problems arise from the Threshold Model.

- **Influence Maximization (IM)** (Kempe, Kleinberg, and Tardos 2003): find a seed set of bounded cardinality that maximizes the number of infected vertices.
 - » Decision version is NP-complete even for bipartite graphs.
 - » NP-complete even for k -regular graphs if we require S to infect all vertices of G – **Target Set Selection (TSS)** (Dreyer and Roberts 2009).

Variations of these problems:

- Directed version;
- Majority version: $t(v) = \lceil \frac{d(v)}{2} \rceil \quad \forall v \in V(G)$;
- TSS with maximum activation time (Keiler et al. 2023; Flocchini et al. 2003; Marcilon and Sampaio 2018);
- TSS with activation time equal to 1 (Araújo and Sampaio 2023);

Problems arising from the Threshold Model


Immunization problems:

- Firefighter;

Problems arising from the Threshold Model

Immunization problems:

- **Firefighter;**
 - A fire breaks at some vertex and will spread;




Problems arising from the Threshold Model

Immunization problems:

> Firefighter;

- » A fire breaks at some vertex and will spread;
- » The goal is to place firefighters to protect the vertices from the fire.




Problems arising from the Threshold Model

Immunization problems:

> Firefighter;

- » A fire breaks at some vertex and will spread;
- » The goal is to place firefighters to protect the vertices from the fire.




Problems arising from the Threshold Model

Immunization problems:

> Firefighter;

- » A fire breaks at some vertex and will spread;
- » The goal is to place firefighters to protect the vertices from the fire.




Problems arising from the Threshold Model

Immunization problems:

> Firefighter;

- » A fire breaks at some vertex and will spread;
- » The goal is to place firefighters to protect the vertices from the fire.
- » NP-complete **even for trees!** (And a bunch of other classes)




Immunization problems:

- **Firefighter**;
 - A fire breaks at some vertex and will spread;
 - The goal is to place firefighters to protect the vertices from the fire.
 - NP-complete **even for trees!** (And a bunch of other classes)
- **Influence Immunization Bounding (IIB)**;
 - A generalization of Firefighter? **No, but sort of...**

First, we need to define what it means to **immunize a vertex**.


- Option 1: raise the vertex threshold above its degree;



Influence Immunization Bounding

First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;




Remark (Option 1)

Infected vertices can also be immunized. In this option, the immunized infected vertices still **can infect others**.

Influence Immunization Bounding

First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;




Remark (Option 1)

Infected vertices can also be immunized. In this option, the immunized infected vertices still **can infect others**.

Influence Immunization Bounding

First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;
- Option 2: make the vertex invisible – remove it.




Remark (Option 2)

In this option, immunized vertices do not infect nor get infected.

First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;
- **Option 2: make the vertex invisible – remove it.**




Remark (Option 2)

In this option, immunized vertices do not infect nor get infected.

Influence Immunization Bounding

Given:

- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;




Influence Immunization Bounding

Given:

- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;
- A seed set $S \subseteq V(G)$;

Remark

Notice that $S = \{a, e, h\}$ is a *target set* for this graph.




Given:

- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;
- A seed set $S \subseteq V(G)$;

Remark

Notice that $S = \{a, e, h\}$ is a *target set* for this graph.




Given:

- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;
- A seed set $S \subseteq V(G)$;

Remark


Notice that $S = \{a, e, h\}$ is a *target set* for this graph.



Influence Immunization Bounding

Given:

- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;
- A seed set $S \subseteq V(G)$;
- Naturals k and l .




Influence Immunization Bounding

Given:

- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;
- A seed set $S \subseteq V(G)$;
- Naturals k and l . **Let** $k = 3$ **and** $l = 2$.

We want to find a immunizing set $Y \subseteq V(G)$ such that:

- $|Y| \leq l$; and



Influence Immunization Bounding

Given:


- A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$;
- A seed set $S \subseteq V(G)$;
- Naturals k and l . **Let $k = 3$ and $l = 2$.**

We want to find a immunizing set $Y \subseteq V(G)$ such that:

- $|Y| \leq l$; and
- By immunizing Y at time $\tau = 0$, the **infection gets restricted to at most k vertices**.

Remark

Notice that we must have $k \geq |S|$.



But before we proceed...

A little of **Parameterized Complexity**.

We can define a (classical) decision problem as follows:

- Let Σ be a finite alphabet, and $Q \subseteq \Sigma^*$.

Input: $x \in \Sigma^*$.

Question: Decide whether $x \in Q$.

We can define a (classical) decision problem as follows:

- Let Σ be a finite alphabet, and $Q \subseteq \Sigma^*$.

Input: $x \in \Sigma^*$.

Question: Decide whether $x \in Q$.

Definition

A **parameter** is a function $\kappa : \Sigma^* \rightarrow \mathbb{N}$ that takes the input of a problem to the naturals.

Example

A parameter for SAT can be $\kappa(\varphi) = \text{"Number of variables of } \varphi\text{"}$, where φ is a CNF formula.

Now we can define a **parameterized problem**.

Definition

A *parameterized problem* is a pair (P, κ) , such that P is a decision problem and κ is a parameter for P .

Now we can define a **parameterized problem**.

Definition

A *parameterized problem* is a pair (P, κ) , such that P is a decision problem and κ is a parameter for P .

p-INDEPENDENT-SET

Input: A graph G and $k \in \mathbb{N}$.

Question: Decide whether G has an independent set of cardinality k .

Parameter: k .

But what is the motivation behind this?

- NP-hard problems cannot have **all instances** solved in polynomial time, unless $P = NP$.

But what is the motivation behind this?

- NP-hard problems cannot have **all instances** solved in polynomial time, unless $P = NP$.
- But in practice, **only a subset** of them is relevant.
 - VLSI design: the number of circuit layers is **usually ≤ 10** ;
 - Computational biology: real instances of DNA chain reconstruction have special properties, e.g., **treewidth ≤ 11** ;
 - Robotics: the number of degrees of freedom in motion planning problems is **usually ≤ 10** .

But what is the motivation behind this?

- › NP-hard problems cannot have **all instances** solved in polynomial time, unless $P = NP$.
- › But in practice, **only a subset** of them is relevant.
 - › VLSI design: the number of circuit layers is **usually ≤ 10** ;
 - › Computational biology: real instances of DNA chain reconstruction have special properties, e.g., **treewidth ≤ 11** ;
 - › Robotics: the number of degrees of freedom in motion planning problems is **usually ≤ 10** .
- › This means that **parameters of the problem matter for its tractability**.

Let $x \in \Sigma^*$ be an instance of a parameterized problem (P, κ) .

Definition (XP)

(P, κ) is **slicewise polynomial** if it admits an algorithm which running time is

$$O(|x|^{\kappa(x)})$$

- **CLIQUE** is in XP parameterized by k : enumerate all subsets of k vertices and check if they form a clique.

Let $x \in \Sigma^*$ be an instance of a parameterized problem (P, κ) .

Definition (XP)

(P, κ) is **slicewise polynomial** if it admits an algorithm which running time is

$$O(|x|^{\kappa(x)})$$

Definition (FPT)

(P, κ) is **fixed-parameter tractable** if it admits an algorithm which running time is

$$O(f(\kappa(x)) \cdot \text{poly}(|x|))$$

- VERTEX COVER is in FPT parameterized by k .

- The class FPT is the parameterized analogous to the class P;
- The class para-NP is the parameterized analogous to the class NP;

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- › k -CLIQUE is the parameterized analogous to 3-SAT;
 - ›› No one has managed to find a FPT algorithm;

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- › k -CLIQUE is the parameterized analogous to 3-SAT;
 - › No one has managed to find a FPT algorithm;
 - › **Hypothesis: k -Clique is not in FPT.**

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- › k -CLIQUE is the parameterized analogous to 3-SAT;
 - › No one has managed to find a FPT algorithm;
 - › **Hypothesis:** k -CLIQUE is not in FPT.
- › The $W[t]$ -hardness is the parameterized analogous of NP-hardness.
 - › k -CLIQUE is $W[1]$ -hard;

- The class FPT is the parameterized analogous to the class P;
- The class para-NP is the parameterized analogous to the class NP;
- k -CLIQUE is the parameterized analogous to 3-SAT;
 - No one has managed to find a FPT algorithm;
 - **Hypothesis:** k -CLIQUE is not in FPT.
- The $W[t]$ -hardness is the parameterized analogous of NP-hardness.
 - k -CLIQUE is $W[1]$ -hard;
 - HITTING SET and DOMINATING SET are $W[2]$ -hard;

- The class FPT is the parameterized analogous to the class P;
- The class para-NP is the parameterized analogous to the class NP;
- k -CLIQUE is the parameterized analogous to 3-SAT;
 - No one has managed to find a FPT algorithm;
 - **Hypothesis:** k -CLIQUE is not in FPT.
- The $W[t]$ -hardness is the parameterized analogous of NP-hardness.
 - k -CLIQUE is $W[1]$ -hard;
 - HITTING SET and DOMINATING SET are $W[2]$ -hard;
 - We can show other problems are $W[t]$ -hard by using FPT-reductions.

Influence Immunization Bounding (cont.)

Influence Immunization Bounding was introduced by (Cordasco, Gargano, and Rescigno 2023).

Parameter	Hardness
k	W[1]-hard $t(v) = 1 \quad \forall v$
l	W[1]-hard $t(v) = 1 \quad \forall v$
$k + l$	FPT
$ S + l$	W[2]-hard Bipartite graphs
$k + S $	FPT
$\Delta(G) + l$	W[2]-hard $t(v) \leq 2 \quad \forall v$
$tw(G)$	W[1]-hard
$nd(G)$	W[1]-hard
$k + nd(G)$	FPT
$l + nd(G)$	FPT
$\min(\Delta(G), k) + tw(G) + l$	FPT

Influence Immunization Bounding (cont.)

Let $G = (V, E)$ be a graph with thresholds $t : V(G) \rightarrow \mathbb{N}$ and seed set $S \subseteq V(G)$.

Definition

Let $Y \subseteq V(G)$. If, by immunizing the vertices of Y , the infection in (G, t) is restricted to **at most** k vertices, we say that Y is a **k -immunizing set**.

Definition

The **k -immunization number of (G, t)** , denoted by

$$\text{Im}(G, t, k)$$

, is size of a **minimum k -immunizing set** of (G, t) .


Influence Immunization Bounding (cont.)

Consider the graph on the right.

Example

$Y = \{c, h\}$ is a 3-immunizing set of (G, t) .

$\text{Im}(G, t, k = 3) = 2$.



Influence Immunization Bounding (cont.)

Consider the graph on the right.

Example

$Y = \{c, h\}$ is a 3-immunizing set of (G, t) .


$\text{Im}(G, t, k = 3) = 2$.

Definition

If $k = |S|$, then we say that $\text{Im}(G, t, k = |S|)$ is the **inhibition number of** (G, t) , and denote it by $\text{In}(G, t)$.

Example

$\text{In}(G, t) = \text{Im}(G, t, k = 3) = 2$.



Influence Immunization Bounding (cont.)

Consider the graph on the right.

Example

$Y = \{c, h\}$ is a 3-immunizing set of (G, t) .

$\text{Im}(G, t, k = 3) = 2$.

Definition

If $k = |S|$, then we say that $\text{Im}(G, t, k = |S|)$ is the **inhibition number of** (G, t) , and denote it by $\text{In}(G, t)$.


Example

$\text{In}(G, t) = \text{Im}(G, t, k = 3) = 2$.

Remark

For any suitable k , we have that

$$\text{Im}(G, t, k) \leq \text{In}(G, t)$$



We can also define a **restricted version** of IIB, which we call R-IIB.

Restricted Influence Immunization Bounding (R-IIB)

Input: A graph $G = (V, E)$ with thresholds $t : V(G) \rightarrow \mathbb{N}$, seed set $S \subseteq V(G)$, and $k, l \in \mathbb{N}$.

Question: Decide whether there exists $Y \subseteq V(G) \setminus S$ such that $|Y| \leq l$ and Y is a k -immunizing set of G .

- R-IIB is also $W[1]$ -hard when parameterized by k or by l .


Influence Immunization Bounding (cont.)

Consider the graph on the right.

Definition

$Y \subseteq V(G)$ is a **restricted k -immunizing set** of (G, t) if Y is a k -immunizing set of (G, t) and $Y \cap S = \emptyset$.

➤ $Y = \{c, h\}$ is not a restricted k -immunizing set of (G, t) .




Influence Immunization Bounding (cont.)

Consider the graph on the right.

Definition

$Y \subseteq V(G)$ is a **restricted k -immunizing set** of (G, t) if Y is a k -immunizing set of (G, t) and $Y \cap S = \emptyset$.

- $Y = \{c, h\}$ is not a restricted k -immunizing set of (G, t) .
- $Y = \{c, g\}$ is a restricted k -immunizing set of (G, t) .




Definition

The **restricted k -immunization number** of (G, t) , denoted by

$$\text{Im}_r(G, t, k)$$

, is the size of a **minimum restricted k -immunizing set** of (G, t) .

- The **restricted inhibition number** $\text{In}_r(G, t)$ is analogous.
- But why study the restricted version?



The restricted version gives an upper bound for the original problem.

Remark

For any suitable k , we have that

$$\text{Im}(G, t, k) \leq \text{Im}_r(G, t, k)$$

- A restricted k -immunizing set for (G, t) is also a (unrestricted) k -immunizing set for (G, t) .