

**Samuel Santos**  
csamuelssm@alu.ufc.br

*UFC*  
*Universidade Federal do Ceará*

December 2024

# Restricting infections on graphs

*Immunization problems*

*Supervised by Ana Karolinnna Maia and Carlos Vinícius G. C. Lima*

Several phenomena happen in a **contagion-like manner**.

- Viruses or bacteria;
- Innovation, (mis-)information, and memes. (Ryan and Gross 1950; Coleman, Katz, and Menzel 1957)


# Modeling Contagion on Graphs: Threshold Model

---

- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.


# Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.




# Modeling Contagion on Graphs: Threshold Model

- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.



# Modeling Contagion on Graphs: Threshold Model


- Let's consider each vertex as an individual.
  - A vertex is either **active (infected)** or **inactive (susceptible)**.
- The individuals change their state based on their neighbors' state.



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:

- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;






# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .
- The diffusion happens in **discrete time steps**.



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:


- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .
- The diffusion happens in **discrete time steps**.



# Modeling Contagion on Graphs: Threshold Model

In the threshold model, we are given:

- A **graph**  $G = (V, E)$ ;
- A **threshold function**  $t : V(G) \rightarrow \mathbb{N}$ ;
- A set of **initial infected vertices** – the *seed set*  $S \subseteq V(G)$ .
- The diffusion happens in **discrete time steps**.
- Once a vertex is infected, it **stays infected** – we call it a  $t$ -**irreversible process**.




Several computational problems arise from the Threshold Model.

- **Influence Maximization** (IM) (Kempe, Kleinberg, and Tardos 2003). NP-complete.
- **Target Set Selection** (TSS) (Dreyer and Roberts 2009). NP-complete.
- Variations:
  - Directed version;
  - Majority version:  $t(v) = \lceil \frac{d(v)}{2} \rceil \quad \forall v \in V(G)$ ;
  - TSS with maximum activation time (Keiler et al. 2023; Flocchini et al. 2003; Marcilon and Sampaio 2018);
  - TSS with activation time equal to 1 (Araújo and Sampaio 2023);

# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model

Immunization problems:

- Firefighter;






# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model

Immunization problems:


- Firefighter;



# Problems arising from the Threshold Model


## Immunization problems:

- Firefighter;
- Influence Immunization Bounding (IIB);
  - A generalization of Firefighter?




First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;
- **Option 2: make the vertex invisible – remove it.**



First, we need to define what it means to **immunize a vertex**.

- Option 1: raise the vertex threshold above its degree;
- **Option 2: make the vertex invisible – remove it.**




## Remark (Option 2)

In this option, immunized vertices do not infect nor get infected.

Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;




Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;

## Remark

Notice that  $S = \{a, e, h\}$  is a *target set* for this graph.




Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;

## Remark

Notice that  $S = \{a, e, h\}$  is a *target set* for this graph.






Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;


## Remark

Notice that  $S = \{a, e, h\}$  is a *target set* for this graph.



Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;
- Naturals  $k$  and  $l$ .




Given:

- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;
- Naturals  $k$  and  $l$ . **Let**  $k = 3$  **and**  $l = 2$ .

We want to find a restricting set  $Y \subseteq V(G)$  such that:

- $|Y| \leq l$ ; and



Given:


- A graph  $G = (V, E)$  with thresholds  $t : V(G) \rightarrow \mathbb{N}$ ;
- A seed set  $S \subseteq V(G)$ ;
- Naturals  $k$  and  $l$ . **Let**  $k = 3$  **and**  $l = 2$ .

We want to find a restricting set  $Y \subseteq V(G)$  such that:

- $|Y| \leq l$ ; and
- By immunizing  $Y$  at time  $\tau = 0$ , the **infection gets restricted to at most  $k$  vertices**.

## Remark

Notice that we must have  $k \geq |S|$ .



*But before we proceed...*  
A little of **Parameterized Complexity**.

## Definition

A *parameterized problem* is a pair  $(P, \kappa)$ , such that  $P$  is a decision problem and  $\kappa$  is a parameter for  $P$ .

**p-INDEPENDENT-SET**

*Input:* A graph  $G$  and  $k \in \mathbb{N}$ .

*Question:* Decide whether  $G$  has an independent set of cardinality  $k$ .

**Parameter:**  $k$ .

**Parameters of the problem matter for its tractability.**

Let  $x \in \Sigma^*$  be an instance of a parameterized problem  $(P, \kappa)$ .

## Definition (XP)

$(P, \kappa)$  is **slicewise polynomial** if it admits an algorithm which running time is

$$O(|x|^{\kappa(x)})$$

- **CLIQUE** is in XP parameterized by  $k$ : enumerate all subsets of  $k$  vertices and check if they form a clique.

Let  $x \in \Sigma^*$  be an instance of a parameterized problem  $(P, \kappa)$ .

## Definition (XP)

$(P, \kappa)$  is **slicewise polynomial** if it admits an algorithm which running time is

$$O(|x|^{\kappa(x)})$$

## Definition (FPT)

$(P, \kappa)$  is **fixed-parameter tractable** if it admits an algorithm which running time is

$$O(f(\kappa(x)) \cdot \text{poly}(|x|))$$

- VERTEX COVER is in FPT parameterized by  $k$ .



- The class FPT is the parameterized analogous to the class P;
- The class para-NP is the parameterized analogous to the class NP;

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- ›  $k$ -CLIQUE is the parameterized analogous to 3-SAT;
  - › No one has managed to find a FPT algorithm;
  - › **Hypothesis:  $k$ -Clique is not in FPT.**

- › The class FPT is the parameterized analogous to the class P;
- › The class para-NP is the parameterized analogous to the class NP;
- ›  $k$ -CLIQUE is the parameterized analogous to 3-SAT;
  - ›› No one has managed to find a FPT algorithm;
  - ›› **Hypothesis:  $k$ -Clique is not in FPT.**
- › The  $W[t]$ -hardness is the parameterized analogous of NP-hardness.
  - ››  $k$ -CLIQUE is  $W[1]$ -hard;
  - ›› HITTING SET and DOMINATING SET are  $W[2]$ -hard;
  - ›› We can show other problems are  $W[t]$ -hard by using FPT-reductions.

# Influence Immunization Bounding (cont.)

Gennaro Cordasco, Luisa Gargano, and Adele A. Rescigno (Apr. 2023). “Immunization in the Threshold Model: A Parameterized Complexity Study”. In: *Algorithmica* 85.11, pp. 3376–3405. ISSN: 1432-0541. DOI: 10.1007/s00453-023-01118-y

Parameter	Hardness
$k$	W[1]-hard $t(v) = 1 \quad \forall v$
$l$	W[1]-hard $t(v) = 1 \quad \forall v$
$k + l$	FPT
$ S  + l$	W[2]-hard Bipartite graphs
$k +  S $	FPT
$\Delta(G) + l$	W[2]-hard $t(v) \leq 2 \quad \forall v$
$tw(G)$	W[1]-hard
$nd(G)$	W[1]-hard
$k + nd(G)$	FPT
$l + nd(G)$	FPT
$\min(\Delta(G), k) + tw(G) + l$	FPT

Let  $G = (V, E)$  be a graph with thresholds  $t : V(G) \rightarrow \mathbb{N}$  and seed set  $S \subseteq V(G)$ .

## Definition

Let  $Y \subseteq V(G)$ . If, by immunizing the vertices of  $Y$ , the infection in  $(G, t)$  is restricted to **at most**  $k$  vertices, we say that  $Y$  is a  **$k$ -restricting set**.

## Definition

The  **$k$ -restricting number of**  $(G, t)$ , denoted by

$$\mathfrak{R}(G, t, k)$$

, is size of a **minimum  $k$ -restricting set** of  $(G, t)$ .


## Influence Immunization Bounding (cont.)

Consider the graph on the right.

### Example

$Y = \{c, h\}$  is a 3-restricting set of  $(G, t)$ .

$$\mathfrak{R}(G, t, k = 3) = 2.$$



## Influence Immunization Bounding (cont.)

Consider the graph on the right.

### Example

$Y = \{c, h\}$  is a 3-restricting set of  $(G, t)$ .


$$\mathfrak{R}(G, t, k = 3) = 2.$$

### Definition

If  $k = |S|$ , then we say that  $\mathfrak{R}(G, t, k = |S|)$  is the **total restricting number** of  $(G, t)$ , and denote it by  $\mathfrak{R}_T(G, t)$ .

### Example

$$\mathfrak{R}_T(G, t) = \mathfrak{R}(G, t, k = 3) = 2.$$



## Influence Immunization Bounding (cont.)

Consider the graph on the right.

### Example

$Y = \{c, h\}$  is a 3-restricting set of  $(G, t)$ .

$$\mathfrak{R}(G, t, k = 3) = 2.$$

### Definition

If  $k = |S|$ , then we say that  $\mathfrak{R}(G, t, k = |S|)$  is the **total restricting number** of  $(G, t)$ , and denote it by  $\mathfrak{R}_T(G, t)$ .


### Example

$$\mathfrak{R}_T(G, t) = \mathfrak{R}(G, t, k = 3) = 2.$$

### Remark

For any suitable  $k$ , we have that

$$\mathfrak{R}(G, t, k) \leq \mathfrak{R}_T(G, t)$$





- Fedor V. Fomin, Petr A. Golovach, and Janne H. Korhonen (2013). “On the Parameterized Complexity of Cutting a Few Vertices from a Graph”. In: *Mathematical Foundations of Computer Science 2013*. Ed. by Krishnendu Chatterjee and Jirí Sgall. Berlin, Heidelberg: Springer Berlin Heidelberg, pp. 421–432. ISBN: 978-3-642-40313-2
- Ara Hayrapetyan et al. (2005). “Unbalanced Graph Cuts”. In: *Algorithms – ESA 2005*. Springer Berlin Heidelberg, pp. 191–202. ISBN: 9783540319511. DOI: 10.1007/11561071\_19. URL: [http://dx.doi.org/10.1007/11561071\\_19](http://dx.doi.org/10.1007/11561071_19)
- Hermish Mehta and Daniel Reichman (2022). *Local treewidth of random and noisy graphs with applications to stopping contagion in networks*. eprint: [arXiv:2204.07827](https://arxiv.org/abs/2204.07827)


- Firefighter is very conceptually related (Anshelevich et al. 2010);
- Game theoretical approach (Aspnes, Chang, and Yampolskiy 2006; P.-A. Chen, David, and Kempe 2010; Moscibroda, Schmid, and Wattenhofer 2006; Meier et al. 2014);
- Spectral graph theory (Ahmad et al. 2020; C. Chen et al. 2016; Chakrabarti et al. 2008; Tariq et al. 2017).





# Our Results

## Definition


Let  $G = (V, E)$  be a graph and  $S \subseteq V(G)$  a seed set of  $G$ . Then  $P = v_1 v_2 \dots v_k$  is a  **$S$ -alternating path** of  $G$  if  $P$  is a path of  $G$  with *at least 3 vertices* and the vertices of  $P$  alternate with respect to their membership in  $S$ .



- **Main observation:** for each  $S$ -alternating path of length 4, we need only one vertex to inhibit the infection.



**Figure:** When the  $S$ -alternating path has length 4, we can inhibit the infection by immunizing only one vertex.




(a) The infection stops by immunizing any vertex. The immunized vertex is shown in blue.



(b) When the  $S$ -alternating path has length 3 and starts with a uninfected vertex, the infection does not spread.

- We can split the path into  $S$ -alternating paths of length 4.



**Figure:** Splitting a bigger  $S$ -alternating path into pieces of length 4 starting with infected vertices.

## Proposition

Let  $G = P_n$  with  $t(v) = 2$  for all  $v \in V(G)$ . Then, for any  $k \in \mathbb{N}$ ,



$$Im(G, t, k) \leq In(G, t) \leq \lceil \frac{n}{4} \rceil$$

# Complete graphs with $t(v) = c$

## Proposition


Let  $G \cong K_n$  be a complete graph on  $n$  vertices with thresholds  $t(v) = c$  for all  $v \in V(G)$ ,  $S \subseteq V(G)$  a seed set of  $G$ , and  $k \in \mathbb{N}$ . Then:

$$Im(G, t, k) = \begin{cases} \min\{|S| - c + 1, n - k\}, & \text{if } |S| \geq c \\ 0, & \text{otherwise.} \end{cases}$$



## Definition

A graph  $G$  is *chordal* if every cycle  $C$  of length at least 4 in  $G$  has a *chord*: an edge between non-consecutive vertices of  $C$ .



Chordal graphs are a superclass of several important graph classes:

- Trees;
- Split Graphs;
- Interval Graphs.




## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

### Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

### Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




- Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .




➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .



➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Definition

Given a graph  $G$ , a vertex  $v \in V(G)$  is a *simplicial vertex* of  $G$  if  $N_G(v)$  is a clique.

## Definition

Given a graph  $G$ , an ordering  $v_1, \dots, v_n$  of  $V(G)$  is a *perfect elimination ordering* if for all  $i \in [n]$ ,  $v_i$  is a simplicial vertex of  $G[\{v_1, \dots, v_i\}]$ .



➤ Perfect elimination ordering:  $f, e, d, c, b, a$ .

## Theorem (Dirac 1961)

*A graph  $G$  is chordal if and only if  $G$  has a perfect elimination ordering.*

## Theorem (Dirac 1961)


*Let  $G$  be a graph. If  $G$  is chordal and not complete, then  $G$  has two non-adjacent simplicial vertices.*

## Theorem (Dirac 1961)

*If a graph  $G$  is chordal, then any induced subgraph of  $G$  is chordal.*

## Definition

Given a graph  $G$ , a set  $D \subseteq V(G)$  is a *dominating set* if every vertex from  $V(G) \setminus D$  has at least one neighbor in  $D$ .




$k$ -DOMINATING SET is:

- W[1]-hard for chordal graphs parameterized by  $k$  (Liu and Song 2009);
- NP-hard for split graphs (Bertossi 1984).



## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \emptyset$ ;
- $U = \emptyset$ ;

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b\};$
- $U = \{a\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b, d, e\};$
- $U = \{a, c\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b, d, e\};$
- $U = \{a, c, f\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

## Proposition

INFLUENCE IMMUNIZATION BOUNDING is  $W[1]$ -hard parameterized by the maximum number of immunized vertices  $l$  on chordal graphs. Moreover, it is NP-complete on split graphs.




- $S = \{b, d, e\};$
- $U = \{a, c, f\};$

Let  $\langle G, k \rangle$  be an instance of  $k$ -DOMINATING SET in which  $G$  is chordal.

- 1 Initialize  $S = \emptyset$  and  $U = \emptyset$ ;
- 2 Find a simplicial vertex  $s$  of  $G$ ;
- 3 Update  $S = S \cup N_G(s)$  and  $U = U \cup \{s\}$ ;
- 4 Repeat steps (2-5) on  $G[V(G) \setminus N_G[s]]$ .
- 5 Define  $t(v) = d_G(v)$  for all  $v$ ;

- $G$  has a dominating set of size  $\leq k$  if and only if  $(G, t, S)$  has a  $|S|$ -restricting set of size  $l \leq k$ .




- IIB is  $W[1]$ -hard for chordal graphs parameterized by  $l$ , and NP-complete for split graphs.

# Hardness for Bipartite Graphs

Cordasco, Gargano, and Rescigno 2023 showed that IIB is  $W[2]$ -hard parameterized by  $|S| + I$  even on bipartite graphs.

## Proposition

*IIB is NP-complete on bipartite graphs even if  $A$  is entirely susceptible and  $B$  is entirely infected.*



➤ Reduction from SET COVER.

- Universe set  $\mathcal{U} = \{a_1, a_2, \dots, a_n\}$ ;
- $\mathcal{S} = \{S_1, S_2, \dots, S_m\}$ ;
- Parameter  $c \in \mathbb{N}$ .


- 1 Create a bipartite graph  $G$  such that  $V(G) = \mathcal{U} \cup \mathcal{S}$  and  $E(G) = \{a_i S_j \mid a_i \in S_j\}$ ;
- 2 Define  $k = |\mathcal{S}|$ ,  $l = c$ , and set the seed set  $S = \mathcal{S}$ ;
- 3 Set  $t(a_i) = d_G(a_i)$ , for all  $i \in [n]$ .



# Hardness for Bipartite Graphs

## Example

- $\mathcal{U} = \{1, 2, 3, 4, 5\}$ ;
- $\mathcal{S} = \{S_1 = \{1, 2, 3\}, S_2 = \{2, 4\}, S_3 = \{3, 4\}, S_4 = \{4, 5\}\}$ ; and
- $c = 2$ .




# Hardness for Bipartite Graphs

## Example

- $\mathcal{U} = \{1, 2, 3, 4, 5\}$ ;
- $\mathcal{S} = \{S_1 = \{1, 2, 3\}, S_2 = \{2, 4\}, S_3 = \{3, 4\}, S_4 = \{4, 5\}\}$ ; and
- $c = 2$ .

## Proposition

$(\mathcal{U}, \mathcal{S})$  has a set cover of size  $\leq c$  if and only if  $(G, t)$  has a  $|\mathcal{S}|$ -restricting set of size  $\leq c$ .



## Definition

A graph  $G$  is planar if it can be drawn on the plane without crossing edges.

## Theorem (Wagner 1937)

*A graph  $G$  is planar if and only if  $G$  does not have a  $K_5$  minor nor a  $K_{3,3}$  minor.*

- In RESTRICTED 3-SAT, we are given a 3-Sat CNF formula in which every variable **occurs exactly 3 times**: twice as positive and once as negative.
  - R-3-SAT is NP-complete (Dahlhaus et al. 1994).

## Example

$$\varphi = (u \vee v \vee \overline{w}) \wedge (\overline{u} \vee v \vee x) \wedge (u \vee \overline{x} \vee \overline{y}) \wedge (\overline{v} \vee w \vee x) \wedge (w \vee z \vee y) \wedge (y \vee \overline{z}) \wedge (z)$$

# Hardness for Planar Bipartite Subcubic Graphs

- In RESTRICTED 3-SAT, we are given a 3-Sat CNF formula in which every variable **occurs exactly 3 times**: twice as positive and once as negative.
  - R-3-SAT is NP-complete (Dahlhaus et al. 1994).

## Example


$$\varphi = (u \vee v \vee \overline{w}) \wedge (\overline{u} \vee v \vee x) \wedge (u \vee \overline{x} \vee \overline{y}) \wedge (\overline{v} \vee w \vee x) \wedge (w \vee z \vee y) \wedge (y \vee \overline{z}) \wedge (z)$$

## Proposition

$\text{R-3-SAT} \leq_P (\text{Planar Bipartite Subcubic}) \text{ IIB.}$

# Hardness for Planar Bipartite Subcubic Graphs

- Given a R-3-SAT formula  $\varphi$ , let:
  - $V(\varphi)$  the set of variables of  $\varphi$ ;
  - $\mathcal{C}(\varphi)$  the set of clauses of  $\varphi$ .
- Let's create a graph  $G_\varphi$  with thresholds  $t_\varphi$ . For each variable  $x \in V(\varphi)$ , we are going to add the following gadget to  $G_\varphi$ :




# Hardness for Planar Bipartite Subcubic Graphs

- For each clause  $C \in \mathcal{C}(\varphi)$ , we are going to add a vertex in  $G_\varphi$  and connect it to its literals, setting  $t_\varphi(C) = |C|$ .


## Example

$$C = (u \vee v \vee \overline{w}).$$



# Hardness for Planar Bipartite Subcubic Graphs

- Example of  $G_\varphi$  for the R-3-SAT formula  
 $\varphi = (u \vee v \vee \bar{w}) \wedge (\bar{u} \vee v \vee x) \wedge (u \vee \bar{x} \vee \bar{y}) \wedge$   
 $(\bar{v} \vee w \vee x) \wedge (w \vee z \vee y) \wedge (y \vee \bar{z}) \wedge (z).$





- Suppose  $\varphi$  has a satisfying assignment  $\mathcal{S} : V(\varphi) \rightarrow \{\text{TRUE}, \text{FALSE}\}$ .

## Proposition

$Y = (\{x \mid \mathcal{S}(x) = \text{TRUE}\} \cup \{\bar{x} \mid \mathcal{S}(x) = \text{FALSE}\})$  is a  $(2|V(\varphi)|)$ -restricting set for  $(G_\varphi, t_\varphi)$  and  $|Y| \leq |V(\varphi)|$ .

- Suppose  $\varphi$  has a satisfying assignment  $\mathcal{S} : V(\varphi) \rightarrow \{\text{TRUE}, \text{FALSE}\}$ .

## Proposition

$Y = (\{x \mid \mathcal{S}(x) = \text{TRUE}\} \cup \{\bar{x} \mid \mathcal{S}(x) = \text{FALSE}\})$  is a  $(2|V(\varphi)|)$ -restricting set for  $(G_\varphi, t_\varphi)$  and  $|Y| \leq |V(\varphi)|$ .

- Now, suppose  $Y$  is a  $(2|V(\varphi)|)$ -restricting set for  $(G_\varphi, t_\varphi)$  and  $|Y| \leq |V(\varphi)|$ .

## Proposition


For every  $x \in V(\varphi)$ , either  $x \in Y$  or  $\bar{x} \in Y$ .

- Thus, we can build a satisfying assignment for  $\varphi$  from  $Y$ .

## Proposition

$G_\varphi$  is planar bipartite subcubic.

# Conclusion and Future Work



### Problem

*Investigate the complexity of IIB on other graph classes, such as cacti and  $k$ -regular.*

### Problem

*Introduce and study directed and reversible versions of IIB.*






### Problem

*Study graph structural parameters and modulators such as  $vc(G)$ ,  $fvs(G)$ ,  $td(G)$  and others.*






### Problem





*Find polynomial algorithms or show NP-completeness for total restriction.*

Thank you.





-  Ahmad, Muhammad et al. (May 2020). “Combinatorial trace method for network immunization”. In: *Information Sciences* 519, pp. 215–228. ISSN: 0020-0255. DOI: 10.1016/j.ins.2020.01.037. URL: <http://dx.doi.org/10.1016/j.ins.2020.01.037>.
-  Anshelevich, Elliot et al. (Dec. 2010). “Approximability of the Firefighter Problem: Computing Cuts over Time”. In: *Algorithmica* 62.1–2, pp. 520–536. ISSN: 1432-0541. DOI: 10.1007/s00453-010-9469-y. URL: <http://dx.doi.org/10.1007/s00453-010-9469-y>.
-  Araújo, Rafael and Rudini Sampaio (May 2023). “Domination and convexity problems in the target set selection model”. In: *Discrete Applied Mathematics* 330, pp. 14–23. ISSN: 0166-218X. DOI: 10.1016/j.dam.2022.12.021. URL: <http://dx.doi.org/10.1016/j.dam.2022.12.021>.
-  Aspnes, James, Kevin Chang, and Aleksandr Yampolskiy (Sept. 2006). “Inoculation strategies for victims of viruses and the sum-of-squares partition problem”. In: *Journal of Computer and System Sciences* 72.6, pp. 1077–1093. ISSN: 0022-0000. DOI: 10.1016/j.jcss.2006.02.003. URL: <http://dx.doi.org/10.1016/j.jcss.2006.02.003>.
-  Bertossi, Alan A (July 1984). “Dominating sets for split and bipartite graphs”. en. In: *Inf. Process. Lett.* 19.1, pp. 37–40.










- 
- Chakrabarti, Deepayan et al. (Jan. 2008). “Epidemic thresholds in real networks”. In: *ACM Transactions on Information and System Security* 10.4, pp. 1–26. ISSN: 1557-7406. DOI: 10.1145/1284680.1284681. URL: <http://dx.doi.org/10.1145/1284680.1284681>.
- 
- Chen, Po-An, Mary David, and David Kempe (June 2010). “Better vaccination strategies for better people”. In: *Proceedings of the 11th ACM conference on Electronic commerce. EC '10*. ACM, pp. 179–188. DOI: 10.1145/1807342.1807370. URL: <http://dx.doi.org/10.1145/1807342.1807370>.
- 
- Chen, Chen et al. (Jan. 2016). “Node Immunization on Large Graphs: Theory and Algorithms”. In: *IEEE Transactions on Knowledge and Data Engineering* 28.1, pp. 113–126. ISSN: 1041-4347. DOI: 10.1109/tkde.2015.2465378. URL: <http://dx.doi.org/10.1109/TKDE.2015.2465378>.
- 
- Coleman, James, Elihu Katz, and Herbert Menzel (Dec. 1957). “The diffusion of an innovation among physicians”. In: *Sociometry* 20.4, p. 253.
- 
- Cordasco, Gennaro, Luisa Gargano, and Adele A. Rescigno (Apr. 2023). “Immunization in the Threshold Model: A Parameterized Complexity Study”. In: *Algorithmica* 85.11, pp. 3376–3405. ISSN: 1432-0541. DOI: 10.1007/s00453-023-01118-y.

-  Dahlhaus, E. et al. (Aug. 1994). "The Complexity of Multiterminal Cuts". In: *SIAM Journal on Computing* 23.4, pp. 864–894. ISSN: 1095-7111. DOI: 10.1137/s0097539792225297. URL: <http://dx.doi.org/10.1137/s0097539792225297>.
-  Dirac, G A (Apr. 1961). "On rigid circuit graphs". en. In: *Abh. Math. Semin. Univ. Hambg.* 25.1-2, pp. 71–76.
-  Dreyer, Paul A. and Fred S. Roberts (2009). "Irreversible k-threshold processes: Graph-theoretical threshold models of the spread of disease and of opinion". In: *Discrete Applied Mathematics* 157.7, pp. 1615–1627. ISSN: 0166-218X. DOI: <https://doi.org/10.1016/j.dam.2008.09.012>. URL: <https://www.sciencedirect.com/science/article/pii/S0166218X08004393>.
-  Flocchini, Paola et al. (Apr. 2003). "On time versus size for monotone dynamic monopolies in regular topologies". In: *Journal of Discrete Algorithms* 1.2, pp. 129–150. ISSN: 1570-8667. DOI: 10.1016/s1570-8667(03)00022-4. URL: [http://dx.doi.org/10.1016/S1570-8667\(03\)00022-4](http://dx.doi.org/10.1016/S1570-8667(03)00022-4).

- 
- Fomin, Fedor V., Petr A. Golovach, and Janne H. Korhonen (2013). “On the Parameterized Complexity of Cutting a Few Vertices from a Graph”. In:
- Mathematical Foundations of Computer Science 2013*
- . Ed. by Krishnendu Chatterjee and Jirí Sgall. Berlin, Heidelberg: Springer Berlin Heidelberg, pp. 421–432. ISBN: 978-3-642-40313-2.

 Hayrapetyan, Ara et al. (2005). “Unbalanced Graph Cuts”. In: *Algorithms – ESA 2005*. Springer Berlin Heidelberg, pp. 191–202. ISBN: 9783540319511. DOI: 10.1007/11561071\_19. URL: [http://dx.doi.org/10.1007/11561071\\_19](http://dx.doi.org/10.1007/11561071_19). Keiler, Lucas et al. (Oct. 2023). “Target set selection with maximum activation time”. In: *Discrete Applied Mathematics* 338, pp. 199–217. ISSN: 0166-218X. DOI: 10.1016/j.dam.2023.06.004. URL: <http://dx.doi.org/10.1016/j.dam.2023.06.004>. Kempe, David, Jon Kleinberg, and Éva Tardos (2003). “Maximizing the spread of influence through a social network”. In: *Proceedings of the Ninth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. KDD '03. Washington, D.C.: Association for Computing Machinery, pp. 137–146. ISBN: 1581137370. DOI: 10.1145/956750.956769. URL: <https://doi.org/10.1145/956750.956769>. Liu, Chunmei and Yinglei Song (July 2009). “Parameterized dominating set problem in chordal graphs: complexity and lower bound”. In: *J. Comb. Optim.* 18.1, pp. 87–97.

- 
- Marcilon, Thiago and Rudini Sampaio (Jan. 2018). “The maximum time of 2-neighbor bootstrap percolation: Complexity results”. In:
- Theoretical Computer Science*
- 708, pp. 1–17. ISSN: 0304-3975. DOI: 10.1016/j.tcs.2017.10.014. URL:
- <http://dx.doi.org/10.1016/j.tcs.2017.10.014>
- .
- 
- 
- Mehta, Hermish and Daniel Reichman (2022).
- Local treewidth of random and noisy graphs with applications to stopping contagion in networks*
- . eprint:
- [arXiv:2204.07827](https://arxiv.org/abs/2204.07827)
- .
- 
- 
- Meier, Dominic et al. (Apr. 2014). “On the Windfall and price of friendship: Inoculation strategies on social networks”. In:
- Computer Networks*
- 62, pp. 221–236. ISSN: 1389-1286. DOI: 10.1016/j.bjp.2013.12.004. URL:
- <http://dx.doi.org/10.1016/j.bjp.2013.12.004>
- .
- 
- 
- Moscibroda, Thomas, Stefan Schmid, and Rogert Wattenhofer (July 2006). “When selfish meets evil: byzantine players in a virus inoculation game”. In:
- Proceedings of the twenty-fifth annual ACM symposium on Principles of distributed computing*
- . PODC06. ACM, pp. 35–44. DOI: 10.1145/1146381.1146391. URL:
- <http://dx.doi.org/10.1145/1146381.1146391>
- .
- 
- 
- Ryan, Bryce and Neal Gross (1950).
- Acceptance and diffusion of hybrid corn seed in two Iowa communities*
- .
- 
- 
- Tariq, Juvaria et al. (2017).
- Scalable Approximation Algorithm for Network Immunization*
- . DOI: 10.48550/ARXIV.1711.00784. URL:
- <https://arxiv.org/abs/1711.00784>
- .

-  Wagner, K (Dec. 1937). “Über eine Eigenschaft der ebenen Komplexe”. de. In: *Math. Ann.* 114.1, pp. 570–590.