

2006 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

3. Consider the following incomplete class that stores information about a customer, which includes a name and unique ID (a positive integer). To facilitate sorting, customers are ordered alphabetically by name. If two or more customers have the same name, they are further ordered by ID number. A particular customer is "greater than" another customer if that particular customer appears later in the ordering than the other customer.

```
public class Customer
{
    // constructs a Customer with given name and ID number
    public Customer(String name, int idNum)
    { /* implementation not shown */ }

    // returns the customer's name
    public String getName()
    { /* implementation not shown */ }

    // returns the customer's id
    public int getID()
    { /* implementation not shown */ }

    // returns 0 when this customer is equal to other;
    //   a positive integer when this customer is greater than other;
    //   a negative integer when this customer is less than other
    public int compareCustomer(Customer other)
    { /* to be implemented in part (a) */ }

    // There may be fields, constructors, and methods that are not shown.
}
```

- (a) Write the `Customer` method `compareCustomer`, which compares this customer to a given customer, `other`. Customers are ordered alphabetically by name, using the `compareTo` method of the `String` class. If the names of the two customers are the same, then the customers are ordered by ID number. Method `compareCustomer` should return a positive integer if this customer is greater than `other`, a negative integer if this customer is less than `other`, and 0 if they are the same.

For example, suppose we have the following `Customer` objects.

```
Customer c1 = new Customer("Smith", 1001);
Customer c2 = new Customer("Anderson", 1002);
Customer c3 = new Customer("Smith", 1003);
```

The following table shows the result of several calls to `compareCustomer`.

<u>Method Call</u>	<u>Result</u>
<code>c1.compareCustomer(c1)</code>	0
<code>c1.compareCustomer(c2)</code>	a positive integer
<code>c1.compareCustomer(c3)</code>	a negative integer

2006 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

Complete method `compareCustomer` below.

```
// returns 0 when this customer is equal to other;  
//    a positive integer when this customer is greater than other;  
//    a negative integer when this customer is less than other  
public int compareCustomer(Customer other)
```

2006 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

- (b) A company maintains customer lists where each list is a sorted array of customers stored in ascending order by customer. A customer may appear in more than one list, but will not appear more than once in the same list.

Write method `prefixMerge`, which takes three array parameters. The first two arrays, `list1` and `list2`, represent existing customer lists. It is possible that some customers are in both arrays. The third array, `result`, has been instantiated to a length that is no longer than either of the other two arrays and initially contains `null` values. Method `prefixMerge` uses an algorithm similar to the merge step of a Mergesort to fill the array `result`. Customers are copied into `result` from the beginning of `list1` and `list2`, merging them in ascending order until all positions of `result` have been filled. Customers who appear in both `list1` and `list2` will appear at most once in `result`.

For example, assume that three arrays have been initialized as shown below.

list1	Arthur 4920	Burton 3911	Burton 4944	Franz 1692	Horton 9221	Jones 5554	Miller 9360	Nguyen 4339
	[0]	[1]	[2]	[3]	[4]	[5]	[6]	[7]

list2	Aaron 1729	Baker 2921	Burton 3911	Dillard 6552	Jones 5554	Miller 9360	Noble 3335
	[0]	[1]	[2]	[3]	[4]	[5]	[6]

result	null	null	null	null	null	null
	[0]	[1]	[2]	[3]	[4]	[5]

In this example, the array `result` must contain the following values after the call `prefixMerge(list1, list2, result)`.

result	Aaron 1729	Arthur 4920	Baker 2921	Burton 3911	Burton 4944	Dillard 6552
	[0]	[1]	[2]	[3]	[4]	[5]

In writing `prefixMerge`, you may assume that `compareCustomer` works as specified, regardless of what you wrote in part (a). Solutions that create any additional data structures holding multiple objects (e.g., arrays, `ArrayLists`, etc.) will not receive full credit.

2006 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

Complete method `prefixMerge` below.

```
// fills result with customers merged from the
// beginning of list1 and list2;
// result contains no duplicates and is sorted in
// ascending order by customer
// precondition:  result.length > 0;
//                  list1.length >= result.length;
//                  list1 contains no duplicates;
//                  list2.length >= result.length;
//                  list2 contains no duplicates;
//                  list1 and list2 are sorted in
//                  ascending order by customer
// postcondition: list1, list2 are not modified
public static void prefixMerge(Customer[] list1,
                               Customer[] list2,
                               Customer[] result)
```