



COPERNICUS MASTER
IN DIGITAL EARTH

With the support of the
Erasmus+ Programme
of the European Union



How reliable are SEN2 cloud detection algorithms? Global uncertainty estimation using Deep Kernel Learning.

Cesar Luis Aybar Camacho

Erasmus Mundus Joint Master Degree Programme
Copernicus Master in Digital Earth
Specialization track GeoData Science

Vannes, France, 2022

Acknowledges



consortium



COPERNICUS MASTER
IN DIGITAL EARTH

With the support of the Erasmus+ Programme of the European Union



Problem definition

```
// Map the function over one month of data and take the median.  
// Load Sentinel-2 TOA reflectance data.  
var dataset = ee.ImageCollection('COPERNICUS/S2')  
    .filterDate('2018-01-01', '2019-01-31')  
    // Pre-filter to get less cloudy granules.  
    .filter(ee.Filter.lt('CLOUDY_PIXEL_PERCENTAGE', 1));  
  
var rgbVis = {  
  min: 0.0,  
  max: 0.3,  
  bands: ['B4', 'B3', 'B2'],  
};  
  
Map.setCenter(-9.1695, 38.6917, 12);  
Map.addLayer(dataset.median().divide(10000), rgbVis, 'RGB');
```

Valencia, Spain



Problem definition

```
// Map the function over one month of data and take the median.  
// Load Sentinel-2 TOA reflectance data.  
var dataset = ee.ImageCollection('COPERNICUS/S2')  
    .filterDate('2018-01-01', '2019-01-31')  
    // Pre-filter to get less cloudy granules.  
    .filter(ee.Filter.lt('CLOUDY_PIXEL_PERCENTAGE', 1));  
  
var rgbVis = {  
  min: 0.0,  
  max: 0.3,  
  bands: ['B4', 'B3', 'B2'],  
};  
  
Map.setCenter(-9.1695, 38.6917, 12);  
Map.addLayer(dataset.median().divide(10000), rgbVis, 'RGB');
```

Iquitos, Peru



Problem definition

```
// Map the function over one month of data and take the median.  
// Load Sentinel-2 TOA reflectance data.  
var dataset = ee.ImageCollection('COPERNICUS/S2')  
    .filterDate('2018-01-01', '2019-01-31')  
    // Pre-filter to get less cloudy granules.  
    .filter(ee.Filter.lt('CLOUDY_PIXEL_PERCENTAGE', 1));  
  
var rgbVis = {  
  min: 0.0,  
  max: 0.3,  
  bands: ['B4', 'B3', 'B2'],  
};  
  
Map.setCenter(-9.1695, 38.6917, 12);  
Map.addLayer(dataset.median().divide(10000), rgbVis, 'RGB');
```

Huancayo, Peru



Problem definition

Is it possible to predict cloud cover more accurately?

Problem definition

Is it possible to predict cloud cover more accurately?

How do cloud cover algorithms work?


Problem definition

Is it possible to predict cloud cover more accurately?

How do cloud cover algorithms work?


What is a cloud?

What is a cloud?




A cloud is a mass of water drops or ice crystals suspended in the atmosphere.

What is a cloud?




A cloud is a mass of water drops or ice crystals suspended in the atmosphere.

What is a cloud?




Cloud classification - CloudSat (Ceccaldi, et al. 2020)

How do cloud cover algorithms work?



Context



Geographical distribution reference cloud detection datasets for Sentinel-2
(Skakun et al. 2022).

<https://cloudsen12.github.io/>

CloudSEN12 - Team ;3

	Herrera Fernando
	LLactayo Valeria
	Cuenca Nicole
	Fernando Prudencio
	Gomez-Chova Luis

	Loja Jhomira
	Bautista Lesly
	Inga Joselyn
	Yali Roy


	Ysuhuaylas Luis
	Diaz Lissette
	Espinoza Wendy
	Aybar Cesar
	Sudmanns Martin

	Gonzales Karen
	Flores Angie
	Esquivel Antony
	Mateo-Garcia Gonzalo

CloudSEN12 team


CloudSEN12 - Map

Distribution of Sentinel-2 reference scenes




Geographical distribution reference cloud detection datasets for Sentinel-2
(Skakun et al. 2022).

CloudSEN12 - Map






CloudSEN12 spatial distribution

CloudSEN12 - Data preparation




- Merging of different spatio-temporal datasets to use as predictors.
- Semi-automatic selection of ROIs (5090x5090 m.)

CloudSEN12 - Data Selection



- Each ROI have multiple IPs. We manually select five IPs considering the background, cloud type, and cloud coverage.


CloudSEN12 - Labeling



- Add to each IP the results of 6 different CD algorithms. In addition, each ROI counts with manual labeling that can be of type: high-quality, scribble, or no annotation.


CloudSEN12 - Labels

ROI 1746




CloudSEN12 - Labels

ROI 2507



CloudSEN12 - Labels

ROI 4683



Methodology

- ➊ The **cloudSEN12 high-quality dataset** is used only for this experiment D ; pixel-by-pixel cloud masking is converted to cloud cover percentages in order to perform a regression task.
- ➋ The dataset of S2 L1C $\{x_1, x_2, \dots, x_n\}$ and corresponding cloud cover percentages $\{\gamma_1, \gamma_2, \dots, \gamma_n\}$ is splitted in train (D_{train}), validation (D_{val}), and test (D_{test}) dataset.
- ➌ **Experiment 01:** Convolutional Neural Network (CNN) for regression.


Methodology

- ➊ The **cloudSEN12 high-quality dataset** is used only for this experiment D ; pixel-by-pixel cloud masking is converted to cloud cover percentages in order to perform a regression task.
- ➋ The dataset of S2 L1C $\{x_1, x_2, \dots, x_n\}$ and corresponding cloud cover percentages $\{\gamma_1, \gamma_2, \dots, \gamma_n\}$ is splitted in train (D_{train}), validation (D_{val}), and test (D_{test}) dataset.
- ➌ **Experiment o2:** CNN with a GP header layer.
 - Residual CNN $f_\theta : x \rightarrow R^J$ with feature space dimensionality J and parameters θ .
 - Exact GP header with parameters $\phi = \{l, s\}$ where l and s are kernel hyperparameters.

Methodology

- ➊ The **cloudSEN12 high-quality dataset** is used only for this experiment D ; pixel-by-pixel cloud masking is converted to cloud cover percentages in order to perform a regression task.
- ➋ The dataset of S2 L1C $\{x_1, x_2, \dots, x_n\}$ and corresponding cloud cover percentages $\{\gamma_1, \gamma_2, \dots, \gamma_n\}$ is splitted in train (D_{train}), validation (D_{val}), and test (D_{test}) dataset.
- ➌ **Experiment o3:** Variational Deep Kernel Learning.
 - Residual NN $f_\theta : x \rightarrow R^J$ with feature space dimensionality J and parameters θ .
 - Approximate GP header with parameters $\phi = \{l, s, \omega\}$ where l and s are kernel hyperparameters, ω GP variational parameters (including m inducing point locations Z).
 - Using a random subset of p points of our training data, $X^{init} \subset X$, compute; **Initial inducing points:** Use found centroids as initial inducing point locations Z in GP. **Initial length scale:** set as 1.

Experiment 01



Experiment o2 - Gaussian processes



Definition

A Gaussian process (GP) is a collection of random variables, any finite number of which have a joint Gaussian distribution.


Nonparametric Regression Model Prior:

$f(x) \sim \mathcal{GP}(m(x), k(x, x'))$, meaning $(f(x_1), \dots, f(x_N)) \sim \mathcal{N}(\mu, K)$, with $\mu_i = m(x_i)$ and $K_{ij} = \text{cov}(f(x_i), f(x_j)) = k(x_i, x_j)$.

$$\underbrace{p(f(x) | \mathcal{D})}_{\text{GP posterior}} \propto \underbrace{p(\mathcal{D} | f(x))}_{\text{Likelihood}} \underbrace{p(f(x))}_{\text{GP prior}}$$




Experiment o2 - Gaussian processes



Experiment o2 - Gaussian processes

RBF KERNEL

$$\sigma^2 \exp\left(-\frac{\|t-t'\|^2}{2l^2}\right)$$

Variance σ = 0.8
Length l = 1.58


PERIODIC

$$\sigma^2 \exp\left(-\frac{2 \sin^2(\pi|t-t'|/p)}{l^2}\right)$$


Variance σ = 0.4
Length l = 0.8
Periodicity p = 0.5

LINEAR


$$\sigma_b^2 + \sigma^2(t - c)(t' - c)$$

Variance σ = 0.67
Variance σ_b = 0.8
Offset c = -2

Experiment o2 - Gaussian processes




Experiment o3 - Stochastic Variational DKL




References

-  Fomin FV, Grandoni F & Kratsch D, 2009, *A note on the complexity of minimum dominating set*, Journal of Discrete Algorithms, **4**(2), pp. 209–214.
-  Grobler PJP & Mynhardt CM, 2009, *Secure domination critical graphs*, Discrete Mathematics, **309**, pp. 5820–5827.
-  Van Rooij JMM & Bodlaender HL, 2011, *Exact algorithms for dominating set*, Discrete Applied Mathematics, **159**, pp. 2147–2164.



Muchas gracias


Context - II



- Cloud labels created by human photo-interpretation and ground-based cameras.

Skakun et al. 2022



Context - II



Skakun et al. 2022


- Cloud labels created by human photo-interpretation and ground-based cameras.
- High class imbalance.

Context - II




- Cloud labels created by human photo-interpretation, active learning and ground-based cameras.
- High class imbalance.
- **The quality of some datasets is poor.**

Context - II




- Cloud labels created by human photo-interpretation and ground-based cameras.
- High class imbalance.
- **The quality of some datasets is poor.**
- Created by ***closed science practices***.
- No temporal features.

Quality Control



Dataset Structure



Technical validation

