CSC4200/5200 – COMPUTER NETWORKING

NETWORK PERFORMANCE

Instructor: Susmit Shannigrahi
sshannigrahi@tntech.edu

Tennessee TECH

Breakout - Questions

- Slide 8
- Slide 15
- Slide 19

Recap - Circuit Switching – TDM and FDM



Circuit Switching

- Dedicated resource divided among participants
- Requires setup, guaranteed performance (unless the link breaks)

Packet Switching

- Shared resource
- Use small chunks of data (packets), send as soon as possible
- Store-and-forward packets

Frequency Division Multiplexing for Circuit Switching



wikipedia

Time Division Multiplexing for Circuit Switching

wikipedia

Packet Switching



Statistical Multiplexing for Packet Switching



- Ensures that slots will not be wasted
- Introduces queuing delay
- :
  - What actions can you take when queue becomes full? There may be many choices.
  - Your choice would have profound implications on performance

How many users can you support?



- 1Mbps link
  - Users are active 10% of the time
  - 10 Simultaneous users = full capacity

Circuit switching = 10 users
Packet switching with 35 users < Probability of 10 sim. Users < 0.0004

https://math.stackexchange.com/questions/918861/probability-problem-in-networking



Performance - Bandwidth



Bits transmitted at a particular bandwidth can be regarded as having some width:

(a) bits transmitted at 1Mbps (each bit 1 μs wide);

(b) bits transmitted at 2Mbps (each bit 0.5 μs wide).

Packets are made of bits – each bit need some time to be processed at the router. This is transmission delay!

Performance - Latency

- Latency = Propagation Delay + Transmission Delay + Queuing Delay
- Propagation = Distance/Speed Of Light (in Copper or Fiber)
- Transmit = Size/Bandwidth



Performance – Queuing Delay

- R: link bandwidth (bps)
- L: packet length (bits)
- A: Average packet arrival rate
- Traffic delay = AL/R

AL/R ~ 0

AL/R ~ 1

Performance – Terminology

- Bits = b
- Bytes = B
- Kilobytes = KB (1024 Bytes or 1000Bytes)
- Megabytes = MB (1024KB or 1000KB)

- Ask ECE folks = 1000, 1Mbps = 1000*1000Bps

- Ask CS folks = 1024, 1MB = 1024*1024Bytes

Performance – Example

- Breakout
  - Calculate the total time required to transfer a 1000-KB file using 1KB packets. Assuming bandwidth is 1.5 Mbps, the RTT of 50 ms, an initial 2 × RTT of “handshaking” before any data is sent.

    Delay = Handshake + Transmission + Propagation + Queuing

Bandwidth x Delay Product

Capacity of a network pipe = Bandwidth (bits) x Delay (Seconds) (a.k.a RTT or Round Trip Delay)

This is the amount of bits that a pipe can hold!

Bandwidth x Delay Product - Example



Bandwidth = 50Mbps
Latency = 100ms

Bandwidth x Delay = $50x10^{6}x100x10^{-3} = 5x10^{6}$ bits = 625 kilobytes

Bandwidth x Delay - Some more examples



Bandwidth = 54Mbps (Wireless G)
RTT = 1ms
How much data can the pipe hold?
BxD = $54x10^{6}x1x10^{-3}$

Bandwidth x Delay – Mars Rover



https://mars.nasa.gov/msl/mission/communications/

https://www.youtube.com/watch?v=NGgzq8eXZOQ

Breakout:
- Bit rate of curiosity: 32000bits/second
- Delay = 14 minutes each way
- BxD = ?

And one more thing - Jitter



Also called Interpacket gap

- why does it happen (which artifact of packet switching?)
- why is it important (think video applications)?
- How do you solve this?

Next Steps

- Read Chapter 1

- Next lecture – Network performance basics