

Ch 09: Dictionaries

Application Program Development

Derek Harter

Department of Computer Science
East Texas A&M University

Summer 2026



EAST TEXAS A&M

Dictionary

A dictionary is an object that stores a collection of data. Each element in a dictionary has two parts: a key and a value. You use a key to locate a specific value.

- **Dictionary:** object that stores a collection of key/value pairs
 - Each element consists of a **key** and a **value**
 - Referred to as: map, associative map, hash, key-value pair, Dictionary, indexed table, etc.
 - key must be an immutable object (e.g. string, int, float, tuple, **not** a list)
 - To retrieve a specific value, need to know and use the key associated with it

Format for creating a dictionary:

```
phonebook = {'Chris': '555-1111',  
             'Katie': '555-2222',  
             'Joanne': '555-3333'}
```



Retrieving a Value from a Dictionary

- Elements in dictionary are unsorted
 - In fact they are indexed (hashed or a tree) by the key

General format for retrieving value from dictionary:

```
dictionary[key]  
number = phonebook['Chris']
```

- if key is in the dictionary, associated value is returned
 - if not, a `KeyError` exception is raised

- To test whether a key is in a dictionary use the `in` and `not in` operators
 - Helps prevent `KeyError` exceptions

```
if key in phonebook:  
    print(f'{key} number is {phonebook[key]}')  
else:  
    print(f'I do not know {key}')
```



Adding Elements to an Existing Dictionary

- Dictionaries are **mutable** objects
- To add a new key-value pair, simply assign a value to a key:
- If key exists in the dictionary, the value associated with the existing key will be changed (e.g. this is a way to modify a record)

```
dictionary[key] = value  
phonebook['Joe'] = '555-0123'
```

```
# modifies phone number if `Chris`  
# already exists  
phonebook['Chris'] = '555-4444'
```



Deleting Elements from an Existing Dictionary

- To delete a key-value pair, use the `del` keyword

```
del dictionary[key]
```

```
del phonebook['Chris']
```

- If key is not in the dictionary, `KeyError` exception is raised
 - So usually check using `key in dictionary` before deleting



Getting the Number of Elements and Mixing Data Types

- `len` function: used to obtain number of elements in a dictionary

```
num_items = len(phonebook)
```

- keys must be immutable objects, but associated values can be any type of object
 - One dictionary can include keys of several different immutable types
 - Though this is an unusual use case
 - Values stored in a single dictionary can be of different types
 - Though also this is not a typical thing to do



Creating an Empty Dictionary and Using a for Loop to Iterate Over a Dictionary

- To create an empty dictionary:
 - use `{}`
 - Use built-in function `dict()`
 - Elements can be added to dictionary as program executes
- Use a for loop to iterate over a dictionary

```
for name in phonebook:  
    print(f'name: {name} num: {phonebook[name]}')
```

both are commonly seen

```
phonebook = {}  
phonebook = dict()
```



EAST TEXAS A&M

(Some) Dictionary Methods

Method	Description
<code>clear()</code>	Clears the contents of a dictionary
<code>get()</code>	Gets the value associated with a specified key, returns default if key not found
<code>items()</code>	Returns all the keys in a dict and their values as a sequence of tuples
<code>keys()</code>	Returns all the keys in a dictionary as a tuple
<code>pop()</code>	Returns the value associated with a key and removes the key-value pair from the dict
<code>popitem()</code>	Returns, as a tuple, the last added key-value pair and removes it.
<code>values()</code>	Returns all the values in dict as a tuple

See [Python Standard Library Documentation](#) (Python, 2026)



EAST TEXAS A&M

Dictionary Comprehensions (1 of 2)

Dictionary Comprehension

A **dictionary comprehension** is an expression that reads a sequence of input elements and uses those input elements to produce a dictionary. (Same idea as a list comprehension)

Using a for loop:

```
numbers = [1, 2, 3, 4]
squares = {}
for item in numbers:
    squares[item] = item**2
```

Using a dictionary comprehension:

```
squares = {item: item**2 for item in numbers}
```



Dictionary Comprehensions (2 of 2)

Example: create dictionary of string keys and their lengths as values

```
names = ['Jeremy', 'Kate', 'Peg']
str_lengths = {item: len(item) for item in names}
print(str_lengths)

{'Jeremy': 6, 'Kate': 4, 'Peg': 3}
```

Example: making a copy of a dictionary

```
dict1 = {'A': 1, 'B': 2, 'C': 3}
dict2 = {k:v for k,v in dict1.items()}
print(dict2)

{'A': 1, 'B': 2, 'C': 3}
```



Summary

- A dictionary is collection that stores key-value pairs
 - You can lookup items using the dictionary key
 - You can add or modify items in a dictionary by (re)assigning the key to a value
 - You can use the `in` and `not in` operators to test if a key is present or not
 - You can use the `del` keyword to remove key-value pairs from a dictionary
- Dictionaries are collection objects that have a lot of useful member methods
 - Among these are `get()`, `items()`, `keys()`, `values()`
- Dictionary comprehensions are a part of the syntax, and work similar to list comprehensions



Python. (2026). *Python 3 standard library documentation*. Retrieved August 13, 2026, from <https://docs.python.org/3/>

