

Ch 04: Performing Calculations with Loops

Application Program Development

Derek Harter

Department of Computer Science
East Texas A&M University

Summer 2026



EAST TEXAS A&M

Calculating a Running Total

Calculating a Running Total

A running total is a sum of numbers that accumulates with each iteration of a loop. The variable used to keep the running total is called an accumulator.




Figure 1: Logic for calculating a running total (Gaddis, 2021, pg.211)

- Programs often need to calculate a total of a series of numbers
 - Typically include two elements
 - 1 A loop that reads each number in series
 - 2 An **accumulator** variable
 - Known as program that keeps a running total: accumulates total and reads in series
 - At end of loop, accumulator will reference the total



The Augmented Assignment Operators

- In many assignment statements, the variable on the left side of the = operator also appears on the right side
- **Augmented assignment operators:** special set of operators designed for this type of common assignment

Table 1: Augmented assignment operators

Operator	Example Usage	Equivalent to
+=	x += 5	x = x + 5
-=	y -= 2	y = y - 2
*=	z *= 10	z = z * 2
/=	a /= b	a = a / b
%=	c %= 3	c = c % 3
//=	x //= 3	x = x // 3
=	y **= 2	y = y2



- **Sentinel:** special value that marks the end of a sequence of items
 - When a program reaches a sentinel, it knows that the end of the sequence of items was reached, and the loop terminates
 - Must be distinctive enough so as not to be mistaken for a regular value in the sequence
 - Example: when reading an input file, empty line can be used as a sentinel

Sentinel

A sentinel is a special value that marks the end of a sequence of values



Input Validation Loops

- Computer cannot tell the difference between good and bad data
 - If user provides bad input, program will produce bad output
 - It is important to design programs such that bad input is never accepted
- **Input validation:** inspecting input before it is processed by the program
 - If input is invalid, prompt user to enter correct data
 - Commonly accomplished using a `while` loop which repeats as long as the input is bad
 - If input is bad, display error message and try again
 - If input is good, continue past loop and process input




Figure 2: Logic for an input validation loop (Gaddis, 2021, pg.218)



Nested Loops

- **Nested loop:** loop that is contained inside another loop
 - Example: analog clock works like nested loop
 - Hours hand moves once for every twelve movements of the minutes hand
 - Seconds hand moves 60 times for each movement of the minutes hand
- Key points about nested loops:
 - Inner loop goes through all of its iterations for each iteration of outer loop
 - Inner loops complete their iterations faster than outer loops
- Total number of iterations in nested loop

$\text{num iter inner loop} \times \text{num iter outer loop}$




Figure 3: Flowchart for a clock simulator (Gaddis, 2021, pg.223)



EAST TEXAS A&M

Summary

- There are several common tasks or calculation you perform with a loop
 - Iterate over a series of items in a collection to process each item
 - For example, calculate a running total of items, using an **accumulator**
- Augmented assignment operators are common when updating the value of a variable, e.g. reassigning updated value back into original variable
- Many loops are *sentinel-controlled loops* that keep processing input until a special **sentinel** value is detected in the input.
- Another common task for loops is **input validation** where input is entered and checked to see if valid, and the loop does not continue until valid input has been received.
- Loops can be nested for many purposes



References

Gaddis, T. (2021). *Starting out with python* (5th). Pearson.



EAST TEXAS A&M