



# Certifying Differential Invariants of Neural Networks using Abstract Duals

CHANDRA KANTH NAGESH

*Department of Computer Science  
University of Colorado Boulder*

Final Project; CSCI – 7135, Fall 2025



## Safety Property

Given a neural network classifier  $f : \mathbb{R}^n \rightarrow \mathbb{R}^k$ , an input  $x_0$ , and a perturbation radius  $\epsilon$ .

## Safety Property

Given a neural network classifier  $f : \mathbb{R}^n \rightarrow \mathbb{R}^k$ , an input  $x_0$ , and a perturbation radius  $\epsilon$ . Verify that classification of  $x_0$  is invariant within an  $\epsilon$ -ball i.e.,

$$\forall x \in \mathbb{B}_\infty(x_0, \epsilon) : \quad \operatorname{argmax}(f(x)) = \operatorname{argmax}(f(x_0))$$

## Safety Property

Given a neural network classifier  $f : \mathbb{R}^n \rightarrow \mathbb{R}^k$ , an input  $x_0$ , and a perturbation radius  $\epsilon$ . Verify that classification of  $x_0$  is invariant within an  $\epsilon$ -ball i.e.,

$$\forall x \in \mathbb{B}_\infty(x_0, \epsilon) : \operatorname{argmax}(f(x)) = \operatorname{argmax}(f(x_0))$$



Original Image



Original Image  
+  $\epsilon = 0.25$




Original Image  
+  $\epsilon = 0.1$

Neural networks are highly non-linear and vulnerable to *adversarial attacks*.

Neural networks are highly non-linear and vulnerable to *adversarial attacks*.



Original Image + tiny perturbations



Continuous input spaces




Safety-Critical Domains

Neural networks are highly non-linear and vulnerable to *adversarial attacks*.



Original Image + tiny perturbations



Continuous input spaces



Safety-Critical Domains

## Possible solution

“Check if *global gradient bounds* can provide a simpler yet effective verification domain compared to *layer-wise relational abstractions*”

The power of global bounds with simplicity of gradient analysis

1. **Simplicity beats complexity**

---

<sup>1</sup>Singh, G. et. al. (2019). An abstract domain for certifying neural networks. 3(POPL), pp.1–30.



The power of global bounds with simplicity of gradient analysis

1. **Simplicity beats complexity**

→ DeepPoly<sup>1</sup> is strictly better than our method

---

<sup>1</sup>Singh, G. et. al. (2019). An abstract domain for certifying neural networks. 3(POPL), pp.1–30.

The power of global bounds with simplicity of gradient analysis

1. **Simplicity beats complexity**

- DeepPoly<sup>1</sup> is strictly better than our method
- However, *suprising results found!*

---

<sup>1</sup>Singh, G. et. al. (2019). An abstract domain for certifying neural networks. 3(POPL), pp.1–30.

The power of global bounds with simplicity of gradient analysis

1. **Simplicity beats complexity**

- DeepPoly<sup>1</sup> is strictly better than our method
- However, *suprising results found!*

2. **Gradient Instability**

---

<sup>1</sup>Singh, G. et. al. (2019). An abstract domain for certifying neural networks. 3(POPL), pp.1–30.

The power of global bounds with simplicity of gradient analysis

1. **Simplicity beats complexity**

- DeepPoly<sup>1</sup> is strictly better than our method
- However, *suprising results found!*

2. **Gradient Instability**

- Found 100% correlation between instability and failure at higher  $\epsilon$

---

<sup>1</sup>Singh, G. et. al. (2019). An abstract domain for certifying neural networks. 3(POPL), pp.1–30.

The power of global bounds with simplicity of gradient analysis

1. **Simplicity beats complexity**

- DeepPoly<sup>1</sup> is strictly better than our method
- However, *suprising results found!*

2. **Gradient Instability**

- Found 100% correlation between instability and failure at higher  $\epsilon$
- Our method detects when the *local linearity assumption collapses*

---

<sup>1</sup>Singh, G. et. al. (2019). An abstract domain for certifying neural networks. 3(POPL), pp.1–30.

## Mathematical Bridge: Mean Value Theorem

$$|f(x) - f(x_0)| \leq \underbrace{\sup_{z \in X} \|\nabla f(z)\|}_{\text{Abstract Duals}} \cdot \|x - x_0\|$$

## Mathematical Bridge: Mean Value Theorem

$$|f(x) - f(x_0)| \leq \underbrace{\sup_{z \in X} \|\nabla f(z)\|}_{\text{Abstract Duals}} \cdot \|x - x_0\|$$

## Key Differences

→ DeepPoly: Tracks affine constraints layer-by-layer ( $x_j \geq \sum w_i x_i$ ). Precise but accumulates error ( $O(L)$ )

## Mathematical Bridge: Mean Value Theorem

$$|f(x) - f(x_0)| \leq \underbrace{\sup_{z \in X} \|\nabla f(z)\|}_{\text{Abstract Duals}} \cdot \|x - x_0\|$$


## Key Differences

- DeepPoly: Tracks affine constraints layer-by-layer ( $x_j \geq \sum w_i x_i$ ). Precise but accumulates error ( $O(L)$ )
- Ours: Approximates the derivative  $\nabla f(x)$ . Coarser, but “jumps” by bypassing intermediate wrapping errors






**Formalization:**  
Affine Arithmetic



**Gradient Anomaly:**  
 $\text{Depth} < 3$ ; Sigmoid




**Instability Metric:**  
Identifies failures



**Evaluation:**  
Tiny/Small/Std.  $\epsilon$




**Formalization:**  
Affine Arithmetic



**Gradient Anomaly:**  
 $\text{Depth} < 3$ ; Sigmoid



**Instability Metric:**  
Identifies failures



**Evaluation:**  
Tiny/Small/Std.  $\epsilon$

## Statement

“Global gradient bounds provide a simpler verification domain for shallow, smooth networks, while relational domains are essential for deep, non-smooth architectures”

Lift standard dual numbers  $\mathbb{D} = \{a + b\eta\}$  to Affine Forms to compute global gradient bounds.

Lift standard dual numbers  $\mathbb{D} = \{a + b\eta\}$  to Affine Forms to compute global gradient bounds.

→ **Value Component:**  $\hat{x} = \alpha_0 + \sum_{i=1}^n \alpha_i \epsilon_i$  (Abstract Input Region)

Lift standard dual numbers  $\mathbb{D} = \{a + b\eta\}$  to Affine Forms to compute global gradient bounds.

→ **Value Component:**  $\hat{x} = \alpha_0 + \sum_{i=1}^n \alpha_i \epsilon_i$  (Abstract Input Region)

→ Propagate the interval through the network:

$$\hat{y} = f(\hat{x}) = \underbrace{\left(\alpha_0 + \sum \alpha_i \epsilon_i\right)}_{\text{Value Interval}} + \underbrace{\left(d_0 + \sum d_i \epsilon_i\right)}_{\text{Gradient } \nabla f} \eta$$

Lift standard dual numbers  $\mathbb{D} = \{a + b\eta\}$  to Affine Forms to compute global gradient bounds.

→ **Value Component:**  $\hat{x} = \alpha_0 + \sum_{i=1}^n \alpha_i \epsilon_i$  (Abstract Input Region)

→ Propagate the interval through the network:

$$\hat{y} = f(\hat{x}) = \underbrace{\left(\alpha_0 + \sum \alpha_i \epsilon_i\right)}_{\text{Value Interval}} + \underbrace{\left(d_0 + \sum d_i \epsilon_i\right)}_{\text{Gradient } \nabla f} \eta$$

→ *Global Lipschitz bound is the supremum:*

$$K = \sup_{x \in X_0} \|\nabla f(x)\|_1 = \sum_j \left( |\beta_{0,j}| + \sum_i |\beta_{i,j}| \right)$$

Now a neuron  $n$  has an **unstable-gradient** if its gradient interval  $[\underline{g}, \overline{g}]$  contains 0

Now a neuron  $n$  has an **unstable-gradient** if its gradient interval  $[\underline{g}, \overline{g}]$  contains 0

$$\exists x_1, x_2 \in X_0 \text{ s.t. } \text{sign} \left( \frac{\partial f}{\partial n}(x_1) \right) \neq \text{sign} \left( \frac{\partial f}{\partial n}(x_2) \right)$$



Now a neuron  $n$  has an **unstable-gradient** if its gradient interval  $[\underline{g}, \overline{g}]$  contains 0

$$\exists x_1, x_2 \in X_0 \text{ s.t. } \text{sign} \left( \frac{\partial f}{\partial n}(x_1) \right) \neq \text{sign} \left( \frac{\partial f}{\partial n}(x_2) \right)$$

## Implication

→ **Geometric Interpretation:** The function is non-monotonic with respect to neuron  $n$  within the input region.

Now a neuron  $n$  has an **unstable-gradient** if its gradient interval  $[\underline{g}, \overline{g}]$  contains 0

$$\exists x_1, x_2 \in X_0 \text{ s.t. } \text{sign} \left( \frac{\partial f}{\partial n}(x_1) \right) \neq \text{sign} \left( \frac{\partial f}{\partial n}(x_2) \right)$$

## Implication

- **Geometric Interpretation:** The function is non-monotonic with respect to neuron  $n$  within the input region.
- Linear approximations (DeepPoly) become loose when curvature is high

## Counter-Intuitive Finding

In **16.1%** of Tiny Net cases ( $\epsilon = 0.01$ ), the simpler Gradient method certified robustness where DeepPoly failed.

## Counter-Intuitive Finding

In **16.1%** of Tiny Net cases ( $\epsilon = 0.01$ ), the simpler Gradient method certified robustness where DeepPoly failed.

Network	$\epsilon$	Count	%
Tiny Net	0.01	5	16.1%
Tiny Net	0.02	3	9.7%
Tiny Net	0.03	2	6.5%
Small/Std	All	0	0.0%

Table: Gradient method outperforms DeepPoly in shallow, smooth networks; {Tiny:  $2 \times 10$ , Small:  $5 \times 20$ , Standard:  $10 \times 20$ }

Experiment	Hypothesis	Result
Gradient Instability	Does zero-crossing gradient (instability) predict verification failure?	<b>100% Correlation</b> between instability and failure at high perturbation ( $\epsilon = 0.12$ ).
ReLU vs. Sigmoid	Does activation smoothness affect domain performance?	DeepPoly dominates on ReLU (100% win rate) not Sigmoid

Table: Summary of structural analysis on MNIST classifiers using `ocaml-nn`<sup>2</sup> with  $\epsilon \in \{0.01 \dots 0.12\}$ .

---

<sup>2</sup><https://github.com/ck090/ocaml-nn/tree/main>

- **Shallow + Smooth** → Use **Gradient (Abstract Duals)**
- **Deep + Non-smooth** → Use **Relational (DeepPoly)**

## Final Takeaway

“Domain complexity does not dictate robustness, however, alignment with function smoothness does. Expanding to Physics-Informed Neural Networks is an exciting future direction”