

FILTER DESIGN TEST CASE

FBAR (Film Bulk Acoustic Resonator) - Band 30 (2300 MHz) for UWB (Ultra-Wideband) Filter
Design Validation and Performance Characterization

DOCUMENT INFORMATION

Document Number:	FD-TC-0017
Revision:	Rev D.9
Author:	Dr. Lena Kowalski
Reviewer:	Dr. Pierre Dubois
Design Center:	Singapore RF Lab
Created Date:	2024-07-17
Last Modified:	2024-08-27
Status:	PASS
Priority:	P3 - Medium

1. OBJECTIVE

This document describes the design, simulation, and characterization of a FBAR (Film Bulk Acoustic Resonator) filter targeting Band 30 (2300 MHz) for UWB (Ultra-Wideband) Filter. The filter is designed on AIN on Si substrate with a target center frequency of 3035.2 MHz and bandwidth of 132.5 MHz. The objective is to validate that the filter meets the required insertion loss, rejection, and linearity specifications for integration into the UWB (Ultra-Wideband) Filter module. This design iteration addresses feedback from the previous revision regarding out-of-band rejection improvements and temperature stability.

2. SCOPE

- Filter Type: FBAR (Film Bulk Acoustic Resonator)
- Frequency Band: Band 30 (2300 MHz)
- Application: UWB (Ultra-Wideband) Filter
- Substrate: AIN on Si
- Package: Flip-Chip BGA
- Design Tool: Matlab RF Toolbox R2024b
- Design Center: Singapore RF Lab

This specification applies to all variants of the FBAR (Film Bulk Acoustic Resonator) design targeting Band 30 (2300 MHz). Results are used to qualify the design for mass production release.

3. DESIGN PARAMETERS

Center Frequency:	3035.2 MHz
Bandwidth (3 dB):	132.5 MHz
Insertion Loss Target:	≤ 1.7 dB
Return Loss Target:	≥ 14.0 dB
Out-of-Band Rejection:	≥ 50.0 dB
Isolation (Duplexer):	≥ 28.0 dB
Q Factor:	9884
Temperature Coefficient:	-16.8 ppm/°C
Die Size:	1.4 x 1.8 mm
Wafer Size:	8-inch
Number of Resonators:	7
Electrode Material:	W

Passivation: SiO2/Si3N4 stack

4. TEST PROCEDURE

1. Open Matlab RF Toolbox R2024b and load the FBAR (Film Bulk Acoustic Resonator) template project.
2. Define the substrate stack: AlN on Si with specified layer thicknesses.
3. Set design targets: center freq 3035.2 MHz, BW 132.5 MHz.
4. Run initial EM simulation with 2D mesh density of 20 cells/wavelength.
5. Optimize resonator geometry using gradient descent (target IL < 1.7 dB).
6. Verify coupling coefficients between resonator stages.
7. Run 3D FEM simulation to account for package parasitics (Flip-Chip BGA).
8. Export GDS-II layout for mask fabrication.
9. Fabricate prototype wafers (8-inch, AlN on Si).
10. Perform on-wafer probing using Keysight N9041B UXA.
11. Measure S-parameters (S11, S21, S12, S22) from 100 MHz to 9106 MHz.
12. Compare measured results against simulation and specification limits.
13. Perform temperature cycling (-40°C to +85°C) and re-measure.
14. Document results and generate summary report.

5. ACCEPTANCE CRITERIA

- Insertion loss at center frequency shall be <= 1.7 dB
- Return loss in passband shall be >= 14.0 dB
- Out-of-band rejection at +/- 199 MHz offset >= 50.0 dB
- Group delay variation across passband shall be <= 6 ns
- Temperature drift over -40°C to +85°C shall be <= 6.4 MHz
- Power handling shall be >= +27 dBm at 1 dB compression
- ESD tolerance >= 2000 V (HBM)
- Die yield on qualification lot >= 87%

6. TEST RESULTS

Measurement Date: 2024-08-27
Devices Tested: 32
Insertion Loss (meas): 1.35 dB
Return Loss (meas): 16.5 dB
Rejection (meas): 53.1 dB
Isolation (meas): 32.5 dB
Q Factor (meas): 9884
Group Delay Variation: 5.1 ns
Power Handling: +31 dBm
Die Yield: 91.3%

Result Classification: PASS

7. OBSERVATIONS AND FINDINGS

- a) The FBAR (Film Bulk Acoustic Resonator) design demonstrated excellent performance for Band 30 (2300 MHz).
- b) Insertion loss met target specification.
- c) Out-of-band rejection exceeded the minimum requirement.
- d) Temperature stability was within specification across full range.
- e) Wafer-level uniformity was excellent (sigma < 1.5%).

8. CORRECTIVE ACTIONS

No corrective actions required. Design passed all acceptance criteria.

9. SIGN-OFF

Author:	Dr. Lena Kowalski	Date:	2024-08-27
Reviewer:	Dr. Pierre Dubois	Date:	2024-08-30
Approver:	Dr. Karen Mitchell	Date:	2024-09-10

END OF DOCUMENT - FD-TC-0017