

FILTER DESIGN TEST CASE

TC-SAW (Temperature Compensated SAW) - Band 1 (2100 MHz) for Millimeter-Wave Beamforming
Design Validation and Performance Characterization

DOCUMENT INFORMATION

Document Number:	FD-TC-0072
Revision:	Rev A.6
Author:	Dr. Ahmed Al-Farsi
Reviewer:	Dr. Elena Vasquez
Design Center:	San Jose Advanced Design Lab
Created Date:	2025-03-24
Last Modified:	2025-05-21
Status:	NEEDS REVIEW
Priority:	P2 - High

1. OBJECTIVE

This document describes the design, simulation, and characterization of a TC-SAW (Temperature Compensated SAW) filter targeting Band 1 (2100 MHz) for Millimeter-Wave Beamforming. The filter is designed on Langasite substrate with a target center frequency of 2252.0 MHz and bandwidth of 194.4 MHz. The objective is to validate that the filter meets the required insertion loss, rejection, and linearity specifications for integration into the Millimeter-Wave Beamforming module. This design iteration addresses feedback from the previous revision regarding out-of-band rejection improvements and temperature stability.

2. SCOPE

- Filter Type: TC-SAW (Temperature Compensated SAW)
- Frequency Band: Band 1 (2100 MHz)
- Application: Millimeter-Wave Beamforming
- Substrate: Langasite
- Package: LGA (Land Grid Array)
- Design Tool: Sonnet EM Suite v16
- Design Center: San Jose Advanced Design Lab

This specification applies to all variants of the TC-SAW (Temperature Compensated SAW) design targeting Band 1 (2100 MHz). Results are used to qualify the design for mass production release.

3. DESIGN PARAMETERS

Center Frequency:	2252.0 MHz
Bandwidth (3 dB):	194.4 MHz
Insertion Loss Target:	<= 3.6 dB
Return Loss Target:	>= 19.0 dB
Out-of-Band Rejection:	>= 37.0 dB
Isolation (Duplexer):	>= 43.0 dB
Q Factor:	4870
Temperature Coefficient:	-25.4 ppm/°C
Die Size:	0.6 x 1.5 mm
Wafer Size:	6-inch
Number of Resonators:	10
Electrode Material:	Al

Passivation: SiO2/Si3N4 stack

4. TEST PROCEDURE

- 1. Open Sonnet EM Suite v16 and load the TC-SAW (Temperature Compensated SAW) template project.
- 2. Define the substrate stack: Langasite with specified layer thicknesses.
- 3. Set design targets: center freq 2252.0 MHz, BW 194.4 MHz.
- 4. Run initial EM simulation with 2D mesh density of 20 cells/wavelength.
- 5. Optimize resonator geometry using gradient descent (target IL < 3.6 dB).
- 6. Verify coupling coefficients between resonator stages.
- 7. Run 3D FEM simulation to account for package parasitics (LGA (Land Grid Array)).
- 8. Export GDS-II layout for mask fabrication.
- 9. Fabricate prototype wafers (6-inch, Langasite).
- 10. Perform on-wafer probing using Rohde & Schwarz FSW Signal Analyzer.
- 11. Measure S-parameters (S11, S21, S12, S22) from 100 MHz to 6756 MHz.
- 12. Compare measured results against simulation and specification limits.
- 13. Perform temperature cycling (-40°C to +85°C) and re-measure.
- 14. Document results and generate summary report.

5. ACCEPTANCE CRITERIA

- Insertion loss at center frequency shall be <= 3.6 dB
- Return loss in passband shall be >= 19.0 dB
- Out-of-band rejection at +/- 292 MHz offset >= 37.0 dB
- Group delay variation across passband shall be <= 9 ns
- Temperature drift over -40°C to +85°C shall be <= 7.2 MHz
- Power handling shall be >= +31 dBm at 1 dB compression
- ESD tolerance >= 1000 V (HBM)
- Die yield on qualification lot >= 85%

6. TEST RESULTS

Measurement Date: 2025-05-21
Devices Tested: 13
Insertion Loss (meas): 3.35 dB
Return Loss (meas): 20.9 dB
Rejection (meas): 39.6 dB
Isolation (meas): 48.3 dB
Q Factor (meas): 4870
Group Delay Variation: 5.5 ns
Power Handling: +36 dBm
Die Yield: 90.2%

Result Classification: NEEDS REVIEW

7. OBSERVATIONS AND FINDINGS

- a) The TC-SAW (Temperature Compensated SAW) design demonstrated below-target performance for Band 1 (2100 MHz).
- b) Insertion loss is marginally above target; electrode thickness optimization recommended.
- c) Out-of-band rejection exceeded the minimum requirement.
- d) Package parasitic effects were consistent with 3D EM model predictions.
- e) Cross-talk between adjacent filter channels was below -55 dB.

8. CORRECTIVE ACTIONS

- 1. Review near-band rejection margin for worst-case temperature.
- 2. Re-run EM simulation with refined mesh for better accuracy.
- 3. Schedule follow-up measurement after design tweak.

9. SIGN-OFF

Author:	Dr. Ahmed Al-Farsi	Date:	2025-05-21
Reviewer:	Dr. Elena Vasquez	Date:	2025-05-25
Approver:	Dr. Hans Weber	Date:	2025-05-30

END OF DOCUMENT - FD-TC-0072