

FILTER DESIGN TEST CASE

FBAR (Film Bulk Acoustic Resonator) - n79 (4.4-5.0 GHz 5G NR) for GPS/GNSS Anti-Jamming Filter
Design Validation and Performance Characterization

DOCUMENT INFORMATION

Document Number:	FD-TC-0078
Revision:	Rev B.2
Author:	Dr. Raj Patel
Reviewer:	Dr. Anya Krishnamurthy
Design Center:	Helsinki 5G Lab
Created Date:	2025-01-19
Last Modified:	2025-01-20
Status:	FAIL
Priority:	P3 - Medium

1. OBJECTIVE

This document describes the design, simulation, and characterization of a FBAR (Film Bulk Acoustic Resonator) filter targeting n79 (4.4-5.0 GHz 5G NR) for GPS/GNSS Anti-Jamming Filter. The filter is designed on Quartz substrate with a target center frequency of 1394.4 MHz and bandwidth of 369.3 MHz. The objective is to validate that the filter meets the required insertion loss, rejection, and linearity specifications for integration into the GPS/GNSS Anti-Jamming Filter module. This design iteration addresses feedback from the previous revision regarding out-of-band rejection improvements and temperature stability.

2. SCOPE

- Filter Type: FBAR (Film Bulk Acoustic Resonator)
- Frequency Band: n79 (4.4-5.0 GHz 5G NR)
- Application: GPS/GNSS Anti-Jamming Filter
- Substrate: Quartz
- Package: LGA (Land Grid Array)
- Design Tool: Matlab RF Toolbox R2024b
- Design Center: Helsinki 5G Lab

This specification applies to all variants of the FBAR (Film Bulk Acoustic Resonator) design targeting n79 (4.4-5.0 GHz 5G NR). Results are used to qualify the design for mass production release.

3. DESIGN PARAMETERS

Center Frequency:	1394.4 MHz
Bandwidth (3 dB):	369.3 MHz
Insertion Loss Target:	<= 1.2 dB
Return Loss Target:	>= 18.0 dB
Out-of-Band Rejection:	>= 32.0 dB
Isolation (Duplexer):	>= 31.0 dB
Q Factor:	6410
Temperature Coefficient:	-16.8 ppm/°C
Die Size:	1.8 x 2.2 mm
Wafer Size:	8-inch
Number of Resonators:	3
Electrode Material:	Pt/Al

Passivation: SiO2/Si3N4 stack

4. TEST PROCEDURE

1. Open Matlab RF Toolbox R2024b and load the FBAR (Film Bulk Acoustic Resonator) template project.
2. Define the substrate stack: Quartz with specified layer thicknesses.
3. Set design targets: center freq 1394.4 MHz, BW 369.3 MHz.
4. Run initial EM simulation with 2D mesh density of 20 cells/wavelength.
5. Optimize resonator geometry using gradient descent (target IL < 1.2 dB).
6. Verify coupling coefficients between resonator stages.
7. Run 3D FEM simulation to account for package parasitics (LGA (Land Grid Array)).
8. Export GDS-II layout for mask fabrication.
9. Fabricate prototype wafers (8-inch, Quartz).
10. Perform on-wafer probing using Rohde & Schwarz ZNA67.
11. Measure S-parameters (S11, S21, S12, S22) from 100 MHz to 4183 MHz.
12. Compare measured results against simulation and specification limits.
13. Perform temperature cycling (-40°C to +85°C) and re-measure.
14. Document results and generate summary report.

5. ACCEPTANCE CRITERIA

- Insertion loss at center frequency shall be <= 1.2 dB
- Return loss in passband shall be >= 18.0 dB
- Out-of-band rejection at +/- 554 MHz offset >= 32.0 dB
- Group delay variation across passband shall be <= 7 ns
- Temperature drift over -40°C to +85°C shall be <= 2.9 MHz
- Power handling shall be >= +28 dBm at 1 dB compression
- ESD tolerance >= 1000 V (HBM)
- Die yield on qualification lot >= 98%

6. TEST RESULTS

Measurement Date: 2025-01-20
Devices Tested: 29
Insertion Loss (meas): 0.93 dB
Return Loss (meas): 20.0 dB
Rejection (meas): 35.0 dB
Isolation (meas): 35.6 dB
Q Factor (meas): 6410
Group Delay Variation: 7.3 ns
Power Handling: +26 dBm
Die Yield: 90.5%

Result Classification: FAIL

7. OBSERVATIONS AND FINDINGS

- a) The FBAR (Film Bulk Acoustic Resonator) design demonstrated below-target performance for n79 (4.4-5.0 GHz 5G NR).
- b) Insertion loss met target specification.
- c) Out-of-band rejection exceeded the minimum requirement.
- d) Group delay flatness improved compared to previous revision.
- e) No delamination observed after 1000-cycle thermal shock test.

8. CORRECTIVE ACTIONS

- 1. Optimize resonator geometry to reduce insertion loss by ~0.3 dB.
- 2. Re-run EM simulation with refined mesh for better accuracy.
- 3. Escalate to advanced materials team for alternative piezoelectric stack.

9. SIGN-OFF

Author: Dr. Raj Patel Date: 2025-01-20
Reviewer: Dr. Anya Krishnamurthy Date: 2025-01-22
Approver: Dr. Hans Weber Date: 2025-02-03

END OF DOCUMENT - FD-TC-0078