

FILTER DESIGN TEST CASE

TC-SAW (Temperature Compensated SAW) - Band 25 (1900 MHz) for Millimeter-Wave Beamforming
Design Validation and Performance Characterization

DOCUMENT INFORMATION

Document Number:	FD-TC-0099
Revision:	Rev D.2
Author:	Dr. Elena Vasquez
Reviewer:	Dr. Lena Kowalski
Design Center:	Irvine Design Center
Created Date:	2025-04-01
Last Modified:	2025-05-25
Status:	FAIL
Priority:	P2 - High

1. OBJECTIVE

This document describes the design, simulation, and characterization of a TC-SAW (Temperature Compensated SAW) filter targeting Band 25 (1900 MHz) for Millimeter-Wave Beamforming. The filter is designed on AIN on Si substrate with a target center frequency of 3304.1 MHz and bandwidth of 294.5 MHz. The objective is to validate that the filter meets the required insertion loss, rejection, and linearity specifications for integration into the Millimeter-Wave Beamforming module. This design iteration addresses feedback from the previous revision regarding out-of-band rejection improvements and temperature stability.

2. SCOPE

- Filter Type: TC-SAW (Temperature Compensated SAW)
- Frequency Band: Band 25 (1900 MHz)
- Application: Millimeter-Wave Beamforming
- Substrate: AIN on Si
- Package: QFN (Quad Flat No-Lead)
- Design Tool: Cadence AWR Microwave Office
- Design Center: Irvine Design Center

This specification applies to all variants of the TC-SAW (Temperature Compensated SAW) design targeting Band 25 (1900 MHz). Results are used to qualify the design for mass production release.

3. DESIGN PARAMETERS

Center Frequency:	3304.1 MHz
Bandwidth (3 dB):	294.5 MHz
Insertion Loss Target:	<= 2.1 dB
Return Loss Target:	>= 12.0 dB
Out-of-Band Rejection:	>= 50.0 dB
Isolation (Duplexer):	>= 30.0 dB
Q Factor:	7547
Temperature Coefficient:	-26.3 ppm/°C
Die Size:	2.8 x 0.6 mm
Wafer Size:	6-inch
Number of Resonators:	8
Electrode Material:	W

Passivation: SiO2

4. TEST PROCEDURE

1. Open Cadence AWR Microwave Office and load the TC-SAW (Temperature Compensated SAW) template project.
2. Define the substrate stack: AlN on Si with specified layer thicknesses.
3. Set design targets: center freq 3304.1 MHz, BW 294.5 MHz.
4. Run initial EM simulation with 2D mesh density of 20 cells/wavelength.
5. Optimize resonator geometry using gradient descent (target IL < 2.1 dB).
6. Verify coupling coefficients between resonator stages.
7. Run 3D FEM simulation to account for package parasitics (QFN (Quad Flat No-Lead)).
8. Export GDS-II layout for mask fabrication.
9. Fabricate prototype wafers (6-inch, AlN on Si).
10. Perform on-wafer probing using Rohde & Schwarz ZNB40.
11. Measure S-parameters (S11, S21, S12, S22) from 100 MHz to 9912 MHz.
12. Compare measured results against simulation and specification limits.
13. Perform temperature cycling (-40°C to +85°C) and re-measure.
14. Document results and generate summary report.

5. ACCEPTANCE CRITERIA

- Insertion loss at center frequency shall be <= 2.1 dB
- Return loss in passband shall be >= 12.0 dB
- Out-of-band rejection at +/- 442 MHz offset >= 50.0 dB
- Group delay variation across passband shall be <= 10 ns
- Temperature drift over -40°C to +85°C shall be <= 10.9 MHz
- Power handling shall be >= +32 dBm at 1 dB compression
- ESD tolerance >= 1000 V (HBM)
- Die yield on qualification lot >= 90%

6. TEST RESULTS

Measurement Date: 2025-05-25
Devices Tested: 63
Insertion Loss (meas): 1.82 dB
Return Loss (meas): 13.6 dB
Rejection (meas): 52.9 dB
Isolation (meas): 34.9 dB
Q Factor (meas): 7547
Group Delay Variation: 3.0 ns
Power Handling: +33 dBm
Die Yield: 81.6%

Result Classification: FAIL

7. OBSERVATIONS AND FINDINGS

- a) The TC-SAW (Temperature Compensated SAW) design demonstrated below-target performance for Band 25 (1900 MHz).
- b) Insertion loss met target specification.
- c) Out-of-band rejection exceeded the minimum requirement.
- d) Slight frequency drift observed at +85°C; TC layer thickness may need adjustment.
- e) Wafer-level uniformity was excellent (sigma < 1.5%).

8. CORRECTIVE ACTIONS

- 1. Optimize resonator geometry to reduce insertion loss by ~0.3 dB.
- 2. Re-run EM simulation with refined mesh for better accuracy.
- 3. Escalate to advanced materials team for alternative piezoelectric stack.

9. SIGN-OFF

Author:	Dr. Elena Vasquez	Date:	2025-05-25
Reviewer:	Dr. Lena Kowalski	Date:	2025-05-27
Approver:	Dr. Karen Mitchell	Date:	2025-05-30

END OF DOCUMENT - FD-TC-0099