

FILTER DESIGN TEST CASE

Lattice Filter - Band 8 (900 MHz) for Public Safety Band Filter
Design Validation and Performance Characterization

DOCUMENT INFORMATION

Document Number:	FD-TC-0100
Revision:	Rev A.3
Author:	Dr. Elena Vasquez
Reviewer:	Dr. Pierre Dubois
Design Center:	Cedar Rapids Lab
Created Date:	2024-11-16
Last Modified:	2024-11-21
Status:	NEEDS REVIEW
Priority:	P1 - Critical

1. OBJECTIVE

This document describes the design, simulation, and characterization of a Lattice Filter filter targeting Band 8 (900 MHz) for Public Safety Band Filter. The filter is designed on Langasite substrate with a target center frequency of 2075.2 MHz and bandwidth of 114.7 MHz. The objective is to validate that the filter meets the required insertion loss, rejection, and linearity specifications for integration into the Public Safety Band Filter module. This design iteration addresses feedback from the previous revision regarding out-of-band rejection improvements and temperature stability.

2. SCOPE

- Filter Type: Lattice Filter
- Frequency Band: Band 8 (900 MHz)
- Application: Public Safety Band Filter
- Substrate: Langasite
- Package: LGA (Land Grid Array)
- Design Tool: Matlab RF Toolbox R2024b
- Design Center: Cedar Rapids Lab

This specification applies to all variants of the Lattice Filter design targeting Band 8 (900 MHz). Results are used to qualify the design for mass production release.

3. DESIGN PARAMETERS

Center Frequency:	2075.2 MHz
Bandwidth (3 dB):	114.7 MHz
Insertion Loss Target:	≤ 1.9 dB
Return Loss Target:	≥ 18.0 dB
Out-of-Band Rejection:	≥ 43.0 dB
Isolation (Duplexer):	≥ 26.0 dB
Q Factor:	10939
Temperature Coefficient:	-5.3 ppm/°C
Die Size:	1.8 x 0.8 mm
Wafer Size:	6-inch
Number of Resonators:	6
Electrode Material:	Pt/Al

Passivation: SiO2

4. TEST PROCEDURE

1. Open Matlab RF Toolbox R2024b and load the Lattice Filter template project.
2. Define the substrate stack: Langasite with specified layer thicknesses.
3. Set design targets: center freq 2075.2 MHz, BW 114.7 MHz.
4. Run initial EM simulation with 2D mesh density of 20 cells/wavelength.
5. Optimize resonator geometry using gradient descent (target IL < 1.9 dB).
6. Verify coupling coefficients between resonator stages.
7. Run 3D FEM simulation to account for package parasitics (LGA (Land Grid Array)).
8. Export GDS-II layout for mask fabrication.
9. Fabricate prototype wafers (6-inch, Langasite).
10. Perform on-wafer probing using Rohde & Schwarz ZNB40.
11. Measure S-parameters (S11, S21, S12, S22) from 100 MHz to 6226 MHz.
12. Compare measured results against simulation and specification limits.
13. Perform temperature cycling (-40°C to +85°C) and re-measure.
14. Document results and generate summary report.

5. ACCEPTANCE CRITERIA

- Insertion loss at center frequency shall be <= 1.9 dB
- Return loss in passband shall be >= 18.0 dB
- Out-of-band rejection at +/- 172 MHz offset >= 43.0 dB
- Group delay variation across passband shall be <= 10 ns
- Temperature drift over -40°C to +85°C shall be <= 1.4 MHz
- Power handling shall be >= +32 dBm at 1 dB compression
- ESD tolerance >= 2000 V (HBM)
- Die yield on qualification lot >= 90%

6. TEST RESULTS

Measurement Date: 2024-11-21
Devices Tested: 23
Insertion Loss (meas): 1.62 dB
Return Loss (meas): 20.4 dB
Rejection (meas): 45.7 dB
Isolation (meas): 31.5 dB
Q Factor (meas): 10939
Group Delay Variation: 7.7 ns
Power Handling: +33 dBm
Die Yield: 82.7%

Result Classification: NEEDS REVIEW

7. OBSERVATIONS AND FINDINGS

- a) The Lattice Filter design demonstrated below-target performance for Band 8 (900 MHz).
- b) Insertion loss met target specification.
- c) Out-of-band rejection exceeded the minimum requirement.
- d) Group delay flatness improved compared to previous revision.
- e) No delamination observed after 1000-cycle thermal shock test.

8. CORRECTIVE ACTIONS

- 1. Review near-band rejection margin for worst-case temperature.
- 2. Re-run EM simulation with refined mesh for better accuracy.
- 3. Schedule follow-up measurement after design tweak.

9. SIGN-OFF

Author:	Dr. Elena Vasquez	Date:	2024-11-21
Reviewer:	Dr. Pierre Dubois	Date:	2024-11-27
Approver:	Dr. James Liu	Date:	2024-12-02

END OF DOCUMENT - FD-TC-0100