



KIET
GROUP OF INSTITUTIONS
Connecting Life with Learning



A

Project Synopsis

on

**X-Mal : An Explainable Deep Learning Framework for
interpreting Malware Classification using Attention Mechanism**

submitted as partial fulfillment for the award of

BACHELOR OF TECHNOLOGY

SESSION 2025-26

in

COMPUTER SCIENCE & ENGINEERING

By

Kanishka (2300290100132) (Team Leader)

Harshita Nathrani (2300290100121)

Meghna Chaudhary (2300290100151)

Pranjali (2300290100179)

Under the supervision of

Ms. Nishu Gupta, Mr. Rishab Singh Rathore

KIET Group of Institutions, Ghaziabad

Affiliated to

Dr. A.P.J. Abdul Kalam Technical University, Lucknow

(Formerly UPTU)

Academic Year 2025-26

Abstract

The exponential rise in sophisticated malware attacks, particularly polymorphic and zero-day variants, poses a critical threat to global cybersecurity infrastructure. Traditional signature-based detection systems, while fast, are increasingly ineffective against these evolving threats as they rely on known databases of malicious code.

Consequently, Deep Learning (DL) approaches have emerged as a robust alternative, capable of automatically learning complex patterns from raw data without manual feature engineering. Specifically, image-based malware detection—converting binaries into grayscale images—has demonstrated remarkable accuracy.

However, a critical barrier remains in the deployment of these advanced DL models: the "Black Box" problem. While Deep Learning models can detect malware with high precision, they fail to provide the reasoning behind their decisions. In cybersecurity operations, where false positives can disrupt business and false negatives can lead to data breaches, analysts require not just a prediction (e.g., "This is Ransomware") but an explanation (e.g., "Because of this specific code segment").

This project, X-Mal, proposes a novel framework that bridges the gap between high-performance detection and interpretability. We employ a Convolutional Neural Network (CNN) to classify malware families using visual representation learning. Crucially, we integrate Explainable AI (XAI) techniques, specifically Gradient-weighted Class Activation Mapping (Grad-CAM), to generate visual heatmaps.

These heatmaps highlight the specific regions of the malware binary that triggered the classification, providing security analysts with actionable insights. The proposed system aims to achieve detection accuracy comparable to state-of-the-art models (>95%) while offering the transparency required for trusted deployment in real-world security operations centers (SOCs).

Introduction

- Background and Motivation Malware (Malicious Software) is the primary weapon in the arsenal of cybercriminals, ranging from Adware and Trojans to destructive Ransomware. According to recent cybersecurity reports, hundreds of thousands of new malware variants are generated daily. Malware authors increasingly use "obfuscation" techniques—modifying the code structure while keeping the behavior the same—to bypass traditional antivirus software.
- To combat this, the industry is shifting towards Artificial Intelligence. Deep Learning models, inspired by the human brain, excel at pattern recognition. By treating a binary file (a sequence of 0s and 1s) as an image, Deep Learning models can "see" the texture of a virus in the same way they recognize a cat in a photo.
- However, the motivation for this specific project stems from a critical industry gap: Trust. A neural network is often opaque; it consists of millions of parameters that are unreadable to humans. If an AI system flags a critical system file as a virus, a security administrator needs to know *why* before deleting it. The lack of interpretability is the primary reason AI adoption lags in sensitive security domains.

Problem Statement and Research Gaps Existing research focuses heavily on maximizing Accuracy but often neglects Interpretability. The current landscape presents the following gaps:

- The Black Box Paradox: The most accurate models (Deep Neural Networks) are the least explainable.
- Semantic Gap: There is a disconnect between the visual features learned by a model and the actual assembly code functions (e.g., API calls) that analysts understand.
- Lack of Localization: Most systems output a simple label (Benign/Malicious) without localizing the threat within the file structure.
- Proposed Contribution This project aims to develop a "Glass Box" model that is both accurate and transparent. Our contributions are:

- Image-Based Detection: Implementing a robust CNN architecture to classify malware from the Maling dataset (or similar) by converting binaries to grayscale images.
 - Explainability Integration: Implementing Grad-CAM (Gradient-weighted Class Activation Mapping) to visualize the decision-making process.
 - Visual Validation: Providing a UI where the original malware image is overlaid with a heatmap, identifying the "suspicious" regions of the code.
- Technical Scope and Terms
 - Deep Learning (DL): A subset of ML using multi-layered neural networks.
 - CNN (Convolutional Neural Network): A class of DL models superior at analyzing visual imagery.
 - Obfuscation: Techniques used by attackers to hide the logic of their code (e.g., packing, encryption).
 - Grad-CAM: An XAI technique that uses the gradients of a target concept flowing into the final convolutional layer to produce a coarse localization map.

Literature Survey

The evolution of malware detection has transitioned through three distinct phases: Signature-based, Heuristic-based, and Learning-based approaches.

- Traditional Approaches: Early work by Moser et al. demonstrated the limitations of static analysis, showing that code obfuscation could easily evade detection. Commercial antiviruses (like Norton or McAfee) relied heavily on signature matching (hashing), which fails against "Zero-Day" (previously unknown) attacks.
- Machine Learning & Deep Learning Nataraj et al. (2011) were pioneers in the field of image-based malware detection. They visualized malware binaries as grayscale images and utilized GIST descriptors with K-Nearest Neighbors (KNN) to achieve high classification accuracy. This proved that malware families share visual structural similarities.
- More recently, Vasan et al. (2020) proposed IMCFN, a deep learning model using fine-tuned CNN architectures like VGG16 and ResNet-50. Their work achieved accuracies exceeding 98% on the Malimg dataset. However, their work was purely performance-oriented and did not offer explanations for the model's decisions.
- Explainable AI in Cybersecurity The integration of XAI is a nascent field. Rino et al. explored the use of LIME (Local Interpretable Model-agnostic Explanations) for tabular malware data. However,
- LIME is computationally expensive and slow for real-time applications. Selvaraju et al. introduced Grad-CAM for computer vision, which offers a more efficient way to visualize CNN decisions.

Conclusion of Survey: While image-based detection is mature, the application of Grad-CAM

to *interpret* these detections remains an active and open research area, justifying the scope of this project.

Methodology / Planning of Work

The project will be executed in the following sequential phases:

Phase 1: Data Acquisition and Preprocessing

- Dataset: We will utilize the Maling Dataset (consisting of 9,339 malware samples from 25 families) or the BIG 2015 dataset.
- Transformation: Raw binary files will be read as 8-bit integers. These vectors will be reshaped into 2D matrices (images) based on file size.
- Normalization: Pixel values will be normalized to the range $[0, 1]$ to facilitate faster model convergence.

Phase 2: Model Development (The "Brain")

- We will design a Convolutional Neural Network (CNN).
- Architecture: The model will consist of:
 - Convolutional Layers (Feature Extraction).
 - MaxPooling Layers (Dimensionality Reduction).
 - Dropout Layers (To prevent Overfitting).
 - Dense/Softmax Layers (Final Classification).
- The model will be trained using the Categorical Cross-Entropy loss function.

Phase 3: Explainability Module (The "Inspector")

- We will implement the Grad-CAM algorithm.
- The system will capture the gradients of the top predicted class with respect to the feature maps of the last convolutional layer.
- These gradients will be pooled to obtain neuron importance weights, generating a heatmap.

Phase 4: Evaluation and Analysis

- Performance Metrics: Accuracy, Precision, Recall, F1-Score, and Confusion Matrix.
- Interpretability Check: Visual inspection of heatmaps to verify if the model is focusing on relevant file sections (e.g., Header, Text Segment) versus irrelevant noise.

Facilities Required for Proposed Work

○ Hardware Requirements

- Processor: Intel Core i5/i7 (10th Gen or newer) or equivalent AMD Ryzen.
- RAM: Minimum 8GB (16GB recommended).
- GPU: NVIDIA GPU (GTX 1650 or higher) for local training, OR access to Cloud GPUs.
- Storage: 20GB free space for datasets and models.

○ Software Requirements

- Operating System: Windows 10/11 or Linux (Ubuntu).
- Programming Language: Python 3.8+.
- IDE: Jupyter Notebook, Google Colab (for cloud training), or VS Code.
- Libraries & Frameworks:
 - Deep Learning: TensorFlow (Keras) or PyTorch.
 - Image Processing: OpenCV, Pillow, Matplotlib.
 - Data Manipulation: NumPy, Pandas, Scikit-learn.
 - XAI Tools: tf-explain or custom Grad-CAM implementation.

References

1. L. Nataraj, S. Karthikeyan, G. Jacob, and B. S. Manjunath, "Malware images: visualization and automatic classification," in *Proceedings of the 8th International Symposium on Visualization for Cyber Security*, 2011.
2. D. Vasan, M. Alazab, S. Wassan, H. Naeem, and B. Safaei, "IMCFN: Image-based malware classification using fine-tuned convolutional neural network architecture," *Computer Networks*, vol. 171, 2020.
3. R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, "Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization," in *IEEE International Conference on Computer Vision (ICCV)*, 2017.
4. Standard Malware Datasets: Malimg Dataset / Microsoft BIG 2015.