

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)

chef

Class ChefOneTickScreen

```
java.lang.Object
  java.awt.Component
    java.awt.Container
      javax.swing.JComponent
        javax.swing.JPanel
          chef.ChefOneTickScreen
```

All Implemented Interfaces:

```
java.awt.image.ImageObserver, java.awt.MenuContainer, java.io.Serializable,
javax.accessibility.Accessible
```

```
public class ChefOneTickScreen
  extends javax.swing.JPanel
```

Panel that will be used when one ticket is selected from the list of tickets screen. Displays the current ticket - the dishes in it. This is where the chef would modify the status of each dish

Author:

aal122 and ns662

See Also:

[Serialized Form](#)

Nested Class Summary

Nested classes/interfaces inherited from class javax.swing.JComponent

```
javax.swing.JComponent.AccessibleJComponent
```

Nested classes/interfaces inherited from class java.awt.Component

```
java.awt.Component.BaselineResizeBehavior
```

Field Summary

Fields

Modifier and Type	Field and Description
-------------------	-----------------------

ChefInterface	ci way to access all the methods in the chef interface
Ticket	currTicket current ticket opened

Fields inherited from class javax.swing.JComponent

TOOL_TIP_TEXT_KEY, UNDEFINED_CONDITION, WHEN_ANCESTOR_OF_FOCUSED_COMPONENT, WHEN_FOCUSED, WHEN_IN_FOCUSED_WINDOW

Fields inherited from class java.awt.Component

BOTTOM_ALIGNMENT, CENTER_ALIGNMENT, LEFT_ALIGNMENT, RIGHT_ALIGNMENT, TOP_ALIGNMENT

Fields inherited from interface java.awt.image.ImageObserver

ABORT, ALLBITS, ERROR, FRAMEBITS, HEIGHT, PROPERTIES, SOMEBITS, WIDTH

Constructor Summary

Constructors

Constructor and Description

ChefOneTickScreen(**ChefInterface** chefInterface)

Constructor

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	setTicket (Ticket t) This is called when ever you switch to this screen, it sets up the ticket to be displayed on the screen.
void	updateScreen () Refreshes the screen

Methods inherited from class javax.swing.JPanel

getAccessibleContext, getUI, getUIClassID, setUI, updateUI

Methods inherited from class javax.swing.JComponent

addAncestorListener, addNotify, addVetoableChangeListener, computeVisibleRect, contains, createToolTip, disable, enable, firePropertyChange, firePropertyChange, firePropertyChange, getActionForKeyStroke, getActionMap, getAlignmentX, getAlignmentY, getAncestorListeners, getAutoscrolls, getBaseline, getBaselineResizeBehavior, getBorder, getBounds, getClientProperty, getComponentPopupMenu, getConditionForKeyStroke, getDebugGraphicsOptions, getDefaultLocale, getFontMetrics, getGraphics, getHeight, getInheritsPopupMenu, getInputMap, getInputMap, getInputVerifier, getInsets, getInsets, getListeners, getLocation, getMaximumSize, getMinimumSize, getNextFocusableComponent, getPopupLocation, getPreferredSize, getRegisteredKeyStrokes, getRootPane, getSize, getToolTipLocation, getToolTipText, getToolTipText, getTopLevelAncestor, getTransferHandler, getVerifyInputWhenFocusTarget, getVetoableChangeListeners, getVisibleRect, getWidth, getX, getY, grabFocus, hide, isDoubleBuffered, isLightweightComponent, isManagingFocus, isOpaque, isOptimizedDrawingEnabled, isPaintingForPrint, isPaintingTile, isRequestFocusEnabled, isValidRoot, paint, paintImmediately, paintImmediately, print, printAll, putClientProperty, registerKeyboardAction, registerKeyboardAction, removeAncestorListener, removeNotify, removeVetoableChangeListener, repaint, repaint, requestDefaultFocus, requestFocus, requestFocus, requestFocusInWindow, resetKeyboardActions, reshape, revalidate, scrollRectToVisible, setActionMap, setAlignmentX, setAlignmentY, setAutoscrolls, setBackground, setBorder, setComponentPopupMenu, setDebugGraphicsOptions, setDefaultLocale, setDoubleBuffered, setEnabled, setFocusTraversalKeys, setFont, setForeground, setInheritsPopupMenu, setInputMap, setInputVerifier, setMaximumSize, setMinimumSize, setNextFocusableComponent, setOpaque, setPreferredSize, setRequestFocusEnabled, setToolTipText, setTransferHandler, setVerifyInputWhenFocusTarget, setVisible, unregisterKeyboardAction, update

Methods inherited from class java.awt.Container

add, add, add, add, add, addContainerListener, addPropertyChangeListener, addPropertyChangeListener, applyComponentOrientation, areFocusTraversalKeysSet, countComponents, deliverEvent, doLayout, findComponentAt, findComponentAt, getComponent, getComponentAt, getComponentAt, getComponentCount, getComponents, getComponentZOrder, getContainerListeners, getFocusTraversalKeys, getFocusTraversalPolicy, getLayout, getMousePosition, insets, invalidate, isAncestorOf, isFocusCycleRoot, isFocusCycleRoot, isFocusTraversalPolicyProvider, isFocusTraversalPolicySet, layout, list, list, locate, minimumSize, paintComponents, preferredSize, printComponents, remove, remove, removeAll, removeContainerListener, setComponentZOrder, setFocusCycleRoot, setFocusTraversalPolicy, setFocusTraversalPolicyProvider, setLayout,

transferFocusDownCycle, validate

Methods inherited from class java.awt.Component

action, add, addComponentListener, addFocusListener, addHierarchyBoundsListener, addHierarchyListener, addInputMethodListener, addKeyListener, addMouseListener, addMouseMotionListener, addMouseWheelListener, bounds, checkImage, checkImage, contains, createImage, createImage, createVolatileImage, createVolatileImage, dispatchEvent, enable, enableInputMethods, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, getBackground, getBounds, getColorModel, getComponentListeners, getComponentOrientation, getCursor, getDropTarget, getFocusCycleRootAncestor, getFocusListeners, getFocusTraversalKeysEnabled, getFont, getForeground, getGraphicsConfiguration, getHierarchyBoundsListeners, getHierarchyListeners, getIgnoreRepaint, getInputContext, getInputMethodListeners, getInputMethodRequests, getKeyListeners, getLocale, getLocation, getLocationOnScreen, getMouseListeners, getMouseMotionListeners, getMousePosition, getMouseWheelListeners, getName, getParent, getPeer, getPropertyChangeListeners, getPropertyChangeListeners, getSize, getToolkit, getTreeLock, gotFocus, handleEvent, hasFocus, imageUpdate, inside, isBackgroundSet, isCursorSet, isDisplayable, isEnabled, isFocusable, isFocusOwner, isFocusTraversable, isFontSet, isForegroundSet, isLightweight, isMaximumSizeSet, isMinimumSizeSet, isPreferredSizeSet, isShowing, isValid, isVisible, keyDown, keyUp, list, list, list, location, lostFocus, mouseDown, mouseDrag, mouseEnter, mouseExit, mouseMove, mouseUp, move, nextFocus, paintAll, postEvent, prepareImage, prepareImage, remove, removeComponentListener, removeFocusListener, removeHierarchyBoundsListener, removeHierarchyListener, removeInputMethodListener, removeKeyListener, removeMouseListener, removeMouseMotionListener, removeMouseWheelListener, removePropertyChangeListener, removePropertyChangeListener, repaint, repaint, repaint, resize, resize, setBounds, setBounds, setComponentOrientation, setCursor, setDropTarget, setFocusable, setFocusTraversalKeysEnabled, setIgnoreRepaint, setLocale, setLocation, setLocation, setName, setSize, setSize, show, show, size, toString, transferFocus, transferFocusBackward, transferFocusUpCycle

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Field Detail

currTicket

```
public Ticket currTicket
```

current ticket opened

```
ci
```

```
public ChefInterface ci
```

way to access all the methods in the chef interface

Constructor Detail

```
ChefOneTickScreen
```

```
public ChefOneTickScreen(ChefInterface chefInterface)
```

Constructor

Parameters:

chefInterface -

Method Detail

```
setTicket
```

```
public void setTicket(Ticket t)
```

This is called when ever you switch to this screen, it sets up the ticket to be displayed on the screen.

Parameters:

t - - ticket to be displayed

```
updateScreen
```

```
public void updateScreen()
```

Refreshes the screen

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)

SUMMARY: NESTED | FIELD | CONSTR | METHOD

DETAIL: FIELD | CONSTR | METHOD