

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)

waiter

Class WaiterMessageListener

```
java.lang.Object
  java.lang.Thread
    waiter.WaiterMessageListener
```

All Implemented Interfaces:

```
java.lang.Runnable
```

```
public class WaiterMessageListener
  extends java.lang.Thread
```

Used to listen from messages from the message controller and decode them.

Author:

cms549

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.Thread

```
java.lang.Thread.State, java.lang.Thread.UncaughtExceptionHandler
```

Field Summary

Fields inherited from class java.lang.Thread

```
MAX_PRIORITY, MIN_PRIORITY, NORM_PRIORITY
```

Constructor Summary

Constructors

Constructor and Description

```
WaiterMessageListener(java.net.Socket listener, WaiterInterface wI)
```

Constructor

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	run() Listens for messages sent from the MC

Methods inherited from class java.lang.Thread

activeCount, checkAccess, countStackFrames, currentThread, destroy, dumpStack, enumerate, getAllStackTraces, getContextClassLoader, getDefaultUncaughtExceptionHandler, getId, getName, getPriority, getStackTrace, getState, getThreadGroup, getUncaughtExceptionHandler, holdsLock, interrupt, interrupted, isAlive, isDaemon, isInterrupted, join, join, join, resume, setContextClassLoader, setDaemon, setDefaultUncaughtExceptionHandler, setName, setPriority, setUncaughtExceptionHandler, sleep, sleep, start, stop, stop, suspend, toString, yield

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

WaiterMessageListener

```
public WaiterMessageListener(java.net.Socket listener,
                             WaiterInterface wI)
```

Constructor

Parameters:

listener - - socket to listen to

wI - - waiter interface

Method Detail

run

```
public void run()
```

Listens for messages sent from the MC

Specified by:

run in interface `java.lang.Runnable`

Overrides:

run in class `java.lang.Thread`

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)

[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)