

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)[SUMMARY: NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)

chef

Class ChefMessageListener

```
java.lang.Object
  java.lang.Thread
    chef.ChefMessageListener
```

All Implemented Interfaces:

```
java.lang.Runnable
```

```
public class ChefMessageListener
  extends java.lang.Thread
```

Used to listen from messages from the message controller and decode them.

Author:

cms549

Nested Class Summary

Nested classes/interfaces inherited from class java.lang.Thread

```
java.lang.Thread.State, java.lang.Thread.UncaughtExceptionHandler
```

Field Summary

Fields inherited from class java.lang.Thread

```
MAX_PRIORITY, MIN_PRIORITY, NORM_PRIORITY
```

Constructor Summary

Constructors

Constructor and Description

```
ChefMessageListener(java.net.Socket listener, ChefInterface wI)
```

Constructor

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
void	run() Listens for messages sent from the MC

Methods inherited from class java.lang.Thread

activeCount, checkAccess, countStackFrames, currentThread, destroy, dumpStack, enumerate, getAllStackTraces, getContextClassLoader, getDefaultUncaughtExceptionHandler, getId, getName, getPriority, getStackTrace, getState, getThreadGroup, getUncaughtExceptionHandler, holdsLock, interrupt, interrupted, isAlive, isDaemon, isInterrupted, join, join, join, resume, setContextClassLoader, setDaemon, setDefaultUncaughtExceptionHandler, setName, setPriority, setUncaughtExceptionHandler, sleep, sleep, start, stop, stop, suspend, toString, yield

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

ChefMessageListener

```
public ChefMessageListener(java.net.Socket listener,
                           ChefInterface wI)
```

Constructor

Parameters:

listener - - socket to listen to

cI - - chef interface

Method Detail

run

```
public void run()
```

Listens for messages sent from the MC

Specified by:

run in interface `java.lang.Runnable`

Overrides:

run in class `java.lang.Thread`

[OVERVIEW](#) [PACKAGE](#) [CLASS](#) [USE](#) [TREE](#) [DEPRECATED](#) [INDEX](#) [HELP](#)

[PREV CLASS](#) [NEXT CLASS](#) [FRAMES](#) [NO FRAMES](#) [ALL CLASSES](#)

SUMMARY: [NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#) [DETAIL: FIELD](#) | [CONSTR](#) | [METHOD](#)