

Computer Programming

Dr. Deepak B Phatak
Dr. Supratik Chakraborty
Department of Computer Science and Engineering
IIT Bombay

Session: Sorting Strings and Other Data Types

Quick Recap of Relevant Topics



- The sorting problem
- Selection sort
- Merge sort
- Counting “basic” steps in sorting an array

Overview of This Lecture




- Sorting strings and other data types
- Other techniques for sorting ...

Food For Thought ...


- We've looked at techniques for sorting arrays of integers
- What if we wanted to sort arrays of
 - floats, doubles, ...
 - strings ...
 - more complex data items ...
- Do we need to re-invent sorting techniques?

NO!!! Almost the same techniques used for integers also work in these other settings!

Recap: How Did We Sort Integers?



Recap: Selection Sort (Decreasing Order)



Recap: Selection Sort in C++ (For Integers)



```
int main() {  
    ... Declarations, input validation and reading elements of array A ...  
    // Selection sort  
    int currTop, currMaxIndex; // A[currTop] ... A[n-1] is unsorted array  
    for (currTop = 0; currTop < n; currTop++) {  
        currMaxIndex = findIndexOfMax(A, currTop, n);  
        swap(A, currTop, currMaxIndex);  
    }  
    ... Rest of code ...  
    return 0;  
}
```

Recap: Selection Sort in C++ (For Integers)



// PRECONDITION: start <= end


// start, end within array bounds of A

```
int findIndexOfMax(int A[], int start, int end) {  
    int i, currMaxIndex = start;  
    for ( i = start ; i < end; i++ ) {  
        if (A[i] >= A[currMaxIndex]) { currMaxIndex = i; }  
    }  
    return currMaxIndex;  
}
```


// POSTCONDITION: A[currMaxIndex] at least as large as

// all elements in A[start] through A[end-1], no change in A


Can We Use The Same Idea To Sort Strings?



Selection Sort (Lexicographic Order)



Selection Sort (Lexicographic Order)




If we can select lexicographically first string in unsorted (sub)-array, we can sort strings lexicographically

How do we select lexicographically first element?

Iterate over array and compare (order) pairs of elements

Selection Sort (Lexicographic Order)



If we have a function to lexicographically compare a pair of strings, we can sort strings !!!

Comparing Strings



- Assume availability of function

// PRECONDITION: s1, s2 strings

bool lexEarlier(string s1, string s2) {

...

}

// POSTCONDITION: return true if and only if s1

// lexicographically before s2

- We'll see later (when we study strings) how to implement **lexEarlier**

Selection Sort in C++ (For Strings)

```
int main() {  
    ... Declarations, input validation and reading elements of array A ...  
    // Selection sort: A is an array of strings  
    int currTop, currLexFirstIndex; //A[currTop] ... A[n-1] is unsorted array  
    for (currTop = 0; currTop < n; currTop++) {  
        currLexFirstIndex = findIndexOfLexFirst(A, currTop, n);  
        swap(A, currTop, currLexFirstIndex);  
    }  
    ... Rest of code ...  
    return 0;  
}
```

Selection Sort In C++ (For Strings)

```
int findIndexOfLexFirst(string A[], int start, int end) {  
    int i, currLexFirstIndex = start;  
    for ( i = start ; i < end; i++ ) {  
        if ( lexEarlier (A[i], A[currLexFirstIndex]) ) {  
            currLexFirstIndex = i;  
        }  
    }  
    return currLexFirstIndex;  
}
```

Array of strings

How About Merge Sort On Strings?



- Did we just get lucky with selection sort?
- Can we sort strings using merge sort, given the function **lexEarlier** ?

What Were The Steps In Merge Sort?

- Divide an array of size n into two sub-arrays of size $\approx n/2$
 - Sub-array sizes may differ by 1 if n is odd
 - Easy!
- Sort each sub-array of size $n/2$
 - Use same technique as for sorting original array (recurse !!!)
 - Termination case of recursion: arrays of size 1
- Merge sorted sub-arrays, each of size $n/2$
 - One pass over each sorted sub-array

Crucial Step

Recap: Merging Sorted Sub-arrays (of int) In C++



```
// PRECONDITION: A[start] ... A[mid-1] and A[mid] ... A[end-1] sorted in  
// decreasing order
```

```
void mergeSortedSubarrays(int A[], int start, int mid, int end) {  
    int i, j; int tempA[100], index = start;  
    for (i = start, j = mid; ((i < mid) || (j < end)); ) { // Merging loop  
        // Determine whether A[i] or A[j] should appear next in sorted order  
        // Update tempA[index] accordingly  
        index++;  
    } // end of merging loop  
    // Copy tempA[start] ... tempA[end-1] to A[start] ... A[end-1]  
    return;  
}
```

```
// POSTCONDITION: A[start] ... A[end-1] sorted in decreasing order
```

Recap: Merging Loop (for int) In C++

```
for (i = start, j = mid; ((i < mid) || (j < end)); ) { // Merging loop
    if ((i < mid) && (j < end)) { // None of the two subarrays fully seen yet
        if (A[j] > A[i])    {tempA[index] = A[j];  j++;}
        else                {tempA[index] = A[i];  i++;}
    }
    else { if (i < mid) {tempA[index] = A[i]; i++;} // A[mid] ... A[end-1] seen
          else        {tempA[index] = A[j]; j++;} // A[start] ... A[mid-1] seen
    }
    index++;
} // end of merging loop
```

Merging Sorted Sub-arrays Of Strings In C++

```
// PRECONDITION: A[start] ... A[mid-1] and A[mid] ... A[end-1] sorted in
// lexicographic order
void mergeSortedSubarrays(string A[], int start, int mid, int end) {
    int i, j; string tempA[100]; int index = start;
    for (i = start, j = mid; ((i < mid) || (j < end)); ) { // Merging loop
        // Determine whether A[i] or A[j] should appear next in sorted order
        // Update tempA[index] accordingly
        index++;
    } // end of merging loop
    // Copy tempA[start] ... tempA[end-1] to A[start] ... A[end-1]
    return;
}
// POSTCONDITION: A[start] ... A[end-1] sorted in lexicographic order
```

Merging Loop (For Strings) In C++

```
for (i = start, j = mid; ((i < mid) || (j < end)); ) { // Merging loop
    if ((i < mid) && (j < end)) { // None of the two subarrays fully seen yet
        if (lexEarlier(A[j], A[i])) {tempA[index] = A[j]; j++;}
        else {tempA[index] = A[i]; i++;}
    }
    else { if (i < mid) {tempA[index] = A[i]; i++;} // A[mid] ... A[end-1] seen
           else {tempA[index] = A[j]; j++;} // A[start] ... A[mid-1] seen
    }
    index++;
} // end of merging loop
```

What About Arrays Of Other Data Types?

- Pretty much the same technique as for int/string arrays
- Define an ordering function/operator
 - \geq for integers
 - `lexEarlier(s1, s2)` for strings
 - ...
- Rest of it is the same ...

Other Sorting Techniques



- Selection sort and merge sort not the only sorting techniques
- Other important sorting techniques
 - Quick sort
 - Heap sort
 - Insertion sort ...All of these can be implemented in C++
- An extremely interesting area of study

Summary



- Sorting strings
 - Key use of comparison operator
- Sorting other data types
- Other sorting techniques