

Electronic Mail (Email)


Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include: <http://commons.wikimedia.org> (Wikipedia, Wikimedia and workbooks); <http://www.sxc.hu> and <http://www.pixabay.com>

Background

- One of Internet's oldest (1971) and very widely used application
- Provides an asynchronous mode of communication
 - Fast, easy, inexpensive
- Evolved over the years to support many features
 - Attachments, confirmation, group-emails, spam-filters etc

Other Email Services

- CC, BCC, high-priority, alternative recipients
- Mailing lists
- Mailboxes to store and manage emails
- Email forwarding (e.g. when people move away);
automated replies


A diagram illustrating email forwarding. It shows a red '@' symbol followed by a red 'A' above it, a red arrow pointing to the right, a red 'B' above it, and another red '@' symbol followed by a red 'B' below it. This represents the transition of an email address from A to B.
- Filters: Detect spam, Message from friends go to mailbox1 etc

Two Basic Components

- User Agents (Mail Readers)
 - Local programs that help people read, send and manage emails
 - Can be text based or GUI based
 - E.g. pine, [↑]elm, Microsoft Outlook, Mozilla Thunderbird



Microsoft
Office Outlook 2007



Two Basic Components

- Message Transfer Agents
 - Daemons (processes) that run in background to move messages from source to destination host
 - Agents implement required protocols

Message Format

Message: From: Date
To :
Dear Madam,
Sub:
Ref:
Blah Blah
Yours Sincerely,
. . . .
Envelope : Address

- Envelope encapsulates the message
- Envelope contains information needed to transport message
 - Destination address, priority, security level etc
 - Message transfer agents use it to route message to correct destination
- Envelope derived from the header fields in the message

RFC 5322 (old RFC 822)

- Message within envelope contains header and body
 - Both are represented in ASCII text
 - Header contains control information for user agents
 - Body is for human consumption
 - Header separated from message body by blank line
- Header is a series of <CRLF> terminated lines
 - Contains type and value separated by a colon
 - *body*
• From: , To: , Date: , Message-ID, , CC: , BCC: , Sender: ,
Subject:, Received: , Return-Path:, Reply-To: etc
 - *secondary*

Message Body and MIME

- Early days, email was made of English text messages, expressed in ASCII
 - No support for foreign languages
 - No support for non-text attachments (pdf, doc, jpg, audio files etc)
- Solution: Multipurpose Internet Mail Extensions (MIME)
 - Additional headers
 - Define content types and subtypes
 - Add structure to message body
 - Encoding rules for non ASCII messages (convert them to ASCII)

Headers added by MIME

Header	Meaning
MIME-Version	Identifies the MIME Version
Content-Description	ASCII string that tells what is in the message
Content-ID	Unique identifier
Content-Type	Type of data contained in the message
Content-Transfer-Encoding	How the data in message is encoded (e.g. <u>7bit</u> , <u>Base64</u>)

Content-Type:

Text/Plain – Unformatted text

Text/Enriched – Simple formatted text

Image/Jpeg – Picture in jpeg format

Video/Mpeg – Video in mpeg format
Application/Msword – word document
Message/Mixed – Message made of independent pieces (each piece has own header line)

Example


- Look at the uploaded message format

Implementation Choices

- First email system was based on file transfer protocol
 - No internal structure; Many features missing
- How about direct connection between sending and receiving host?
 - Receiver machine may not always be on
 - User may want to retrieve mail from multiple machines
- Need always-on hosts → Shared Mail Servers


Architecture

- Sending mails is a PUSH operation
 - SMTP protocol
- Receiving mails is a PULL operation
 - POP3, IMAP, HTTP



Mail Servers

- Each user has a mailbox in a mail server, where user messages are stored
- Mail server also maintains a message queue of outgoing messages
 - In case of failure, attempts retransmissions and informs sender if it drops the message
- Both client and server side of SMTP run on a mail server



Summary

- Email is one of the oldest and a very popular application
- Enabled by User agents and Message transfer agents
- Email Messages are ASCII based and made up of header fields and body
- Architecture based on mail servers who move messages between hosts
 - Mail transfer protocol: SMTP
 - Mail access protocol: POP3/IMAP/HTTP