

CS 228 : Logic in Computer Science

Krishna. S

Summary

- ▶ Proof Rules
- ▶ Soundness : If $\varphi \vdash \psi$, then $\varphi \models \psi$.
- ▶ Completeness : If $\varphi \models \psi$, then $\varphi \vdash \psi$.
- ▶ Normal Forms

Satisfiability Checking : Horn Formulae

- ▶ A **Horn Formula** is a particularly nice kind of CNF formula, which can be **quickly** checked for satisfiability.

Satisfiability Checking : Horn Formulae

- ▶ A **Horn Formula** is a particularly nice kind of CNF formula, which can be **quickly** checked for satisfiability.
- ▶ A formula F is a Horn formula if it is in CNF and every disjunction contains at most one positive literal.

Satisfiability Checking : Horn Formulae

- ▶ A **Horn Formula** is a particularly nice kind of CNF formula, which can be **quickly** checked for satisfiability.
- ▶ A formula F is a Horn formula if it is in CNF and every disjunction contains at most one positive literal.
- ▶ $p \wedge (\neg p \vee \neg q \vee r) \wedge (\neg a \vee \neg b)$ is Horn, but $a \vee b$ is not Horn.

Satisfiability Checking : Horn Formulae

- ▶ A **Horn Formula** is a particularly nice kind of CNF formula, which can be **quickly** checked for satisfiability.
- ▶ A formula F is a Horn formula if it is in CNF and every disjunction contains at most one positive literal.
- ▶ $p \wedge (\neg p \vee \neg q \vee r) \wedge (\neg a \vee \neg b)$ is Horn, but $a \vee b$ is not Horn.
- ▶ A basic Horn formula is one which has no \wedge . Every Horn formula is a conjunction of basic Horn formulae.

Satisfiability Checking : Horn Formulae

- ▶ Three types of basic Horn : no positive literals, no negative literals, have both positive and negative literals.

Satisfiability Checking : Horn Formulae

- ▶ Three types of basic Horn : no positive literals, no negative literals, have both positive and negative literals.
- ▶ Basic Horn with both positive and negative literals are written as an implication $p \wedge q \wedge \cdots \wedge r \rightarrow s$ involving only positive literals.

Satisfiability Checking : Horn Formulae

- ▶ Three types of basic Horn : no positive literals, no negative literals, have both positive and negative literals.
- ▶ Basic Horn with both positive and negative literals are written as an implication $p \wedge q \wedge \cdots \wedge r \rightarrow s$ involving only positive literals.
- ▶ Basic Horn with no negative literals are of the form p and are written as $\top \rightarrow p$.

Satisfiability Checking : Horn Formulae

- ▶ Three types of basic Horn : no positive literals, no negative literals, have both positive and negative literals.
- ▶ Basic Horn with both positive and negative literals are written as an implication $p \wedge q \wedge \cdots \wedge r \rightarrow s$ involving only positive literals.
- ▶ Basic Horn with no negative literals are of the form p and are written as $\top \rightarrow p$.
- ▶ Basic Horn with no positive literals are written as $p \wedge q \wedge \cdots \wedge r \rightarrow \perp$.

Satisfiability Checking : Horn Formulae

- ▶ Three types of basic Horn : no positive literals, no negative literals, have both positive and negative literals.
- ▶ Basic Horn with both positive and negative literals are written as an implication $p \wedge q \wedge \cdots \wedge r \rightarrow s$ involving only positive literals.
- ▶ Basic Horn with no negative literals are of the form p and are written as $\top \rightarrow p$.
- ▶ Basic Horn with no positive literals are written as $p \wedge q \wedge \cdots \wedge r \rightarrow \perp$.
- ▶ Thus, a Horn formula is written as a conjunction of implications.

The Horn Algorithm

Given a Horn formula H ,

- ▶ Mark all occurrences of p , whenever $\top \rightarrow p$ is a subformula.

The Horn Algorithm

Given a Horn formula H ,

- ▶ Mark all occurrences of p , whenever $\top \rightarrow p$ is a subformula.
- ▶ If there is a subformula of the form $(p_1 \wedge \cdots \wedge p_m) \rightarrow q$, where each p_i is marked, and q is not marked, mark q . Repeat this until there are no subformulae of this form and proceed to the next step.

The Horn Algorithm

Given a Horn formula H ,

- ▶ Mark all occurrences of p , whenever $\top \rightarrow p$ is a subformula.
- ▶ If there is a subformula of the form $(p_1 \wedge \cdots \wedge p_m) \rightarrow q$, where each p_i is marked, and q is not marked, mark q . Repeat this until there are no subformulae of this form and proceed to the next step.
- ▶ Consider subformulae of the form $(p_1 \wedge \cdots \wedge p_m) \rightarrow \perp$. If there is one such subformula with all p_i marked, then say **Unsat**, otherwise say **Sat**.

An Example

$$(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$$

An Example

$$(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$$

► $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$

An Example

$$(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$$

- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$
- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$

An Example

$$(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$$

- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$
- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$
- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$

An Example

$$(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$$

- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$
- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$
- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$
- ▶ $(\top \rightarrow A) \wedge (C \rightarrow D) \wedge ((A \wedge B) \rightarrow C) \wedge ((C \wedge D) \rightarrow \perp) \wedge (\top \rightarrow B).$

The Horn Algorithm

The Horn algorithm concludes **Sat** iff H is satisfiable.

The Horn Algorithm

The Horn algorithm concludes **Sat** iff H is satisfiable.

- ▶ Let $S = \{p_1, \dots, p_n\}$ be the set of propositions occurring in H . At the end of the algorithm, some of these are marked.

The Horn Algorithm

The Horn algorithm concludes Sat iff H is satisfiable.

- ▶ Let $S = \{p_1, \dots, p_n\}$ be the set of propositions occurring in H . At the end of the algorithm, some of these are marked.
- ▶ Assume H is satisfiable. Then there is an assignment α of S such that $\alpha \models H$. For each basic Horn formula B of H , $\alpha(B) = 1$. Also, $\alpha(\perp) = 0$ and $\alpha(\top) = 1$.

The Horn Algorithm

The Horn algorithm concludes Sat iff H is satisfiable.

- ▶ Let $S = \{p_1, \dots, p_n\}$ be the set of propositions occurring in H . At the end of the algorithm, some of these are marked.
- ▶ Assume H is satisfiable. Then there is an assignment α of S such that $\alpha \models H$. For each basic Horn formula B of H , $\alpha(B) = 1$. Also, $\alpha(\perp) = 0$ and $\alpha(\top) = 1$.
- ▶ If B has the form $\top \rightarrow p_i$, then $\alpha(p_i) = 1$. If B has the form $(p_1 \wedge \dots \wedge p_n) \rightarrow q$, where each $\alpha(p_i) = 1$, then $\alpha(q) = 1$. Hence, $\alpha(p_i)$ agrees with the marking of the algo.

The Horn Algorithm

- ▶ Will the algo say unsat?

The Horn Algorithm

- ▶ Will the algo say unsat?
- ▶ If it does, there is some $(p_1 \wedge \dots p_m) \rightarrow \perp$, where all p_i 's are marked.

The Horn Algorithm

- ▶ Will the algo say unsat?
- ▶ If it does, there is some $(p_1 \wedge \dots p_m) \rightarrow \perp$, where all p_i 's are marked.
- ▶ Then $\alpha(p_i) = 1$ for all i and $\alpha((p_1 \wedge \dots p_m) \rightarrow \perp) = 0$, a contradiction to the assumption about α .

The Horn Algorithm

- ▶ Will the algo say unsat?
- ▶ If it does, there is some $(p_1 \wedge \dots p_m) \rightarrow \perp$, where all p_i 's are marked.
- ▶ Then $\alpha(p_i) = 1$ for all i and $\alpha((p_1 \wedge \dots p_m) \rightarrow \perp) = 0$, a contradiction to the assumption about α .
- ▶ Conversely, assume that the algo says *Sat*. Show that there exists a satisfying assignment α , using the markings made by the algo.

The Horn Algorithm

- ▶ Will the algo say unsat?
- ▶ If it does, there is some $(p_1 \wedge \dots p_m) \rightarrow \perp$, where all p_i 's are marked.
- ▶ Then $\alpha(p_i) = 1$ for all i and $\alpha((p_1 \wedge \dots p_m) \rightarrow \perp) = 0$, a contradiction to the assumption about α .
- ▶ Conversely, assume that the algo says *Sat*. Show that there exists a satisfying assignment α , using the markings made by the algo. **Let α be the assignment of \mathcal{S} defined by $\alpha(p_i) = 1$ iff p_i is marked. We claim that $\alpha \models H$.**

The Horn Algorithm

- ▶ Will the algo say unsat?
- ▶ If it does, there is some $(p_1 \wedge \dots p_m) \rightarrow \perp$, where all p_i 's are marked.
- ▶ Then $\alpha(p_i) = 1$ for all i and $\alpha((p_1 \wedge \dots p_m) \rightarrow \perp) = 0$, a contradiction to the assumption about α .
- ▶ Conversely, assume that the algo says **Sat**. Show that there exists a satisfying assignment α , using the markings made by the algo. **Let α be the assignment of \mathcal{S} defined by $\alpha(p_i) = 1$ iff p_i is marked. We claim that $\alpha \models H$.**
- ▶ Show that $\alpha \models B$ for each basic Horn formula B of H .

The Horn Algorithm

- ▶ If B has the form $\top \rightarrow p$, then p is marked in step 1 of the algo, and so $\alpha(B) = 1$.

The Horn Algorithm

- ▶ If B has the form $\top \rightarrow p$, then p is marked in step 1 of the algo, and so $\alpha(B) = 1$.
- ▶ If B has the form $p_1 \wedge \dots p_m \rightarrow q$, then q is either \perp or an atomic formula.

The Horn Algorithm

- ▶ If B has the form $\top \rightarrow p$, then p is marked in step 1 of the algo, and so $\alpha(B) = 1$.
- ▶ If B has the form $p_1 \wedge \dots p_m \rightarrow q$, then q is either \perp or an atomic formula.
- ▶ If some p_i was not marked, then $\alpha(p_i) = 0$, and hence $\alpha(B) = 1$.

The Horn Algorithm

- ▶ If B has the form $\top \rightarrow p$, then p is marked in step 1 of the algo, and so $\alpha(B) = 1$.
- ▶ If B has the form $p_1 \wedge \dots p_m \rightarrow q$, then q is either \perp or an atomic formula.
- ▶ If some p_i was not marked, then $\alpha(p_i) = 0$, and hence $\alpha(B) = 1$.
- ▶ Assume all the p_i 's were marked. Then $\alpha(p_i) = 1$ for all i . Since the algo said *Sat*, $q \neq \perp$. Then q is also marked (step 2 of algo). Hence, $\alpha(q) = 1$, and we have $\alpha(B) = 1$.

The Horn Algorithm

- ▶ If B has the form $\top \rightarrow p$, then p is marked in step 1 of the algo, and so $\alpha(B) = 1$.
- ▶ If B has the form $p_1 \wedge \dots p_m \rightarrow q$, then q is either \perp or an atomic formula.
- ▶ If some p_i was not marked, then $\alpha(p_i) = 0$, and hence $\alpha(B) = 1$.
- ▶ Assume all the p_i 's were marked. Then $\alpha(p_i) = 1$ for all i . Since the algo said *Sat*, $q \neq \perp$. Then q is also marked (step 2 of algo). Hence, $\alpha(q) = 1$, and we have $\alpha(B) = 1$.
- ▶ Thus, the markings of the algorithm gives rise to a satisfying assignment α if the algorithm said *Sat*.

Complexity of Horn

- ▶ Given a Horn formula ψ with n propositions, how many times do you have to read ψ ?
- ▶ Step 1: Read once
- ▶ Step 2: Read at most n times
- ▶ Step 3: Read once

Resolution

- ▶ Resolution is a technique used to check if a formula in CNF is satisfiable. Call each conjunct in the CNF a clause.

Resolution

- ▶ Resolution is a technique used to check if a formula in CNF is satisfiable. Call each conjunct in the CNF a clause.
- ▶ If $\psi = (a \vee b \vee \neg d) \wedge (d \vee \neg a \vee b)$, then $C_1 = \{a, b, \neg d\}$ and $C_2 = \{d, \neg a, b\}$ are the two clauses.

Resolution

- ▶ Resolution is a technique used to check if a formula in CNF is satisfiable. Call each conjunct in the CNF a clause.
- ▶ If $\psi = (a \vee b \vee \neg d) \wedge (d \vee \neg a \vee b)$, then $C_1 = \{a, b, \neg d\}$ and $C_2 = \{d, \neg a, b\}$ are the two clauses.
- ▶ We also write ψ as $\{\{a, b, \neg d\}, \{d, \neg a, b\}\}$.

Resolution

- ▶ Resolution is a technique used to check if a formula in CNF is satisfiable. Call each conjunct in the CNF a clause.
- ▶ If $\psi = (a \vee b \vee \neg d) \wedge (d \vee \neg a \vee b)$, then $C_1 = \{a, b, \neg d\}$ and $C_2 = \{d, \neg a, b\}$ are the two clauses.
- ▶ We also write ψ as $\{\{a, b, \neg d\}, \{d, \neg a, b\}\}$.
- ▶ Let C_1, C_2 be two clauses. Assume $a \in C_1$ and $\neg a \in C_2$ for some atomic formula a . Then the clause $R = (C_1 - \{a\}) \cup (C_2 - \{\neg a\})$ is a **resolvent** of C_1 and C_2 .

Resolution

- ▶ Resolution is a technique used to check if a formula in CNF is satisfiable. Call each conjunct in the CNF a clause.
- ▶ If $\psi = (a \vee b \vee \neg d) \wedge (d \vee \neg a \vee b)$, then $C_1 = \{a, b, \neg d\}$ and $C_2 = \{d, \neg a, b\}$ are the two clauses.
- ▶ We also write ψ as $\{\{a, b, \neg d\}, \{d, \neg a, b\}\}$.
- ▶ Let C_1, C_2 be two clauses. Assume $a \in C_1$ and $\neg a \in C_2$ for some atomic formula a . Then the clause $R = (C_1 - \{a\}) \cup (C_2 - \{\neg a\})$ is a **resolvent** of C_1 and C_2 .
- ▶ Let $C_1 = \{a_1, \neg a_2, a_3\}$ and $C_2 = \{a_2, \neg a_3, a_4\}$. As $a_3 \in C_1$ and $\neg a_3 \in C_2$, we can find the resolvent. A resolvent is $\{a_1, a_2, \neg a_2, a_4\}$.

Resolution

- ▶ Resolution is a technique used to check if a formula in CNF is satisfiable. Call each conjunct in the CNF a clause.
- ▶ If $\psi = (a \vee b \vee \neg d) \wedge (d \vee \neg a \vee b)$, then $C_1 = \{a, b, \neg d\}$ and $C_2 = \{d, \neg a, b\}$ are the two clauses.
- ▶ We also write ψ as $\{\{a, b, \neg d\}, \{d, \neg a, b\}\}$.
- ▶ Let C_1, C_2 be two clauses. Assume $a \in C_1$ and $\neg a \in C_2$ for some atomic formula a . Then the clause $R = (C_1 - \{a\}) \cup (C_2 - \{\neg a\})$ is a **resolvent** of C_1 and C_2 .
- ▶ Let $C_1 = \{a_1, \neg a_2, a_3\}$ and $C_2 = \{a_2, \neg a_3, a_4\}$. As $a_3 \in C_1$ and $\neg a_3 \in C_2$, we can find the resolvent. A resolvent is $\{a_1, a_2, \neg a_2, a_4\}$.
- ▶ Resolvent **not** unique : $\{a_1, a_3, \neg a_3, a_4\}$ is also a resolvent.

Resolution

- ▶ Let F be a formula in CNF, and let C be a clause in F . Then $F \vdash C$ (Prove!)

Resolution

- ▶ Let F be a formula in CNF, and let C be a clause in F . Then $F \vdash C$ (Prove!)
- ▶ Let F be a formula in CNF. Let R be a resolvent of two clauses of F . Then $F \vdash R$ (Prove!)

Completeness of Resolution

Show that resolution can be used to determine whether any given formula is satisfiable.

- ▶ Given F in CNF, let $\text{Res}^0(F) = \{C \mid C \text{ is a clause in } F\}$.

Completeness of Resolution

Show that resolution can be used to determine whether any given formula is satisfiable.

- ▶ Given F in CNF, let $Res^0(F) = \{C \mid C \text{ is a clause in } F\}$.
- ▶ $Res(F) = Res^0(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^0(F)\}$

Completeness of Resolution

Show that resolution can be used to determine whether any given formula is satisfiable.

- ▶ Given F in CNF, let $Res^0(F) = \{C \mid C \text{ is a clause in } F\}$.
- ▶ $Res(F) = Res^0(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^0(F)\}$
- ▶ $Res^n(F) = Res^{n-1}(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^{n-1}(F)\}$

Completeness of Resolution

Show that resolution can be used to determine whether any given formula is satisfiable.

- ▶ Given F in CNF, let $Res^0(F) = \{C \mid C \text{ is a clause in } F\}$.
- ▶ $Res(F) = Res^0(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^0(F)\}$
- ▶ $Res^n(F) = Res^{n-1}(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^{n-1}(F)\}$
- ▶ $Res^0(F)$ is finite : there are finitely many clauses that can be derived from F .

Completeness of Resolution

Show that resolution can be used to determine whether any given formula is satisfiable.

- ▶ Given F in CNF, let $Res^0(F) = \{C \mid C \text{ is a clause in } F\}$.
- ▶ $Res(F) = Res^0(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^0(F)\}$
- ▶ $Res^n(F) = Res^{n-1}(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^{n-1}(F)\}$
- ▶ $Res^0(F)$ is finite : there are finitely many clauses that can be derived from F .
- ▶ $Res^1(F)$ is finite : finitely many resolvents can be obtained from clauses of F

Completeness of Resolution

Show that resolution can be used to determine whether any given formula is satisfiable.

- ▶ Given F in CNF, let $Res^0(F) = \{C \mid C \text{ is a clause in } F\}$.
- ▶ $Res(F) = Res^0(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^0(F)\}$
- ▶ $Res^n(F) = Res^{n-1}(F) \cup \{R \mid R \text{ is a resolvent of two clauses in } Res^{n-1}(F)\}$
- ▶ $Res^0(F)$ is finite : there are finitely many clauses that can be derived from F .
- ▶ $Res^1(F)$ is finite : finitely many resolvents can be obtained from clauses of F
- ▶ There is some m such that $Res^m(F) = Res^{m+1}(F)$. Denote it by $Res^*(F)$.

Example

Let $F = \{\{a_1, a_2, \neg a_3\}, \{\neg a_2, a_3\}\}$.

► $Res^0(F) = F$

Example

Let $F = \{\{a_1, a_2, \neg a_3\}, \{\neg a_2, a_3\}\}$.

- ▶ $Res^0(F) = F$
- ▶ $Res^1(F) = F \cup \{a_1, a_2, \neg a_2\} \cup \{a_1, \neg a_3, a_3\}$.

Example

Let $F = \{\{a_1, a_2, \neg a_3\}, \{\neg a_2, a_3\}\}$.

- ▶ $Res^0(F) = F$
- ▶ $Res^1(F) = F \cup \{a_1, a_2, \neg a_2\} \cup \{a_1, \neg a_3, a_3\}$.
- ▶ $Res^2(F) = Res^1(F) \cup \{a_1, a_2, \neg a_3\} \cup \{a_1, a_3, \neg a_2\}$