# User Datagram Protocol (UDP)

#### Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include: <a href="http://commons.wikimedia.org">http://commons.wikimedia.org</a> (Wikipedia, Wikimedia and workbooks); <a href="http://www.sxc.hu">http://www.sxc.hu</a> and <a href="http://www.pixabay.com">http://www.pixabay.com</a>

#### Recap

- Transport layer provides logical communication between processes
- Internet supports a few transport layer protocols
  - UDP, TCP, RPC, RTP
- UDP: 'bare bones' transport protocol

## **User Datagram Protocol**

- Provides Mux/Demux capability over besteffort network layer service
- UDP segments can be lost, duplicated, delivered out of order to applications
- Connectionless: no handshaking between UDP sender, receiver
- Each UDP segment handled independently of others

#### Why used?



- No connection establishment (which can add delay)
  - DNS uses UDP
- Simple: no connection state at sender, receiver
  - A server can support more clients
- Small segment header: Less overhead per packet



## Why used?

- No congestion control: UDP can blast away as fast as desired
- No retransmission delays: Useful for real-time applications like VoIP, online games
- Want additional features? Applications have to implement them themselves

#### **Example Protocols**

- DHCP ~
- RIP 🗸
- . DNS
- SNMP (Simple Network Management Protocol)
  - Used for managing nodes (switches, routers, printers, servers etc) on IP networks


## **UDP Segment Format**

- Source/Destination Port: Identifies sending/receiving process
  - Client: Ephemeral port; Server: Well-known port

weder	Source Port	<b>Destination Port</b>
	Length	Checksum
y wad ->	<b>Application Data</b>	

# **UDP Segment Format**

• Length: Specifies the total length of the segment in bytes



#### **Checksum**

- Optional in IPv4, Compulsory in IPv6
- Ensures correctness of message
- Uses same algorithm as IP checksum

<b>Source Port</b>	<b>Destination Port</b>
Length	Checksum
Applic	ation Data

#### **Checksum**

- Calculated over UDP header, body and pseudoheader
  - Pseudoheader: three fields from IP (protocol number, source IP, destination IP) and UDP length field
  - Pseudoheader included to help verify if packet is indeed delivered to the right host

## Summary

- UDP is a simple transport protocol
- Provides multiplexing/demultiplexing and simple error detection capability
- Finds good use in many protocols in spite of its simplicity