

# CS310 Automata Theory – 2016-2017

Nutan Limaye

Indian Institute of Technology, Bombay  
[nutan@cse.iitb.ac.in](mailto:nutan@cse.iitb.ac.in)

Lecture 27: Turing machines, computability  
March 27, 2017

# At the end of last class

## Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

# At the end of last class

## Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

# At the end of last class

## Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

# At the end of last class

## Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

$$EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}.$$

# At the end of last class

## Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

$$EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}.$$

Started with trying to prove  $REG_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$ .

# Undecidability of Halt

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable.

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ .

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ . If it rejects then reject,

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ . If it rejects then reject, else do as per  $M$  on  $w$ .

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ . If it rejects then reject, else do as per  $M$  on  $w$ .

$\mathcal{A}$  accepts  $(M, w)$  if  $M$  accepts  $w$

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ . If it rejects then reject, else do as per  $M$  on  $w$ .

$\mathcal{A}$  accepts  $(M, w)$  if  $M$  accepts  $w$  and rejects it if either  $M$  rejects  $w$

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ . If it rejects then reject, else do as per  $M$  on  $w$ .

$\mathcal{A}$  accepts  $(M, w)$  if  $M$  accepts  $w$  and rejects it if either  $M$  rejects  $w$  or  $M$  loops forever on  $w$ .

# Undecidability of Halt

Reducing  $A_{TM}$  to another problem to prove undecidability.

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}$$

We would like to show that Halt is undecidable.

Assume that Halt is decidable. Let  $\mathcal{H}$  be the TM deciding Halt.

$\mathcal{A}$ : Run  $\mathcal{H}$  on  $(M, w)$ . If it rejects then reject, else do as per  $M$  on  $w$ .

$\mathcal{A}$  accepts  $(M, w)$  if  $M$  accepts  $w$  and rejects it if either  $M$  rejects  $w$  or  $M$  loops forever on  $w$ .

$\mathcal{H}$  decides Halt if and only if  $\mathcal{A}$  decides  $A_{TM}$ .

# The halting problem

## Lemma

*The halting problem,  $Halt = \{(M, w) \mid M \text{ halts on } w\}$ , is undecidable.*

# The halting problem

## Lemma

*The halting problem,  $Halt = \{(M, w) \mid M \text{ halts on } w\}$ , is undecidable.*


Another way to describe the same proof.

# The halting problem

## Lemma

*The halting problem,  $Halt = \{(M, w) \mid M \text{ halts on } w\}$ , is undecidable.*

Another way to describe the same proof.




# The halting problem

## Lemma

*The halting problem,  $Halt = \{(M, w) \mid M \text{ halts on } w\}$ , is undecidable.*

Another way to describe the same proof.




# The halting problem

## Lemma

The halting problem,  $Halt = \{(M, w) \mid M \text{ halts on } w\}$ , is undecidable.

Another way to describe the same proof.




If  $Halt$  is decidable then  $\mathcal{A}$  decides  $A_{TM}$

# The halting problem

## Lemma

The halting problem,  $Halt = \{(M, w) \mid M \text{ halts on } w\}$ , is undecidable.

Another way to describe the same proof.



If  $Halt$  is decidable then  $\mathcal{A}$  decides  $A_{TM}$ , which is a contradiction.

# Emptiness problem for TM

## Lemma

*The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.*

Assume for the sake of contradiction that it is decidable.

# Emptiness problem for TM

## Lemma

*The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.*

Assume for the sake of contradiction that it is decidable. Let  $T$  be a machine that decides  $E_{TM}$ .

# Emptiness problem for TM

## Lemma

*The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.*

Assume for the sake of contradiction that it is decidable. Let  $T$  be a machine that decides  $E_{TM}$ .

Let  $T'_{M,w}$  be as follows:

# Emptiness problem for TM

## Lemma

*The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.*

Assume for the sake of contradiction that it is decidable. Let  $T$  be a machine that decides  $E_{TM}$ .

Let  $T'_{M,w}$  be as follows:

On input  $x$

{

if  $w \neq x$  then reject

else do as per  $M$

}

# Emptiness problem for TM

## Lemma

The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.

Assume for the sake of contradiction that it is decidable. Let  $T$  be a machine that decides  $E_{TM}$ .

Let  $T'_{M,w}$  be as follows:

On input  $x$

{

if  $w \neq x$  then reject

else do as per  $M$

}

$$L(T'_{M,w}) = \begin{cases} \{w\} & \text{if } M \text{ acc } w \\ \emptyset & \text{otherwise} \end{cases}$$

# Emptiness problem for TM

## Lemma

The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.

Assume for the sake of contradiction that it is decidable. Let  $T$  be a machine that decides  $E_{TM}$ .

Let  $T'_{M,w}$  be as follows:

On input  $x$

{

if  $w \neq x$  then reject

else do as per  $M$

}

Let  $A$  be as follows:

$$L(T'_{M,w}) = \begin{cases} \{w\} & \text{if } M \text{ acc } w \\ \emptyset & \text{otherwise} \end{cases}$$

# Emptiness problem for TM

## Lemma

The emptiness problem for TMs,  $E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}$ , is undecidable.

Assume for the sake of contradiction that it is decidable. Let  $T$  be a machine that decides  $E_{TM}$ .

Let  $T'_{M,w}$  be as follows:

On input  $x$

{

if  $w \neq x$  then reject

else do as per  $M$

}

$$L(T'_{M,w}) = \begin{cases} \{w\} & \text{if } M \text{ acc } w \\ \emptyset & \text{otherwise} \end{cases}$$

Let  $A$  be as follows:

On input  $M, w$

{

Create machine  $T'_{M,w}$ .

If  $T$  on  $\langle T'_{M,w} \rangle$  rejects  
then accept

else reject

}

# Equality for TM

## Lemma

*The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.*

# Equality for TM

## Lemma

*The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.*

Assume for the sake of contradiction that  $EQ_{TM}$  is decidable. Let  $M$  be the TM for it.

# Equality for TM

## Lemma

*The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.*

Assume for the sake of contradiction that  $EQ_{TM}$  is decidable. Let  $M$  be the TM for it.

Let  $M_1$  be a machine that rejects all strings. That is,  $L(M_1) = \emptyset$ .

# Equality for TM

## Lemma

*The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.*

Assume for the sake of contradiction that  $EQ_{TM}$  is decidable. Let  $M$  be the TM for it.

Let  $M_1$  be a machine that rejects all strings. That is,  $L(M_1) = \emptyset$ .

Given a machine  $M_2$  as an input, use  $M$  to check whether  $L(M_2) = L(M_1)$

# Equality for TM

## Lemma

The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.

Assume for the sake of contradiction that  $EQ_{TM}$  is decidable. Let  $M$  be the TM for it.

Let  $M_1$  be a machine that rejects all strings. That is,  $L(M_1) = \emptyset$ .

Given a machine  $M_2$  as an input, use  $M$  to check whether  $L(M_2) = L(M_1)$ , i.e. to check whether  $L(M_2) = \emptyset$  or not.

# Equality for TM

## Lemma

The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.

Assume for the sake of contradiction that  $EQ_{TM}$  is decidable. Let  $M$  be the TM for it.

Let  $M_1$  be a machine that rejects all strings. That is,  $L(M_1) = \emptyset$ .

Given a machine  $M_2$  as an input, use  $M$  to check whether  $L(M_2) = L(M_1)$ , i.e. to check whether  $L(M_2) = \emptyset$  or not.

This implies that if  $EQ_{TM}$  is decidable then  $E_{TM}$  is decidable.

# Equality for TM

## Lemma

The equality problem for TMs,  $EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}$ , is undecidable.

Assume for the sake of contradiction that  $EQ_{TM}$  is decidable. Let  $M$  be the TM for it.

Let  $M_1$  be a machine that rejects all strings. That is,  $L(M_1) = \emptyset$ .

Given a machine  $M_2$  as an input, use  $M$  to check whether  $L(M_2) = L(M_1)$ , i.e. to check whether  $L(M_2) = \emptyset$  or not.

This implies that if  $EQ_{TM}$  is decidable then  $E_{TM}$  is decidable.

But from the previous result we know that  $E_{TM}$  is undecidable.

# Regularity checking

## Lemma

$REG_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

# Regularity checking

## Lemma

$\text{REG}_{\text{TM}} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  is a TM that decides  $\text{REG}_{\text{TM}}$ .

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  is a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be s.t.

$$L(R'_{M,w}) = \begin{cases} \{0^n 1^n \mid n \geq 0\} & \text{if } M \text{ rej } w \\ \Sigma^* & \text{if } M \text{ acc } w \end{cases}$$

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  is a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be s.t.

$$L(R'_{M,w}) = \begin{cases} \{0^n 1^n \mid n \geq 0\} & \text{if } M \text{ rej } w \\ \Sigma^* & \text{if } M \text{ acc } w \end{cases}$$

If we get such an  $R'_{M,w}$  we can design  $A$  as follows.

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  is a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be s.t.

$$L(R'_{M,w}) = \begin{cases} \{0^n 1^n \mid n \geq 0\} & \text{if } M \text{ rej } w \\ \Sigma^* & \text{if } M \text{ acc } w \end{cases}$$

If we get such an  $R'_{M,w}$  we can design  $A$  as follows.

# Regularity checking

## Lemma

$\text{REG}_{\text{TM}} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  is a TM that decides  $\text{REG}_{\text{TM}}$ .

Let  $R'_{M,w}$  be s.t.

Let  $A$  be as follows:

$$L(R'_{M,w}) = \begin{cases} \{0^n 1^n \mid n \geq 0\} & \text{if } M \text{ rej } w \\ \Sigma^* & \text{if } M \text{ acc } w \end{cases}$$

If we get such an  $R'_{M,w}$  we can design  $A$  as follows.

# Regularity checking

## Lemma

$\text{REG}_{\text{TM}} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  is a TM that decides  $\text{REG}_{\text{TM}}$ .

Let  $R'_{M,w}$  be s.t.

$$L(R'_{M,w}) = \begin{cases} \{0^n 1^n \mid n \geq 0\} & \text{if } M \text{ rej } w \\ \Sigma^* & \text{if } M \text{ acc } w \end{cases}$$

If we get such an  $R'_{M,w}$  we can design  $A$  as follows.

Let  $A$  be as follows:

On input  $M, w$

{

Create machine  $R'_{M,w}$ .

If  $R$  on  $\langle R'_{M,w} \rangle$  accepts  
then accept

else reject

}

# Regularity checking

## Lemma

$REG_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  be a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be as follows:

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  be a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be as follows:

On input  $x$

{

if  $x = 0^n 1^n$

then accept

else run  $M$  on  $w$  and

    if  $M$  acc  $w$  then acc

    else rej

}

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  be a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be as follows:

Let  $A$  be as follows:

On input  $x$

{

if  $x = 0^n 1^n$

then accept

else run  $M$  on  $w$  and

    if  $M$  acc  $w$  then acc

    else rej

}

# Regularity checking

## Lemma

$\text{REG}_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}$  is undecidable.

Assume for the sake of contradiction that a TM  $R$  be a TM that decides  $\text{REG}_{TM}$ .

Let  $R'_{M,w}$  be as follows:

On input  $x$

{

if  $x = 0^n 1^n$

then accept

else run  $M$  on  $w$  and

    if  $M$  acc  $w$  then acc  
    else rej

}

Let  $A$  be as follows:

On input  $M, w$

{

Create machine  $R'_{M,w}$ .

If  $R$  on  $\langle R'_{M,w} \rangle$  accepts  
then accept

else reject

}

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

Input  $(M, w) \longrightarrow N$

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

Input  $(M, w) \longrightarrow N$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N)$

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

Input  $(M, w) \longrightarrow N$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N)$

if  $w \notin L(M) \longrightarrow L(N) = \Sigma^*$

# Universality of CFLs

## Lemma

$\text{ALL}_{\text{CFL}} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

Input  $(M, w) \longrightarrow N$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N)$

if  $w \notin L(M) \longrightarrow L(N) = \Sigma^*$

We will do the proof on Thursday (after the Tutorial 10 is solved).

## Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

## Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

## Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

## Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

## Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

$$\{M \mid M \text{ never moves left on any input}\}.$$

## Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

$$\{M \mid M \text{ never moves left on any input}\}.$$

Rice's theorem: A systematic way of proving undecidability of languages.



# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages.

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages.

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages. ✓

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages. ✓

Set of context-free languages.

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages. ✓

Set of context-free languages. ✓

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$ .

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$ . ✓

# Property $P$

## Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$ . ✓