

# CS310 Automata Theory – 2016-2017

Nutan Limaye

Indian Institute of Technology, Bombay

[nutan@cse.iitb.ac.in](mailto:nutan@cse.iitb.ac.in)

Lecture 30: Turing machines, computability

March 30, 2017

# At the end of last class

## Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ hants on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

$$EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}.$$

$$REG_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}.$$

Note that undecidability of  $REG_{TM}$  and  $E_{TM}$  can be proved using Rice's theorem.

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages.

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

For any property  $P$ , let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

For any property  $P$ , let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ , i.e. the set of all Turing machine such that  $L(M) \in P$ .

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

For any property  $P$ , let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ , i.e. the set of all Turing machine such that  $L(M) \in P$ .

We say that a property  $P$  is trivial if either  $\mathcal{L}_P = \emptyset$  or  $\mathcal{L}_P$  is the set of all the Turing recognizable languages.



## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

For any property  $P$ , let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ , i.e. the set of all Turing machine such that  $L(M) \in P$ .

We say that a property  $P$  is trivial if either  $\mathcal{L}_P = \emptyset$  or  $\mathcal{L}_P$  is the set of all the Turing recognizable languages.

### Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ .*

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

For any property  $P$ , let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ , i.e. the set of all Turing machine such that  $L(M) \in P$ .

We say that a property  $P$  is trivial if either  $\mathcal{L}_P = \emptyset$  or  $\mathcal{L}_P$  is the set of all the Turing recognizable languages.

### Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

## Property $P$ and $\mathcal{L}_P$

Rice's theorem: A systematic way of proving undecidability of languages.

### Definition

A property  $P$  is simply a subset of Turing recognizable languages. We say that a language  $L$  satisfies a property  $P$ , if  $L \in P$ .

For any property  $P$ , let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ , i.e. the set of all Turing machine such that  $L(M) \in P$ .

We say that a property  $P$  is trivial if either  $\mathcal{L}_P = \emptyset$  or  $\mathcal{L}_P$  is the set of all the Turing recognizable languages.

### Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that*  
 $\mathcal{L}_P = \{M \mid L(M) \in P\}.$

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

When is the theorem NOT applicable?

Rice's theorem cannot be used to prove undecidability of languages which deal with machine behaviour.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$ .

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

When is the theorem NOT applicable?

Rice's theorem cannot be used to prove undecidability of languages which deal with machine behaviour.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$ .

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$ .

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

When is the theorem NOT applicable?

Rice's theorem cannot be used to prove undecidability of languages which deal with machine behaviour.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$ .

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$ .

$\{\langle M \rangle \mid M \text{ has no useless state}\}$ .



# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

When is the theorem NOT applicable?

Rice's theorem cannot be used to prove undecidability of languages which deal with machine behaviour.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$ .

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$ .

$\{\langle M \rangle \mid M \text{ has no useless state}\}$ .

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

When is the theorem NOT applicable?

Rice's theorem cannot be used to prove undecidability of languages which deal with machine behaviour.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$ .

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$ .

$\{\langle M \rangle \mid M \text{ has no useless state}\}$ .

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

It is only used to prove undecidability.

# Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

When is the theorem NOT applicable?

Rice's theorem cannot be used to prove undecidability of languages which deal with machine behaviour.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$ .

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$ .

$\{\langle M \rangle \mid M \text{ has no useless state}\}$ .

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

It is only used to prove undecidability.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$ .

Not applicable, but language decidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$ .

Not applicable, but language decidable.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at least 10 states}\}$ .

Applicable, but property is trivial.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$ .

Not applicable, but language decidable.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at least 10 states}\}$ .

Applicable, but property is trivial.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at most 10 states}\}$ .

Applicable and property is not trivial, therefore undecidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$ .

Not applicable, but language decidable.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at least 10 states}\}$ .

Applicable, but property is trivial.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at most 10 states}\}$ .

Applicable and property is not trivial, therefore undecidable.

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}$ .

Not applicable, but the language is decidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$ .

Not applicable, but language decidable.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at least 10 states}\}$ .

Applicable, but property is trivial.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at most 10 states}\}$ .

Applicable and property is not trivial, therefore undecidable.

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}$ .

Not applicable, but the language is decidable.

$\{M \mid L(M) \text{ contains } \langle M \rangle\}$ .

Applicable, the property is not trivial, therefore undecidable.

$\{M \mid L(M) \text{ is finite } \}$ .

Applicable, the property is not trivial, therefore undecidable.



# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$ .

Not applicable, but language decidable.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at least 10 states}\}$ .

Applicable, but property is trivial.

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with at most 10 states}\}$ .

Applicable and property is not trivial, therefore undecidable.

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}$ .

Not applicable, but the language is decidable.

$\{M \mid L(M) \text{ contains } \langle M \rangle\}$ .

Applicable, the property is not trivial, therefore undecidable.

$\{M \mid L(M) \text{ is finite } \}$ .

Applicable, the property is not trivial, therefore undecidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid M \text{ has a useless state}\}$ .

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid M \text{ has a useless state}\}$ .

Not applicable, but the language is in fact undecidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid M \text{ has a useless state}\}$ .

Not applicable, but the language is in fact undecidable.

Rice's theorem cannot be used to prove the undecidability of this language!

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{(M, w) \mid M \text{ writes a symbol } a \text{ on the tape on input } w\}$ .

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{(M, w) \mid M \text{ writes a symbol } a \text{ on the tape on input } w\}$ .

Not applicable, but the language is in fact undecidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{(M, w) \mid M \text{ writes a symbol } a \text{ on the tape on input } w\}$ .

Not applicable, but the language is in fact undecidable.

Rice's theorem cannot be used to prove the undecidability of this language!

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\left\{ \begin{array}{l} M \\ \hline \end{array} \mid \begin{array}{l} M \text{ tries to write on the left of the cell when it} \\ \text{is at the leftmost bit of the input} \end{array} \right\}.$$



# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\left\{ M \mid \begin{array}{l} M \text{ tries to write on the left of the cell when it} \\ \text{is at the leftmost bit of the input} \end{array} \right\}.$$

Not applicable, but the language is in fact undecidable.

# Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\left\{ M \mid \begin{array}{l} M \text{ tries to write on the left of the cell when it} \\ \text{is at the leftmost bit of the input} \end{array} \right\}.$$

Not applicable, but the language is in fact undecidable.

Rice's theorem cannot be used to prove the undecidability of this language!

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ .*

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

Proof Idea:

Let  $P$  be a non-trivial property.

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

Proof Idea:

Let  $P$  be a non-trivial property.

Assume that  $\mathcal{L}_P$  is decidable.

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

Proof Idea:

Let  $P$  be a non-trivial property.

Assume that  $\mathcal{L}_P$  is decidable.

Using this assumption prove that  $A_{TM}$  is decidable.

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

Proof Idea:

Let  $P$  be a non-trivial property.

Assume that  $\mathcal{L}_P$  is decidable.

Using this assumption prove that  $A_{TM}$  is decidable.

More specifically:

$$(M, w) \longrightarrow N$$



# Proof of Rice's theorem

## Theorem

Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

Proof Idea:

Let  $P$  be a non-trivial property.

Assume that  $\mathcal{L}_P$  is decidable.

Using this assumption prove that  $A_{TM}$  is decidable.

More specifically:

$$(M, w) \longrightarrow N$$

$$\text{if } w \in L(M) \longrightarrow \langle N \rangle \in \mathcal{L}_P$$

# Proof of Rice's theorem

## Theorem

Let  $P$  be a property such that it is not trivial. Recall that  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

Proof Idea:

Let  $P$  be a non-trivial property.

Assume that  $\mathcal{L}_P$  is decidable.

Using this assumption prove that  $A_{TM}$  is decidable.

More specifically:

$$(M, w) \longrightarrow N$$

$$\text{if } w \in L(M) \longrightarrow \langle N \rangle \in \mathcal{L}_P$$

$$\text{if } w \notin L(M) \longrightarrow \langle N \rangle \notin \mathcal{L}_P$$

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ .*

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

Design of  $N$

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$



# Proof of Rice's theorem

## Theorem

*Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.*

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$ <sup>1</sup>

---

<sup>1</sup>We will remove this assumption later.

# Proof of Rice's theorem

## Theorem

Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$

on input  $x$

```
{  
    if  $M$  accepts  $w$   
    then if  $M_1$  accepts  $x$   
        then accept  
}
```

# Proof of Rice's theorem

## Theorem

Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$

on input  $x$

{  
    if  $M$  accepts  $w$   
    then if  $M_1$  accepts  $x$   
        then accept  
}

Claim:  $w \in L(M)$  if and only if  $\langle N \rangle \in \mathcal{L}_P$

# Proof of Rice's theorem

## Theorem

Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$

on input  $x$

{  
    if  $M$  accepts  $w$   
    then if  $M_1$  accepts  $x$   
        then accept  
}

Claim:  $w \in L(M)$  if and only if  $\langle N \rangle \in \mathcal{L}_P$   
if  $w \in L(M)$  then  $L(N) = L(M_1)$ .

# Proof of Rice's theorem

## Theorem

Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$

on input  $x$

{  
    if  $M$  accepts  $w$   
    then if  $M_1$  accepts  $x$   
        then accept  
}

Claim:  $w \in L(M)$  if and only if  $\langle N \rangle \in \mathcal{L}_P$

if  $w \in L(M)$  then  $L(N) = L(M_1)$ .

if  $w \notin L(M)$  then  $L(N) = \emptyset$ .

# Proof of Rice's theorem

## Theorem

Let  $P$  be a non-trivial property of Turing recognizable languages. Let  $\mathcal{L}_P = \{M \mid L(M) \in P\}$ . Then  $\mathcal{L}_P$  is undecidable.

## Design of $N$

Let  $M_1$  be the TM s.t.  $L(M_1)$  has Property  $P$ .

Let  $L(M_2)$  be the TM s.t.  $L(M_2) = \emptyset$ .

we assume that  $\emptyset$  does not have property  $P$

on input  $x$

{  
if  $M$  accepts  $w$   
then if  $M_1$  accepts  $x$   
then accept  
}

Claim:  $w \in L(M)$  if and only if  $\langle N \rangle \in \mathcal{L}_P$

if  $w \in L(M)$  then  $L(N) = L(M_1)$ .

if  $w \notin L(M)$  then  $L(N) = \emptyset$ .

## Getting rid of the assumption on $P$

We now show how to get around the assumption.

Suppose  $\emptyset$  has property  $P$ .

## Getting rid of the assumption on $P$

We now show how to get around the assumption.

Suppose  $\emptyset$  has property  $P$ .

Consider  $\overline{P}$ .



# Getting rid of the assumption on $P$

We now show how to get around the assumption.

Suppose  $\emptyset$  has property  $P$ .

Consider  $\overline{P}$ .

Now  $\emptyset$  does not have property  $\overline{P}$ .

# Getting rid of the assumption on $P$

We now show how to get around the assumption.

Suppose  $\emptyset$  has property  $P$ .

Consider  $\overline{P}$ .

Now  $\emptyset$  does not have property  $\overline{P}$ .

Use Rice's theorem on  $\mathcal{L}_{\overline{P}}$  to prove undecidability.

# Getting rid of the assumption on $P$

We now show how to get around the assumption.

Suppose  $\emptyset$  has property  $P$ .

Consider  $\overline{P}$ .

Now  $\emptyset$  does not have property  $\overline{P}$ .

Use Rice's theorem on  $\mathcal{L}_{\overline{P}}$  to prove undecidability.

Conclude undecidability of  $\mathcal{L}_P$ .

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ )



# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

# Universality of CFLs

## Lemma

$ALL_{CFL} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all string (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

## Filling in the details

The following two details need to be addressed.

$Q_1$  How should we design  $N_{M,w}$ ?



## Filling in the details

The following two details need to be addressed.

$Q_1$  How should we design  $N_{M,w}$ ?

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that  $ALL_{CFL}$  is decidable.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.



## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

If  $C$  accepts then  
reject;

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

If  $C$  accepts then  
reject;

else accept.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

If  $C$  accepts then  
reject;

else accept.

## Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

## Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

## Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:  
 $C_1, C_2, \dots, C_\ell$  such that

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is an accepting configuration.



# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is an accepting configuration.

for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

## Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is an accepting configuration.

for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is an accepting configuration.

for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

- $C_1$  is a start configuration.

- $C_\ell$  is an accepting configuration.

- for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

- $C_1$  is a start configuration.

- $C_\ell$  is a rejecting configuration.

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

- $C_1$  is a start configuration.

- $C_\ell$  is an accepting configuration.

- for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

- $C_1$  is a start configuration.

- $C_\ell$  is a rejecting configuration.

- for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

- $C_1$  is a start configuration.

- $C_\ell$  is an accepting configuration.

- for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:

$C_1, C_2, \dots, C_\ell$  such that

- $C_1$  is a start configuration.

- $C_\ell$  is a rejecting configuration.

- for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

## Details for $Q_1$ : reduction via computation history

Interprete input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:



## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

- $x$  does not have the pattern of a computational history of  $x$

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration OR

$x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration OR

$x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR

$x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration OR

$x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR

$x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .

If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .  
 $N_{M,w}$  will reject  $\tilde{x}$

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration OR

$x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR

$x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .

If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .  
 $N_{M,w}$  will reject  $\tilde{x}$ , i.e.  $\tilde{x} \notin L(N_{M,w})$ .

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration OR

$x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR

$x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .

If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .

$N_{M,w}$  will reject  $\tilde{x}$ , i.e.  $\tilde{x} \notin L(N_{M,w})$ .

If  $M$  does not accept  $w$ , then

no matter what  $x$  is,  $N_{M,w}$  will accept  $x$

## Details for $Q_1$ : reduction via computation history

Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:

$x$  does not have the pattern of a computational history of  $x$  OR

$x$  is a computational history, but  $C_1$  is not a start configuration OR

$x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR

$x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .

If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .

$N_{M,w}$  will reject  $\tilde{x}$ , i.e.  $\tilde{x} \notin L(N_{M,w})$ .

If  $M$  does not accept  $w$ , then

no matter what  $x$  is,  $N_{M,w}$  will accept  $x$ , i.e.  $L(N_{M,w}) = \Sigma^*$ .