

CS310 Automata Theory – 2016-2017

Nutan Limaye

Indian Institute of Technology, Bombay
nutan@cse.iitb.ac.in

Lecture 28: Turing machines, computability
March 27, 2017

At the end of last class

Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

At the end of last class

Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

At the end of last class

Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

At the end of last class

Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

$$EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}.$$

At the end of last class

Introduction to Turing machines

Undecidability of the following languages:

$$A_{TM} = \{(M, w) \mid M \text{ accepts } w\}.$$

$$\text{Halt} = \{(M, w) \mid M \text{ halts on } w\}.$$

$$E_{TM} = \{\langle M \rangle \mid L(M) = \emptyset\}.$$

$$EQ_{TM} = \{(M_1, M_2) \mid L(M_1) = L(M_2)\}.$$

$$REG_{TM} = \{\langle M \rangle \mid L(M) \text{ is regular}\}.$$

Universality of CFLs

Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Universality of CFLs

Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

Universality of CFLs

Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

Input $(M, w) \longrightarrow N$

Universality of CFLs

Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

Input $(M, w) \longrightarrow N$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N)$

Universality of CFLs

Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

Input $(M, w) \longrightarrow N$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N)$

if $w \notin L(M) \longrightarrow L(N) = \Sigma^*$

Universality of CFLs

Lemma

$ALL_{CFL} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$ is undecidable.

Proof Strategy

Input $(M, w) \longrightarrow N$

if $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N)$

if $w \notin L(M) \longrightarrow L(N) = \Sigma^*$

We will do the proof on Thursday (after the Tutorial 10 is solved).

Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

Rice's theorem

The following languages are undecidable.

$\{M \mid L(M) \text{ is regular}\}$.

$\{M \mid L(M) \text{ is context-free}\}$.

Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

$$\{M \mid M \text{ never moves left on any input}\}.$$

Rice's theorem

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

$$\{M \mid M \text{ never moves left on any input}\}.$$

Rice's theorem: A systematic way of proving undecidability of languages.



Property P

Definition

A property P is simply a subset of Turing recognizable languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$. ✓

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$. ✓

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

For any property P , let $\mathcal{L}_P = \{M \mid L(M) \in P\}$

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

For any property P , let $\mathcal{L}_P = \{M \mid L(M) \in P\}$, i.e. the set of all Turing machine such that $L(M) \in P$.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

For any property P , let $\mathcal{L}_P = \{M \mid L(M) \in P\}$, i.e. the set of all Turing machine such that $L(M) \in P$.

We say that a property P is trivial if either $\mathcal{L}_P = \emptyset$ or \mathcal{L}_P is the set of all the Turing recognizable languages.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$?

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting $a^* b^*$ is in \mathcal{L}_P .

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting $a^* b^*$ is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$?

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting $a^* b^*$ is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$? No.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting $a^* b^*$ is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$? No. For example, a TM accepting $\{a^n b^n \mid n \geq 0\}$ is not in \mathcal{L}_P .

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting $a^* b^*$ is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$? No. For example, a TM accepting $\{a^n b^n \mid n \geq 0\}$ is not in \mathcal{L}_P .

Therefore, P is not trivial.

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$?

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No.

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$?

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$? No.

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$? No. For example, a TM M that accepts a single string $\{a\}$ is not in \mathcal{L}_P .

Examples of properties

Examples

2 $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}$.

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \Sigma^*$? No. For example, a TM M that accepts a single string $\{a\}$ is not in \mathcal{L}_P .

Example of a trivial property

Examples

$$3. \quad \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

But any TM can be converted into another one that has even number of states.

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

But any TM can be converted into another one that has even number of states.

Therefore, any Turing recognizable language has property P .

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

But any TM can be converted into another one that has even number of states.

Therefore, any Turing recognizable language has property P .

Therefore, P is in fact all Turing recognizable languages.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

It is only used to prove undecidability.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

It is only used to prove undecidability.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid M \text{ runs for atmost 10 steps on } aab\}.$$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid M \text{ runs for atmost 10 steps on } aab\}.$$

Not applicable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid M \text{ runs for atmost 10 steps on } aab\}.$$

Not applicable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at least 10 states}\}$.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at least 10 states}\}$.

Applicable, but property is trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at least 10 states}\}$.

Applicable, but property is trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid M \text{ has at most 10 states}\}.$$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}.$

Not applicable, but the language is decidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}.$

Not applicable, but the language is decidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{M \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial, therefore undecidable.