Lecture 4

Air Quality:

Measurement Methods, Effect of Meteorology on Pollutants Dispersion

Harish C. Phuleria
CESE, IIT Bombay

Email: phuleria@iitb.ac.in







Recap 1

$PM_{2.5}$ / PM_{10} : Mass concentration of all particles having **aerodynamic diameter** $\leq$ 2.5 / 10μm





$$V_s = \frac{D_p^2 \rho_p C_c g}{18\eta}$$





Recap 2

















Complex Mixture

- **Bulk composition:** EC, OC, Nitrate, Sulfate, Ammonium, dust
- **Trace constituents:** Heavy metals, PAHs, …

Today's Learning Objectives !

- To learn about monitoring methods and thus able to quantify pollutants' concentrations

- To explain effects of meteorology and the physics of dispersion of pollutants in the atmosphere

Quantifying pollutants: Particle mass concentration (PM$_{10}$/PM$_{2.5}$)

- How do you measure the mass concentration of PM ?

$$C = \Delta m/Q.t$$



Quantifying pollutants: Particle mass concentration

- Measure mass of clean filter
- Measure mass of filter after exposure
- Measure flow rate and exposure time
- Calculate concentration

- Corrections for blank filter
- Corrections for temperature/ humidity

$C = \Delta m/Q.t$



Particle mass measurements



Inertial Collection. (a) Impactor, (b) Cyclone.



- Filter substrates are collected using impactors/cyclones (for desired size) and designed flow rate (with a suction pump)
- Collected filters are conditioned in laboratory & weighed with precision microbalance

Sizing of Particles

- Inertial Impactors
  - Mass based (> 56 nm)
- Optical Particle Counters
  - Number based (> 400 nm)
- Electrical Mobility
  - Sizing (> 6 nm)
  - Counting (Condensation Particle Counters or Electron microscopy)



Particle sizing: MOUDI
(Micro-Orifice Uniform Deposit Impactor)





Successively nozzle diameter and stopping distance are decreasing to collect smaller particle size ranges !!!

Particle (biological) sizing:
Anderson impactor

Anderson six-stage viable impactor



www.thermoscientific.com

OPC (Optical Particle counters)



- Light Scattering
- Light Extinction

  $0.4 > l_{opt} > 0.7\ \mu m$
- Linear dependence of light scattering on particle mass concentration
- Extinction also depends on light absorbing nature of aerosols
- Single Particle /Cloud of Particles

Ultrafine/Nanoparticle Particle Counting:
CPC (Condensation particle counter)



Willeke and Baron, 1999;
www.tsi.com

Ultrafine/Nanoparticle Particle sizing:
SMPS (Scanning mobility particle sizer)





Willeke & Baron, 1999;
www.tsi.com

Ultrafine/Nanoparticle Particle sizing:
Electron microscopy

TEM images are formed using transmitted electrons (instead of the visible light) which can produce magnification details up to 1,000,000x with resolution better than 10 A_o





Willeke & Baron, 1999;
http://www.rsic.iitb.ac.in/tem.html

Other PM (& gas) Instruments

- High Volume (Hi-Vol) Samplers (1.2 Lakhs)
  - Gravimetric (Q =1 m^3/min; weight =60 kg)
  - Regulatory (PM_{10} or $PM_{2.5}$, SO_2, NO_2)

Cyclone inlet (PM_{10})



Impinger (NO_2, SO_2)



CPCB, 2011

Other PM Instruments

www.airmetrics.com

- Mini Volume (Mini-Vol) Samplers (2 Lakhs)
  - Gravimetric (Q=5 L/min)
  - Regulatory (PM_{10}, $PM_{2.5}$)

- DustTrak (4 Lakhs)
  - Real time (1 minute resolution; Q=3 L/min)
  - PM_x (x = 1, 2.5, 4, 10)

www.tsi.com

Choice of instruments is a function of its cost, intended analysis, time resolution, portability, ease of use

Time-integrated (passive) methods - Gases



- Gases are collected in tubes/badges by diffusion
- Absorption substrate inside are coated with chemicals (e.g triethanolamine for NO_2)
- Post-collection analysed in wet-labs using colorometry

Ogawa NO_x

Passam NO_2/O_3

Ogawa deployed in field

Measurement methods - Gases

Passive samplers with electrochemical sensors; usually CO, CO_2,NO_x, O_3, HCHO, NH_3 etc. can be measured



Stacked reference gas monitors at AQM station; all gases are actively sampled and anlysed in real-time

Personal/Indoor Monitoring Methods

For personal and/or indoor monitoring, important criteria are:

- portability (instrument size),
- battery run-time, and
- noise it makes while running

Learning Objective 2 !

- To learn about monitoring methods and thus able to quantify pollutants’ concentrations

- To explain effects of meteorology and the physics of dispersion of pollutants in the atmosphere

Mixing/Dispersion

Meteorology

- Vertical
  - Temperature
    - Lapse Rate
- Horizontal
  - Wind
    - Speed
    - Direction

Other met. parameters

- Sunlight
- Precipitation
- Humidity

A number of following slides have been taken/adapted from Prof. Sethi's ES200 lectures from last years !

Types of Sources

- Point
- Line
- Area

Please note !

25 min. duration

?

Quiz on :

Mon, 6.Nov

Syllabus:

All what is covered so far!