Deeper examination of some functions of the `datana` package

Examples

April 8, 2026

xxx This document expands on examples of different functions from the datana package (Salas-Eljatib and Campos 2025), implemented in R (R Core Team 2025). The main idea of such a report is to provide most of the utilities and versatility of the aforementioned package's functions.

Contents

1 `interp` **2**
1.1 About this function 2
1.2 Example 2

2 `plotrend` **4**
2.1 About this function 4
2.2 Datos para el ejemplo 4

3 `descstat` **5**
3.1 about this function 5
3.2 Datos para el ejemplo 5

1 interp

1.1 About this function

The `interp` function was created for the analysis process of taper data. The idea is that with this function missing data is generated (*i.e.* commercial heights and diameters) which allow to obtain commercial volumes, in addition to be a requirement in order to the data to complain to the following assumptions:

1. Decreasing diameter in height.
2. To always exists a section at stump height (generally at 0.3 m), dbh height, and between the mentioned values (generally 0.8m).
3. That the diameter outside bark is always larger than the diameter inside bark for the same height.
4. That the last section (the tip of the tree) has diameter equals 0 (zero) and $hl = h$.

1.2 Example

Loading taper data of a tree:

```
df <- read.csv((./resources/ahusa.csv"))
head(df[, c("dl.cc", "hl")])
```

```
dl.cc   hl
1 11.02 0.05
2  8.46 1.30
3  8.10 1.58
4  7.86 2.37
5  6.90 3.16
6  6.70 3.95
```

This tree doesn't have a section at height 0.8 m, so this is interpolated.

```
library(datana)
## the height will be 0.8 m
new.section <- 0.8
interpolated <- interp(x = df$dl.cc, y = df$hl, ylu = new.section)
interpolated$datares
```

```
x    y interpolated
1  11.020000 0.05        FALSE
2   9.378939 0.80         TRUE
3   8.460000 1.30        FALSE
4   8.100000 1.58        FALSE
5   7.860000 2.37        FALSE
6   6.900000 3.16        FALSE
7   6.700000 3.95        FALSE
8   6.000000 4.74        FALSE
9   5.500000 5.53        FALSE
```

```
10  4.400000 5.60        FALSE
11  3.500000 6.32        FALSE
12  2.820000 7.11        FALSE
13  0.000000 9.00        FALSE
```

2 plotrend

2.1 About this function

2.2 Datos para el ejemplo

Se cargan los datos de ahusamiento de un árbol

```
df <- datana::maple
head(df)
```

```
tree  dbh leaf branch   bole  bark  total
1    1  9.1 0.67  21.30   9.94  1.51  33.42
2    2  9.1 0.54  20.30   6.21  0.63  27.68
3    3  9.9 0.72  19.26  13.93  1.69  35.60
4    4 10.2 0.60  21.77  17.68  1.60  41.65
5    5 16.7 2.90  28.47 101.94 11.37 144.68
6    6 17.2 2.39  26.94  90.26 12.35 131.94
```

Se ajusta un modelo lineal

```
m1 <- lm(leaf ~ dbh, data = df)
m1
```

```
Call:
lm(formula = leaf ~ dbh, data = df)

Coefficients:
(Intercept)          dbh
    -6.1498       0.5375
```

Usando la función

```
datana::plotrend(x = df$dbh, y = residuals(m1), xlab = "DBH (cm)")
abline(h = 0)
```



Figure 1: Example plot generated with the `plotrend` function.

3 descstat

3.1 about this function

3.2 Datos para el ejemplo

Se cargan los datos de ahusamiento de un árbol

```
library(datana)
df <- datana::maple
head(df)
descstat(df)
```

```
tree  dbh leaf branch   bole  bark  total
1    1  9.1 0.67  21.30   9.94  1.51  33.42
2    2  9.1 0.54  20.30   6.21  0.63  27.68
3    3  9.9 0.72  19.26  13.93  1.69  35.60
4    4 10.2 0.60  21.77  17.68  1.60  41.65
5    5 16.7 2.90  28.47 101.94 11.37 144.68
6    6 17.2 2.39  26.94  90.26 12.35 131.94

            tree    dbh   leaf  branch     bole    bark    total
n         29.000 29.000 29.000  29.000   29.000  29.000   29.000
Minimum    1.000  9.100  0.540  19.260    6.210   0.630   27.680
Maximum   29.000 43.900 25.790 482.820 1154.170 118.690 1781.140
Mean      15.000 29.948  9.946 139.828  508.944  52.972  712.001
Median    15.000 32.500  8.550 121.290  588.350  57.220  759.600
Std. Dev.  8.515 11.456  7.600 113.904  336.156  35.199  479.196
CV(%)     56.765 38.252 76.409  81.460   66.050  66.449   67.303
```

Se ajusta un modelo lineal

```
m1 <- lm(leaf ~ dbh, data = df)
m1
```

```
Call:
lm(formula = leaf ~ dbh, data = df)

Coefficients:
(Intercept)          dbh
    -6.1498       0.5375
```

Usando la función

```
datana::plotrend(x = df$dbh, y = residuals(m1), xlab = "DBH (cm)")
abline(h = 0)
```

References

R Core Team (2025). *R: A language and environment for statistical computing*. `http://www.R-project.org`. R Foundation for Statistical Computing. Vienna, Austria.

Salas-Eljatib, C. and N. Campos (2025). `datana`*: Data and functions to accompany Análisis de datos con R*. R package version 1.1.4. DOI: `10.32614/CRAN.package.datana`. URL: `https://cran.r-project.org/package=datana`.