

**\*\* AD HOC & NORMAL THINGS**

```

#include<bits/stdc++.h>
using namespace std;
typedef long long ll;
// policy Based ds
#include<ext/pb_ds/assoc_contain
er.hpp>
// #include<ext/pb_ds/tree_policy
.hpp>
using namespace __gnu_pbds;
typedef tree<long long ,
null_type, greater_equal<long
long>,
rb_tree_tag, tree_order_statistic
s_node_update> ordered_set;
//
cout<<os.find_by_order(val)<<en
dl; // k-th element it
// less_equal = multiset, less =
set, greater_equal = multiset
decreasing, greater = set
decreasing
//
cout<<os.order_of_key(val)<<endl
; // strictly smaller or
greater
#define order(s, x)
s.order_of_key(x)
#define elemat(s, x)
s.find_by_order(x)
#define
boost ios_base::sync_with_std
io(0); cin.tie(0); cout.tie(0);
#define endl "\n"
#define all(x) x.begin(),
x.end()
#define
read freopen("input.txt", "r",
stdin)
#define
write freopen("output.txt", "w",
stdout)
#define pb push_back
#define ff first
#define ss second
#define GCD(a, b) __gcd(a, b)
#define PI 2.0124 * acos(0.0)125
#define LCM(a, b) (a * b) /
GCD(a, b)126

```

```

#define mem(a, b) memset(a, b,
sizeof(a))
#define popcountL
__builtin_popcountll
#define popcount
__builtin_popcount
inline bool checkBit(int N, int
pos){return (bool)(N & (1 <<
pos));}
inline int setBit(int N, int
pos) { return N = N | (1 <<
pos); }
inline int unsetBit(int N, int
pos) {return N = (N & ~(1 <<
pos));}
inline int toggleBit(int N, int
pos) {return N = (N ^ (1 <<
pos));}
const ll sz=2e7+123;
#define INF 1000000000000000000
const ll MOD=1000000007;
const ll base = 31;
#define stringLen
18446744073709551620
inline void normal(ll &a) { a %=
MOD; (a < 0) && (a += MOD); }
inline ll modMul(ll a, ll b) { a
%= MOD, b %= MOD; normal(a),
normal(b); return (a*b)%MOD; }
inline ll modAdd(ll a, ll b) { a
%= MOD, b %= MOD; normal(a),
normal(b); return (a+b)%MOD; }
inline ll modSub(ll a, ll b) { a
%= MOD, b %= MOD; normal(a),
normal(b); a -= b; normal(a);
return a; }
inline ll modPow(ll b, ll p) {
ll r = 1; while(p) { if(p&1) r =
modMul(r, b); b = modMul(b, b);
p >>= 1; } return r; }
inline ll modInverse(ll a) {
return modPow(a, MOD-2); }
inline ll modDiv(ll a, ll b) {
return modMul(a, modInverse(b));
}
//Graph direction array[8]
//dx[]={0,0,1,-1,-1,1,1,-1};
//dy[]={1,-1,0,0,-1,-1,1,1};
//Bishop direction array[8]
//dx[]={0,0,1,-1,-1,1,1,-1};

```

```

//dy[]={1,-1,0,0,-1,-1,1,1};
//Knight Direction array[8]
//dx[]={1,1,2,2,-1,-1,-2,-2};
//dy[]={2,-2,1,-1,2,-2,1,-1};

```

**\*\* NUMBER THEORY****FAISAL AMIN ABIR****PRIME GENERATION**

```

bitset<sz>is_prime;
vi prime;
void primeGen(int n){
for(int i=3; i<=n;
i+=2)is_prime[i]=1;
int nn = sqrt(n)+1;
for(ll i=3; i<nn; i+=2){
if(is_prime[i]==0)continue;
for(int j=i*i; j<=n; j+=(i+i)){
is_prime[j]=0;}}
is_prime[2]=1;
prime.pb(2);
for(int i=3; i<=n; i+=2){
if(is_prime[i])prime.pb(i);}}

```

**PRIME FACTORIZATION**

```

vector<long
long>factorization(long long
n){//O(sqrt(n)/ln(sqrt(n)) +
log2 n)
vector<long long>factors;
for(auto u:prime){
if(1LL*u*u > n) break;
if(n%u==0){// factors.push_back
(u);//for generating unique
factors keep this line here
while(n%(u)==0){
factors.push_back(u);//for
generating all factors keep this
line here
n/=u;}}}
if(n>1)factors.push_back(n);
return factors;}
SEGMENTED SIEVE
vector<char> segmentedSieve(long
long L, long long R){
// generate all primes up to
sqrt(R)
long long lim = sqrt(R);
vector<char> mark(lim + 1,
false);

```

```

vector<long long> primes;
for (long long i = 2; i <= lim;
++i) {
if (!mark[i]) {
primes.emplace_back(i);
for (long long
j=i*i; j<=lim; j+=i)
mark[j]=true;}}
vector<char> isPrime(R - L + 1,
true);
for (long long i:primes)
for (long long j=max(i*i, (L+i-
1)/i*i); j<=R; j+=i)
isPrime[j-L]=false;
if (L==1) isPrime[0] = false;
return isPrime;}
SUM OF DIVS
long long SOD(long long n){
long long res=1;
for(auto u:prime){
if(1LL*u*u > n)break;
if(n%u==0){
long long sum=1;
long long power = 1;
while(n%u==0){
n/=u;
power *= u;
sum += power;}}
res *= sum;}}
if(n>1)res*=(1+n);
return res;}
SUM OF NUMBER OF DIVS
int SNOD(int n){
int sq = sqrt(n), res=0;
for(int i=1; i<=sq; i++){
res += (n/i) - i;}
res += 2;
res += sq;
return res;}
NUMBER OF DIVS
ll NOD(ll n){
ll ans=1;
if(n>1000000000000000000){
for(ll i=0; ++i){
if(prime[i]*prime[i]*prime[i]>n)
{
break;
}
if(n%prime[i]==0){
ll cnt = 0;

```

```

while (n%prime[i]== 0){
n /= prime[i];
cnt++;}
ans*=(cnt+1);}
if(isprime(n)){ans*=2;}
else
if(issquareprime(n)){ans*=3;}
else if(n!=1){ans*=4;}
else{
ll limit=sqrt(n);
for (ll
i=0;prime[i]<=limit;++i){
if(n%prime[i]== 0){
ll cnt = 0;
while (n% prime[i]== 0){
n /= prime[i];
cnt++;
}
ans*=(cnt+1);
limit=sqrt(n);
}
}
if(n!=1)ans*=2;}
return ans;
}
//for NOD count each prime
factors+1 and multiply all of
them 2,2,3,3,3 (3)*(4)

```

### GEOEMTRIC SUM

```

//**Give a,n will give
a^1+a^2+a^3+...+a^n**
const ll MOD=1e9+7;
ll GeoSum(ll a, ll n){
ll sz = 0;ll ret = 0;ll mul = 1;
int MSB = 63 -
__builtin_clzll(n);
while(MSB >= 0){
ret = ret * (1 + mul); mul =
(mul *mul) % MOD; sz <= 1;
if( (n >> MSB) & 1) {
mul = (mul *a) % MOD; ret +=
mul; sz++;}
ret %= MOD; MSB--;}
return ret;}

```

### NCR USING RECURRENCE

```

**ncr using recurrence{nCr = (n-
1)Cr + (n-1)C(r-1)}**
void fncr(){
for(int i = 0; i < N; ++i) {

```

```

for(int j = 0; j < N; ++j) {
if (j == 0 || j == i) ncr[i][j]
= 1;
else ncr[i][j] = ncr[i-1][j-1]
+ncr[i-1][j];
}}
NCR%M USING MODULAR
MULTIPLICATIVEINVERSE
void precal(){
fact[0]=invFact[0]=1;
for(int i=1; i<=N; i++){
fact[i]=((fact[i-
1]%MOD)*(i%MOD))%MOD;}
invFact[N]=bigmod(fact[N],MOD-
2);
for(int i=N-1; i>=1; i--){
invFact[i]=((invFact[i+1]%MOD)*
(i+1)%MOD)%MOD;}
cout<<((fact[n]*invFact[r])%MOD*
invFact[n-r])%MOD<<endl;
/**ncr if it stays in long
long**
ll n,r,ans=1;
cin>>n>>r;
for(int i=1; i<=r; i++){
ans=ans*(n-i+1);
ans/=i;}
LUCAS THEOREM(N AND R IS VERY
BIG BUT MOD IS SMALL)
precal(){factorial and inverse
factorialmod}
ll Lucas(ll n,ll r){
if(r<0||r>n){
return 0;}
if(r==0||r==n){
return 1;}
if(n>=MOD){
return(Lucas(n/MOD,r/MOD)%MOD*Lu
cas(n%MOD,r%MOD)%MOD)%MOD;}
return(((fact[n]*invFact[r])%MOD
)*invFact[n-r])%MOD;}
EXTENDED GCD AND LINEAR
DIOPHANTINE EQUATION
int gcd(int a, int b, int& x,
int& y) {
if (b == 0) {
x = 1; y = 0;
return a;}
int x1, y1;
int d = gcd(b, a % b, x1, y1);

```

```

x = y1;
y = x1 - y1 * (a / b);
return d;}
LINEAR DIOPHANTINE
bool find_any_solution(int a,
int b, int c, int &x0, int &y0,
int &g) {
g = gcd(abs(a), abs(b), x0, y0);
if (c % g) {
return false;}
x0 *= c / g;
y0 *= c / g;
if (a < 0) x0 = -x0;
if (b < 0) y0 = -y0;
return true;}
void shift_solution(int &x, int
&y, int a, int b, int cnt) {
x += cnt * b;
y -= cnt * a;}
int find_all_solutions(int a,
int b, int c, int minx, int
maxx, int miny, int maxy) {
int x, y, g;
if (!find_any_solution(a, b, c,
x, y, g))
return 0;
a /= g;
b /= g;
int sign_a = a > 0 ? +1 : -1;
int sign_b = b > 0 ? +1 : -1;
shift_solution(x, y, a, b, (minx
- x) / b);
if (x < minx)
shift_solution(x, y, a, b,
sign_b);
if (x > maxx)
return 0;
int lx1 = x;
shift_solution(x, y, a, b, (maxx
- x) / b);
if (x > maxx)
shift_solution(x, y, a, b, -
sign_b);
int rx1 = x;
shift_solution(x, y, a, b, -
(miny - y) / a);
if (y < miny)
shift_solution(x, y, a, b, -
sign_a);
if (y > maxy)

```

```

return 0;
int lx2 = x;
shift_solution(x, y, a, b, -
(maxy - y) / a);
if (y > maxy)
shift_solution(x, y, a, b,
sign_a);
int rx2 = x;
if (lx2 > rx2)
swap(lx2, rx2);
int lx = max(lx1, lx2);
int rx = min(rx1, rx2);
if (lx > rx)
return 0;
return (rx - lx) / abs(b) + 1;}

```

### FAYSAL AHAMMED CHOWDHURY

LINEAR SIEVE in  $O(n)$  upto  $10^7$  but memory takes 32 times more:

```

const int N = 10000000;
vector<int> spf(N + 1);
vector<int> primes;
void linear_sieve(){ // O(n)
for (int i = 2; i <= N; ++i){
if (spf[i] == 0){
spf[i] = i;
primes.push_back(i);}
for (int j = 0; i * primes[j] <=
N; ++j){
spf[i * primes[j]] = primes[j];
if (primes[j] == spf[i])
{break;}}}}
SPF SIEVE
const int N = 1e6 + 9;
int spf[N];
void spf_sieve() {
for (int i = 2; i < N; i++) {
spf[i] = i;}
for (int i = 2; i < N; i++) {
if (spf[i] == i) {
for (int j = i; j < N; j += i) {
spf[j] = min(spf[j], i);}}}}
SOD:  $((p_1^{e_1+1}-1)/p_1-1) * ((p_2^{e_2+1}-1)/p_2-1) * \dots$ 
DIVISIBILITY BY 11:

```

$$10! = 3628800$$

$$4! = 24$$

$$10! / 2^4 = 10 \times 9 \times 8 \times 7 \times 6 \times 5 \times 4 \times 3 \times 2 \times 1 / 2^4 = 10 \times 9 \times 3 \times 7 \times 3 \times 5 \times 1 = 2700$$

**Legendre's Formula:**

( $N! / p^x$ ) max value of  $x$  ( $p$  must be prime)

```
int legendre(int n, int p){
    int ex = 0;
    while(n) {
        ex += (n / p);
        n /= p;
    }
    return ex;
}
```

**Digit Count of a number:**

$\log_{10}(n) + 1$  ( $\log_{10}$  for 10 base number)

**How many Trailing zeros of  $n$ ? -**  
Max power of base which divides  $n$ .

**Phi function:**

$$\phi(n) = \phi(p_1^{e_1} \times p_2^{e_2} \times \dots \times p_k^{e_k})$$

$$= \phi(p_1^{e_1}) \times \phi(p_2^{e_2}) \times \dots \times \phi(p_k^{e_k})$$

$$= p_1^{e_1} \times \left(\frac{p_1-1}{p_1}\right) \times p_2^{e_2} \times \left(\frac{p_2-1}{p_2}\right) \times \dots \times p_k^{e_k} \times \left(\frac{p_k-1}{p_k}\right)$$

$$= n \times \left(\frac{p_1-1}{p_1}\right) \times \left(\frac{p_2-1}{p_2}\right) \times \dots \times \left(\frac{p_k-1}{p_k}\right)$$

\* for  $n > 2$ ,  $\phi(n)$  is always even

\* sum of all  $\phi(d)$  - divisors of  $n$ , is  $n$ .

**Euler Totient Function:**

```
// if we need phi(x) multiple
times, then memoize it
map<int, int> dp;
int phi(int n) {
    if (dp.count(n)) return dp[n];
    int ans = n, m = n;
    for (int i = 2; i * i <= m; i++) {
        if (m % i == 0) {
            while (m % i == 0) m /= i;
            ans = ans * (i - 1) / i;
        }
    }
    return ans;
}
```

```
ans = ans / i * (i - 1);}}
if (m > 1) ans = ans / m * (m - 1);
return dp[n] = ans;
Phi from 1 to n in  $O(n \log \log n)$ :
void phi_1_to_n(int n) {
    vector<int> phi(n + 1);
    for (int i = 0; i <= n; i++)
        phi[i] = i;
    for (int i = 2; i <= n; i++) {
        if (phi[i] == i) {
            for (int j = i; j <= n; j += i)
                phi[j] -= phi[j] / i;
        }
    }
}
```

**Logarithm:**

$\log(ab) = \log(a) + \log(b)$   
 $\log(a^x) = x \log(a)$

**First K digit of  $n^k$ :**

```
int firstk(int n, int k) {
    double a = k * log10(n);
    double b = a - floor(a);
    double c = pow(10, b);
    return floor(c * 100);
}
```

**Series:**

Arithmetic progression:

$S(n) = (n/2) * (a + p)$   $p$  is last element

Or,  $S(n) = (n/2) * (2a + (n-1)d)$

$d$  is common difference

Geometric Progression:

$S(n) = (a * (1 - r^n)) / (1 - r)$   $r < 1$

$S(n) = (a * (r^n - 1)) / (r - 1)$   $r > 1$

\*  $1^2 + 2^2 + \dots + n^2 = (n * (n+1) * (2n+1)) / 6$

\*  $1^3 + 2^3 + \dots + n^3 = (n^2 * (n+1)^2) / 4$

**Problems:**

\* Minimal natural number  $N$ , so that  $N!$  contains exactly  $Q$  zeroes on the trail.

- Binary search over  $N$  and find how many trailing zeros  $N$  has by Legendre's formula.

\* Given a number  $N^M$ , find out the number of integer bases in which it has exactly  $T$  trailing zeroes:

```
int
solve_greater_or_equal(vector<int> e, int t) {
    int ans = 1;
    for(auto i: e) {
        ans = 1LL * ans * (i / t + 1) % mod;
    }
    return ans;
}

int solve_equal(vector<int> e, int t) {
    return (solve_greater_or_equal(e, t) - solve_greater_or_equal(e, t + 1) + mod) % mod;
}
```

```
int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
}
```

```
int n, m, t, cs = 0;
while(cin >> n >> m >> t and n != 0) {
    vector<int> e;
    for(int i = 2; i * i <= n; i++) {
        if(n % i == 0) {
            int ex = 0;
            while(n % i == 0) {
                ex++;
                n /= i;
            }
            e.push_back(ex * m);
        }
    }
    if(n > 1) e.push_back(m);
    cout << "Case " << ++cs << ": " << solve_equal(e, t) << '\n';
}
```

```
return 0;
}

*  $n!$  (factorial  $n$ ) has at least  $t$  trailing zeroes in  $b$  based number system. Given the value of  $n$  and  $t$ , what is the maximum possible value of  $b$ ?
```

```
const int N = 1e5 + 9, mod = 10000019;
vector<bool> is_prime(N, true);
vector<int> primes;
```

```
int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    sieve();
}
```

```
int t, cs = 0; cin >> t;
while(t--) {
    int n, zeroes; cin >> n >> zeroes;
    vector<pair<int, int>> ans;
    for(auto p: primes) {
        if(p > n) break;
        int pw = legendre(n, p);
        if(pw / zeroes != 0) {
            ans.push_back({p, pw / zeroes});
        }
    }
    int max_base = 1;
    for(auto i: ans) {
        max_base = 1LL * max_base * power(i.first, i.second) % mod;
    }
    cout << "Case " << ++cs << ": ";
    cout << (ans.size() == 0 ? -1 : max_base) << '\n';
}

return 0;
}
```

**Combinatorics:**

\*  $nCr$ ,  $nPr$  using recurrence -  
const int N = 2005, mod = 1e9 + 7;  
int C[N][N], fact[N];

```
void prec() { //  $O(n^2)$ 
    //  $nCr = (n-1)C(r-1) + (n-1)Cr$ 
    for (int i = 0; i < N; i++) {
        C[i][0] = C[i][i] = 1;
        for (int j = 1; j < i; j++) {
            C[i][j] = (C[i-1][j-1] + C[i-1][j]) % mod;
        }
    }
}
```

```
fact[0] = 1;
for (int i = 1; i < N; i++) {
    fact[i] = 1ll * fact[i - 1] * i
    % mod;
}

int nCr(int n, int r) {
    if (n < r) return 0;
    return C[n][r];
}
```

```
int nPr(int n, int r) {
    if (n < r) return 0;
    return 1ll * C[n][r] * fact[r] %
    mod;
}
```

**Combinations (nCr, nPr):**

```
const int N = 1e6 + 1, mod =
10000003;
int fact[N], ifact[N];
```

```
int inverse(int x) {
    return power(x, mod - 2, mod);
}
```


```
void prec() {
    fact[0] = 1;
    for (int i = 1; i < N; i++) {
        fact[i] = 1ll * fact[i - 1] * i
        % mod;
    }
    ifact[N - 1] = inverse(fact[N -
    1]);
    for (int i = N - 2; i >= 0; i--) {
        ifact[i] = 1ll * ifact[i + 1] *
        (i + 1) % mod;
    }
}
```

```
int nCr(int n, int r) {
    return 1ll * fact[n] * ifact[r]
    % mod * ifact[n - r] % mod;
}
```

```
int nPr(int n, int r) {
    return 1ll * fact[n] * ifact[n -
    r] % mod;
}
```

```
}
Stars and Bars:
* Find the number of k-tuples
of non-negative integers whose
sum is n.
- (n + k - 1)! / (n! * (k-1)!)
or C(n+k-1, n)
* Find the number of k-tuples
of non-negative integers whose
sum is <= n.
- (n + k)! / (n! * k!) or
C(n+k, n)
* Combinations with repetitions
- C(n+k-1, k)
* How many ways to go from (0,0)
to (n,m)
- C(n+m, n)
```

**Pascals Triangle is equivalent to nCr**



**Multinomial Coefficient**  
(a<sub>1</sub>+a<sub>2</sub>+...+a<sub>k</sub>)<sup>n</sup>

Powers are given of k numbers.  
coefficient?

```
int n, k; cin >> n >> k;
int ans = fact[n];
for (int i = 1; i <= k; i++) {
    int x; cin >> x;
    ans = 1ll * ans * ifact[x] %
    mod;
}
```

**Binomial Theorem:**

$$(a + b)^n = \sum_{k=0}^n \binom{n}{k} a^{n-k} b^k$$

**Properties of Pascal's Triangle:**

```
i = 0 to n ΣC(n,i) = 2^n
i = 0 to n where i is even
ΣC(n,i) = 2^(n-1)
```

```
i = 0 to n where i is odd
ΣC(n,i) = 2^(n-1)
```

**Built-in Functions:**

```
set(), reset(), flip(), count(),
test(), any(), none(), all(),
to_ulong()
__builtin_popcount(x),
__builtin_clz(x),
__builtin_ctz(x)
* Power Tower:
```

$$n^x \bmod m = n^{\varphi(m)+x \bmod \varphi(m)} \bmod m$$

```
const int N = 1e5 + 9;
using ll = long long;
```

```
map<ll, ll> mp;
ll phi(ll n) {
    if (mp.count(n)) return mp[n];
    ll ans = n, m = n;
    for (ll i = 2; i * i <= m; i++) {
        if (m % i == 0) {
            while (m % i == 0) m /= i;
            ans = ans / i * (i - 1);
        }
    }
}
```

```
if (m > 1) ans = ans / m * (m -
1);
return mp[n] = ans;
}
```

```
inline ll MOD(ll x, ll m) {
    if (x < m) return x;
    return x % m + m;
}
ll power(ll n, ll k, ll mod) {
    ll ans = MOD(1, mod);
    while (k) {
        if (k & 1) ans = MOD(ans * n,
        mod);
        n = MOD(n * n, mod);
        k >>= 1;
    }
    return ans;
}
```

```
int a[N];
// if x >= log2(m), then a^x =
a^(MOD(x, phi(m))) % m
ll yo(ll l, ll r, ll m) {
    if (l == r) return MOD(a[l], m);
```

```
if (m == 1) return 1;
return power(a[l], yo(l + 1, r,
phi(m)), m);
}
int32_t main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    int n, m; cin >> n >> m;
    for (int i = 1; i <= n; i++) {
        cin >> a[i];
    }
    int q; cin >> q;
```

```
while (q--) {
    int l, r; cin >> l >> r;
    cout << yo(l, r, m) % m << '\n';
}
return 0;
}
```

**Expected value:**

আমরা আরো জেনারেলাইজেশন করতে পারি, আমরা এক্ষেত্রে ধরেছি  $n$  টা পাশে 1 থেকে  $n$  পর্যন্ত প্রতিটা সংখ্যা একবার করে আছে। এখন আমরা ধরে ডাইসের  $i$  তম সাইটে যে সংখ্যা লেখা আছে সেটা হলো  $x(i)$  এবং ডাইস ছুড়ে মারলে  $i$  তম সাইডটা পাবার প্রোবাবিলিটি আগের মতোই  $p(i)$ । এখন ফর্মুলাটা হবে

$$E = p(1) * x(1) + p(2) * x(2) + \dots + p(n) * x(n) = \sum_{i=1}^n p(i) \cdot x(i)$$

সরজভাবে বলতে গেলে প্রতিটা  $i$  এর জন্য আমরা  $i$  তম সাইটে যে সংখ্যাটা লেখা আছে সেটাকে  $i$  তম সাইড পাবার প্রোবাবিলিটি দিয়ে গুণ করছি এবং সবগুলো গুণফল যোগ করে দিচ্ছি।

**\*\* DATA STRUCTURES**

**Faysal Ahammed**

**Segment Tree:**

```
const int N = 1e5 + 9;
int a[N];
```

```
struct ST {
    int tree[4 * N];
    void build(int n, int b, int e)
    {
        if(b == e) {
            tree[n] = a[b]; // change here
            return;
        }
        int mid = (b + e) >> 1, l = n <<
        1, r = l + 1;
        build(l, b, mid);
        build(r, mid + 1, e);
    }
}
```



```

tree[n] = tree[l] + tree[r]; //
change here
}
void upd(int n, int b, int e,
int i, int x) {
if(b > i || e < i) return;
if(b == e && b == i) {
tree[n] = x; // change here
return;
}
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
upd(l, b, mid, i, x);
upd(r, mid + 1, e, i, x);
tree[n] = tree[l] + tree[r]; //
change here
}
int query(int n, int b, int e,
int i, int j) {
if(b > j || e < i) return 0; //
return appropriate value
if(b >= i && e <= j) return
tree[n];
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
int L = query(l, b, mid, i, j);
int R = query(r, mid + 1, e, i,
j);
return (L + R); // change this
} st;
Segment Tree Lazy:
const int N = 1e5 + 9;
int a[N];

struct ST {
int tree[4 * N], lazy[4 * N];
ST() {
memset(tree, 0, sizeof(tree));
memset(lazy, 0, sizeof(lazy));
}
void push(int n, int b, int e) {
if(lazy[n] == 0) return;
tree[n] += lazy[n] * (e - b +
1); // change here
if(b != e) {
int l = n << 1, r = l + 1;
lazy[l] += lazy[n]; // change
here

```

```

lazy[r] += lazy[n]; // change
here
}
lazy[n] = 0;
}
void build(int n, int b, int e)
{
lazy[n] = 0;
if(b == e) {
tree[n] = a[b]; // change here
return;
}
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
build(l, b, mid);
build(r, mid + 1, e);
tree[n] = tree[l] + tree[r]; //
change here
}
void upd(int n, int b, int e,
int i, int j, int x) {
push(n, b, e);
if(b > j || e < i) return;
if(b >= i && e <= j) {
lazy[n] += x; // change here
push(n, b, e);
return;
}
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
upd(l, b, mid, i, j, x);
upd(r, mid + 1, e, i, j, x);
tree[n] = tree[l] + tree[r]; //
change here
}
int query(int n, int b, int e,
int i, int j) {
push(n, b, e);
if(b > j || e < i) return 0; //
return appropriate value
if(b >= i && e <= j) return
tree[n];
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
int L = query(l, b, mid, i, j);
int R = query(r, mid + 1, e, i,
j);
return L + R; // change here
}
} st;

```

### Strongest Community:

```

const int N = 1e5 + 9;
int a[N];

```

```

struct node {
int first_element,
first_element_cnt;
int last_element,
last_element_cnt;
int max_cnt;
};

```

```

node merge(node l, node r) {
if(l.first_element == -1) return
r;
if(r.first_element == -1) return
l;
node ans;
ans.max_cnt = max(l.max_cnt,
r.max_cnt);
if(l.last_element ==
r.first_element) {
ans.max_cnt = max(ans.max_cnt,
l.last_element_cnt +
r.first_element_cnt);
}
ans.first_element =
l.first_element;
ans.first_element_cnt =
l.first_element_cnt;
if(l.first_element ==
r.first_element) {
ans.first_element_cnt +=
r.first_element_cnt;
}
ans.last_element =
r.last_element;
ans.last_element_cnt =
r.last_element_cnt;
if(r.last_element ==
l.last_element) {
ans.last_element_cnt +=
l.last_element_cnt;
}
return ans;
}

```

```

struct ST {
node tree[4 * N];

```

```

void build(int n, int b, int e)
{
if(b == e) {
tree[n].first_element = a[b];
tree[n].first_element_cnt = 1;
tree[n].last_element = a[b];
tree[n].last_element_cnt = 1;
tree[n].max_cnt = 1;
return;
}
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
build(l, b, mid);
build(r, mid + 1, e);
tree[n] = merge(tree[l],
tree[r]); // change here
}
node query(int n, int b, int e,
int i, int j) {
if(b > j || e < i) return {-1, -
1, -1, -1};
if(b >= i && e <= j) return
tree[n];
int mid = (b + e) >> 1, l = n <<
1, r = l + 1;
return merge(query(l, b, mid, i,
j), query(r, mid + 1, e, i, j));
// change this
} st;
Segment tree with arithmetic
progression [update the range l
to r with the arithmetic
progression a+b*(i-l)]:
using ll = long long;
const int N = 2e5 + 9;
const ll inf = 1e18;

pair<ll, ll> merge(pair<ll, ll>
l, pair<ll, ll> r) {
l.first = min(l.first, r.first);
l.second = max(l.second,
r.second);
return l;
}

struct ST {
pair<ll, ll> tree[4 * N];
ll lazy[4 * N];

```

```

void push(int n, int b, int e) {
    if (lazy[n] == 0) return;
    tree[n].first += lazy[n];
    tree[n].second += lazy[n];
    if (b != e) {
        int l = n << 1, r = l + 1;
        lazy[l] += lazy[n];
        lazy[r] += lazy[n];
    }
    lazy[n] = 0;
}

void build(int n, int b, int e)
{
    lazy[n] = 0;
    if (b == e) {
        tree[n] = {0, 0};
        return;
    }
    int mid = (b + e) >> 1, l = n << 1, r = l + 1;
    build(l, b, mid);
    build(r, mid + 1, e);
    tree[n] = merge(tree[l], tree[r]);
}

void upd(int n, int b, int e, int i, int j, ll x) {
    push(n, b, e);
    if (b > j || e < i) return;
    if (b >= i && e <= j) {
        lazy[n] += x;
        push(n, b, e);
        return;
    }
    int mid = (b + e) >> 1, l = n << 1, r = l + 1;
    upd(l, b, mid, i, j, x);
    upd(r, mid + 1, e, i, j, x);
    tree[n] = merge(tree[l], tree[r]);
}

pair<ll, ll> query(int n, int b, int e, int i, int j) {
    push(n, b, e);
    if (b > j || e < i) return {inf, -inf};
    if (b >= i && e <= j) return tree[n];
    int mid = (b + e) >> 1, l = n << 1, r = l + 1;

```

```

pair<ll, ll> L = query(l, b, mid, i, j);
pair<ll, ll> R = query(r, mid + 1, e, i, j);
return merge(L, R);
}
} st;

int32_t main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    int n, q; cin >> n >> q;
    st.build(1, 1, n);
    while (q--) {
        int type; cin >> type;
        if (type == 1) {
            int l, r; cin >> l >> r;
            if (l == r) {
                cout << 1 << '\n';
                continue;
            }
            pair<ll, ll> ans = st.query(1, 1, n, l + 1, r);
            if (ans.first == 0 and ans.second == 0) {
                cout << 1 << '\n';
            }
            else {
                cout << 0 << '\n';
            }
        }
        else {
            int l, r; ll a, b; cin >> l >> r >> a >> b;
            st.upd(1, 1, n, l, l, a);
            if (l != r) {
                st.upd(1, 1, n, l + 1, r, b);
            }
            ll x = 1ll * b * (r - l) + a;
            st.upd(1, 1, n, r + 1, r + 1, -x);
        }
        push(n, b, e);
    }

    return 0;
}

Searching for the first element greater than a given amount:

```

```

int get_first(int v, int tl, int tr, int l, int r, int x) {
    if (tl > r || tr < l) return -1;
    if (t[v] <= x) return -1;

    if (tl == tr) return tl;

    int tm = tl + (tr - tl) / 2;
    int left = get_first(2 * v, tl, tm, l, r, x);
    if (left != -1) return left;
    return get_first(2 * v + 1, tm + 1, tr, l, r, x);
}

Counting the number of zeros, searching for the k-th zero:
int find_kth(int v, int tl, int tr, int k) {
    if (k > t[v])
        return -1;
    if (tl == tr)
        return tl;
    int tm = (tl + tr) / 2;
    if (t[v * 2] >= k)
        return find_kth(v * 2, tl, tm, k);
    else
        return find_kth(v * 2 + 1, tm + 1, tr, k - t[v * 2]);
}

Faisal Amin Abir
Trie Prefix tree
struct trieNode {
    int cnt;
    trieNode *child[2];
    trieNode() {
        cnt = 0;
        for (int i = 0; i < 2; i++) {
            child[i] = NULL;
        }
    };
    trieNode *root;
    void insert(int num) {
        binary form
        trieNode *cur = root;
        for (int i = 20; i >= 0; i--) {
            int ind = (bool)(num & (1 << i));
            if (!cur->child[ind]) {
                cur->child[ind] = new trieNode();
            }

```

```

        }
        cur = cur->child[ind];
        cur->cnt++;
    }

    **Min XOR with value set**
    -1 X: Add x to set
    -2 x: for each element set it to element^x
    -3: print the minimum of the set
    int X = 0;
    void solve(int test) {
        int type, x;
        si(type);
        if (type == 1) {
            si(x);
            insert(x^X);
        }
        else if (type == 2) {
            si(x);
            X^=x;
        }
        else {
            int res = query(X);
            printf("%d\n", res);
        }
    }

    ** Segment Tree **
    **LAZY Propagation **
    const ll N = 2e5 + 123;
    ll arr[N], t[4*N], lazy[4*N], lazySet[4*N];
    bool isSet[4*N];
    ll n, m;
    void build(ll v, ll l, ll r) {
        if (l == r) {
            t[v] = arr[l];
            return;
        }
        ll mid = (l + r) >> 1;
        build(2*v, l, mid);
        build(2*v + 1, mid + 1, r);
        t[v] = t[2*v] + t[2*v + 1];
    }

    void checkSet(ll v, ll L, ll R) {
        if (isSet[v] == 1) {
            isSet[v] = 0;
            ll x = lazySet[v];
            lazySet[v] = 0;
            t[v] = (R - L + 1) * x;
            if (L != R) {
                isSet[2*v] = isSet[2*v + 1] = 1;
                lazy[2*v] = lazy[2*v + 1] = 0;
            }
        }
    }

```

```

lazySet[2*v] = lazySet[2*v+1] =
x;
}
}
}
void checkAdd(ll v, ll L, ll R){
if(lazy[v]!=0){
ll x = lazy[v];
lazy[v]=0;
t[v] += (R-L+1) * x;
if(L!=R){
lazy[2*v] += x;
lazy[2*v+1] += x;
}
}
}
void add(ll v, ll L, ll R, ll l,
ll r, ll value){
checkSet(v, L, R);
checkAdd(v, L, R);
if(L > r or R < l) return;
if( L >= l and R <= r){
t[v] += (R-L+1) * value;
if(L!=R){
lazy[2*v] += value;
lazy[2*v+1] += value;
}
}
return;
}
ll mid = (L+R)>>1;
add(2*v, L, mid, l, r, value);
add(2*v+1, mid+1, R, l, r,
value);
t[v] = t[2*v] + t[2*v+1];
}

void set_value(ll v, ll L, ll R,
ll l, ll r, ll value){
checkSet(v, L, R);
checkAdd(v, L, R);
if(L>r or R < l)return;
if(L>=l and R<=r){
t[v] = (R-L+1) * value;
if(L!=R){
isSet[2*v] = isSet[2*v+1] = 1;
lazy[2*v] = lazy[2*v+1] = 0;
lazySet[2*v] = lazySet[2*v+1] =
value;
}
}
return;
}

```

```

}
ll mid = (L+R)>>1;
set_value(2*v, L, mid, l, r,
value);
set_value(2*v+1, mid+1, R, l, r
, value);
t[v] = t[2*v] + t[2*v+1];
}

ll query(ll v, ll L, ll R, ll l,
ll r){
checkSet(v, L, R);
checkAdd(v, L, R);
if(L>r or R<l)return 0;
if(L>=l and R <= r) return t[v];
ll mid = (L+R)>>1;
return query(2*v, L, mid, l, r)
+ query(2*v+1, mid+1, R, l, r);
}

void solve(){
cin>>n>>m;
for(ll i=1; i<=n; i++){
cin>>arr[i];
}
build(1, 1, n);
for(ll i=0; i<m; i++){
ll c;
cin>>c;
if(c==1){
ll a, b, x;
cin>>a>>b>>x;
add(1, 1, n, a, b, x);
}
else if(c==2){
ll a, b, x;
cin>>a>>b>>x;
set_value(1, 1, n, a, b, x);
}
else{
ll a, b;
cin>>a>>b;
cout << query(1, 1, n, a, b) <<
endl;
}}

**Max subarray sum in L to R
with update**
const int mx=50005;
LL num[mx];
struct node{

```

```

LL left,right,sum,answer;
};
node tree[4*mx];
node merge(node a,node b){
node x;
x.left=max(a.left,a.sum+b.left);
x.right=max(b.right,a.right+b.su
m);
x.answer=max(max(a.answer,b.answ
er),a.right+b.left);
x.sum=a.sum+b.sum;
return x;
}
void buildSegmentTree(int at,int
L,int R){
if(L==R){
tree[at].left=num[L];
tree[at].right=num[L];
tree[at].sum=num[L];
tree[at].answer=num[L];
return;
}
int mid=(L+R)/2;
buildSegmentTree(at*2,L,mid);
buildSegmentTree(at*2+1,mid+1,R)
;
tree[at]=merge(tree[at*2],tree[a
t*2+1]);
}
void
updateSegemntTreeWithNew(int
at,int L,int R,int pos,int
value){
if(pos>R || pos<L){
return;
}
if(L>=pos && R<=pos){
tree[at].left=value;
tree[at].right=value;
tree[at].sum=value;
tree[at].answer=value;
return;
}
int mid=(L+R)/2;
updateSegemntTreeWithNew(at*2,L,
mid,pos,value);
updateSegemntTreeWithNew(at*2+1,
mid+1,R,pos,value);
tree[at]=merge(tree[at*2],tree[a
t*2+1]);
}

```

```

}
node def;
node querySegmentTree(int at,int
L,int R,int l,int r){
if(r<L || R<l)return def;
if(l<=L && R<=r) return
tree[at];
int mid=(L+R)/2;
node
x=querySegmentTree(at*2,L,mid,l,
r);
node
y=querySegmentTree(at*2+1,mid+1,
R,l,r);
return merge(x,y);
}
int main(){
def.answer=-100000000;
def.left=-100000000;
def.right=-100000000;
def.sum=-100000000;
int n;
si(n);
Rep(i,1,n){
sl(num[i]);}
buildSegmentTree(1,1,n);
int q,l,r,x;
si(q);
while(q--){
siii(x,l,r);
if(x==0){
updateSegemntTreeWithNew(1,1,n,l
,r);
}
else{
node
ans=querySegmentTree(1,1,n,l,r);
printf("%lld\n",ans.answer);
}
}
return 0;
}

**Longest increasing
subsequence**
for(int i=n; i>=1; i--){
int qr=query(1,1,m,arr[i]+1,m);
int
now=query(1,1,m,arr[i],arr[i]);
now=max(now,1+qr);
update(1,1,m,arr[i],now);
}

```

```

}
**All possible longest increasing subsequence**
for(int i=1; i<=n; i++){
    scl(arr[i].x)
    arr[i].y=i+1;
}
sort(arr+1,arr+n+1,cmp);
for(int i=1; i<=n; i++){
    ll n d=arr[i].y;
    ll n q1=query(1,1,n+1,1,d-1);
    update(1,1,n+1,d,d,q1+1);
}
ll n ans=query(1,1,n+1,1,n+1);
printf("Case %d: %lld\n",xx,ans);
** Merge sort tree without update **
vector<int>:: iterator child;
vector<int>vi2[4*maxii];
int arr3[maxii];
int n,m;
int cc=1;
void segment(int node,int b,int e){
    if(b==e){
        vi2[node].pb(arr3[b]);
        return;
    }
    int left=2*node;
    int right=left+1;
    int mid=(b+e)/2;
    segment(left,b,mid);
    segment(right,mid+1,e);
    int ff=0,hh=0;
    while(ff<vi2[left].size() && hh<vi2[right].size()){
        if(vi2[left][ff]<=vi2[right][hh]){
            vi2[node].pb(vi2[left][ff]);
            ff++;
        }
        else{
            vi2[node].pb(vi2[right][hh]);
            hh++;
        }
    }
    while(ff<vi2[left].size()){
        vi2[node].pb(vi2[left][ff]);
        ff++;
    }

```

```

}
while(hh<vi2[right].size()){
    vi2[node].pb(vi2[right][hh]);
    hh++;
}
}
int w;
int query(int node,int b,int e,int st,int en){
    if(st>e || en<b) return 0;
    if(b>=st && e<=en){
        int di=vi2[node].size();
        int p=lower_bound(vi2[node].begin(),vi2[node].end(),w)-vi2[node].begin();
        return di-p;
    }
    int mid=(b+e)/2;
    int left=2*node;
    int right=left+1;
    int q1=query(left,b,mid,st,en);
    int q2=query(right,mid+1,e,st,en);
    return q1+q2;
}
**Merge sort tree with update**
#include<bits/stdc++.h>
#include<ext/pb_ds/assoc_container.hpp>
#include<ext/pb_ds/tree_policy.hpp>
#define pii pair<int,int>
using namespace __gnu_pbds;
using namespace std;
typedef tree<pii, null_type, less<pii>, rb_tree_tag, tree_order_statistics_node_update> ordered_set;
const int maxn=3e5+5;
int arr[maxn];
ordered_set segtree[4*maxn];
void build(int at,int L,int R){
    if(L==R){
        segtree[at].insert({arr[L],L});
        return;
    }
    int mid=(L+R)>>1;
    int left=at*2;
    int right=at*2+1;

```

```

    build(left,L,mid);
    build(right,mid+1,R);
    for(pii i:segtree[left])segtree[at].insert(i);
    for(pii i:segtree[right])segtree[at].insert(i);
}
void update(int at,int L,int R,int pos,pii rp,pii pt){
    if(pos>R || pos<L){
        return;
    }
    segtree[at].erase(rp);
    segtree[at].insert(pt);
    if(L==R){
        return;
    }
    int mid=(L+R)>>1;
    if(pos<=mid)update(at*2,L,mid,pos,rp,pt);
    else update(at*2+1,mid+1,R,pos,rp,pt);
}
int query(int at,int L,int R,int l,int r,int val){
    if(r<L || R<l) return 0;
    if(l<=L && R<=r) return segtree[at].order_of_key({val,0});
    int mid=(L+R)>>1;
    return query(at*2,L,mid,l,r,val)+query(at*2+1,mid+1,R,l,r,val);
}
**Total number of subarray whose sum less than t**
void solve(int test){
    LL n,t,res=0;
    sll(n,t);
    Rep(i,1,n){
        sl(arr[i]);
        arr[i]+=arr[i-1];
    }
    build(1,1,n);
    Rep(i,1,n){
        res+=query(1,1,n,i,n,arr[i-1]+t);
    }

```

```

}
printf("%lld\n",res);
}
**Mo's Algorithm distinct element in range**
const int N = 2e5+2;
const int BLOCK = 450;
int arr[N], n, freq[N], cnt, ans[N];
struct query{
    int l, r, index;
}q[200001];
void add(int value){
    freq[value]++;
    if(freq[value]==1)cnt++;
}
void remove(int value){
    freq[value]--;
    if(freq[value]==0)cnt--;
}
bool comp(query q1, query q2){
    if((q1.l / BLOCK) == (q2.l / BLOCK)){
        return q1.r < q2.r;
    }
    return (q1.l / BLOCK) < (q2.l / BLOCK);
}
void solve(){
    cin>>n;
    int m;
    cin>>m;
    for(int i=0; i<n; i++) cin>>arr[i];
    map<int, int>maps;
    int c=0;
    for(int i=0; i<n; i++){
        if(maps[arr[i]]==0){
            c++;
            maps[arr[i]]=c;
        }
    }
    for(int i=0; i<n; i++) arr[i] = maps[arr[i]];
    for(int i=0; i<m; i++){
        int x, y;
        cin>>x>>y;
        x--, y--;
        q[i].index = i;
        q[i].l = x;
        q[i].r = y;
    }

```



```

}
sort(q, q + m, comp);
int L=0, R=-1;
for(int i=0; i<m; i++){
int currL = q[i].l;
int currR = q[i].r;
int indx = q[i].index;
while(L-1 >= currL){//adding
value
L--;
add(arr[L]);
}
while(R+1<=currR){
R++;
add(arr[R]);
}
while(L<currL){//removing value
remove(arr[L]);
L++;
}
while(R > currR){
remove(arr[R]);
R--;
}
ans[indx] = cnt;
}
for(int i=0; i<m; i++) cout <<
ans[i] << endl;
}

```

## \*\* GRAPH THEORY

Faysal Ahammed

### BFS:

```

const int N = 1e5 + 9;
vector<int> g[N];
vector<bool> vis(N, false);

void bfs(int u) {
queue<int> q;
q.push(u);
vis[u] = true;
while(!q.empty()) {
int top = q.front(); q.pop();
for(auto v: g[top]) {
if(!vis[v]) {
q.push(v);
vis[v] = true;}}}}

```

### Find Cycle:

```

const int N = 2e5 + 9;
vector<int> g[N];
vector<int> par(N, -1);
vector<int> col(N, 0);
int cycle_start, cycle_end;
set<int> cycle;

void find_cycle(int u) {
col[u] = 1;
for (auto v: g[u]) {
if (col[v] == 0) {
par[v] = u;
find_cycle(v);
}
else if(col[v] == 1 and v !=
par[u]) {
cycle_end = u;
cycle_start = v;
}
}
col[u] = 2;
}

int32_t main() {
ios_base::sync_with_stdio(0);
cin.tie(0);

int n, m; cin >> n >> m;
for(int i = 1; i <= m; i++) {
int u, v; cin >> u >> v;
g[u].push_back(v);
g[v].push_back(u);
}

find_cycle(1);
int cur = cycle_end;
while (cur != cycle_start) {
cycle.insert(cur);
cur = par[cur];
}
cycle.insert(cur);

return 0;
}

```

### Topological Sort:

```

const int N = 1e5 + 9;
vector<int> g[N];
vector<int> indeg(N, 0);

```

```

int32_t main() {
ios_base::sync_with_stdio(0);
cin.tie(0);

int n, m; cin >> n >> m;
while(m--) {
int u, v; cin >> u >> v;
g[u].push_back(v);
indeg[v]++;
}

queue<int> q;
for(int i = 1; i <= n; i++) {
if(indeg[i] == 0) {
q.push(i);
}}

vector<int> ans;
while(!q.empty()) {
int top = q.front();
q.pop();
ans.push_back(top);
for(auto v: g[top]) {
indeg[v]--;
if(indeg[v] == 0) {
q.push(v);}}}

if(ans.size() == n) {
for(auto i: ans) {
cout << i << ' ';}
cout << '\n';}
else {
cout << "IMPOSSIBLE\n";}

return 0;
}

```

### Bellman Ford:

```

using ll = long long;
const int N = 1005;
const ll inf = 1e18;
vector<pair<int, int>> g[N];
vector<ll> dis(N, inf);
int n, m;
bool cycle;

void bellman_ford(int src) {
dis[src] = 0;
for (int i = 1; i <= n; i++) {

```

```

for (int u = 1; u <= n; u++) {
for (auto [v, w] : g[u]) {
if (dis[v] > dis[u] + w and
dis[u] != inf) {
if (i == n) cycle = true;
dis[v] = dis[u] + w;}}}}

int main() {
cin >> n >> m;
while (m--) {
int u, v, w; cin >> u >> v >> w;
g[u].push_back({ v,w });
g[v].push_back({ u,w });
}

cycle = false;
bellman_ford(1);

for (int u = 1; u <= n; u++) {
cout << dis[u] << ' ';
}
cout << '\n';

return 0;
}

Dijkstra:
using ll = long long;
const int N = 1e5 + 9;
const ll inf = 1e18;
vector<pair<int, int>> g[N];
vector<bool> vis(N, false);
vector<ll> dis(N, inf);
int n, m;

void dijkstra(int u) {
dis[u] = 0;
priority_queue<pair<ll, int>,
vector<pair<ll, int>>,
greater<pair<ll, int>>> pq;
pq.push({ 0, u });
while (!pq.empty()) {
int selected_node =
pq.top().second;
ll d = pq.top().first;
pq.pop();
if (vis[selected_node])
continue;
vis[selected_node] = true;

```

```

for (auto [v, w] :
g[selected_node]) {
if (dis[v] > (1ll * d + w)) {
dis[v] = 1ll * d + w;
pq.push({ dis[v], v });}}}}

Floyd Warshall:
using ll = long long;
const int N = 505;
const ll inf = 1e18;
int g[N][N];
ll dis[N][N];
int n, m;

void floyd_warshall() {
for (int i = 1; i <= n; i++) {
for (int j = 1; j <= n; j++) {
if (i == j) dis[i][j] = 0;
else if (g[i][j] == 0) dis[i][j]
= inf;
else dis[i][j] = g[i][j];
}
}

for (int k = 1; k <= n; ++k) {
for (int i = 1; i <= n; ++i) {
for (int j = 1; j <= n; ++j) {
if (dis[i][k] < inf and
dis[k][j] < inf)
dis[i][j] = min(dis[i][j],
dis[i][k] + dis[k][j]);
}}}}

Kruskal's MST:
const int N = 3e5 + 9, mod =
1e9;

struct dsu {
vector<int> par, rnk, size; int
c;
dsu(int n) : par(n+1),
rnk(n+1,0), size(n+1,1), c(n) {
for (int i = 1; i <= n; ++i)
par[i] = i;
}

int find(int i) { return (par[i]
== i ? i : (par[i] =
find(par[i]))) };
bool same(int i, int j) { return
find(i) == find(j); }

```

```

int get_size(int i) { return
size[find(i)]; }
int count() { return c; }
//connected components
int merge(int i, int j) {
if ((i = find(i)) == (j =
find(j))) return -1; else --c;
if (rnk[i] > rnk[j]) swap(i, j);
par[i] = j; size[j] += size[i];
if (rnk[i] == rnk[j]) rnk[j]++;
return j;
}
};

```

```

int32_t main() {
ios_base::sync_with_stdio(0);
cin.tie(0);
int n, m; cin >> n >> m;
vector<array<int, 3>> ed;
for(int i = 1; i <= m; i++){
int u, v, w; cin >> u >> v >> w;
ed.push_back({w, u, v});
}
sort(ed.begin(), ed.end());
long long ans = 0;
dsu d(n);
for (auto e: ed){
int u = e[1], v = e[2], w =
e[0];
if (d.same(u, v)) continue;
ans += w;
d.merge(u, v);
}
cout << ans << '\n';
return 0;
}

```

**Tree Diameter:** max  
cost(distance) between 2 nodes.  
Dfs from any node and get 1 of  
the 2 nodes. Then dfs again from  
this node and get another 1.  
From every node, 1 of these two  
nodes is the max cost.

**Faisal Amin Abir**

**\*\*Bellman Ford with negative  
cycle\*\***  
ll INF = 1e16+7; int n; int m;

```

struct edge{ ll a, b, cost;;
ll d[5005]; edge e[5005];
ll p[5005];
void solve(int v){
ll x=-1; d[v]=0;
for(int i=0; <n; i++){
x=-1;
for(ll j=0; j<m; j++){
if(d[e[j].a] < INF)
if(d[e[j].b] > d[e[j].a] +
e[j].cost){
d[e[j].b] = max(-INF,d[e[j].a] +
e[j].cost);
p[e[j].b] = e[j].a; x = e[j].b;
}
}
if(x== -1) cout << "NO" << endl;
else{
ll y = x;
for(ll i = 0; i<n; i++) y =
p[y];
vector<ll>path;
for(ll curr=y;;curr=p[curr]){
path.push_back(curr);
if(curr==y && path.size()>1){
break;
}
}
reverse(path.begin(),
path.end());
cout << "YES" << endl;
for(auto u:path) cout << u << "
";
return ;
}
}

int main(){
cin>>n>>m;
for(int i=0; i<m; i++){
edge ee; cin>> ee[i].a;
cin>>ee[i].b>>ee[i].cost;
}
solve(1); return 0;
}

```

**\*\* FLOYD\_Warshall\*\***

```

void Floyd_Warshall(){
for(int i=0; i<n; i++){
for(int j=0; j<n; j++){
dis[i][j] = 100000000;
}
}
}

```

```

dis[i][i]=0;
for(int k=1; k<=n; k++){
for(int i=1; i<=n; i++){
for(int j=1; j<=n; j++){
dis[i][j] = min(dis[i][j],
dis[i][k] + dis[k][j]);}}}}

```

**\*\*Lexicographically minimum  
topological sort\*\***

```

vector<int> vi[maxii];
vector<int>:: iterator child;
int check[maxii];
int in[maxii];
int n,m;
int cycle =0;
void dfs(int node){
if(cycle){
return;}
check[node]=1;
for(auto child: vi[node]){
if(check[child]==0){
dfs(child);
}
else if(check[child]==1){
cycle=1;return ;
}}check[node]=2;
}

int main(){
int test=1;
for(int xx=1; xx<=test; xx++){
cin>>n>>m;
int a,b;
for(int i=1; i<=m; i++){
cin>>a>>b;
vi[a].push_back(b);
in[b]++;
}
for(int i=1; i<=n; i++){
if(check[i]==0){
dfs(i);
}}
if(cycle){
cout<<-1;
return 0;}
priority_queue<pair<int,int>,vec
tor<
pair<int,int>,greater<pair<int,
int> > > que;
for(int i=1; i<=n; i++){
if(in[i]==0){

```

```

que.push({i,0});
}}
while(!que.empty()){
int node=que.top().first;
int das=que.top().second;
que.pop();
if(das==0){
cout<<node<<" ";
for(int child:vi[node])
{
in[child]--;
que.push({child,in[child]});
}}}}
** HLD to find max between u and
v, with euler path, LCA and
segtree **
// dfs for subtree cal, dfs2 for
euler
const int N = 1e4+1;;
const int K = __lg(N) + 2;
int LOG[N], parent[N], value[N],
level[N], subtree[N], first[N],
chain[N], in[N], out[N],
lca[N][K], head[N], t[4*N], n;
vector<pair<int, int>>g[N];
vector<int>euler;
void dfs(int v, int par, int
val){
parent[v]=par;
value[v]=val;
lca[v][0] = par;
int sub = 1;
for(auto u:g[v]){
if(u.ff==par)continue;
level[u.ff] = level[v] + 1;
dfs(u.ff, v, u.ss);
sub += subtree[u.ff];
}
subtree[v]=sub;
}
void dfs2(int v, int par, int
time, int matha){
euler.pb(v);
head[v] = matha;
int sub=0, node=0;
in[v] = time;
for(auto u:g[v]){
if(u.ff==par) continue;
if(subtree[u.ff]>sub){
sub = subtree[u.ff];

```

```

node = u.ff;
}}
if(sub!=0){
dfs2(node, v, time+1, matha);
time = out[node];}
for(auto u:g[v]){
if(u.ff == par or u.ff == node)
continue;
dfs2(u.ff, v, time+1, u.ff);
time=out[u.ff];
}
out[v] = time;
}
void build(int v, int l, int r){
if(l==r){
t[v] = value[euler[l]];
return;
}
int mid = (l+r) >> 1;
build(2*v, l, mid);
build(2*v+1, mid+1, r);
t[v] = max(t[2*v], t[2*v+1]);
}
int max_query(int v, int L, int
R, int l, int r){
if(L>R or R<l) return 0;
if(L>=l and R<=r) return t[v];
int mid = (L+R) >> 1;
int left = max_query(2*v, L,
mid, l, r);
int right = max_query(2*v+1,
mid+1, R, l, r);
return max(left, right);
}
void update(int v, int l, int r,
int index, int value){
if(l==r){
t[v] = value;
return;
}
int mid = (l+r) >> 1;
if(index <= mid) update(2*v, l,
mid, index, value);
else update(2*v+1, mid+1, r,
index, value);
t[v] = max(t[2*v], t[2*v+1]);
}
void buildLCA(){
for(int i=1; i<K; i++){
for(int j=1; j<=n; j++){

```

```

int x = lca[j][i-1];
if(x != -1){
lca[j][i] = lca[x][i-1];
}}}}
int find_Lca(int a, int b){
if(level[a] < level[b]) swap(a,
b);
int z = level[a] - level[b];
while(z>0){
int i = LOG[z];
a = lca[a][i];
z-= (1<<i);
}
if(a==b) return a;
for(int i=K-1; i>=0; i--){
if(lca[a][i]!=-1 and
lca[b][i]!=lca[a][i]){
a = lca[a][i];
b = lca[b][i];
}
}
return lca[a][0];
}
void init(){
for(int i=1; i<=n; i++) {
g[i].clear();
for(int j=0; j<K; j++){
lca[i][j]=-1;}}
euler.clear();
}
int find_max(int a, int root){
if(chain[a] == chain[root]){
return max_query(1, 0, n-1,
in[root], in[a]);
}
else{
int x = max_query(1, 0, n-1,
in[head[a]], in[a]);
x = max(x,
find_max(parent[head[a]],
root));
return x;
}
}
void solve(){
cin>>n;
init();
vector<pair<int, int>>edge;
for(int i=1; i<n; i++){
int x,y, cost;
cin>>x>>y>>cost;

```

```

g[x].push_back({y, cost});
g[y].push_back({x, cost});
edge.pb({x, y});
}
dfs(1, -1, -1);
dfs2(1, -1, 0, 1);
int currChain=1;
for(int i=0; i<n; i++){
int x = euler[i];
chain[x] = currChain;
if(in[x]==out[x]) currChain++;
}
build(1, 0, n-1);
buildLCA();
while(1){
string s;
cin>>s;
if(s=="DONE")break;
if(s=="QUERY"){
int a, b;
cin>>a>>b;
int y = find_Lca(a, b);
update(1, 0, n-1, in[y], 0);
int ans = find_max(a, y);
ans = max(ans, find_max(b, y));
cout << ans << endl;
update(1,0, n-1, in[y],
value[y]);
}
else{
int index, val;
cin>>index>>val;
index--;
int a, b;
a = edge[index].ff;
b = edge[index].ss;
if(parent[a]==b) update(1, 0, n-
1, in[a], val), value[a]=val;
else{
update(1, 0, n-1, in[b], val);
value[b]=val;
}
}
}
int main(){
LOG[1] = 0;
for(int i=2; i<N; i++){
LOG[i] = LOG[i/2] + 1;
}
solve();
return 0;
}

```

**SSC find toposort, component**

```

->given a forest, tell which
node to forward mail to reach
max people, lexicographically
smallest one;
const int N = 1e5+123;
vector<int>g1[N], g2[N], g3[N],
topo;
int totalCom, com[N], got,
countCom[N], minCom[N], dis[N],
indeg[N];
bool vis1[N], vis2[N], vis3[N];
int n, m;
void reset(){
for(int i=0; i<=n; i++){
g1[i].clear();
g2[i].clear();
g3[i].clear();
indeg[i]=dis[i]=countCom[i]=com[i]=vis1[i]=vis2[i]=vis3[i]=0;
minCom[i]=INT_MAX;
}
totalCom=0;
topo.clear();
got=0;
}
void dfs1(int v){
if(vis1[v])return;
vis1[v]=1;
for(auto u:g1[v]){
dfs1(u);
}
topo.pb(v);
}
void dfs2(int v){
if(vis2[v])return;
vis2[v]=1;
com[v]=totalCom;
countCom[totalCom]++;
minCom[totalCom] =
min(minCom[totalCom], v);
for(auto u:g2[v]){
dfs2(u);
}
}
void solve(){
cin>>n;
reset();
vector<pair<int, int>>v;

```

```

for(int i=0; i<n; i++){
int x, y;
cin>>x>>y;
g1[x].pb(y);
g2[y].pb(x);
v.pb({x, y});
}
for(int i=1; i<=n; i++){
if(vis1[i]==0)
dfs1(i);
}
reverse(all(topo));
for(auto u:topo){
if(vis2[u]==0){
totalCom++;
dfs2(u);
}
}
for(auto u:v){
int f = com[u.ff];
int t = com[u.ss];
if(f!=t){ // from B to A, we
find the node in reverse
direction to get highest count
g3[t].pb(f);
indeg[f]++;
}
}
using pii = pair<int, int>;
priority_queue<pii, vector<pii>,
greater<pii>>q;
for(int i=1; i<=totalCom; i++){
if(indeg[i]==0){
q.push({countCom[i], i});
dis[i]=countCom[i];
}
}
while(!q.empty()){
int from = q.top().ss;
q.pop();
for(auto u:g3[from]){
if(dis[u]<dis[from]+countCom[u])
{
dis[u] = dis[from] +
countCom[u];
q.push({dis[u], u});
}
}
}
int tot=0;

```

```

int ans=INT_MAX;
for(int i=1; i<=totalCom; i++){
if(dis[i]>tot){
tot = dis[i];
ans = minCom[i];
}
else if(tot == dis[i]){
ans = min(ans, minCom[i]);
}
}
cout << "Case " << ++test << ":
" << ans << endl;
}
SSC to find component of
component
const int N = 1e5+123;
vector<int>g1[N], g2[N], g3[N],
topo, topoCom;
int com[N], totalCom;
bool vis1[N], vis2[N], vis3[N],
vis4[N];
void dfs1(int v){// find the
toposort of the given graph
if(vis1[v])return;
vis1[v]=1;
for(auto u:g1[v]){
dfs1(u);
}
topo.pb(v);
}
void dfs2(int v){ // find the
scc from the toposort using the
transpose of given graph
if(vis2[v])return;
vis2[v]=1;
com[v]=totalCom;
for(auto u:g2[v]){
dfs2(u);
}
}
void dfs3(int v){ // find the
toposort of the component graph
if(vis3[v])return;
vis3[v]=1;
for(auto u:g3[v]){
dfs3(u);
}
topoCom.pb(v);
}
void dfs4(int v){// runs by the
toposort of the component graph
if(vis4[v])return;
vis4[v]=1;
for(auto u:g3[v]){
dfs4(u);
}
}

```

```

}
void solve(){
int n,m;
cin>>n>>m;
vector<pair<int, int>>v;
for(int i=0; i<m; i++){
int x, y;
cin>>x>>y;
g1[x].pb(y);
g2[y].pb(x);
v.pb({x, y});
}
for(int i=1; i<=n; i++){
if(vis1[i]==0){
dfs1(i);
}
}
reverse(all(topo));
for(auto u:topo){
if(vis2[u]==0){
totalCom++;
dfs2(u);
}
}
for(auto u:v){
int from = com[u.ff];
int to = com[u.ss];
if(from!=to){
g3[to].pb(from);
}
}
for(int i=1; i<=totalCom; i++){
if(vis3[i]==0){
dfs3(i);
}
}
reverse(all(topoCom));
int start = topoCom[0];
dfs4(start);
for(int i=1; i<=totalCom; i++){
if(vis4[i]==0){
cout << 0 << endl;
return;
}
}
vector<int>nodes;
for(int i=1; i<=n; i++){
if(com[i]==start){
nodes.pb(i);
}
}
cout << nodes.size() << endl;
for(auto u:nodes)cout<<u<<" ";
cout << endl;
}
Kruskals

```



```

#define MX 100005
int parent[MX], R[MX];
struct kruskalStruct{
int u,v,w;
};
static bool cmp(kruskalStruct
&a, kruskalStruct &b){
return a.w < b.w;
}
void init(int v){
for(int i = 0; i <= v; i++){
parent[i] = i;
R[i] = 1;
}
}
int Find(int p){
if(p == parent[p]) return p;
return parent[p] =
Find(parent[p]);
}
bool Union(int u,int v){
int p = Find(u);
int q = Find(v);
if(p != q) {
if(R[p] >= R[q]){
parent[q] = p;
R[p] += R[q];
}
else{
parent[p] = q;
R[q] += R[p];
}
return true;
}
return false;
}
vector<kruskalStruct> store;
void kruskalsMST(){
int vertex,edge;
cin >> vertex >> edge;
init(vertex);
for(int i = 0; i < edge; i++) {
int u,v,w;
cin >> u >> v >> w;
kruskalStruct ks;
ks.u = u;
ks.v = v;
ks.w = w;
store.push_back(ks);
}

```

```

sort(store.begin(),store.end(),c
mp);
int totalWeight = 0;
for(int i = 0; i < store.size();
i++){
if(Union(store[i].u,store[i].v))
totalWeight += store[i].w;
}
cout << "Kruskal's MST : " <<
totalWeight << endl;
}

```

**\*\* STRING**

**Faisal Amin Abir**

```

**String Multiply**
string multiply(string num1,
string num2){
int len1 = num1.size();
int len2 = num2.size();
if (len1 == 0 || len2 ==
0)return "0";
vector<int> result(len1 + len2,
0);
int i_n1 = 0;
int i_n2 = 0;
for (int i=len1-1; i>=0; i--){
int carry = 0;
int n1 = num1[i] - '0';
i_n2 = 0;
for (int j=len2-1; j>=0; j--){
int n2 = num2[j] - '0';
int sum = n1*n2 + result[i_n1
+i_n2] + carry;
carry = sum/10;
result[i_n1 + i_n2] = sum % 10;
i_n2++;
}
if (carry > 0)result[i_n1 +
i_n2]+= carry;
i_n1++;
}
int i = result.size() - 1;
while (i>=0 && result[i] == 0)i-
-;
if (i == -1)return "0";
string s = "";

```

```

while (i >= 0)s
+=std::to_string(result[i--]);
return s;
}

```

```

**String division**
string longDivision(string
number, int divisor){
string ans;
int idx = 0;
int temp = number[idx] - '0';
while (temp < divisor)
temp = temp * 10 +
(number[++idx] - '0');
while (number.size() > idx){
ans += (temp / divisor) + '0';
temp = (temp % divisor) * 10 +
number[++idx] - '0';
}
if (ans.length() == 0)return
"0";
return ans;
}

```

**\*\*String Double Hashing\*\***

```

const int MAXN=1000006;
namespace DoubleHash{
long long P[2][MAXN];
long long H[2][MAXN];
long long R[2][MAXN];
long long base[2];
long long mod[2];
void gen(){
base[0] = 194931325911;
base[1] = 199729387711;
mod[0] = 209157322711;
mod[1] = 211756680711;
for(int j=0;j<2;j++){
for(int i=0;i<MAXN;i++){
H[j][i]=R[j][i] = 011;
P[j][i] = 111;
}
}
for(int j=0;j<2;j++){
for(int i=1;i<MAXN;i++){
P[j][i] = (P[j][i-1] *
base[j])%mod[j];
}
}
}

```

```

}
void make_hash(string arr){
int len = arr.size();
for(int j=0;j<2;j++){
for (int i = 1; i <= len;
i++)H[j][i] = (H[j][i - 1] *
base[j] + arr[i - 1] + 1007) %
mod[j];
// for (int i = len;
i >= 1; i--)R[j][i] = (R[j][i +
1] * base[j] + arr[i - 1] +
1007) % mod[j];
}
}
inline long long range_hash(int
l,int r,int idx){
long long hashval = H[idx][r +
1] - ((long long)P[idx][r - l +
1] * H[idx][l] % mod[idx]);
return (hashval < 0 ? hashval +
mod[idx] : hashval);
}
inline long long
reverse_hash(int l,int r,int
idx){
long long hashval = R[idx][l +
1] - ((long long)P[idx][r - l +
1] * R[idx][r + 2] % mod[idx]);
return (hashval < 0 ? hashval +
mod[idx] : hashval);
}
inline long long range_dhash(int
l,int r){
long long x = range_hash(l,r,0);
return
(x<<32)^range_hash(l,r,1);
}
inline long long
reverse_dhash(int l,int r){
long long x =
reverse_hash(l,r,0);
return
(x<<32)^reverse_hash(l,r,1);
}
}
char str1[MAXN];
using namespace DoubleHash;
**Reverse Hashing to Find
longest palindromic substring**

```

```

int f1(int index){
if(index == 0 or index==n-1)
return 1;
int ans = 1;
int l = 1, r = min(index, n-1-index);
while( l <= r){
int mid = (l+r) >> 1;
ll h1 = range_hash(index+1, index + mid);
ll h2 = reverse_range_hash(index-mid, index-1);
if(h1==h2){
ans = 1 + ( 2 * mid);
l = mid+1;
}
else r = mid-1;
}
return ans;
}

int f2(int index){
if(index==0 or index==n-2)
return 2;
int ans=2;
int l = 1, r = min(index+1, n-1-index);
while( l <= r){
int mid = (l+r) >> 1;
ll h1 = range_hash(index-mid+1, index);
ll h2 = reverse_range_hash(index + 1, index+mid);
if(h1==h2){
ans = 2 * mid;
l = mid+1;
}
else r = mid-1;
}
return ans;
}

void solve(){
cin>>s;
n = s.size();
ll ans=1;
ll l = 0, r=0;
for(int i=0; i<n; i++){
ll x = f1(i); //for odd length i is mid elem
if(x > ans){

```

```

ans = x;
l = i - (x/2);
r = i + (x/2);
}
if(i + 1 < n and s[i] == s[i+1]){
ll y = f2(i); // for even length
if( y > ans){
ans = y;
l = i - (y/2) + 1;
r = i + (y/2);
}}
for(int i=l ; i<=r ; i++)
cout<<s[i];
}

```

**\*\*Manacher to Find the Longest Palindromic Substring\*\***

```

void solve(){
string s;
cin>>s;
string temp = "";
temp.pb('#');
for(auto u:s){
temp.pb(u);
temp.pb('#');
}
int n = temp.length();
int l=0, r=-1;
int pi[n]={0};
for(int i=0; i<n; i++){
int k=0;
if( i > r){
k = 0;
}
else{
k = min(r-i, pi[l + r - i]);
}
while( i + k + 1 < n && i - k - 1 >=0 && temp[i + k + 1] == temp[i - k - 1]){
k++;
}
pi[i]=k;
if( i + k > r){
r = i + k;
l = i - k;
}
}
int even=0, odd=0, index=0, index2=0, ans=0;

```

```

for(int i=0; i<n; i++){
if(i%2==1){
index++;
}
if(pi[i]>ans){
ans = pi[i];
if(i%2){
odd=1;
even=0;
}
index2 = index;
}
else{
even=1;
odd=0;
index2=index;
}}
index2--;
if(odd){
int l = index2, r = index2;
int k = 1;
while(k<ans){
l--, r++;
k+=2;
}
for(int i=l; i<=r; i++)cout<<s[i];
}
else {
int l = index2, r = index2+1;
int k = 2;
while( k < ans){
l--, r++;
k+=2;
}
for(int i=l; i<=r; i++)cout<<s[i];
}
}

```

**->Given a string with m <= 2e5 operations:**

```

a. Change the char at index to x
b. find if substring between given l, r is palindrome?
const int N = 2e5+12;
ll t[4*N], reverse_t[4*N], power[N], inv[N];
string s;
int n, q;
void build(int v, int l, int r){
if(l==r){
t[v] = (power[l] * (s[l]-'a'+1)) % MOD;

```

```

reverse_t[v] = (power[n-1-l] * (s[l]-'a'+1)) % MOD;
return;
}
int mid = (l+r) >> 1;
build(2*v, l, mid);
build(2*v+1, mid+1, r);
t[v] = (t[2*v] + t[2*v+1]) % MOD;
reverse_t[v] = (reverse_t[2*v] + reverse_t[2*v+1]) % MOD;
}
void update(int v, int l, int r, int index, char ch){
if(l==r){
s[l]=ch;
t[v] = (power[l] * (s[l]-'a'+1)) % MOD;
reverse_t[v] = (power[n-1-l] * (s[l]-'a'+1)) % MOD;
return;
}
int mid = (l+r) >> 1;
if(index <= mid) update(2*v, l, mid, index, ch);
else update(2*v+1, mid+1, r, index, ch);
t[v] = (t[2*v] + t[2*v+1]) % MOD;
reverse_t[v] = (reverse_t[2*v] + reverse_t[2*v+1]) % MOD;
}

```

```

pair<ll, ll> query(int v, int L, int R, int l, int r){
if(L>r or R<l ) return {0, 0};
if(L>=l and R<=r) return {t[v], reverse_t[v]};
int mid = (L+R) >> 1;
pair<ll, ll> p1 = query(2*v, L, mid, l, r);
pair<ll, ll> p2 = query(2*v+1, mid+1, R, l, r);
return {(p1.ff + p2.ff) % MOD, (p1.ss + p2.ss) % MOD};
}
void solve(){
cin>>n>>q;
cin>>s;
power[0]=1;

```

```

power[1]=base;
inv[0]=1;
inv[1]=modPow(base, MOD-2);
for(int i=2; i<n; i++){
    power[i] = (1LL * power[i-1] *
    base) % MOD;
    inv[i] = ( 1LL * inv[i-1] *
    inv[1]) % MOD;
}
build(1, 0, n-1);
while(q--){
    int x;
    cin>>x;
    if(x==1){
        int index; char ch;
        cin>>index >> ch;
        update(1, 0, n-1, index-1, ch);
    }
    else{
        int l, r;
        cin>>l>>r;
        l--, r--;
        pair<ll, ll> p = query(1, 0, n-
        1, l, r);
        ll h1 = (inv[l] * p.ff) % MOD;
        ll h2 = (inv[n-1-r] * p.ss) %
        MOD;
        if(h1==h2){
            cout << "YES" << endl;
        }
        else cout << "NO" << endl;
    }
}

```

**FAYSAL AHAMMED**

### Hashing:

#### \* Double Hashing with Reverse:

```

const int MOD1 = 127657753, MOD2
= 987654319;
const int p1 = 137, p2 = 277; //
change here
int ip1, ip2;
pair<int, int> pw[N], ipw[N];
void prec() {
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {

```

```

        pw[i].first = 1ll * pw[i -
        1].first * p1 % MOD1;
        pw[i].second = 1ll * pw[i -
        1].second * p2 % MOD2;
    }
    ip1 = power(p1, MOD1 - 2, MOD1);
    ip2 = power(p2, MOD2 - 2, MOD2);
    ipw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        ipw[i].first = 1ll * ipw[i -
        1].first * ip1 % MOD1;
        ipw[i].second = 1ll * ipw[i -
        1].second * ip2 % MOD2;
    }
}
struct Hashing {
    int n;
    string s;
    vector<pair<int, int>> hash_val;
    vector<pair<int, int>>
    rev_hash_val;
    Hashing() {}
    Hashing(string _s) {
        s = _s;
        n = s.size();
        hash_val.emplace_back(0, 0);
        for (int i = 0; i < n; i++) {
            pair<int, int> p;
            p.first = (hash_val[i].first +
            1ll * s[i] * pw[i].first % MOD1)
            % MOD1;
            p.second = (hash_val[i].second +
            1ll * s[i] * pw[i].second %
            MOD2) % MOD2;
            hash_val.push_back(p);
        }
        rev_hash_val.emplace_back(0, 0);
        for (int i = 0, j = n - 1; i <
        n; i++, j--) {

```

```

            pair<int, int> p;
            p.first = (rev_hash_val[i].first
            + 1ll * s[i] * pw[j].first %
            MOD1) % MOD1;
            p.second =
            (rev_hash_val[i].second + 1ll *
            s[i] * pw[j].second % MOD2) %
            MOD2;
            rev_hash_val.push_back(p);
        }
    }
    pair<int, int> get_hash(int l,
    int r) { // 1 indexed
        pair<int, int> ans;
        ans.first = (hash_val[r].first -
        hash_val[l - 1].first + MOD1) *
        1ll * ipw[l - 1].first % MOD1;
        ans.second = (hash_val[r].second
        - hash_val[l - 1].second + MOD2)
        * 1ll * ipw[l - 1].second %
        MOD2;
        return ans;
    }
    pair<int, int> rev_hash(int l,
    int r) { // 1 indexed
        pair<int, int> ans;
        ans.first =
        (rev_hash_val[r].first -
        rev_hash_val[l - 1].first +
        MOD1) * 1ll * ipw[n - r].first %
        MOD1;
        ans.second =
        (rev_hash_val[r].second -
        rev_hash_val[l - 1].second +
        MOD2) * 1ll * ipw[n - r].second
        % MOD2;
        return ans;
    }
}

```

```

pair<int, int> get_hash() { // 1
indexed
return get_hash(1, n);
}
bool is_palindrome(int l, int r)
{
return get_hash(l, r) ==
rev_hash(l, r);
}
};
Hashing with Updates and
Reverse:
using T = array<int, 2>;
const T MOD = {127657753,
987654319};
const T p = {137, 277}; //
change here

T operator + (T a, int x)
{return {(a[0] + x) % MOD[0],
(a[1] + x) % MOD[1]}};
T operator - (T a, int x)
{return {(a[0] - x + MOD[0]) %
MOD[0], (a[1] - x + MOD[1]) %
MOD[1]}};
T operator * (T a, int x)
{return {(int)((long long) a[0]
* x % MOD[0]), (int)((long long)
a[1] * x % MOD[1])}};
T operator + (T a, T x) {return
{(a[0] + x[0]) % MOD[0], (a[1] +
x[1]) % MOD[1]}};
T operator - (T a, T x) {return
{(a[0] - x[0] + MOD[0]) %
MOD[0], (a[1] - x[1] + MOD[1]) %
MOD[1]}};
T operator * (T a, T x) {return
{(int)((long long) a[0] * x[0] %

```

```

MOD[0]), (int)((long long) a[1]
* x[1] % MOD[1]));}
ostream& operator << (ostream&
os, T hash) {return os << "(" <<
hash[0] << ", " << hash[1] <<
")";}
T pw[N], ipw[N];
void prec() {
pw[0] = {1, 1};
for (int i = 1; i < N; i++) {
pw[i] = pw[i - 1] * p;
}
ipw[0] = {1, 1};
T ip = {power(p[0], MOD[0] - 2,
MOD[0]), power(p[1], MOD[1] - 2,
MOD[1])};
for (int i = 1; i < N; i++) {
ipw[i] = ipw[i - 1] * ip;
}
}
struct Hashing {
int n;
string s; // 1 - indexed
vector<array<T, 2>> t; //
(normal, rev) hash
array<T, 2> merge(array<T, 2> l,
array<T, 2> r) {
l[0] = l[0] + r[0];
l[1] = l[1] + r[1];
return l;
}
void build(int node, int b, int
e) {
if (b == e) {
t[node][0] = pw[b] * s[b];
t[node][1] = pw[n - b + 1] *
s[b];
return;
}

```

```

int mid = (b + e) >> 1, l = node
<< 1, r = l | 1;
build(l, b, mid);
build(r, mid + 1, e);
t[node] = merge(t[l], t[r]);
}
void upd(int node, int b, int e,
int i, char x) {
if (b > i || e < i) return;
if (b == e && b == i) {
t[node][0] = pw[b] * x;
t[node][1] = pw[n - b + 1] * x;
return;
}
int mid = (b + e) >> 1, l = node
<< 1, r = l | 1;
upd(l, b, mid, i, x);
upd(r, mid + 1, e, i, x);
t[node] = merge(t[l], t[r]);
}
array<T, 2> query(int node, int
b, int e, int i, int j) {
if (b > j || e < i) return
{T({0, 0}}, T({0, 0}));
if (b >= i && e <= j) return
t[node];
int mid = (b + e) >> 1, l = node
<< 1, r = l | 1;
return merge(query(l, b, mid, i,
j), query(r, mid + 1, e, i, j));
}
Hashing() {}
Hashing(string _s) {
n = _s.size();
s = "." + _s;
t.resize(4 * n + 1);
build(1, 1, n);
}
void upd(int i, char c) {

```

```

upd(1, 1, n, i, c);
s[i] = c;
}
T get_hash(int l, int r) { // 1
- indexed
return query(1, 1, n, l, r)[0] *
ipw[l - 1];
}
T rev_hash(int l, int r) { // 1
- indexed
return query(1, 1, n, l, r)[1] *
ipw[n - r];
}
T get_hash() {
return get_hash(1, n);
}
bool is_palindrome(int l, int r)
{
return get_hash(l, r) ==
rev_hash(l, r);
}
};

```

#### Longest Common Prefix:

Binary Search over len and get true/false by hashing in  $O(1)$ .

#### Lexicographically Min Cyclic Shift:

```

// return 0 if both equal
// return 1 if first substring
greater
// return -1 if second substring
greater
int compare(int i, int j, int x,
int y) {
int common_prefix = lcp(i, j, x,
y);
int len1 = j - i + 1, len2 = y -
x + 1;

```

```

if (common_prefix == len1 and
len1 == len2) return 0;
else if (common_prefix == len1)
return -1;
else if (common_prefix == len2)
return 1;
else return (s[i + common_prefix
- 1] < s[x + common_prefix - 1]
? -1 : 1);
}
int start = 1, end = k;
for (int i = 1; i + k - 1 <= n;
i++) {
int x = compare(start, end, i, i
+ k - 1);
if (x == 1) {
start = i, end = i + k - 1;
}
}
cout << s.substr(start - 1, k)
<< '\n';
Cyclic Shift trick: s += s
Number of Palindromic Substring
between l to r in  $O(n^2)$ :
int is_palindrome(int i, int j)
{ //  $O(n^2)$ 
if (i > j) return 1;
int &ans = dp2[i][j];
if (ans != -1) return ans;
ans = 1;
if (s[i] == s[j]) {
ans &= is_palindrome(i + 1, j -
1);
}
else {
ans = 0;
}
return ans;
}

```



```

}

int fun(int i, int j) { //
    O(n^2)
    if (i > j) return 0;
    int &ans = dp[i][j];
    if (ans != -1) return ans;
    ans = is_palindrome(i, j) +
    fun(i + 1, j) + fun(i, j - 1) -
    fun(i + 1, j - 1);
    return ans;
}

Number of Palindromic Substrings
of a String in O(n log n):
string s;
Hashing hash_s;
int n;

bool ok(int l, int r) {
    return hash_s.is_palindrome(l,
    r);
}

int32_t main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    prec(); // must include

    cin >> s;
    n = s.size();
    hash_s = Hashing(s);

    long long ans = 0;
    for (int i = 1; i <= n; i++) {
        int l = 0, r = min(n - i, i -
        1), cnt = 1;
        while (l <= r) {
            int mid = (l + r) >> 1;
            if (ok(i - mid, i + mid)) {

```

```

        cnt = mid;
        l = mid + 1;
        }
        else {
            r = mid - 1;
        }
        ans += cnt + 1;
    }
    for (int i = 2; i <= n; i++) {
        if (s[i - 1] == s[i - 2]) {
            int l = 0, r = min(n - i, i -
            1), cnt = 2;
            while (l <= r) {
                int mid = (l + r) >> 1;
                if (ok(i - 1 - mid, i + mid)) {
                    cnt = mid;
                    l = mid + 1;
                }
                else {
                    r = mid - 1;
                }
            }
            ans += cnt + 1;
        }
    }
    cout << ans << '\n';
    return 0;
}

```

## \*\* DYNAMIC PROGRAMMING

### FAYSAL AHAMMED

```

Knapsack-2 (constraints- n <=
100, w <= 10^9, value <= 1000):
int max_val = 0;
for (int i = n + 1; i >= 1; i--)
{
    for (int current_value = 0;
    current_value <= n * 1000;
    current_value++) {

```

```

        if (i == n + 1) {
            if (current_value == 0)
                dp[i][current_value] = 0;
            else dp[i][current_value] = inf;
        }
        else {
            ll &ans = dp[i][current_value];
            ans = dp[i + 1][current_value];
            if (current_value - value[i] >=
            0) {
                ans = min(ans, weight[i] + dp[i
                + 1][current_value - value[i]]);
            }
            if (ans <= w) {
                max_val = max(max_val,
                current_value);
            }
        }
        cout << max_val << '\n';
    }
    LCS:
    int fun(int i, int j) {
        if (i >= n or j >= m) return 0;
        int &ans = dp[i][j];
        if (ans != -1) return ans;
        ans = fun(i + 1, j);
        ans = max(ans, fun(i, j + 1));
        if (s1[i] == s2[j]) {
            ans = max(ans, 1 + fun(i + 1, j
            + 1));
        }
        return ans;
    }
    void print(int i, int j) {
        if (i >= n or j >= m) return;
        if (s1[i] == s2[j]) {
            cout << s1[i];
            path(i + 1, j + 1);
            return;
        }
        int ans1 = fun(i + 1, j);
        int ans2 = fun(i, j + 1);
        if (ans1 > ans2) {
            path(i + 1, j);
        }
        else {
            path(i, j + 1);
        }
    }
    LIS:
    st.build(1, 1, M);
    for (int i = 1; i <= n; i++) {

```

```

        dp[i] = 1;
        if (a[i] != 1) {
            int mx = st.query(1, 1, M, 1,
            a[i] - 1);
            mx++;
            dp[i] = max(dp[i], mx);
        }
        st.upd(1, 1, M, a[i], dp[i]);
    }

    int ans = 0;
    for (int i = 1; i <= n; i++) {
        ans = max(ans, dp[i]);
    }
    cout << ans << '\n';
    Edit Distance (make two string
    same by add, remove, replace any
    index with min cost):
    int fun(int i, int j) {
        if (i == n) {
            if (j == m) return 0;
            return m - j;
        }
        if (j == m) return n - i;
        int &ans = dp[i][j];
        if (ans != -1) return ans;
        ans = inf;
        if (s1[i] == s2[j]) {
            ans = min(ans, fun(i + 1, j +
            1));
        }
        ans = min(ans, 1 + fun(i + 1, j
        + 1));
        ans = min(ans, 1 + fun(i + 1,
        j));
        ans = min(ans, 1 + fun(i, j +
        1));
        return ans;
    }
    Longest Palindromic Subsequence:
    int fun(int i, int j) {
        if (i > j) return 0;
        if (i == j) return 1;
        int &ans = dp[i][j];
        if (ans != -1) return ans;
        ans = 0;
        if (s[i] == s[j]) {
            ans = max(ans, 2 + fun(i + 1, j
            - 1));
        }
    }

```

```

else {
ans = max(ans, fun(i + 1, j));
ans = max(ans, fun(i, j - 1));
}
return ans;
}

```

### Coin Change:

Repetition allowed (or max k times for k)

Repetition not allowed - fun(int i, int current\_amount)

Repetition fixed - loop inside fun()

Order doesn't matter - fun(amount) and loop inside fun()

**Project** (start time, ending time, profit are given, what's the max profit?):

-Sort by endtime, then dp[i] = max profit if i is the last index taken. Like LIS. Code-sort(a + 1, a + 1 + n); st.build(1, 1, M); for (int i = 1; i <= n; i++) { dp[i] = a[i][2]; ll mx = st.query(1, 1, M, 1, a[i][1] - 1); mx += a[i][2]; dp[i] = max(dp[i], mx); st.upd(1, 1, M, a[i][0], dp[i]); }

ll ans = 0; for (int i = 1; i <= n; i++) { ans = max(ans, dp[i]); }

cout << ans << '\n';

**Slime** (n numbers are given, everytime merge 2 consecutive element until there is just 1 element such that cost is min, the cost of merge two element = sum of them):

- Think reverse: we are given the final sum, from i to j. Now we will cut any point between i to j and calculate the cost ll fun(int i, int j) { if (i == j) return 0;

```

ll &ans = dp[i][j];
if (ans != -1) return ans;
ll cur = 0;
for (int x = i; x <= j; x++) {
cur += a[x];
}
ans = inf;
for (int x = i; x < j; x++) {
ans = min(ans, cur + fun(i, x) + fun(x + 1, j));
}
return ans;
}

```

**Sub-Palindromic Tree** (Given a tree, each node has a character. Now tell us the maximum path which has longest palindromic subsequence):

```

const int N = 2005, inf = 1e9;
vector<int> g[N];
int n;
string s;
int nxt[N][N];
vector<int> vec;
int dp[N][N];

```

```

void dfs(int u, int p) {
vec.push_back(u);
for (auto v: g[u]) {
if (v != p) {
dfs(v, u);
}
}
}
int fun(int u, int v) {
if (v == u) return 1;
int &ans = dp[u][v];
if (ans != -1) return ans;
ans = 0;
if (s[u] == s[v]) {
ans = 2 + (nxt[u][v] == v ? 0 : fun(nxt[u][v], nxt[v][u]));
} else {
ans = max(fun(nxt[u][v], v), fun(u, nxt[v][u]));
}
return ans;
}
void solve() {
cin >> n >> s;
s = '.' + s;
for (int i = 1; i < n; i++) {

```

```

int u, v; cin >> u >> v;
g[u].push_back(v);
g[v].push_back(u);
}
for (int u = 1; u <= n; u++) {
for (auto x: g[u]) {
vec.clear();
dfs(x, u);
for (auto v: vec) {
nxt[u][v] = x;
}
}
}
for (int u = 1; u <= n; u++) {
for (int v = 1; v <= n; v++) {
dp[u][v] = -1;
}
}
int ans = 0;
for (int u = 1; u <= n; u++) {
for (int v = 1; v <= n; v++) {
ans = max(ans, fun(u, v));
}
}
cout << ans << '\n';
for (int i = 1; i <= n; i++) {
g[i].clear();
}
}
Dice-1 (choose N numbers from 1 to k, how many ways the sum of them is S?) [N, K <= 1000, S <= 15000]:
for (int i = n + 1; i >= 1; i--) {
{
for (int cur_sum = 0; cur_sum <= s; cur_sum++) {
if (i == n + 1) {
dp[0][cur_sum] = (cur_sum == 0);
}
else {
int &ans = dp[0][cur_sum];
int mn = min(k, cur_sum);
ans = 0;
// for (int x = 1; x <= mn; x++) {
// ans += dp[1][cur_sum - x];
// ans %= mod;
// }
ans = (dp[1][cur_sum - 1] - (cur_sum - mn - 1 < 0 ? 0 : dp[1][cur_sum - mn - 1]) + mod) % mod;
}
}
}

```

```

for (int cur_sum = 0; cur_sum <= s; cur_sum++) {
dp[1][cur_sum] = dp[0][cur_sum];
}
for (int cur_sum = 1; i != 1 and cur_sum <= s; cur_sum++) {
dp[1][cur_sum] += dp[1][cur_sum - 1];
dp[1][cur_sum] %= mod;
}
cout << dp[0][s] << '\n';
Dice-2 (choose N numbers from 1 to k, if sum of them = s, then score = multiply of the n numbers, sum of scores?) [N, K <= 1000, S <= 15000]:
for (int i = n + 1; i >= 1; i--) {
{
for (int cur_sum = 0; cur_sum <= s; cur_sum++) {
if (i == n + 1) {
dp[0][cur_sum] = cur_sum == 0;
}
else {
int &ans = dp[0][cur_sum];
ans = 0;
int mn = min(k, cur_sum);
// for (int x = 1; x <= mn; x++) {
// ans += 1ll * x * dp[1][cur_sum - x] % mod;
// ans %= mod;
// }
int l = cur_sum - mn, r = cur_sum - 1;
ans = (pref[l] - pref[r + 1] + mod) % mod;
ans -= 1ll * (s - r) * ((dp[1][r] - (l ? dp[1][l - 1] : 0) + mod) % mod) % mod;
ans += mod;
ans %= mod;
}
}
for (int cur_sum = 0; cur_sum <= s; cur_sum++) {
dp[1][cur_sum] = dp[0][cur_sum];
}
pref[0] = dp[1][0];
for (int cur_sum = 1; i != 1 and cur_sum <= s; cur_sum++) {

```

```

pref[cur_sum] = dp[1][cur_sum];
dp[1][cur_sum] += dp[1][cur_sum - 1];
dp[1][cur_sum] %= mod;
}
for (int cur_sum = s - 1, j = 2;
i != 1 and cur_sum >= 0;
cur_sum--, j++) {
pref[cur_sum] = (1ll *
pref[cur_sum] * j % mod) +
pref[cur_sum + 1];
pref[cur_sum] %= mod;
}}
cout << dp[0][s] << '\n';
* If dp stores only true/false
use bitset.

```

## \*\* MICELLANEOUS

### FAYSAL AHAMMED

#### Ternary Search (Pyramid):

```

double surface_area;
double fun(double square_area) {
double base = sqrt(square_area);
double triangle_area =
surface_area - square_area;
double per_triangle_area =
triangle_area / 4;
double triangle_height =
(per_triangle_area * 2) / base;
double x = base / 2;
double height =
sqrt((triangle_height *
triangle_height) - (x * x));
double volume = (base * base *
height) / 3;
if (x > triangle_height) volume
= 0;
return volume;
}
int cs = 0;
int32_t main() {
ios_base::sync_with_stdio(0);
cin.tie(0);
int t; cin >> t;
while (t--) {
cin >> surface_area;
cout << fixed <<
setprecision(4);

```

```

double l = 0, r = surface_area,
ans = -1;
int it = 100;
while (it--) {
double mid1 = l + (r - l) / 3;
double mid2 = r - (r - l) / 3;
double x = fun(mid1);
double y = fun(mid2);
if (x > y) {
ans = x;
r = mid2;
}
else {
l = mid1;
}
}
cout << "Case " << ++cs << ": ";
cout << ans << '\n';
}
return 0;

```

#### 2D Prefix Sum:

```

int n, m; cin >> n >> m;
for (int i = 1; i <= n; i++) {
for (int j = 1; j <= m; j++) {
cin >> a[i][j];
}}
for (int i = 1; i <= n; i++) {
for (int j = 1; j <= m; j++) {
prefix[i][j] = prefix[i - 1][j]
+ prefix[i][j - 1] - prefix[i - 1][j - 1] + a[i][j];
}}
int q; cin >> q;
while (q--) {
int x1, y1, x2, y2; cin >> x1 >>
y1 >> x2 >> y2;
cout << prefix[x2][y2] -
prefix[x1 - 1][y2] -
prefix[x2][y1 - 1] + prefix[x1 - 1][y1 - 1] << '\n';
}

```

#### 2D Difference Array:

```

int n, m; cin >> n >> m;
for (int i = 1; i <= n; i++) {
for (int j = 1; j <= m; j++) {
char c; cin >> c;
a[i][j] = c - '0';
}}
int q; cin >> q;

```

```

while (q--) {
int x1, y1, x2, y2, x; cin >> x1
>> y1 >> x2 >> y2;
x = 1;
d[x1][y1] += x;
d[x1][y2 + 1] -= x;
d[x2 + 1][y1] -= x;
d[x2 + 1][y2 + 1] += x;
}

```

```

for (int i = 1; i <= n; i++) {
for (int j = 1; j <= m; j++) {
d[i][j] += d[i - 1][j] + d[i][j
- 1] - d[i - 1][j - 1];
}}

```

#### // new updated array

```

for (int i = 1; i <= n; i++) {
for (int j = 1; j <= m; j++) {
cout << (d[i][j] + a[i][j]) % 2;
}
cout << '\n';
}

```

#### PBDS:

```

#include<ext/pb_ds/assoc_contain
er.hpp>
#include<ext/pb_ds/tree_policy.h
pp>
using namespace __gnu_pbds;

```

```

template <typename T> using
o_set = tree<T, null_type,
less<T>, rb_tree_tag,
tree_order_statistics_node_updat
e>;

```

#### Custom Hash for GP HashTable:

```

const int RANDOM =
chrono::high_resolution_clock::n
ow().time_since_epoch().count();
struct chash {
int operator()(int x) const {
return x ^ RANDOM; }
};

```

#### Direction Array:

```

int dx[] = {+0, +0, +1, -1, -1,
+1, -1, +1};
int dy[] = {-1, +1, +0, +0, +1,
+1, -1, -1};

```

#### Custom Comparator:

```

bool cmp(pair<int, int> a,
pair<int, int> b) {
if (a.first != b.first) return
a.first > b.first;
return a.second < b.second; //
comparator function must return
false for equal elements
}
Custom Comparator for map,set,
multiset, pq:
struct cmp {
bool operator()(const int& a,
const int& b) const {
return a > b;
}
};

```

#### Mex with Array Updates:

```

int n, q; cin >> n >> q;
set<int> missing_numbers;
for (int i = 0; i <= n + 200;
i++) {
missing_numbers.insert(i);
}

```

```

int a[n + 1];
map<int, int> freq;
for (int i = 1; i <= n; i++) {
cin >> a[i];
freq[a[i]]++;
missing_numbers.erase(a[i]);
}

```

```

while (q--) {
int i, x; cin >> i >> x;
int y = a[i];
a[i] = x;
missing_numbers.erase(x);
freq[y]--;
freq[x]++;
if (freq[y] == 0) {
freq.erase(y);
missing_numbers.insert(y);
}
cout << *missing_numbers.begin()
<< '\n';
}

```

#### Coordinate Compression (faster):

```

vector<int> a({100, 9, 10, 10,
9});
vector<int> v = a;

```





$$\sum_{k=1}^{n-1} \frac{1}{k(k+1)} = \sum_{k=1}^{n-1} \left( \frac{1}{k} - \frac{1}{k+1} \right) = 1 - \frac{1}{n}.$$

$$\ln n = \log_e n \quad (\text{natural logarithm}),$$

For all real  $a > 0, b > 0, c > 0$ , and  $n$ ,

$$a = b^{\log_b a},$$

$$\log_c(ab) = \log_c a + \log_c b,$$

$$\log_b a = \frac{\log_c a}{\log_c b},$$

$$\log_b a = \frac{1}{\log_a b},$$

$$\log_b(1/a) = -\log_b a,$$

$$a^{\log_b c} = c^{\log_b a},$$

$$(a+b)^2 = a^2 + 2ab + b^2$$

$$(a-b)^2 = a^2 - 2ab + b^2$$

$$a^2 + b^2 = (a+b)^2 - 2ab$$

$$a^2 + b^2 = (a-b)^2 + 2ab$$

$$(a+b)^2 = (a-b)^2 + 4ab$$

$$(a-b)^2 = (a+b)^2 - 4ab$$

$$a^2 + b^2 = \frac{(a+b)^2 + (a-b)^2}{2}$$

$$ab = \left( \frac{a+b}{2} \right)^2 - \left( \frac{a-b}{2} \right)^2$$

$$(x+a)(x+b) = x^2 + (a+b)x + ab$$

$$2(ab+bc+ac) = (a+b+c)^2 - (a^2+b^2+c^2)$$

$$(a+b)^3 = a^3 + 3a^2b + 3ab^2 + b^3 = a^3 + b^3 + 3ab(a+b)$$

$$a^3 + b^3 = (a+b)^3 - 3ab(a+b)$$

$$(a-b)^3 = a^3 - 3a^2b + 3ab^2 - b^3 = a^3 - b^3 - 3ab(a-b)$$

$$a^3 - b^3 = (a-b)^3 + 3ab(a-b)$$

$$a^3 + b^3 = (a+b)(a^2 - ab + b^2)$$

$$a^3 - b^3 = (a-b)(a^2 + ab + b^2)$$

$$\sum_{i=1}^n i = \frac{n(n+1)}{2},$$

$$\sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}.$$

$$\sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}$$

**Geometric series:**

$$\sum_{i=0}^n c^i = \frac{c^{n+1} - 1}{c - 1}, \quad c \neq 1$$

$$\sum_{i=0}^{\infty} c^i = \frac{1}{1-c},$$

$$\sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, \quad |c| < 1,$$

$$\binom{n}{k} = \frac{n!}{(n-k)!k!},$$

$$\sum_{k=0}^n \binom{n}{k} = 2^n,$$

$$\binom{n}{k} = \binom{n}{n-k}$$

$$\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}$$

$$\binom{n}{m} \binom{m}{k} = \binom{n}{k} \binom{n-k}{m-k}$$

$$\sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n}.$$

$$\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}$$

$$\sum_{k=0}^n \binom{r}{k} \binom{s}{n-k} = \binom{r+s}{n}$$

$$\binom{n}{k} = (-1)^k \binom{k-n-1}{k}$$

$$\left\{ \begin{matrix} n \\ 1 \end{matrix} \right\} = \left\{ \begin{matrix} n \\ n \end{matrix} \right\} = 1,$$

$$\left\{ \begin{matrix} n \\ 2 \end{matrix} \right\} = 2^{n-1} - 1,$$

$$\left\{ \begin{matrix} n \\ n-1 \end{matrix} \right\} = \left[ \begin{matrix} n \\ n-1 \end{matrix} \right] = \binom{n}{2}$$

$$\sum_{k=0}^n \left[ \begin{matrix} n \\ k \end{matrix} \right] = n!,$$

$$C_n = \frac{1}{n+1} \binom{2n}{n}$$

$$\log_b x = \frac{\log_a x}{\log_a b}, \quad \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

Euler's number  $e$ :

$$e = 1 + \frac{1}{2} + \frac{1}{6} + \frac{1}{24} + \frac{1}{120} + \dots$$

$$\lim_{n \rightarrow \infty} \left( 1 + \frac{x}{n} \right)^n = e^x.$$

$$\left( 1 + \frac{1}{n} \right)^n < e < \left( 1 + \frac{1}{n} \right)^{n+1}.$$

$$\left( 1 + \frac{1}{n} \right)^n = e - \frac{e}{2n} + \frac{11e}{24n^2} - O\left( \frac{1}{n^3} \right).$$

Pascal's Triangle

1
1 1
1 2 1
1 3 3 1
1 4 6 4 1
1 5 10 10 5 1
1 6 15 20 15 6 1
1 7 21 35 35 21 7 1
1 8 28 56 70 56 28 8 1
1 9 36 84 126 126 84 36 9 1
1 10 45 120 210 252 210 120 45 10 1

Binomial distribution:

$$\Pr[X = k] = \binom{n}{k} p^k q^{n-k}, \quad q = 1 - p,$$

$$E[X] = \sum_{k=1}^n k \binom{n}{k} p^k q^{n-k} = np.$$

Euler's equation:

$$e^{ix} = \cos x + i \sin x, \quad e^{i\pi} = -1.$$


Area:

$$A = \frac{1}{2}hc,$$

$$= \frac{1}{2}ab \sin C,$$

$$= \frac{c^2 \sin A \sin B}{2 \sin C}.$$

Heron's formula:



Law of cosines:

$$c^2 = a^2 + b^2 - 2ab \cos C.$$

$$\sin \frac{\pi}{2} = \sqrt{\frac{1 - \cos x}{2}},$$

$$\cos \frac{\pi}{2} = \sqrt{\frac{1 + \cos x}{2}},$$

$$\tan \frac{\pi}{2} = \sqrt{\frac{1 - \cos x}{1 + \cos x}},$$

$$= \frac{1 - \cos x}{\sin x},$$

$$= \frac{\sin x}{1 + \cos x},$$

$$\cot \frac{\pi}{2} = \sqrt{\frac{1 + \cos x}{1 - \cos x}},$$

$$= \frac{1 + \cos x}{\sin x},$$

$$= \frac{\sin x}{1 - \cos x},$$

Euler's function:  $\phi(x)$  is the number of positive integers less than  $x$  relatively prime to  $x$ . If  $\prod_{i=1}^n p_i^{e_i}$  is the prime factorization of  $x$  then

$$\phi(x) = \prod_{i=1}^n p_i^{e_i-1} (p_i - 1).$$

Euler's theorem: If  $a$  and  $b$  are relatively prime then

$$1 \equiv a^{\phi(b)} \pmod{b}.$$

Fermat's theorem:

$$1 \equiv a^{p-1} \pmod{p}.$$

The Euclidean algorithm: if  $a > b$  are integers then


$$\gcd(a, b) = \gcd(a \bmod b, b).$$

If  $\prod_{i=1}^n p_i^{e_i}$  is the prime factorization of  $x$  then


$$S(x) = \sum_{d|x} d = \prod_{i=1}^n \frac{p_i^{e_i+1} - 1}{p_i - 1}.$$

Perfect Numbers:  $x$  is an even perfect number iff  $x = 2^{n-1}(2^n - 1)$  and  $2^n - 1$  is prime.


Wilson's theorem:  $n$  is a prime iff  $(n-1)! \equiv -1 \pmod{n}$ .



$$AB^2 = AC^2 + BC^2 + 2 \cdot BC \cdot CD$$



$$AB^2 = AC^2 + BC^2 - 2 \cdot BC \cdot CD$$



$$AB^2 + AC^2 = 2(AD^2 + BD^2)$$

$$d^2 = \frac{2(b^2 + c^2) - a^2}{4}$$

$$e^2 = \frac{2(c^2 + a^2) - b^2}{4}$$

$$f^2 = \frac{2(a^2 + b^2) - c^2}{4}$$

$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

$$\log_a M = \log_b M \times \log_a b$$

$$(x+y)^n = x^n + nx^{n-1}y + \frac{n(n-1)}{1 \cdot 2} x^{n-2}y^2 + \frac{n(n-1)(n-2)}{1 \cdot 2 \cdot 3} x^{n-3}y^3 + \dots + y^n$$

$$n! = n(n-1)(n-2) \cdots 3 \cdot 2 \cdot 1$$

$$\binom{n}{r} = {}^nC_r, \quad {}^nC_n = 1$$

$$\binom{n}{r} = {}^nC_r = \frac{n!}{r!(n-r)!}, \quad \binom{n}{0} = {}^nC_0 = 1$$

$$\binom{n}{n} = {}^nC_n = 1, \quad 0! = 1$$

$$\binom{n}{k} = \frac{n!}{(n-k)!k!}$$

$$\sum_{k=0}^n \binom{n}{k} = 2^n$$

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}$$

$$\sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}$$

$$\sum_{i=1}^n i^3 = \frac{n^2(n+1)^2}{4}$$

Triangle:

$$\text{area} = \sqrt{s(s-a)(s-b)(s-c)}$$

$$\text{area} = \frac{1}{2}(x_1y_2 + x_2y_3 + x_3y_1 - x_2y_1 - x_3y_2 - x_1y_3)$$

Cube:

$$\text{area} = abc$$

$$\text{diag} = \sqrt{a^2 + b^2 + c^2}$$

Circle:

$$\text{circumference} = 2\pi r$$

$$\text{area} = \pi r^2$$

$$\text{eqn} : (x-h)^2 + (y-k)^2 = r^2 \dots (i)$$

$$(x-h)^2 + (y-k)^2 = r^2 \text{ বা, } x^2 + y^2 - 2hx - 2ky + (h^2 + k^2 - r^2) = 0$$

$$h^2 + k^2 - r^2 = c$$


$$\text{বা, } g^2 + f^2 - c = r^2$$

$$\text{অতএব ব্যাসার্ধ, } r = \sqrt{g^2 + f^2 - c}$$

Cone:

$$\frac{1}{3}\pi r^2 h$$

volume:



$$\text{area} = \frac{1}{2}(BD \times AC)$$

$$\therefore P(x_1, y_1) \text{ বিন্দু হতে } ax + by + c = 0 \text{ রেখার লম্ব দৈর্ঘ্য} = \frac{|ax_1 + by_1 + c|}{\sqrt{a^2 + b^2}}$$

$$\therefore \text{সমান্তরাল রেখা দুইটির মধ্যবর্তী দূরত্ব } MN = ON - OM = \frac{|c_1 - c_2|}{\sqrt{a^2 + b^2}}$$

$$x^2 + y^2 = r^2 \text{ এবং } y = mx + c$$

$$\text{tangent condition: } c = \pm r \sqrt{1 + m^2}$$

বহিঃস্থ কোন বিন্দু  $(x_1, y_1)$  থেকে  $x^2 + y^2 + 2gx + 2fy + c = 0$  বৃত্তের অভ্যন্তরীণ স্পর্শক দুইটির সমীকরণ


$$(x^2 + y^2 + 2gx + 2fy + c)(x_1^2 + y_1^2 + 2gx_1 + 2fy_1 + c) = \{x x_1 + y y_1 + g(x + x_1) + f(y + y_1) + c\}^2$$

Area:

$$\begin{aligned} A &= \frac{1}{2}hc, \\ &= \frac{1}{2}ab \sin C, \\ &= \frac{c^2 \sin A \sin B}{2 \sin C}. \end{aligned}$$

Heron's formula:

$$\begin{aligned} A &= \sqrt{s \cdot s_a \cdot s_b \cdot s_c}, \\ s &= \frac{1}{2}(a + b + c), \\ s_a &= s - a, \\ s_b &= s - b, \\ s_c &= s - c. \end{aligned}$$



Law of cosines:

$$c^2 = a^2 + b^2 - 2ab \cos C$$

Euler's function:  $\phi(x)$  is the number of positive integers less than  $x$  relatively prime to  $x$ . If  $\prod_{i=1}^n p_i^{e_i}$  is the prime factorization of  $x$  then

$$\phi(x) = \prod_{i=1}^n p_i^{e_i-1} (p_i - 1).$$

Euler's theorem: If  $a$  and  $b$  are relatively prime then

$$1 \equiv a^{\phi(b)} \pmod{b}.$$

Fermat's theorem:

$$1 \equiv a^{p-1} \pmod{p}.$$