



CATEGORICAL DATA IN THE TIDYVERSE

Introduction to qualitative data

Emily Robinson
Data Scientist



Course overview


- Identifying and inspecting qualitative variables
- Working with the forcats package
- Making effective visualizations



Final chapter

Hell Is Other People In A Pressurized Metal Tube

Percentage of 874 air-passenger respondents who said action is very or somewhat rude



FIVETHIRTYEIGHT

SOURCE: SURVEYMONKEY AUDIENCE

41% of Fliers Think You're Rude if You Recline Your Seat



What are qualitative variables?

- Categorical vs. Ordinal data

Categorical (nominal) data





Ordinal data

Annual Income Options:

- "0-\$50,000"
- "\$50,000-150,000"
- "\$150,000-500,000"
- "More than \$500,000"



Qualitative variables in R

- Names vs. question on programming languages

Qualitative variables in R

- Look at your whole dataset

```
library(fivethirtyeight)
print(college_all_ages)
# A tibble: 173 x 11
  major_code major      major_category      total employed
  <int> <chr>      <chr>      <int> <int>
1    1100 General Ag... Agriculture & Na... 128148  90245
2    1101 Agricultur... Agriculture & Na...  95326  76865
3    1102 Agricultur... Agriculture & Na...  33955  26321
4    1103 Animal Sci... Agriculture & Na... 103549  81177
# ... with 163 more rows, and 6 more variables:
#   employed_fulltime_yearround <int>, unemployed <int>,
#   unemployment_rate <dbl>, p25th <dbl>, median <dbl>,
#   p75th <dbl>
```

- Look at your variables one at a time:

```
is.factor(college_all_ages$major_category)
[1] FALSE
```




CATEGORICAL DATA IN THE TIDYVERSE

Let's practice!



CATEGORICAL DATA IN THE TIDYVERSE

Understanding your qualitative variables

Emily Robinson
Data Scientist

Introduction to the dataset

- Dataset: Kaggle 2017 Data Science survey

```
# A tibble: 16,716 x 228
  GenderSelect      Country      Age EmploymentStatus
  <chr>           <chr>    <int> <chr>
1 Non-binary, gender... NA      NA Employed full-time
2 Female          United ... 30 Not employed, but lo...
3 Male            Canada    28 Not employed, but lo...
4 Male            United ... 56 Independent contract...
5 Male            Taiwan    38 Employed full-time
6 Male            Brazil    46 Employed full-time
7 Male            United ... 35 Employed full-time
8 Female          India     22 Employed full-time
9 Female          Austral... 43 Employed full-time
10 Male           Russia    33 Employed full-time
# ... with 16,706 more rows, and 224 more variables:
#   StudentStatus <chr>, LearningDataScience <chr>,
#   CodeWriter <chr>, CareerSwitcher <chr>,
#   CurrentJobTitleSelect <chr>, TitleFit <chr>,
#   CurrentEmployerType <chr>, MLToolNextYearSelect <chr>,
#   MLMethodNextYearSelect <chr>,
#   LanguageRecommendationSelect <chr>,
#   PublicDatasetsSelect <chr>,
```

Converting characters to factors

```
is.character(multipleChoiceResponses$LearningDataScienceTime)
[1] TRUE
```

```
multipleChoiceResponses %>%
  mutate_if(is.character, as.factor)
```

```
# A tibble: 16,716 x 228
  GenderSelect      Country    Age EmploymentStatus
  <fct>           <fct>    <int> <fct>
1 Non-binary, gender... NA      NA Employed full-time
2 Female           United ... 30 Not employed, but lo...
3 Male             Canada 28 Not employed, but lo...
4 Male             United ... 56 Independent contract...
5 Male             Taiwan 38 Employed full-time
6 Male             Brazil 46 Employed full-time
7 Male             United ... 35 Employed full-time
8 Female           India 22 Employed full-time
# ... with 16,706 more rows, and 224 more variables:
#   StudentStatus <fct>, LearningDataScience <fct>,
#   CodeWriter <fct>, CareerSwitcher <fct>,
#   CurrentJobTitleSelect <fct>, TitleFit <fct>,
#   CurrentEmployerType <fct>, MLToolNextYearSelect <fct>,
```

Summarising factors

- Get the number of categories (levels)

```
nlevels(multipleChoiceResponses$LearningDataScienceTime)
[1] 6
```

- Get the list of categories (levels)

```
levels(multipleChoiceResponses$LearningDataScienceTime)
[1] "< 1 year"      "1-2 years"     "10-15 years"  "15+ years"
[5] "3-5 years"     "5-10 years"
```

- Get number of levels for every factor variable

```
multipleChoiceResponses %>%
  summarise_if(is.factor, nlevels)
# A tibble: 1 x 215
#   GenderSelect Country EmploymentStatus StudentStatus
#   <int>      <int>          <int>          <int>
#1         4        52            7            2
# ... with 211 more variables: LearningDataScience <int>,
#   CodeWriter <int>, CareerSwitcher <int>,
```



CATEGORICAL DATA IN THE TIDYVERSE


Let's practice!



CATEGORICAL DATA IN THE TIDYVERSE


Making Better Plots


Emily Robinson
Data Scientist



Reordering factors


```
ggplot(WorkChallenges) +  
  geom_point(aes(x = fct_reorder(question, perc_problem), y = perc_problem))
```






Reordering bar chart

```
ggplot(multiple_choice_responses) +  
  geom_bar(aes(x = fct_infreq(CurrentJobTitleSelect)))
```



Reversing factor levels

```
ggplot(multiple_choice_responses) +  
  geom_bar(aes(x = fct_rev(fct_infreq(CurrentJobTitleSelect))))
```





CATEGORICAL DATA IN THE TIDYVERSE

Let's practice!