

Computing with Transistors

Dr. Charles R. Severance

www.ca4e.com


online.dr-chuck.com


Outline

- The transistor replacing tubes in digital applications
 - Faster than a relay or tube
 - Far less heat and electricity
 - More reliable and long lasting
 - No moving parts
- Amplifiers, Tubes and Transistors – It's complicated
 - Transistor radios
- Evolution of transistor technology and manufacturing
 - BJT -> PMOS -> NMOS -> CMOS
- The "digital logic gate" abstraction

Valves / Tubes / Vacuum Tubes

- The first purely electronic devices to store data and do computations were called "Valves" in the UK
 - About 1000 times faster than physical relays
- Designed to amplify analog signals
- Early application long distance analog telephone calls – needed an amplifier every 10 miles or so
- Tube was invented in 1912 Dr. Lee De Forest



TUNG-SOL

GLASS BULB
MINIATURE BUTTON
9 PIN BASE E9-1
OUTLINE DRAWING
JEDEC 6-2

TRIODE PENTODE

MINIATURE TYPE


UNIPOTENTIAL CATHODE

HEATER

6.3 VOLTS 450±30 MA.

AC OR DC

ANY MOUNTING POSITION




**BOTTOM VIEW
BASING DIAGRAM
JEDEC 9GF**

<https://frank.pocnet.net/sheets/127/6/6CG8A.pdf>

THE 6CG8A CONTAINS A MEDIUM-MU TRIODE AND SHARP CUTOFF PENTODE IN THE 9-PIN MINIATURE CONSTRUCTION. IT IS DESIGNED PRIMARILY FOR USE AS A COMBINED OSCILLATOR AND MIXER IN TELEVISION RECEIVERS UTILIZING AN INTERMEDIATE FREQUENCY IN THE ORDER OF 40 MC. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES WHICH ARE SIMILARLY CONTROLLED.


Building "Digital" Valves / Tubes

- The design of tubes could be tweaked so to move quickly from low voltage to high voltage as the input voltage increased
 - Voltage low = off
 - Voltage high = on
- With the correct design, a range of slightly lower input would be lifted on output



Flaws of Valves

- Take lots of power
- Lots of heat because tubes had an internal heater that helped release electrons from the cathode.
- Physically large
- Expensive to manufacture
- Soft electronic glow in the dark




https://en.wikipedia.org/wiki/Valve_amplifier

Semi-Conductors

Transistors

- Building a better Triode (Tube)
- Three kinds of materials w.r.t electricity
 - Conducting like metal
 - Insulating like plastic
 - Semi-conductor
- Certain crystalline materials like silicon can be modified by adding impurities ('doping') so they conduct electricity under certain conditions — hence, *semiconductors*.



<https://en.wikipedia.org/wiki/Transistor>



<https://commons.wikimedia.org/wiki/File:1st-Transistor.jpg>

Nobel Prize!




- Transistors are constructed by layering crystals with carefully designed impurities
 - Silicon with N-Doping
 - Silicon with P-Doping
- When voltages are applied to the crystals, sub-atomic stuff happens at the boundaries between the different types of crystals that affect the flow of electrons through the crystals

https://en.wikipedia.org/wiki/Nobel_Prize_in_Physics



Transistor audio amplifiers – not so simple


- A typical transistor amplifier (whether NMOS or BJT) inverts the signal — so an additional stage is used to restore phase.
- A few more transistors improve the quality of the amplified signal.



<https://en.wikipedia.org/wiki/Amplifier>

Transistor Radios

- Once amplifier style transistors were available, during the 1940's there was an effort to build small, battery-powered "transistor radios"
- Often the marketing included the number of transistors – "The Sony TR-826 radio has eight transistors!"



https://en.wikipedia.org/wiki/Transistor_radio

Hi End Tube-Based Audio Amplifiers

- Many and professional musical performers feel that that amplifiers that use tubes produce better sound with less distortion
- New high-end audio amplifiers can cost upwards of \$50,000
- This is not an audio class - so back to digital logic 😊


https://en.wikipedia.org/wiki/Valve_amplifier



Macintosh MC240 - \$3500


Building "Digital" Transistors

- The design of transistors could be tweaked to move quickly from high voltage to low voltage as the input voltage increased
 - Voltage low = off
 - Voltage high = on
- With the right design, a range of slightly lower input would be corrected on output
- AI: Difference between a Bipolar Junction Transistor and NMOS transistor



Two Kinds of "Digital" Transistors

- NMOS conducts when the input (gate) voltage is high
- PMOS conducts when the input is low.
- Modern chips use both
- CMOS – Complementary Metal-Oxide-Semiconductor



<https://en.wikipedia.org/wiki/MOSFET>

The Four Eras of Transistor Manufacturing


Approx. Years	Dominant Technology	Key Feature	Processors	Limitation that Led to Next Step
1950s–1960s	Bipolar Junction Transistor (BJT)	Fast and well-understood		Power-hungry, hard to integrate
Late 1960s–early 1970s	PMOS	Easier to fabricate MOS logic	Intel 4004	Slow, used negative voltages
1973–1983	NMOS	Faster, simpler power supply	Intel 8080 Zilog Z-80	Still wasted static power
1983–present	CMOS	Extremely low power, scalable	Intel 486	Became universal

ChatGPT: Describe the historical timeline for the transition from Bipolar Junction Transistor (BPT) to Complementary Metal-Oxide-Semiconductor (CMOS) transistor technology.

From Transistors to Gates

We use transistors to implement "gates"



- When we build digital logic we think in terms of **abstractions** that we call "gates"
- Gates let us think about in 1's and 0's instead of voltages
- The simplest gate is a "not" gate where the output is the opposite of the input
- It demonstrates a circuit that reacts – like a simple "if" statement
- We will build more complex logic circuits




Input	Output
0	1
1	0

[https://en.wikipedia.org/wiki/Inverter_\(logic_gate\)](https://en.wikipedia.org/wiki/Inverter_(logic_gate))


Not gates over time..



PMOS - 1972





NMOS - 1978




CMOS - 1983


Not gates over time..



PMOS - 1972





NMOS - 1978




CMOS - 1983


Not gates over time..



PMOS - 1972





NMOS - 1978






CMOS - 1983

TL;DR – Not Gates Over Time

- Before the 1980's, logic gates built from transistors were slow, had low density, took a lot of heat and took a lot of power.
- When CMOS was practical in the 1980s, CPUS went from the size of large cabinets to single chips
- As size reduced things got much faster
- From now on we will only speak of CMOS 😊



Layout a CMOS NOT Gate (Demo)



<https://www.ca4e.com/tools/cmos/>

Digital Logic

- To design more complex circuits from half-adders to CPUs it is much easier to think in terms of gates than transistors
- Gates are an abstraction
 - On / OFF or 1 / 0
- The basic gates come from mathematical logic (and IF statements)
 - Not / And / Or / Exclusive Or
- We also talk about gates that can be built with fewer transistors
 - NAND / NOR

Classic Mathematical Logic Gates

Not



A	Q
0	1
1	0

Two transistors

And



A	B	Q
0	0	0
0	1	0
1	0	0
1	1	1

Six transistors

Or



A	B	Q
0	0	0
0	1	1
1	0	1
1	1	1

Six transistors

Exclusive Or



A	B	Q
0	0	0
0	1	1
1	0	1
1	1	0

Eight transistors

NAND and NOR

Fewer transistors




NAND



A	B	Q
0	0	1
0	1	1
1	0	1
1	1	0

Four transistors




NOR



A	B	Q
0	0	1
0	1	0
1	0	0
1	1	0



Four transistors




Layout a CMOS NAND Gate



A	B	Q
0	0	1
0	1	1
1	0	1
1	1	0



Sneak Peek: Digital Logic Design



Summary

- Semiconductors
- Tuning tubes and transistor for digital applications (as compared to amplifier applications)
- Building gates from transistors
- Transistor technology evolution PMOS, NMOS and CMOS logic

Acknowledgements / Contributions

These slides are Copyright 2025- Charles R. Severance (online.dr-chuck.com) as part of www.ca4e.com and made available under a Creative Commons Attribution 4.0 License. Please maintain this last slide in all copies of the document to comply with the attribution requirements of the license. If you make a change, feel free to add your name and organization to the list of contributors on this page as you republish the materials.

Initial Development: Charles Severance, University of Michigan School of Information

Insert new Contributors and Translators here including names and dates

Continue new Contributors and Translators here