

Recurrent Neural Networks

10/10 points (100%)

Quiz, 10 questions

✓ **Congratulations! You passed!**

Next Item



1. Suppose your training examples are sentences (sequences of words). Which of the following refers to the j^{th} word in the i^{th} training example?

1 / 1
points

☒ $x^{(i)<j>}$

Correct

We index into the i^{th} row first to get the i^{th} training example (represented by parentheses), then the j^{th} column to get the j^{th} word (represented by the brackets).

☐ $x^{<i>(j)}$


☐ $x^{(j)<i>}$

☐ $x^{<j>(i)}$



2. Consider this RNN:

1 / 1
points



This specific type of architecture is appropriate when (check all that apply):

☒ $T_x = T_y$

Recurrent Neural Networks

10/10 points (100%)

Quiz, 10 questions

Correct

It is appropriate when every input should be matched to an output.

☐ $T_x < T_y$


☐ $T_x > T_y$

☐ $T_x = 1$



3. To which of these tasks would you apply a many-to-one RNN architecture? (Check all that apply).

1 / 1
points



Speech recognition (input an audio clip and output a transcript)



Un-selected is correct



Sentiment classification (input a piece of text and output a 0/1 to denote positive or negative sentiment)



Correct



Recurrent Neural Networks

Quiz, 10 questions

10/10 points (100%)



Image classification (input an image and output a label)



Un-selected is correct



Gender recognition from speech (input an audio clip and output a label indicating the speaker's gender)




Correct



4. You are training this RNN language model.

1 / 1
points



At the t^{th} time step, what is the RNN doing? Choose the best answer.



Estimating $P(y^{<1>}, y^{<2>}, \dots, y^{<t-1>})$



Estimating $P(y^{<t>})$



Estimating $P(y^{<t>} \mid y^{<1>}, y^{<2>}, \dots, y^{<t-1>})$



Correct




Estimating $P(y^{<t>} \mid y^{<1>}, y^{<2>}, \dots, y^{<t>})$



Recurrent Neural Networks

1 / 1
Quiz, 10 questions
points

5. You have finished training a language model RNN and are using it to sample random sentences, as follows:



What are you doing at each time step t ?

- ☐ (i) Use the probabilities output by the RNN to pick the highest probability word for that time-step as $\hat{y}^{<t>}$. (ii) Then pass the ground-truth word from the training set to the next time-step.
- ☐ (i) Use the probabilities output by the RNN to randomly sample a chosen word for that time-step as $\hat{y}^{<t>}$. (ii) Then pass the ground-truth word from the training set to the next time-step.
- ☐ (i) Use the probabilities output by the RNN to pick the highest probability word for that time-step as $\hat{y}^{<t>}$. (ii) Then pass this selected word to the next time-step.
- ☒ (i) Use the probabilities output by the RNN to randomly sample a chosen word for that time-step as $\hat{y}^{<t>}$. (ii) Then pass this selected word to the next time-step.



Correct



6. You are training an RNN, and find that your weights and activations are all taking on the value of NaN ("Not a Number"). Which of these is the most likely cause of this problem?

1 / 1
points

- ☐ Vanishing gradient problem.
- ☒ Exploding gradient problem.



Correct

Recurrent Neural Networks

ReLU activation function $g(.)$ used to compute $g(z)$, where z is too large.

10/10 points (100%)

Quiz, 10 questions



Sigmoid activation function $g(.)$ used to compute $g(z)$, where z is too large.



7.

Suppose you are training a GRU. You have a 10000 word vocabulary, and are using an LSTM with 100-dimensional activations $a^{<t>}$. What is the dimension of Γ_u at each time step?

1 / 1
points



1



100



Correct



300



10000



8.

Here're the update equations for the GRU.

1 / 1
points

GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

Alice proposes to simplify the GRU by always removing the Γ_u . I.e., setting $\Gamma_u = 1$. Betty proposes to simplify the GRU by removing the Γ_r . I. e., setting $\Gamma_r = 1$ always. Which of these models is more likely to work without vanishing gradient problems even when trained on very long input sequences?



Recurrent Neural Networks

10/10 points (100%)

Quiz, 10 questions

☐ Alice's model (removing Γ_u), because if $\Gamma_r \approx 0$ for a timestep, the gradient can propagate back through that timestep without much decay.

☐ Alice's model (removing Γ_u), because if $\Gamma_r \approx 1$ for a timestep, the gradient can propagate back through that timestep without much decay.

☒ Betty's model (removing Γ_r), because if $\Gamma_u \approx 0$ for a timestep, the gradient can propagate back through that timestep without much decay.



Correct

☐ Betty's model (removing Γ_r), because if $\Gamma_u \approx 1$ for a timestep, the gradient can propagate back through that timestep without much decay.



9. Here are the equations for the GRU and the LSTM:

1 / 1
points

GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

LSTM

$$\tilde{c}^{<t>} = \tanh(W_c[a^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[a^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_f = \sigma(W_f[a^{<t-1>}, x^{<t>}] + b_f)$$

$$\Gamma_o = \sigma(W_o[a^{<t-1>}, x^{<t>}] + b_o)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + \Gamma_f * c^{<t-1>}$$

$$a^{<t>} = \Gamma_o * c^{<t>}$$

From these, we can see that the Update Gate and Forget Gate in the LSTM play a role similar to _____ and _____ in the GRU. What should go in the the blanks?

☒ Γ_u and $1 - \Gamma_u$



Correct

☐ Γ_u and Γ_r

☐ $1 - \Gamma_u$ and Γ_u



Recurrent Neural Networks

10/10 points (100%)

Quiz, 10 questions



1 / 1
points



10. You have a pet dog whose mood is heavily dependent on the current and past few days' weather. You've collected data for the past 365 days on the weather, which you represent as a sequence as $x^{<1>}, \dots, x^{<365>}$. You've also collected data on your dog's mood, which you represent as $y^{<1>}, \dots, y^{<365>}$. You'd like to build a model to map from $x \rightarrow y$. Should you use a Unidirectional RNN or Bidirectional RNN for this problem?

- ☐ Bidirectional RNN, because this allows the prediction of mood on day t to take into account more information.
- ☐ Bidirectional RNN, because this allows backpropagation to compute more accurate gradients.
- ☒ Unidirectional RNN, because the value of $y^{<t>}$ depends only on $x^{<1>}, \dots, x^{<t>}$, but not on $x^{<t+1>}, \dots, x^{<365>}$

Correct

- ☐ Unidirectional RNN, because the value of $y^{<t>}$ depends only on $x^{<t>}$, and not other days' weather.