


# What is Point Cloud?



## **A point cloud:**

A collection of data points defined in a three-dimensional coordinate system (X, Y, Z).

## **Irregular Format:**

Point clouds are unordered, have variable point counts, and exhibit non-uniform distribution.

# **Traditional CNN Approach for Point Clouds: Point Cloud → Voxelization/Image Projection**

*but with 2 major issues...*

## **1. Data Explosion**

- Massive memory
- $64^3$  grid = 262K voxels
- Computational burden



## **2. Information Loss**

- Quantization errors
- Loss of fine details
- Geometric invariance

**Point Cloud**



**3D Voxel Grids**




# Point Cloud



# Collections of images



# PointNet Architecture



## Key ideas:

- 1. Point-wise:** Shared MLP for each point
- 2. Order-free:** Max pooling makes the model permutation invariant
- 3. Geometry-aware:** T-Net learns point cloud alignment automatically

# Point Cloud Features

Most features were **handcrafted** for specific tasks.

- Features are either:
  - **Intrinsic** (shape-based, rotation-invariant)
  - **Extrinsic** (coordinate-based, change with rotation)
- Also divided into:
  - **Local features** (neighborhood shape)
  - **Global features** (overall object shape)

So it's hard to find the **best feature combination** for each task.

**PointNet learns features directly from raw points, without handcrafting.**



# Deep Learning on 3D Data

Approach	Key Papers	Method	Pros	Cons	Accuracy
Volumetric CNN	<ul style="list-style-type: none"><li>• 3DShapeNets</li><li>• VoxNet</li><li>• FPNN</li></ul>	Voxelize $\rightarrow$ 3D Conv	<ol style="list-style-type: none"><li>1. Mature 3D conv</li><li>2. Structured</li></ol>	<ol style="list-style-type: none"><li>1. Resolution limited</li><li>2. Memory intensive</li><li>3. Sparse but dense storage</li></ol>	77-86%
Multi-view CNN	<ul style="list-style-type: none"><li>• MVCNN</li><li>• Vol+MV</li></ul>	Render $\rightarrow$ 2D Conv	<ol style="list-style-type: none"><li>1. Leverage 2D CNNs</li><li>2. Best performance</li></ol>	<ol style="list-style-type: none"><li>1. Rendering overhead</li><li>2. View selection</li><li>3. Hard to extend to segmentation</li></ol>	90.1%
Spectral CNN	<ul style="list-style-type: none"><li>• Spectral</li><li>• Geodesic</li></ul>	Graph conv on mesh	Geometric operations	<ol style="list-style-type: none"><li>1. Only manifold meshes</li><li>2. Organic shapes only</li></ol>	N/A
Feature-based DNN	<ul style="list-style-type: none"><li>• 3D Deep Shape Descriptor</li><li>• 3D Mesh Labeling</li></ul>	Features $\rightarrow$ MLP	Simple pipeline	<ol style="list-style-type: none"><li>1. Handcrafted features</li><li>2. Not end-to-end</li></ol>	Lower

# Deep Learning on Unordered Sets

Point clouds = **unordered sets**, rarely studied in deep learning.

Prior work (Vinyals et al.) handles general sets but **no geometry**.

**PointNet is the first to handle unordered geometric point sets.**



# Problem Statement

## Point Cloud

$$\{P_i \in (x, y, z) | (x, y, z) \in \mathbb{R}^3, i = 1, \dots, n\}$$





## PointNet



**Classification (k x 1)**



**Part Segmentation  
/Semantic Segmentation  
(n x m)**



# Deep Learning on Point Sets

Properties of Point Sets in  $\mathbb{R}^n$

**Unordered**  
( $N!$  Permutation)




**Symmetry Function**

$$f(\{x_1, \dots, x_n\}) \approx g(h(x_1), \dots, h(x_n))$$

$$g := \prod_{k=1}^n \mathbb{R}^K \rightarrow \mathbb{R}$$

**Locality**  
(Interaction among points)




**Local and Global Information Aggregation**

$$f(G, L) \approx \text{Concat}(G, L, \text{axis} = 1)$$

$$G \in \mathbb{R}^{(n \times K_1)}, L \in \mathbb{R}^{(n \times K_2)}$$

$$f(G, L) \in \mathbb{R}^{(n \times (K_1 + K_2))}$$

**Invariance under transformations**




**Joint Alignment Network**

$$\begin{matrix} x_1 & y_1 & z_1 \\ \vdots & \vdots & \vdots \\ x_n & y_n & z_n \end{matrix} \times T$$

$$T \in \mathbb{R}^{(3 \times 3)}$$

# Deep Learning on Point Sets






# Deep Learning on Point Sets

***$N!$  Permutation: Row-wise Independent Invariance under transformations***


## Input/Feature Transform

$$\begin{matrix} P_1^T \\ P_2^T \\ P_3^T \end{matrix} \times A = \begin{matrix} h_1^T \\ h_2^T \\ h_3^T \end{matrix} \leftrightarrow \begin{matrix} P_3^T \\ P_1^T \\ P_2^T \end{matrix} \times A = \begin{matrix} h_3^T \\ h_1^T \\ h_2^T \end{matrix} \quad L_{reg} = \|\mathbb{I} - AA^T\|_F^2$$

## Classification Network



**T-Net:** predict Affine Transformation Matrix



## Segmentation Network





# Deep Learning on Point Sets

***N!* Permutation: Row-wise Independent**

**Shared Weight MLP ~ 1D Convolution**

$$\begin{array}{ccccccc} P_1^T & & w_{11} & \dots & w_{k1} & & y_1^T \\ P_2^T & \times & w_{12} & \dots & w_{k2} & = & y_2^T \\ P_3^T & & w_{13} & \dots & w_{k3} & & y_3^T \end{array} \quad \begin{array}{ccccccc} P_3^T & & w_{11} & \dots & w_{k1} & & y_3^T \\ P_1^T & \times & w_{12} & \dots & w_{k2} & = & y_1^T \\ P_2^T & & w_{13} & \dots & w_{k3} & & y_2^T \end{array}$$

*Classification Network*



*Segmentation Network*

# Deep Learning on Point Sets



**Classification:**  
Symmetry Function (Unorder)

**MaxPooling** (axis = 0)

$$\text{maxpool}(P_1, P_2, P_3) = \text{maxpool}(P_3, P_1, P_2)$$

Universal approximation & Stability

*Classification Network*



*Segmentation Network*





# Deep Learning on Point Sets

**Segmentation:**  
Interaction among Points

**Concatenate** (axis = 1)

Combination of Local Geometry and Global Semantic

*Classification Network*



*Segmentation Network*







# Deep Learning on Point Sets

## Output of PointNet

**Classification:** ( $k \times 1$ )       $k$  class label

**Segmentation:** ( $n \times m$ )       $m$  class(part) label for every points

### Classification Network



### Segmentation Network

# Supplementary

## Universal Approximation

$$f: \chi \rightarrow \mathbb{R}$$
$$\chi = \{S | S \subseteq [0,1]^3, |S| = n\}$$

$$d_H(S, S') < \delta \Rightarrow |f(S) - f(S')| < \epsilon$$
$$\forall \epsilon > 0, \exists \delta > 0, \quad S, S' \in \chi$$

Continuity

$$\bigcup_{S \in \chi} |f(S) - \gamma(\max_{x_i \in S} \{h(x_i)\})| < \epsilon$$

## Bottleneck dimension and stability

### Input/Feature Transform

### Shared Weight MLP ~ 1D Convolution


### MaxPooling (axis = 0)

### MLP

$$\gamma(\max_{x_i \in S} \{h(x_i)\})$$

Hausdorff distance

$$d_H(X, Y) := \max \left\{ \sup_{x \in X} d(x, Y), \sup_{y \in Y} d(X, y) \right\},$$



# Supplementary

## Universal Approximation



$$\Phi_j(x) \approx \begin{cases} 1, & x \in C_j \\ 0, & \text{otherwise} \end{cases}$$

But continuous like Dirac-Delta Function

$$h(x) = (\alpha\phi_1(x), \alpha\phi_2(x), \dots, \alpha\phi_k(x)) \in \mathbb{R}^k$$

$$u(s) = \max_{x_i \in S} \{h(x_i)\} \approx \begin{cases} \alpha, & S \cap C_j \neq \emptyset \\ 0, & S \cap C_j = \emptyset \end{cases}$$

$$\gamma(x) : \mathbb{R}^k \rightarrow \mathbb{R}$$

$$\bigcup_{S \in \chi} |f(S) - \gamma(\max_{x_i \in S} \{h(x_i)\})| < \epsilon$$


$\therefore$  sufficiently large  $k$ ,  $\gamma(\max_{x_i \in S} \{h(x_i)\})$  can approximate **any** permutation invariance function.

*Bottleneck dimension and stability*

**MaxPooling** (axis = 0)


$$u = \max_{x_i \in S} \{h(x_i)\}$$
$$u : \chi \rightarrow \mathbb{R}^K$$

Bottleneck k



(a)  $\forall S, \exists C_S, N_S \subseteq \chi, f(T) = f(S) \text{ if } C_S \subseteq T \subseteq N_S$

(b)  $|C_S| \leq K$



$f(S) = f(S')$       Stability

# Experiments

## Task1: 3D Classification

Dataset:

- ModelNet40
- (12K shapes, 40 classes)

Results:

- MVCNN: 90.1% (80 views)
- VoxNet: 85.9% (12 views)
- **PointNet: 89.2% (single view)**

→ On par with SOTA

→ 141× faster than MVCNN

	input	#views	accuracy avg. class	accuracy overall
SPH [11]	mesh	-	68.2	-
3DShapeNets [28]	volume	1	77.3	84.7
VoxNet [17]	volume	12	83.0	85.9
Subvolume [18]	volume	20	86.0	<b>89.2</b>
LFD [28]	image	10	75.5	-
MVCNN [23]	image	80	<b>90.1</b>	-
Ours baseline	point	-	72.6	77.4
Ours PointNet	point	1	86.2	<b>89.2</b>

Table 1. **Classification results on ModelNet40.** Our net achieves state-of-the-art among deep nets on 3D input.

	#params	FLOPs/sample
PointNet (vanilla)	0.8M	148M
PointNet	3.5M	440M
Subvolume [18]	16.6M	3633M
MVCNN [23]	60.0M	62057M

Table 6. **Time and space complexity of deep architectures for 3D data classification.** PointNet (vanilla) is the classification PointNet without input and feature transformations. FLOP stands for floating-point operation. The “M” stands for million. Subvolume and MVCNN used pooling on input data from multiple rotations or views, without which they have much inferior performance.

# Experiments

## Task2: Part Segmentation

Dataset:

- ShapeNet Parts
- (16K shapes, 50 parts)

Results:

- Yi et al.: 81.4% mIoU
- 3D CNN: 79.4% mIoU
- **PointNet: 83.7% mIoU**

→ +2.3% improvement

→ Robust to missing / partial points

	mean	aero	bag	cap	car	chair	ear phone	guitar	knife	lamp	laptop	motor	mug	pistol	rocket	skate board	table
# shapes		2690	76	55	898	3758	69	787	392	1547	451	202	184	283	66	152	5271
Wu [27]	-	63.2	-	-	-	73.5	-	-	-	74.4	-	-	-	-	-	-	74.8
Yi [29]	81.4	81.0	78.4	77.7	<b>75.7</b>	87.6	61.9	<b>92.0</b>	85.4	<b>82.5</b>	<b>95.7</b>	<b>70.6</b>	91.9	<b>85.9</b>	53.1	69.8	75.3
3DCNN	79.4	75.1	72.8	73.3	70.0	87.2	63.5	88.4	79.6	74.4	93.9	58.7	91.8	76.4	51.2	65.3	77.1
Ours	<b>83.7</b>	<b>83.4</b>	<b>78.7</b>	<b>82.5</b>	74.9	<b>89.6</b>	<b>73.0</b>	91.5	<b>85.9</b>	80.8	95.3	65.2	<b>93.0</b>	81.2	<b>57.9</b>	<b>72.8</b>	<b>80.6</b>

Table 2. **Segmentation results on ShapeNet part dataset.** Metric is mIoU(%) on points. We compare with two traditional methods [27] and [29] and a 3D fully convolutional network baseline proposed by us. Our PointNet method achieved the state-of-the-art in mIoU.

# Experiments

## Task3: Scene Segmentation

Dataset:

- Stanford 3D Indoor Scenes
- (271 rooms, 13 classes)

Results:

- Baseline: 20.1% mIoU
- **PointNet: 47.7% mIoU**

→ 137% relative improvement

→ Unified architecture for all tasks

	mean IoU	overall accuracy
Ours baseline	20.12	53.19
Ours PointNet	<b>47.71</b>	<b>78.62</b>

Table 3. **Results on semantic segmentation in scenes.** Metric is average IoU over 13 classes (structural and furniture elements plus clutter) and classification accuracy calculated on points.