

JavaScript is disabled on your browser. Please enable JavaScript to use all the features on this page. [Skip to main content](#)[Skip to article](#)

ScienceDirect

- * Journals & Books
- * Help
- * Search

Gergo Gyori

IT University of Copenhagen

* View ****PDF****

* Download full issue

Search ScienceDirect

Outline

1. Highlights
2. Abstract
3. 4. Keywords
5. MSC
6. 1\ Introduction
7. 2\ Related work
8. 3\ Overall flow of proposed MATP-DESURF-based FER
9. 4\ Foreground extraction
10. 5\ MATP-DESURF-based facial key points
11. 6\ PPCSO-based feature selection
12. 7\ LSTM-CNN classification
13. 8\ Experiments
14. 9\ Conclusion
15. Acknowledgments
16. References

Show full outline

Cited by (70)

Figures (15)

1. 2. 3. 4. 5. 6.

Show 9 more figures

Tables (5)

1. Table 1
2. Table 2
3. Table 3
4. Table 4
5. Table 5

Pattern Recognition Letters

Volume 139, November 2020, Pages 157-165

Multi angle optimal pattern-based deep learning for automatic facial expression recognition

Author links open overlay panelDeepak Kumar Jain a b, Zhang Zhang a b, Kaiqi Huang a b

Show more

Outline

Add to Mendeley

Share

Cite

<https://doi.org/10.1016/j.patrec.2017.06.025>Get rights and content

Highlights

* ?

Rectification of problems due to sudden illumination changes and proper alignment of feature set for an effective FER.

* ?

Isolation of foreground from the background of an image to facilitate the facial key points extraction.

* ?

Elimination of unwanted noise and smoothen by using AMF filtering technique.

* ?

MATP-based texture pattern and DESURF-LOP-based facial key points to the FER outperform the traditional methods.

* ?

PPCSO-based feature selection and LSTM-CNN based classification recognize the expressions accurately.

Abstract

Facial Expression Recognition (FER) plays the vital role in the Human Computer Interface (HCI) applications. The illumination and pose variations affect the FER adversely. The projection of complex 3D actions on the image plane and the inaccurate alignment are the major issues in the FER process. This paper presents the novel Multi-Angle Optimal Pattern-based Deep Learning (MAOP-DL) method to rectify the problem from sudden illumination changes, find the proper alignment of a feature set by using multi-angle-based optimal configurations. The proposed method includes the five major processes as Extended Boundary Background Subtraction (EBBS), Multi-Angle Texture Pattern+STM, Densely Extracted SURF+Local Occupancy Pattern (LOP), Priority Particle Cuckoo Search Optimization (PPCSO) and Long Short-Term Memory-Convolutional Neural Network (LSTM-CNN). Initially, the EBBS algorithm subtracts the background and isolates the foreground from the images which overcome the illumination and pose variation. Then, the MATP-STM extracts the texture patterns and DESURF-LOP extracts the relevant key features of the facial points. The PPCSO algorithm selects the relevant features from the MATP-STM feature set to speed up the classification. The employment of LSTM-CNN predicts the required label for the facial expressions. The major key findings of the proposed work are clear image analysis, effective handling of pose/illumination variations and the facial alignment. The proposed MAOP-DL validates its effectiveness on two standard databases such as CK+ and MMI regarding various metrics and confirm their assurance of wide applicability in recent applications.

* Previous article in issue

* Next article in issue

Keywords

STM

SURF

CNN

LSTM

MSC

41A10

65D05

65D17

1\ Introduction

Rapid growth of Human-Computer Interfaces (HCI) induces the challenges in Facial Expression Recognition (FER). Even though the frontal view recognition is well on the basis of the appearance or geometry model, the Multiview Facial Expression Recognition (MFER) is the challenging issue [8]. Illumination conditions, age and size variations in the facial image and videos that lead to the development of Automatic FER in three stages such as face detection and tracking, feature extraction and emotion classification in [19] and [13]. With

numerous development of applications such as automatic video indexing, surveillance and assisted living, detection and recognition of actions in natural settings is an important stage. Recently, the two type of datasets with the same actions in the wild and video clips introduces the new complexities to the recognition community. The lack of constraints on such type of data makes the classification as challenging one. Recently, an Automated Face Recognition (AFR) [5] is an attractive research study due to the extensive applications of mobile phone authentication to surveillance. There are two types of environments available for AFR such as controlled (frontal, neutral expressions and uniform illumination) and uncontrolled environment (arbitrary poses, non-uniform illumination and occlusions. AFR in an uncontrolled environment [16] is the challenging task due to its intense pose variations which are considered as major uncertain blocks in AFR. Temporal alignment and the semantic aware dynamic representation were the major issues in FER due to the repeatable property of low-level features. Manual designed cuboids have the capability to capture the low-level information instead of high-level information provided the less discriminative capability [12]. The major requirement like all the images is available prior to congealing leads to offline tasks with low efficiency [18]. The combination of expression dynamics with the 3D facial geometry [21] provided the wealth information that opens up the new researches [37] on the capture of a face in all motions and detection of cues.

The provision of temporal coherence and the achievement of required matching accuracy depend on the estimation of similarity between the expressions. The data driven approaches [11], [32] predict the k-nearest neighbors which are considered as the candidates for each frame. The proposal of expression transfer method refined the expression retrieved from the database. The dense registration of point clouds is the computational task in AFR due to the large size 3D vertices in the facial mesh. Besides, the existence of landmarks is the pre-requisite for FER. The partial separation of facial cues induced the complications in automatic FER applications. Hence, the issues addressed in the automatic FER are foreground/background separation, facial key point's extraction, the dimensionality of features and multi-labeling-based recognition. The major contributions of proposed MAOP-DL model are listed as follows:

* ?

The Extended Boundary Background Subtraction (EBBS) isolates the background and foreground of images that made the system as adaptive to sudden illumination changes.

* ?

The combination of Multi-Angular Texture Pattern (MATP) and the Spatio-Temporal Matching (STM) algorithm extracts the different features that provide the clear image analysis and proper alignment.

* ?

The Densely Extracted SURF model integrated with the Local Occupancy Pattern (LOP) algorithm govern the facial key points to accurately identify the muscle variations during the expression.

* ?

Finally, the application of Priority Particle Cuckoo Search Optimization (PPCSO) algorithm on MATP-features reduces the dimensionality and the utilization of Long Short Term Memory-Convolution Neural Network (CNN) improves the classification performance effectively.

The rest of the paper is organized as follows. Section 2 presents a description about the previous research studies relevant to an automated FER

and their issues. Section 3 describes the implementation process of proposed MATP-DESURF model for an effective FER. Section 4 investigates the performance of proposed system with the various performance metrics over the existing methods. Finally, Section 5 presents the conclusion and future enhancement of proposed research work.

2\ Related work

Due to the small, partially visible and the occluded relevant objects in human interactions, the recognition of mutual contexts between each other is the difficult task. Yao et al. [31] proposed the mutual context model in which objects and human pose are jointly modeled in recognition of human-pose interaction activities. The interference learned from the Action Units (AU) was static and the temporal changes in facial expressions led to more discrimination in intensity levels. Rudovic et al. [20] proposed the novel Conditional Ordinal Random Field (CORF) model to model the context-sensitive approach for facial action recognition.). Oh et al. [17] proposed Radial Basis Function RBF-Neural network on the basis of the combination of Principle Component Analysis (PCA) and Linear Discriminant Analysis (LDA). The improper facial alignments and the occlusions are the major issues in traditional PCA-LDA-based dimensionality reduction techniques. Siddiqi et al. [27] introduced the robust FER system that employed the Step-Wise LDA (SWLDA) to select the localized features from the expression frames. Happy et al. [6] proposed the novel facial landmark detection and the salient patch-based FER under the diverse resolutions of the image. Fast network training with low human supervision in an optimization process decreases the network generalization ability.

On the basis of learning, several approaches are evolved in research studies to deal with the issues in an accurate recognition. Barakova et al. [1] proposed the interpretation method of emotions that were detected in facial expressions in the context of events. The genetic search and the optimization of parameters were regarded as the next step toward the automatic analysis of facial expressions. Iosifidis et al. [7] proposed the graph-based embedded ELM algorithm that exploited both the penalty and SL criteria in infinite dimensional spaces. The dense registration of point clouds is the computational task in AFR due to the large size 3D vertices in the facial mesh. Besides, the existence of landmarks is the pre-requisite for facial expression recognition. Zhao et al. [35] presented the probabilistic framework on the basis of Bayesian Belief Network (BBN) on the basis of Statistical Feature Models (SFM) and Gibbs-Boltzmann distribution for geometric and appearance features. Blur and illumination were the major problems and by using the blurring operation of given images convex set was formed. Vageeswaran et al. [28] proposed the blur-robust algorithm to solve the convex optimization problems. Recovery of High Resolution (HR) images from the Low-Resolution (LR) sequences was the major objective of superresolution and achieved by hallucination methods. Ma et al. [15] reviewed the several maps-based models under pose, illumination and expressions (hallucination problems). The modeling of mappings was performed by using the redundant and sparse representation.

The selection of representative features and the uncertain class labels made the feature selection as critical task. Wang et al. [30] proposed the unsupervised feature selection for the recognition of facial features in presence of class labels. The utilization of Zernike Moments (ZM) offered the promising recognition rates with its rotational invariances. Sariyanidi [22] modified the ZM to obtain the local representation by computing the moments of each pixel of face image on the basis of the local neighborhood. Sariyanidi et

al. [23] reviewed and analyzed several states of art solutions by splitting up the pipeline of face recognition process into four stages as registration, representation, dimensionality reduction and recognition. Senechal et al. [24] utilized the multi-kernel SVM for each AU with the Local Gabor Binary Pattern histograms and the Active Appearance Model (AAM) coefficients. The capture of complex decision boundary is the difficult task in spontaneous emotions analysis. Shan [25] constructed the strong classifier by using the combination of weak classifiers with the AdaBoost approach. The features to recognize the smile expression are the intensity difference between the pixels exist in the grayscale images.

During the image annotation process, the selection of features prior to investigation of properties of feature combination do not provide any significant contribution. Zhang et al. [33] introduced the regularization-based feature selection algorithm to leverage both the sparsity and clustering properties of features for annotation phase. Complex variations, gross errors and preservation of local details of image introduced the difficulties in shape priors modeling. Zhang et al. [34] proposed the Sparse Shape Composition model (SSC) to address the aforementioned challenges. The partial separation of facial cues induced the complications in automatic FER applications and such problem is regarded as identity-independent ER problem. Kung et al. [10] proposed the Dual Subspace Non-negative Graph Embedding (DSNGE) for the representation of expressive images on two subspaces as identity and expression. Borude et al. [2] discussed the methods available for facial features tracking under various illuminations, pose variations and lighting conditions. Guo et al. [4] proposed the dynamic facial expression recognition which was formulated with the longitudinal group wise registration problem. The major contributions of the dynamic recognition are diffeomorphic growth model, built of salient longitudinal facial expression, sparse representation (spatial and temporal domain) guided the recognition effectively. The survey of traditional research studies indicated that the presence of illumination and pose variations, dimensionality of features were the major issues in FER applications.

3\ Overall flow of proposed MATP-DESURF-based FER

An accurate automated recognition of facial expressions with the diverse illumination/pose variations, high dimensionality of features and the exact facial key points is the major focus of the research work proposed in this paper. Fig. 1 shows the overall workflow of proposed MATP-DESURF-based FER.

1. Download: Download high-res image (681KB)
2. Download: Download full-size image

Fig. 1. Overall Flow of Proposed MAOP-DL for FER.

Initially, the RGB image from the real-time database is considered as the input to the system. The presence of noise introduces the difficulties in pixel intensity estimation. Hence, the input image is preprocessed with the Adaptive Median Filtering (AMF) to remove the noise and smoothen the image that leads to intensity normalization. Then, the EBBS algorithm is applied to the noise-free image to isolate the background and foreground. The feature points are necessary to recognize the emotions in HCI applications.

This paper proposes the novel MATP combined with Densely Extracted SURF model, LOP and STM algorithm to extract the feature key points. The split-up of extracted patterns into several grids and the extraction of facial key point features increase the dimensionality. Hence, the PPCSO is used in a proposed system to select the optimal relevant features. The optimally selected result is matched with the training feature grid through LSTM-CNN classification to recognize the expressions. The isolation of background and foreground prior to

the feature extraction and the dimensionality reduction through the optimization in proposed work provided the properly aligned feature set for FER.

4\.. Foreground extraction

The noise removal is the initial stage of proposed work. The presence of impulsive noise and the distortion in object boundaries induce the difficulties in image processing. In this paper, the AMF [26] is used to remove the noise and reduce the distortion (excessive thinning and thickening) in two levels. The application of size of the window to filter the image pixels is adaptive in nature. The noise present in the image is removed through AMF as follows:

Level 1: Check whether the median pixel value of the image (I_{med}) is in between the ranges of minimum and maximum pixels (I_{min}, I_{max}) and if it exists, then the value is not considered as an impulse. Then, the algorithm goes to level 2 to check the next pixel. Otherwise, the size of the window is increased and the level 1 is repeated until the median value is not an impulse.

Level 2: Check the current pixel is in the ranges of minimum and maximum pixels and if it exists, then the filtered image pixel is unchanged.

Otherwise, the pixel is regarded as corrupted and the filtered image pixel is assigned the median value for level 2.

An isolation of background from the foreground of noise-free image is the next stage in proposed work. This paper utilizes the EBBS algorithm to extract the foreground from the noise-free image. The algorithm comprises three essential processes such as cell formation, directionality estimation, and the intensity depth analysis to extract the foreground from the images. To implement this processes, the window formation is the prior step. Hence, the window necessary to project the input image is formed as follows: (1) $W = I(i?1toi+1, j?1toj+1)$ Once the window is formed, the magnitude that represents the multiple cells of window is computed. The normal distribution of (G) values in each cell and the weight for window are responsible for the magnitude estimation. In the proposed EBBS algorithm, the directionality-based ROI with depth analysis plays the major role in foreground extraction. The mathematical formulation of directionality ($D^-(x, y)$) is defined as follows: (2) $D^-(x, y) = \frac{1}{\sigma} \sum_{i=1}^N G(x, y, i)$ where, σ = Standard deviation and N = Size of Window By convoluting the directionality ($D^-(x, y)$) with the window formed (W), the weight corresponds to the magnitude estimation is updated such as (3) $W^-(x, y) = W(x, y) * D^-(x, y)$ Where $W(x, y)$ = Initial Window and $W^-(x, y)$ = Size of window. The updated weight values from the Eq. (3) are used to estimate the magnitude for depth analysis (T_e) as follows: (4) $T_e(x, y) = \frac{W(x, y) \times W^-(x, y)}{W(x, y)^2}$ The magnitudes obtained from Eq. (4) are compared with the updated weight values. If the magnitude is greater than the updated weight value, then the encoded form of likelihood value (L) for the patterns necessary to isolate foreground and background is predicted. The Algorithm 1 to extract the foreground output as follows

1. Download: Download high-res image (143KB)
2. Download: Download full-size image

Algorithm 1. EBBS algorithm.

The encoded values (E) are multiplied with the average value of magnitude of the intensity depth to extract the patterns. If the value of the patterns are greater than zero, then the foreground of the image. The values are replaced with zero otherwise.

The cells that represent the noise-free image are formed and the binary difference of pixel values is sequentially estimated as shown in Fig. 2.

1. Download: Download high-res image (417KB)
2. Download: Download full-size image

Fig. 2. Cell formation.

Figs. 3 and 4 clearly depicts the foreground extraction based on the directionality values. From Fig. 3, the connected components from the magnitude estimation are predicted. The layers from the magnitude values are separated for foreground and background. By performing the deep intensity analysis through the encoding process, the background of the image is subtracted and foreground necessary for FER is extracted.

1. Download: Download high-res image (190KB)
2. Download: Download full-size image

Fig. 3. Directionality-based ROI extraction.

1. Download: Download high-res image (110KB)
2. Download: Download full-size image

Fig. 4. Foreground extraction.

5\.. MATP-DESURF-based facial key points

The muscle variations of facial key points (left eye, right eye, nose and mouth) play the major role in FER analysis. Hence, the prediction of facial key points is the next stage of proposed work. The output from the EBBS algorithm is considered as the input to the MATP algorithm.

5.1. Multi-Angle texture pattern

In this stage, the window size is extended to 5×5 for projection of EBBS output. Then, the median value of projected image is computed. Initially, the window over the EBBS image is formed with the size of 5×5 . Within this window, the cells with 3×3 is extracted separately. By applying the angle-based difference estimation, the rules required for the vector prediction is formed.

The algorithm to compute the patterns in multi-angular form is listed as follows (see Algorithm 2).

1. Download: Download high-res image (112KB)
2. Download: Download full-size image

Algorithm 2. Multi-angular texture pattern.

The magnitude value corresponding to the difference between the window formation (T_1 , T_2) are mathematically expressed as follows: $(5) \text{mag} = (\text{double}((T_1(3,4) - T_2(3,3))^2 + ((T_1(3,4) - T_2(3,3))^2))$ The comparison between the center pixel with the neighboring pixels is performed and then the decimal coding is performed to extract the patterns. The bitwise OR operation is performed with two types of patterns ($Pt_2 - Pt_1$) extracted the relevant patterns and then mesh grid is constructed. The coordination among the values in the meshgrid is predicted with sparse form.

Finally, the angle-based texture patterns as shown in Fig. 5 that are necessary to predict the facial key points are predicted. The STM comprises the four major processes such as index estimation, cluster formation, template separation and tag representation. The STM is spanned by 3D blocks densely sampled from the dictionary that cover the local variations of spatial and temporal space. The application of bank of learned filters extract the low-level features from each block. The features are directly learned from the input dataset proved the generalizability. In proposed work, the query patterns derived from the MATP process is passed to the cluster formation. The index corresponding to the dense samples from the dictionary and the input MATP are estimated and then clustered.

1. Download: Download high-res image (106KB)
2. Download: Download full-size image

Fig. 5. MATP Pattern.

The STM are arranged in four parts as Left eye, right eye, nose and mouth as shown in Figs. 6 and 7. Using this STM, the patterns relevant to the facial key points are extracted through the DESURF-LOP process.

1. Download: Download high-res image (300KB)
2. Download: Download full-size image

Fig. 6. STM Block Diagram.

1. Download: Download high-res image (354KB)
2. Download: Download full-size image

Fig. 7. STM arrangement.

5.2. DESURF-LOP

The histogram relevant to the facial key point features is the next stage of proposed work. The unique coordinates in sparse form are extracted into separate clusters as follows: (6) $C_{xy} = \{i, S_{xy} = S(x?1)(y?1)0, \text{elsewhere } i = 1 \text{ to } N\}$. The pattern of image pixel at and and their distance ($_D i _$) are used to find the coefficients of matrix called Hessian matrix ($H(S, _? _)$) as follows: (7) $H(S, ?) = (L_{xx}(C, ?) L_{xy}(C, ?) L_{xy}(C, ?) L_{yy}(C, ?))$ where, (8) $L_{xx}(C, ?) = ?i=1 N D_i (PT(C)_{xy})^* ?$. Then, the matching points of STM output with the testing input are predicted as follows: (9) $V_s = \{?dx, ?|dx|, ?dy, ?|dy|\}$. The region corresponds to the matching points are extracted as follows: (10) $R_{xy} = PT(V_s)$. Finally, the features relevant to the histogram of matching points are extracted as follows: (11) $F_i = B_i$, where $i = 1 \text{ to } N$. Fig. 8 shows the pictorial representation of working process in DESURF-LOP-based facial key points prediction. With increase of features, the computations required for classification is more. Hence, the selection of number of relevant features is the prior stage to classification. Optimization procedures play the major role in feature selection process. Among various procedures, the Cuckoo Search (CS) is used to select the features necessary for classification. But, the enhanced form of CS is used in this paper to improve the classification performance further.

1. Download: Download high-res image (440KB)
2. Download: Download full-size image

Fig. 8. DESURF-LOP Facial key point feature extraction.

6\ PPSO-based feature selection

The characteristics of suitable fitness function assigning and the objective function formulation with either maximizing or minimizing objective is inherited to find the relevant features. The fitness of the solution is directly proportional to the objective function value of maximization problem. The fitness function formulation in traditional method are modified with the help of searching radius and the length of particles as (12) $F_t = \{\text{Mean}(C), (k \times l)\}$ Where, $_C = \{F(1), F(2), \dots \dots F(N)\}$ denotes the cuckoo particles (13) $k = k + r(N?1) \times ?C_i$ $_r _$ = searching radius $_N _$ = Length of the particles (14) $l = 1? \text{mean}(C)k$. The feature vectors are modeled as cuckoos in this CS algorithm and find the coordinates of each cuckoo is defined by using the fitness function. By using the prediction of best cluster point and the value (d) defined in (15), the radius of cluster is updated. (15) $d = \text{Min}(F_t) \pm (? \times (\text{Max}(F_t) ? \text{Min}(F_t)))$ where $_? _ = 1$. The index represent the Cluster Head (CH) is computed by comparing the value of current cluster with best cluster point. Once the Cluster head is formed, then the new value of coordinates to be found in order to reach the best cluster point. Mutation and crossover in Cuckoo search (CS) are responsible for updating the positions of cuckoos. The mathematical formulation of reproduction and mutation to select the cluster head and the updated radius are listed as follows: (16) $X_{\text{update}}(i) = x(i?1) + ((O?1?) \times \text{Cos}(F_t))$ (17) $Y_{\text{update}}(n) = y(i?1) + ((O?1?) \times \text{Cos}(F_t))$. Based on the comparison between the fitness function with the probability of laying eggs defined in (18) serves the base for mutation and they described as

follows: (18) $C(m) = (1 - \frac{1}{M+1}) \frac{1}{1}$ (19) $X_{mut}(i) = x(i) + (C(m) \times (\text{Max}(x) - \text{Min}(x)))$ (20) $Y_{mut}(n) = y(n) + (C(m) \times (\text{Max}(y) - \text{Min}(y)))$ After

the mutation is over, the mean value of fitness function corresponds to the new coordinates is predicted. Then, check whether the computed values are greater than zero or not. If they are greater than zero, then changes in radius is allowed and cuckoos corresponds to feature vectors are moved towards that point. Otherwise, the changes in radius are prevented. Then, the average magnitude of the fitness function is estimated which serves as the base value for selected feature set (SF) and tested feature set (TS). The Algorithm 3 for PPCSO is listed

1. Download: Download high-res image (218KB)
2. Download: Download full-size image

Algorithm 3. Priority particle cuckoo search optimization.

7. LSTM-CNN classification

The model proposed in this paper isolates the foreground and background prior to feature extraction. Besides, the relevant feature selection through the PPCSO reduces the dimensionality of features. Hence, the labelling of facial expression is the final stage of this work. The features (SF) and tested features (TS) from PPCSO are passed to the LSTM-CNN as shown in Fig. 9. Initially, the labels are initialized as n and $L=1$. The features corresponds to the F1 are assigned as S. The maximum and the mean of selected features (SF) are computed and they can be regarded as M and N respectively. The limit of sub-divided intervals for the classification process lies in the ranges between $(1 < n < N)$. Then, the rules necessary to perform the classification process are extracted as follows. (21) $R = SF(M \times N) \times L$ The neighbor link parameter (τ) and the kernel function (K) are necessary for accurate classification (22) $\tau = SF \times TS(t)$ (23) $K = R \times \tau(t)$ The training feature set with the neighbor link and the kernel parameter for the mapping process is constructed by (24) $SF_i = K_i + \tau_i \times R \times \tau(i) + \tau_i$ The probability distribution on feature set for neighboring features to update the kernel function is computed as follows: (25) $\tau(t) = \frac{1}{n} \sum_{i=1}^n \frac{1}{N} \exp[-(\tau(t) - S_i)^2]$

1. Download: Download high-res image (332KB)
2. Download: Download full-size image

Fig. 9. LSTM-CNN classification.

Finally, the Point Kernel Classifier (PKC) checks whether the value of selected features is compared with the probability distribution for each column (t) ($S_t > \tau(t)$) defined in (25). The kernel function formulation for the class labels are listed as

follows: (26) $V_t(TS) = \frac{1}{n} \sum_{m=1}^M (SF_p, m \times TS_p, m)$ If the probability distribution function is greater than count of selected features S_t , then the corresponding labels ($C = L(\tau(t))$) are assigned to the images to indicate the expressions (anger, disgust, fear, happiness, sadness, and surprise).

8. Experiments

The proposed MAOP-DL is evaluated on two databases. The experimental details are shown and the comparative analysis is discussed in this section.

8.1. Databases

CK+ Database: The Cohn-Kanade database [9] contains the expressions of 100 university students with the age variations of 18 to 30. Among them, the 65% are female, 15% are African-American and 3% are either Asian or Latino. There are six emotions based on the prototype description are the subjects of this database. To validate the effectiveness of proposed work, image sequences from 96 subjects are selected. Fig. 10 shows some normalized samples with all expressions.

1. Download: Download high-res image (78KB)

2. Download: Download full-size image

Fig. 10. Example of six basic expressions from the Cohn+Kanade + database (anger, disgust, fear, happiness, sadness, and surprise).

****MMI Database**** : This database is the most challenging database [29] compared to CK+database. There are 30 students and research staff members with the age of 19 to 62 are included in this database. Among them, 44% are female with the background of European, Asian or South American ethnic background. Typical pictures of persons showing emotions can be seen in Fig. 11. There are 213 image sequences with the labels of six expressions are included in the database. To validate the proposed system, there are 205 images are selected. Table 1 Presents the abbreviations of Conventional learning methods used for Comparison.

1. Download: Download high-res image (164KB)
2. Download: Download full-size image

Fig. 11. Example images from the MMI. The emotions from left to right are: Anger, Disgust, Fear, Happiness, Sadness, Surprise.

Table 1. Abbreviations of Methods.

| Method | Description |
|--------|--|
| ADL | Patches selected by ADaboost are used |
| AFL | All the patches of whole Face are used |
| CPL | Common Patches are used |
| CSPL | Common and Specific Patches are used |

---|---

ADL| Patches selected by ADaboost are used

AFL| All the patches of whole Face are used

CPL| Common Patches are used

CSPL| Common and Specific Patches are used

8.2. Results comparisons

We investigate the performance of Proposed MOAP-DL over the existing single scale methods regarding the recognition rate and F1-measure as in Table 2 for CK+ database in this section. In existing methods, the CSPL provides the better F1 measures of 0.7440, 0.9134, 0.8432, 0.9462, 0.8619 and 0.9870 for the expressions of anger, disgust, fear, happiness sadness and surprise respectively. The recognition rate of CSPL [37] is 0.8989 which is also higher than the existing methods. But, the proper alignment and optimized texture features in proposed MAOP-DL increased the F1-measure to 0.9482, 0.9558, 0.9487, 0.8592, 0.8816 and 0.9440 respectively. Besides, the recognition rate also improved to 0.9617. The comparative analysis shows that the proposed MAOP-DL improves the F1-measure by 20.42(anger), 4.24(Disgust), 10.55(Fear),1.97(sadness) compared to CSPL respectively,however the expression of Happy and surprise failed to recognise accurately. The recognition rate for MAOP-DL also 6.28% higher than the CSPL method.

Table 2. Recognition Rate and F-1 measure analysis for CK+ database.

| Expression | AFL | ADL | CPL | CSPL | MOAP-DL |
|------------------|--------|--------|--------|--------|---------|
| Anger | 0.6407 | 0.6281 | 0.7144 | 0.7440 | 0.9482 |
| Disgust | 0.8782 | 0.8776 | 0.8927 | 0.9134 | 0.9558 |
| Fear | 0.8235 | 0.8206 | 0.8209 | 0.8432 | 0.9487 |
| Happiness | 0.9416 | 0.9381 | 0.9305 | 0.9462 | 0.8592 |
| Sadness | 0.8204 | 0.8346 | 0.8515 | 0.8619 | 0.8816 |
| Surprise | 0.9806 | 0.9791 | 0.9827 | 0.9870 | 0.9440 |
| Recognition Rate | 0.8694 | 0.8226 | 0.8842 | 0.8989 | 0.9617 |

---|---|---|---|---|---

Anger| 0.6407| 0.6281| 0.7144| 0.7440| 0.9482

Disgust| 0.8782| 0.8776| 0.8927| 0.9134| 0.9558

Fear| 0.8235| 0.8206| 0.8209| 0.8432| 0.9487

Happiness| 0.9416| 0.9381| 0.9305| 0.9462| 0.8592

Sadness| 0.8204| 0.8346| 0.8515| 0.8619| 0.8816

Surprise| 0.9806| 0.9791| 0.9827| 0.9870| 0.9440

Recognition Rate| 0.8694| 0.8226| 0.8842| 0.8989| 0.9617

Table 3 presents the comparative analysis of recognition rate analysis of proposed and the existing methods (sparse+A+T, sparse+A and conventional+A) [4] various expressions. In existing methods, the sparse+A+T provides the better recognition rate of 95.8, 97.9, 96.5, 98.2, 94.5 and 97% for the expressions of anger, disgust, fear, happiness sadness and surprise respectively. But, the proper alignment and optimized texture features in

proposed MAOP-DL increased the recognition rate to 98.6745, 98.8218, 98.9691, 98.6745, 98.5272 and 98.6745% respectively. The comparative analysis shows that the proposed MAOP-DL improves the recognition rate by 2.91, 0.92, 2.51, 0.48, 4.02 and 1.7% compared to sparse+A+T respectively.

Table 3. Recognition Rate analysis for MMI database.

Expression| Conventional+A| Sparse+A| Sparse+A+T| MOAP-DL

---|---|---|---|---

Anger| 92.2| 93.8| 95.8| 98.67
Disgust| 95.1| 97.1| 97.9| 98.82
Fear| 93.9| 96| 96.5| 98.96
Happiness| 97.5| 97.6| 98.2| 98.67
Sadness| 91.9| 92.3| 94.5| 98.52
Surprise| 94.5| 95.3| 97| 98.67

We compare the accuracy of recognition with the following methods to show the effectiveness of MAOP-DL: Graph-preserving Sparse NMF (GSNMF) [36], Common and Specific Patches (CSPL) [38] and Dual Sub-space NGE(DSNGE) [10] in Table 4.

Table 4. Recognition Accuracy Analysis for CK+ database.

Methods| CK+

---|---

GSNMF [36]| 72.17
CSPL [38]| 89.9
DSNGE [10]| 94.82
Ours| 96.17

In existing methods, the DSNGE provides better performance (94.92%) than the existing methods. The foreground extraction prior to the pattern extraction and feature selection and the enhanced STM models with the multi-angular patterns in proposed MAOP-DL further improves the recognition accuracy to 96.17%. The comparison between the MAOP-DL with the DSNGE shows that the MAOP-DL provided the 1.3% improvement compared to DSNGE models respectively.

In existing methods, the CNN provides better performance (97.81%) than the existing methods. The foreground extraction prior to the pattern extraction and feature selection and the enhanced STM models with the multi-angular patterns in proposed MAOP-DL further improves the recognition accuracy to 98.72% as shown in Table 5. The comparison between the MAOP-DL with the CNN shows that the MAOP-DL provided the 0.91% improvement compared to CNN models respectively.

Table 5. Recognition Accuracy Analysis for MMI database.

Methods| MMI

---|---

CSPL [38]| 73.53
3D-CNN [3]| 95
CNN [14]| 97.81
Ours| 98.72

Fig. 12(a) and (b) shows the ROC performance analysis of proposed MAOP-DL with the existing SVM for CK+ database and MMI database respectively. From the Fig. 12(a) and (b), it is observed that the proposed MAOP-DL provides the high true positive rate for small values of false positive rate due to the angle-based texture pattern and optimal selected features compared to SVM models respectively for CK+ and MMI database.

- 1. Download: Download high-res image (607KB)
- 2. Download: Download full-size image

Fig. 12. ROC analysis of (a) CK+ database and (b) MMI database.

9\ Conclusion

This paper proposed the MAOP-DL for the clear image analysis and effective

learning of facial expressions. The selection of key point features based on intensity difference analysis, relevant feature selection and the neural network based classification carried out in proposed MAOP-DL enhanced the recognition performance compared to the existing methods. The effectiveness of proposed MAOP-DL is validated over the number of state-of-art methods on CK+ and MMI database with the parameters of recognition rate and F1- measure. The novel feature extraction based on the multi angle and the noise removal through the EBBS contributed towards the illumination variation handling and the matching accuracy effectively. The major limitations of proposed work are less performance in involuntary expression handling, low intensity and short duration expressions are not handled, Spot and recognition of muscle variations, due to these limitations observed in short duration FER analysis, Future work should focus on the analysis of microexpression (involuntary expression with low intensity and short duration) by extending the multi-angle-based feature descriptors to spot and recognize it.

Acknowledgments

This work is supported by the National Key Research and Development Program of China (2016YFB1001005), the National Natural Science Foundation of China (Grant No. 61473290, Grant No. 61673375), the National High Technology Research and Development Program of China (863 Program) under Grant 2015AA042307, and the Projects of Chinese Academy of Science (Grant No. QYZDB-SSW-JSC006, Grant No. 173211KYSB20160008).

Special issue articles Recommended articles

References

1. [1]
E.I. Barakova, R. Gorbunov, M. Rauterberg
Automatic interpretation of affective facial expressions in the context of interpersonal interaction
IEEE Trans. Hum. Mach. Syst., 45 (4) (2015), pp. 409-418
[View in Scopus](#)[Google Scholar](#)
2. [2]
P.R. Borude, S. Gandhe, P. Dhulekar, G. Phade
Identification and tracking of facial features
Procedia Comput. Sci., 49 (2015), pp. 2-10
[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)
3. [3]
Y.-H. Byeon, K.-C. Kwak
Facial expression recognition using 3D convolutional neural network
Int. J. Adv. Comput. Sci. Appl., 5 (12) (2014)
[Google Scholar](#)
4. [4]
Y. Guo, G. Zhao, M. Pietikäinen
Dynamic facial expression recognition with atlas construction and sparse representation
IEEE Trans. Image Process., 25 (5) (2016), pp. 1977-1992
[View in Scopus](#)[Google Scholar](#)
5. [5]
S. Hadfield, R. Bowden
Hollywood 3d: recognizing actions in 3d natural scenes
Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (2013), pp. 3398-3405
[Crossref](#)[View in Scopus](#)[Google Scholar](#)
6. [6]

S. Happy, A. Routray

Automatic facial expression recognition using features of salient facial patches

IEEE Trans. Affective Comput., 6 (1) (2015), pp. 1-12

[View in Scopus](#)[Google Scholar](#)

7. [7]

A. Iosifidis, A. Tefas, I. Pitas

Graph embedded extreme learning machine

IEEE Trans. Cybern., 46 (1) (2016), pp. 311-324

[View in Scopus](#)[Google Scholar](#)

8. [8]

M. Jampour, V. Lepetit, T. Mauthner, H. Bischof

Pose-specific non-linear mappings in feature space towards multiview facial expression recognition

Image Vis. Comput., 58 (2017), pp. 38-46

[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)

9. [9]

T. Kanade, J.F. Cohn, Y. Tian

Comprehensive database for facial expression analysis

Automatic Face and Gesture Recognition, 2000. Proceedings. Fourth IEEE International Conference on, IEEE (2000), pp. 46-53

[View in Scopus](#)[Google Scholar](#)

10. [10]

H.-W. Kung, Y.-H. Tu, C.-T. Hsu

Dual subspace nonnegative graph embedding for identity-independent expression recognition

IEEE Trans. Inf. Forensics Secur., 10 (3) (2015), pp. 626-639

[Crossref](#)[View in Scopus](#)[Google Scholar](#)

11. [11]

K. Li, F. Xu, J. Wang, Q. Dai, Y. Liu

A data-driven approach for facial expression synthesis in video

Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on, IEEE (2012), pp. 57-64

[View in Scopus](#)[Google Scholar](#)

12. [12]

M. Liu, S. Shan, R. Wang, X. Chen

Learning expressionlets on spatio-temporal manifold for dynamic facial expression recognition

Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (2014), pp. 1749-1756

[View in Scopus](#)[Google Scholar](#)

13. [13]

A.T. Lopes, E. de Aguiar, A.F. De Souza, T. Oliveira-Santos

Facial expression recognition with convolutional neural networks: coping with few data and the training sample order

Pattern Recognit., 61 (2017), pp. 610-628

[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)

14. [14]

A.T. Lopes, E. de Aguiar, T. Oliveira-Santos

A facial expression recognition system using convolutional networks

Graphics, Patterns and Images (SIBGRAPI), 2015 28th SIBGRAPI Conference on, IEEE (2015), pp. 273-280

[Crossref](#)[View in Scopus](#)[Google Scholar](#)

15. [15]

X. Ma, H. Song, X. Qian

Robust framework of single-frame face superresolution across head pose, facial expression, and illumination variations

IEEE Trans. Hum. Mach. Syst., 45 (2) (2015), pp. 238-250

[View in Scopus](#)[Google Scholar](#)

16. [16]

K. Niinuma, H. Han, A.K. Jain

Automatic multi-view face recognition via 3d model based pose regularization

Biometrics: Theory, Applications and Systems (BTAS), 2013 IEEE Sixth

International Conference on, IEEE (2013), pp. 1-8

[Crossref](#)[Google Scholar](#)

17. [17]

S.-K. Oh, S.-H. Yoo, W. Pedrycz

Design of face recognition algorithm using PCA-LDA combined for hybrid data pre-processing and polynomial-based RBF neural networks: design and its application

Expert Syst. Appl., 40 (5) (2013), pp. 1451-1466

[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)

18. [18]

X. Peng, Q. Hu, J. Huang, D.N. Metaxas, Track facial points in unconstrained

videos, arXiv:1609.02825 (2016).

[Google Scholar](#)

19. [19]

H. Qayyum, M. Majid, S.M. Anwar, B. Khan

Facial expression recognition using stationary wavelet transform features

Math. Prob. Eng., 2017 (2017)

[Google Scholar](#)

20. [20]

O. Rudovic, V. Pavlovic, M. Pantic

Context-sensitive dynamic ordinal regression for intensity estimation of facial action units

IEEE Trans. Pattern Anal. Mach. Intell., 37 (5) (2015), pp. 944-958

[View in Scopus](#)[Google Scholar](#)

21. [21]

G. Sandbach, S. Zafeiriou, M. Pantic, D. Rueckert

Recognition of 3D facial expression dynamics

Image Vis. Comput., 30 (10) (2012), pp. 762-773

[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)

22. [22]

E. Sariyanidi, V. Dabov, S.C. Tek, B. Tunc, M. Gökmen

Local zernike moments: a new representation for face recognition

2012 19th IEEE International Conference on Image Processing, IEEE (2012), pp.

585-588

[Crossref](#)[View in Scopus](#)[Google Scholar](#)

23. [23]

E. Sariyanidi, H. Gunes, A. Cavallaro

Automatic analysis of facial affect: a survey of registration, representation, and recognition

IEEE Trans. Pattern Anal. Mach. Intell., 37 (6) (2015), pp. 1113-1133

[View in Scopus](#)[Google Scholar](#)

24. [24]

T. Senechal, V. Rapp, H. Salam, R. Segulier, K. Bailly, L. Prevost

Facial action recognition combining heterogeneous features via multikernel learning

IEEE Trans. Syst. Man, Cybern. Part B (Cybern.), 42 (4) (2012), pp. 993-1005

[CrossrefView in ScopusGoogle Scholar](#)

25. [25]

C. Shan

Smile detection by boosting pixel differences

IEEE Trans. Image Process., 21 (1) (2012), pp. 431-436

[View in ScopusGoogle Scholar](#)

26. [26]

C. Shan

Smile detection by boosting pixel differences

IEEE transactions on image processing, 21 (1) (2012), pp. 431-436

[View in ScopusGoogle Scholar](#)

27. [27]

M.H. Siddiqi, R. Ali, A.M. Khan, Y.-T. Park, S. Lee

Human facial expression recognition using stepwise linear discriminant analysis and hidden conditional random fields

IEEE Trans. Image Process., 24 (4) (2015), pp. 1386-1398

[View in ScopusGoogle Scholar](#)

28. [28]

P. Vageeswaran, K. Mitra, R. Chellappa

Blur and illumination robust face recognition via set-theoretic characterization

IEEE Trans. Image Process., 22 (4) (2013), pp. 1362-1372

[View in ScopusGoogle Scholar](#)

29. [29]

M. Valstar, M. Pantic

Induced disgust, happiness and surprise: an addition to the MMI facial expression database

Proc. 3rd Intern. Workshop on EMOTION (satellite of LREC): Corpora for Research on Emotion and Affect (2010), p. 65

[Google Scholar](#)

30. [30]

L. Wang, K. Wang, R. Li

Unsupervised feature selection based on spectral regression from manifold learning for facial expression recognition

IET Comput. Vis., 9 (5) (2015), pp. 655-662

[CrossrefView in ScopusGoogle Scholar](#)

31. [31]

B. Yao, L. Fei-Fei

Recognizing human-object interactions in still images by modeling the mutual context of objects and human poses

IEEE Trans. Pattern Anal. Mach. Intell., 34 (9) (2012), pp. 1691-1703

[View in ScopusGoogle Scholar](#)

32. [32]

X. Yu, J. Yang, L. Luo, W. Li, J. Brandt, D. Metaxas

Customized expression recognition for performance-driven cutout character animation

Applications of Computer Vision (WACV), 2016 IEEE Winter Conference on, IEEE (2016), pp. 1-9

[Google Scholar](#)

33. [33]

S. Zhang, J. Huang, H. Li, D.N. Metaxas

Automatic image annotation and retrieval using group sparsity

IEEE Trans. Syst. Man, Cybern. Part B (Cybern.), 42 (3) (2012), pp. 838-849

[View in Scopus](#)[Google Scholar](#)

34. [34]

S. Zhang, Y. Zhan, M. Dewan, J. Huang, D.N. Metaxas, X.S. Zhou
Towards robust and effective shape modeling: sparse shape composition
Med. Image Anal., 16 (1) (2012), pp. 265-277

[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)

35. [35]

X. Zhao, E. DellandréA, J. Zou, L. Chen
A unified probabilistic framework for automatic 3D facial expression analysis
based on a Bayesian belief inference and statistical feature models
Image Vis. Comput., 31 (3) (2013), pp. 231-245

[View PDF](#)[View article](#)[View in Scopus](#)[Google Scholar](#)

36. [36]

R. Zhi, M. Flierl, Q. Ruan, W.B. Kleijn
Graph-preserving sparse nonnegative matrix factorization with application to
facial expression recognition
IEEE Trans. Syst. Man, Cybern. Part B (Cybern.), 41 (1) (2011), pp. 38-52

[View in Scopus](#)[Google Scholar](#)

37. [37]

L. Zhong, Q. Liu, P. Yang, J. Huang, D.N. Metaxas
Learning multiscale active facial patches for expression analysis
IEEE Trans. Cybern., 45 (8) (2015), pp. 1499-1510

[View in Scopus](#)[Google Scholar](#)

38. [38]

L. Zhong, Q. Liu, P. Yang, B. Liu, J. Huang, D.N. Metaxas
Learning active facial patches for expression analysis
Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on, IEEE
(2012), pp. 2562-2569

[View in Scopus](#)[Google Scholar](#)

Cited by (70)

* ### Emotion recognition from unimodal to multimodal analysis: A review
2023, Information Fusion

[Show abstract](#)

The omnipresence of numerous information sources in our daily life brings up new alternatives for emotion recognition in several domains including e-health, e-learning, robotics, and e-commerce. Due to the variety of data, the research area of multimodal machine learning poses special problems for computer scientists; how did the field of emotion recognition progress in each modality and what are the most common strategies for recognizing emotions? What part does deep learning play in this? What is multimodality? How did it progress? What are the methods of information fusion? What are the most used datasets in each modality and in multimodal recognition? We can understand and compare the various methods by answering these questions.

* ### FMD-Yolo: An efficient face mask detection method for COVID-19 prevention and control in public
2022, Image and Vision Computing

Citation Excerpt :

Besides, people are also suggested to keep distances in public places and take routine temperature screening [1], all of which are convenient and effective methods for reducing transmission of COVID-19. In the past few years, with the rapid development of deep learning, computer vision (CV) has been widely used in facial expression recognition [12,13,41], disease diagnosis [42] and so on. At the same time, CV techniques have boomed and many classical object detection methods have emerged, including one-stage, two-stage and other anchor-free algorithms like Faster RCNN [26], RetinaNet [20], YOLOv3 [29],

YOLOv4 [3], CornerNet [17], FCOS [34], etc.

Show abstract

Coronavirus disease 2019 (COVID-19) is a world-wide epidemic and efficient prevention and control of this disease has become the focus of global scientific communities. In this paper, a novel face mask detection framework FMD-Yolo is proposed to monitor whether people wear masks in a right way in public, which is an effective way to block the virus transmission. In particular, the feature extractor employs Im-Res2Net-101 which combines Res2Net module and deep residual network, where utilization of hierarchical convolutional structure, deformable convolution and non-local mechanisms enables thorough information extraction from the input. Afterwards, an enhanced path aggregation network En-PAN is applied for feature fusion, where high-level semantic information and low-level details are sufficiently merged so that the model robustness and generalization ability can be enhanced. Moreover, localization loss is designed and adopted in model training phase, and Matrix NMS method is used in the inference stage to improve the detection efficiency and accuracy. Benchmark evaluation is performed on two public databases with the results compared with other eight state-of-the-art detection algorithms. At $\text{IoU} = 0.5$ level, proposed FMD-Yolo has achieved the best precision AP_{50} of 92.0% and 88.4% on the two datasets, and AP_{75} at $\text{IoU} = 0.75$ has improved 5.5% and 3.9% respectively compared with the second one, which demonstrates the superiority of FMD-Yolo in face mask detection with both theoretical values and practical significance.

* ### Hybrid deep neural networks for face emotion recognition

2018, Pattern Recognition Letters

Citation Excerpt :

Separating these transient relations have been examined utilizing customary techniques before. Cases of these endeavors are Concealed Markov Models [13,14,47,48] (which join the data and then apply division on recordings), Spatio Temporal Shrouded Markov Models by combing S-HMM and T-HMM [15], Dynamic Bayesian Networks? [16] is related to multi-tactile data combination paradigm, Bayesian transient models to catch the dynamic outward appearance progress, and Conditional Irregular Fields (CRFs) [17,18] and their augmentations. Recently, "Convolutional Neural Networks" (CNN) has turned into the most mainstream approach in the deep learning techniques.

Show abstract

Deep Neural Networks (DNNs) outperform traditional models in numerous optical recognition missions containing Facial Expression Recognition (FER) which is an imperative process in next-generation Human-Machine Interaction (HMI) for clinical practice and behavioral description. Existing FER methods do not have high accuracy and are not sufficient practical in real-time applications. This work proposes a Hybrid Convolution-Recurrent Neural Network method for FER in Images. The proposed network architecture consists of Convolution layers followed by Recurrent Neural Network (RNN) which the combined model extracts the relations within facial images and by using the recurrent network the temporal dependencies which exist in the images can be considered during the classification. The proposed hybrid model is evaluated based on two public datasets and Promising experimental results have been obtained as compared to the state-of-the-art methods.

* ### Facial Emotion Recognition Using Conventional Machine Learning and Deep Learning Methods: Current Achievements, Analysis and Remaining Challenges

2022, Information (Switzerland)

* ### Deep Facial Expression Recognition: A Survey

2022, IEEE Transactions on Affective Computing

* ### A Survey of AI-Based Facial Emotion Recognition: Features, ML DL Techniques, Age-Wise Datasets and Future Directions

2021, IEEE Access

[View all citing articles on Scopus](#)

[View Abstract](#)

© 2017 Published by Elsevier B.V.

Part of special issue

Special Issue on Intelligent Pattern Recognition Applications for Computer

Vision and Biomedical Signal Processing

[View special issue](#)

Recommended articles

* ### A brief Review of Deep Learning Based Approaches for Facial Expression and Gesture Recognition Based on Visual Information

Materials Today: Proceedings, Volume 29, Part 2, 2020, pp. 462-469

Samta Jain Goyal, ?, Rajesh Singh Jadon

[View PDF](#)

* ### Kernel-based convolution expansion for facial expression recognition

Pattern Recognition Letters, Volume 160, 2022, pp. 128-134

M. Amine Mahmoudi, ?, Hedi Tabia

[View PDF](#)

* ### Facial expression recognition with Convolutional Neural Networks: Coping with few data and the training sample order

Pattern Recognition, Volume 61, 2017, pp. 610-628

André Teixeira Lopes, ?, Thiago Oliveira-Santos

[View PDF](#)

* ### Facial expression recognition via learning deep sparse autoencoders

Neurocomputing, Volume 273, 2018, pp. 643-649

Nianyin Zeng, ?, Abdullah M. Dobaie

[View PDF](#)

* ### Landmark guidance independent spatio-channel attention and complementary context information based facial expression recognition

Pattern Recognition Letters, Volume 145, 2021, pp. 58-66

Darshan Gera, S Balasubramanian

[View PDF](#)

* ### Predicting the citations of scholarly paper

Journal of Informetrics, Volume 13, Issue 1, 2019, pp. 407-418

Xiaomei Bai, ?, Ivan Lee

[View PDF](#)

[Show 3 more articles](#)

Article Metrics

Citations

* Citation Indexes: 69

Captures

* Readers: 69

[View details](#)

* [About ScienceDirect](#)

* [Remote access](#)

* [Shopping cart](#)

* [Advertise](#)

* [Contact and support](#)

* [Terms and conditions](#)

* [Privacy policy](#)

[Cookies are used by this site. Cookie Settings](#)

All content on this site: Copyright © 2024 Elsevier B.V., its licensors, and

contributors. All rights are reserved, including those for text and data mining, AI training, and similar technologies. For all open access content, the Creative Commons licensing terms apply.

Cookie Preference Center

We use cookies which are necessary to make our site work. We may also use additional cookies to analyse, improve and personalise our content and your digital experience. For more information, see our Cookie Policy and the list of Google Ad-Tech Vendors.

You may choose not to allow some types of cookies. However, blocking some types may impact your experience of our site and the services we are able to offer. See the different category headings below to find out more or change your settings.

Allow all

Manage Consent Preferences

Strictly Necessary Cookies

Always active

These cookies are necessary for the website to function and cannot be switched off in our systems. They are usually only set in response to actions made by you which amount to a request for services, such as setting your privacy preferences, logging in or filling in forms. You can set your browser to block or alert you about these cookies, but some parts of the site will not then work. These cookies do not store any personally identifiable information.

Cookie Details List?

Functional Cookies

Functional Cookies

These cookies enable the website to provide enhanced functionality and personalisation. They may be set by us or by third party providers whose services we have added to our pages. If you do not allow these cookies then some or all of these services may not function properly.

Cookie Details List?

Performance Cookies

Performance Cookies

These cookies allow us to count visits and traffic sources so we can measure and improve the performance of our site. They help us to know which pages are the most and least popular and see how visitors move around the site.

Cookie Details List?

Targeting Cookies

Targeting Cookies

These cookies may be set through our site by our advertising partners. They may be used by those companies to build a profile of your interests and show you relevant adverts on other sites. If you do not allow these cookies, you will experience less targeted advertising.

Cookie Details List?

Back Button

Cookie List

Search Icon

Filter Icon

Clear

checkbox label label

Apply Cancel

Consent Leg.Interest

checkbox label label

checkbox label label

checkbox label label

Confirm my choices