

Guidance on how to use Tobacco Scan Data:

1. Call MerchantStack's endpoint to GET the registration link for the merchant
2. Open the registration link in the browser where the merchant has to register
3. After successfully registration the merchant has be able to open the Tobacco Scan Data app
4. The next step requires setting up Tobacco Scan Data settings
5. Call the endpoint for sending orders from the Tobacco Scan Data API
6. Call the endpoint for updating the discount setup to the Scandata Discount Setup API
7. Call the endpoint for updating the subscription to the Scan Data Subscription API

IMPORTANT: This document provides testing data ONLY for the TEST environment. When you feel satisfied with this implementation – we will provide the PRODUCTION environment.

MerchantStack Third-party API documentation

Overview

This endpoint generates a registration link for a third-party merchant. It sends a GET request with information about the POS software provider and the merchant and returns a registration link with a one time token.

Endpoint Summary:

Method:	URL
GET:	https://api-sandbox.merchantstack.net/api/v1/third-party/{merchantId}/registration-link

Request Parameters:

<i>Parameter</i>	<i>Type</i>	<i>Required</i>	<i>Description</i>
------------------	-------------	-----------------	--------------------

merchantId	String	Yes	Unique merchant identifier used by POS software provider
------------	--------	-----	--

Headers:

<i>Header Name</i>	<i>Required</i>	<i>Description</i>
x-client-id	Yes	Client id provided by MerchantStack to verify POS software provider
x-client-secret	Yes	Client secret provided by MerchantStack to verify POS software provider

Sample Response:

```
{
  "url": "https://sandbox.merchantstack.net/auth/third-party/register?token=MwCKXOWKQFOPc4VImGcmL3Pc7wGn3lEMQzoCjnznRGRUVmAkriCwx iYKcLYpyJmK"
}
```

Fields description:

<i>Field</i>	<i>Type</i>	<i>Required</i>	<i>Description</i>
url	String	Yes	Registration link for the merchant

token	String	Yes	One time token, which grants access to registration in MerchantStack for the merchant
-------	--------	-----	---

Scandata Order API Documentation

Endpoint Summary:

Method:	URL
GET	https://ou0pldf2p4.execute-api.us-west-2.amazonaws.com/v1/orders/sandbox

Headers:

<i>Header Name</i>	<i>Required</i>	<i>Description</i>
X-SECRET	Yes	Client secret provided by CSIWorks to verify the POS software provider

Example of order body POST:

```
{
  "id": "order-12345",
  "merchantId": "merchant-67890",
  "createdTime": "2025-06-20T17:50:30.678Z",
  "customerId": "customer-11223",
  "customerPhoneNumber": "+1234567890",
  "deviceId": "device-99887",
}
```

```
"lineItems": [  
  {  
    "id": "lineitem-001",  
    "itemId": "item-abc-123",  
    "categories": [  
      {  
        "id": "category-001",  
        "name": "Tobacco"  
      },  
      {  
        "id": "category-002",  
        "name": "Cigarettes"  
      }  
    ],  
    "manufacturer": "Manufacturer Inc.",  
    "sku": "CC123456",  
    "productCode": "PCC-2025",  
    "name": "Tobacco item",  
    "uom": "pack",  
    "innerQuantity": 1,  
    "price": 250,  
    "buyDownPrice": 50,  
    "buyDownDescription": "Manufacturer promotional discount" ,  
    "discounts": [  
      {  
        "id": "discount-001",  
        "discountId": "loyalty-001",  
        "name": "Loyalty Discount",  
        "amount": 100,  
        "discountCode": "LOYALTY2025",  
        "discountType": "LOYALTY_PROGRAM",  
        "minItemsCountRequired": 1  
      },  
      {  
        "id": "discount-002",  
        "discountId": "",  
        "name": "Buy 1 Get 2$ Off",  
        "amount": 200,  
        "discountCode": "MULTIPACK2025",  
        "discountType": "MULTI_PACK",  
        "minItemsCountRequired": 1  
      }  
    ]  
  }  
]
```

```
]
}
```

Fields description:

Order:

Description:

Represents a merchant's order, including line items, discounts and customer-related information.

<i>Field</i>	<i>Type</i>	<i>Description</i>	<i>Required</i>
id	string	Unique identifier for the order	yes
merchantId	string	Identifier of the merchant associated with the order.	yes
createdTime	string (formatted as ISO 8601)	Represents the date and time when the order was created	yes
customerId	string	Unique identifier of the customer. (required if any line item contains a LOYALTY_PROGRAM discount)	conditional
customerPhoneNumber	string	Customer's phone number. (required if any line item contains a LOYALTY_PROGRAM discount)	conditional

deviceId	string	Identifier of the device where the order was created	no
lineItems	array of LineItem	List of line items included in the order	yes

LineItem:

Description:

Represents a single item within an order, including product information and associated discounts.

<i>Field</i>	<i>Type</i>	<i>Description</i>	<i>Required</i>
id	string	Unique identifier for the line item	yes
itemId	string	Identifier of the related product/item	yes
categories	array of Category	List of categories the item belongs to	yes
manufacturer	string	Manufacturer name of the item	yes
sku	string	Stock Keeping Unit for the item	yes
productCode	string	Product code assigned to the item	yes

name	string	Name of the item	yes
uom	string	Unit of measurement (e.g., pack, carton)	yes
innerQuantity	integer	Quantity inside a unit (e.g., 12)	yes
discounts	array of Discount	Discounts applied to this line item	no
price	integer (long)	Base price of the item (in cents e.g., 250)	yes
buyDownPrice	integer (long)	Buy-down amount (in cents e.g., 150)	no
buyDownDescription	string	Description of the buy-down promotion	no

Category:

Description:

Represents a category that can be assigned to a product.

<i>Field</i>	<i>Type</i>	<i>Description</i>	<i>Required</i>
id	string	Unique identifier of the category	yes

name	string	Name of the category.	yes
------	--------	-----------------------	-----

Discount:

Description:

Represents a discount applied to a line item.

<i>Field</i>	<i>Type</i>	<i>Description</i>	<i>Required</i>
id	string	Unique identifier of the discount record.	yes
discountId	string	Identifier of the related discount	yes
name	string	Name of the discount.	yes
amount	integer (long)	Amount of the discount (in cents e.g., 100)	yes
discountCode	string	Code associated with the discount (required for LOYALTY_PROGRAM discount or COUPON)	conditional
discountType	string (enum)	Type of discount. Must be one of: - LOYALTY_PROGRAM - MULTI_PACK - MANUFACTURER_FUNDED	yes

		• RETAILER_FUNDED • COUPON	
minItemsCountRequired	integer	Minimum number of items required to apply the discount.	yes

Requirements:

General rules:

- Only **Tobacco** items and categories are allowed.
- **Only paid orders are accepted.**

Discount type allowed values:

- LOYALTY_PROGRAM
- MULTI_PACK
- MANUFACTURER_FUNDED
- RETAILER_FUNDED
- COUPON

Discount rules:

- Max 1 MULTI_PACK discount per LineItem.
 - Max 1 RETAILER_FUNDED discount per LineItem.
 - Max 3 MANUFACTURER_FUNDED discounts per LineItem.
 - customerId and customerPhoneNumber must be provided if there is any LOYALTY_PROGRAM discount.
-

Error validation message examples:

If X-SECRET header is missing in the request:

Error status = 400 (Bad request), Message = "Missing X-Secret header"

Model	Status	Request fields	Response error message
-------	--------	----------------	------------------------

Order	400 (Bad request)	"merchantId": "" "id": "" "createdTime": 123532425	"Missing required field: merchantId" "Missing required field: id" "Invalid type for field: createdTime"
Line Item	400 (Bad request)	"uom": "" "productCode": "" "uom": 1 "innerQuantity": "price": "buyDownPrice":	"Missing required field: uom" "Missing required field: productCode" "Invalid type for field: uom" "Invalid JSON"
Category	400 (Bad request)	"id": ""	"Missing required field: id"
Discount	400 (Bad request)	"amount": null "amount": "123" "amount":	"Missing required field: amount" "Invalid type for field: amount" "Invalid JSON"

Conditional errors validation message examples:

Model	Status	Request fields	Response error message
Discount	400 (Bad request)	"discountCode": "" "discountType": "LOYALTY_PROGRAM" "amount":	"Missing required field: discountCode" "Invalid JSON"
Order & Discount	400 (Bad request)	"customerPhoneNumber": "" "discountType": "LOYALTY_PROGRAM" "minItemsCountRequired":	"customerId and customerPhoneNumber must be provided if there is any LOYALTY_PROGRAM discount" "Invalid JSON"
Discount	400 (Bad request)	"discountCode": "" "discountType": "COUPON" "amount":	"Missing required field: discountCode" "Invalid JSON"
Discount	400 (Bad request)	"discounts": [{ "id": "discount-001", "discountType": "MULTI_PACK" }, { "id": "discount-002", "discountType": "MULTI_PACK" }]	"Too many MULTI_PACK discounts in item lineitem11. Max 1 MULTI_PACK discount per LineItem"

Notes:

- Report generation starts every Friday for the current week
- IF you want to see an example of report – you can set up dates of a previous week in the API Call and then click “Resend file” on the “Reports” page on the Web. (The report will be ready in 5 minutes)

Scan Data Subscription API

The system supports independent merchant billing if you choose to manage billing on your side.

Overview

This endpoint updates the Scan Data subscription configuration for a specific merchant. It allows the POS provider to set the subscription ID, subscription type, app status, and, if applicable, the subscription amount when merchant billing is handled independently.

Endpoint Summary:

Method:	URL
PUT	https://api-sandbox.merchantstack.net/api/v1/third-party/{merchantId}/scandata-subscription

Request Parameters:

<i>Parameters</i>	<i>Type</i>	<i>Required</i>	<i>Description</i>
merchantId	string	Yes	The merchant identifier

Headers:

<i>Header</i>	<i>Required</i>	<i>Description</i>
x-client-id	Yes	Client ID provided by MerchantStack to verify POS software provider
x-client-secret	Yes	Client secret provided by

		MerchantStack to verify POS software provider
--	--	---

Example of subscription body PUT:

```
{
  "subscriptionId": "sub-00001",
  "subscriptionType": "FULL",
  "appStatus": "ACTIVE",
  "subscriptionAmount": 1500
}
```

Fields description

Field	Type	Required	Description
subscriptionId	string	Yes	Unique identifier of the subscription
subscriptionType	string	Yes	Type of scandata subscription (see values below)
appStatus	string	Yes	Current status of the app (see values below)
subscriptionAmount	number (long)	No	Subscription amount in cents

Requirements:

SubscriptionType allowed values:

- ALTRIA_ONLY
- REYNOLDS_ONLY
- ITG_ONLY
- FULL

AppStatus allowed values:

- ACTIVE
- INACTIVE
- UNINSTALLED

Response

<i>Status Code</i>	<i>Description</i>
200 OK	Subscription updated successfully. Empty body.

Guidance of how to use Discount Setup:

1. Register all discount setups from your POS system using this API before sending any orders.
2. Use the registered discountId values in the Discount objects when sending orders via the Scandata Order API.
3. For LOYALTY_PROGRAM discount type, ScanData will configure the required Loyalty Codes on its side based on the registered setup.
4. Reports generated by ScanData include only discounts registered through this API.

Scandata Discount Setup API

Overview

This API allows POS software providers to register and manage discount configurations from their POS system that should be included in tobacco ScanData reports submitted to manufacturers (Altria, Reynolds, ITG).

Before sending orders via the ScanData Order API, the POS software provider must register all discount setups configured in their POS system that they wish to include in the reports.

1. Save Discount Setup Batch

Overview

Creates or replaces a batch of ScanData discount setups for a merchant in a single request.

Endpoint Summary:

Method	URL
POST	https://api-sandbox.merchantstack.net/api/v1/third-party/{merchantId}/scandata-discount/batch

Request Parameters:

Parameter	Type	Required	Description
merchantId	string	Yes	Unique merchant identifier used by POS software provider

Headers:

Header Name	Required	Description
x-client-id	Yes	Client ID provided by MerchantStack to verify POS software provider
x-client-secret	Yes	Client secret provided by MerchantStack to verify POS software provider

Example of discounts body POST:

```
[  
  {  
    "discountId": "loyalty-001",  
    "name": "Loyalty Reward",  
    "amount": 50,  
    "discountType": "LOYALTY_PROGRAM",  
    "minItemsCountRequired": 3,  
    "manufacturer": "ALTRIA"  
  },  
  {  
    "discountId": "multipack-001",
```

```
"name": "Buy 2 Save $1",  
"amount": 100,  
"discountType": "MULTI_PACK",  
"minItemsCountRequired": 2,  
"manufacturer": "REYNOLDS"  
}  
]
```

Fields description:

Field	Type	Required	Description
discountId	string	Yes	Unique identifier of the discount. Must match the discountId field in the Discount object of the Scandata Order API.
name	string	Yes	Display name of the discount
amount	integer (long)	Yes	Discount amount in cents
discountType	string (enum)	Yes	Type of discount (see allowed values below)

minItemsCountRequired	integer	Yes	Minimum number of items required to apply the discount
manufacturer	string (enum)	Yes	Manufacturer the discount applies to (see allowed values below)

Requirements:

Discount type allowed values:

- LOYALTY_PROGRAM
- MULTI_PACK
- MANUFACTURER_FUNDED
- RETAILER_FUNDED

Manufacturer allowed values:

- ALTRIA
- REYNOLDS

Response

Status Code Description

200 OK

Batch saved successfully. Empty body.

2. Save or Update Discount Setup

Overview

Creates or updates a single scandata discount setup for a merchant.

Endpoint Summary

Method	URL
PUT	https://api-sandbox.merchantstack.net/api/v1/third-party/{merchantId}/scandata-discount

Request Parameters:

Parameter	Type	Required	Description
merchantId	string	Yes	Unique merchant identifier used by POS software provider

Headers:

Header Name	Required	Description
x-client-id	Yes	Client ID provided by MerchantStack to verify POS software provider
x-client-secret	Yes	Client secret provided by MerchantStack to verify POS software provider

Example of discount body PUT:

```
{  
  "discountId": "loyalty-001",  
  "name": "Loyalty Reward",  
  "amount": 50,
```

```

"discountType": "LOYALTY_PROGRAM",

"minItemsCountRequired": 3,

"manufacturer": "ALTRIA"
}

```

Fields description:

Field	Type	Required	Description
discountId	string	Yes	Unique identifier of the discount. Must match the discountId field in the Discount object of the Scandata Order API.
name	string	Yes	Display name of the discount
amount	integer (long)	Yes	Discount amount in cents
discountType	string (enum)	Yes	Type of discount (see allowed values below)
minItemsCountRequired	integer	Yes	Minimum number of items required to apply the discount
manufacturer	string (enum)	Yes	Manufacturer the discount applies to (see allowed values below)

Requirements:

Discount type allowed values:

- LOYALTY_PROGRAM
- MULTI_PACK
- MANUFACTURER_FUNDED
- RETAILER_FUNDED

Manufacturer allowed values:

- ALTRIA
- REYNOLDS

Response

Status Code	Description
200 OK	Discount setup saved/updated successfully. Empty body.

3. Delete Discount Setup

Overview

Deletes a ScanData discount setup for a merchant.

Endpoint Summary:

Method	URL
DELETE	https://api-sandbox.merchantstack.net/api/v1/third-party/{merchantId}/scandata-discount/{discountId}

Request Parameters:

Parameter	Type	Required	Description
merchantId	string	Yes	Unique merchant identifier used by POS software provider
discountId	string	Yes	Identifier of the discount setup to delete

Headers:

Header Name	Required	Description
x-client-id	Yes	Client ID provided by MerchantStack to verify POS software provider
x-client-secret	Yes	Client secret provided by MerchantStack to verify POS software provider

Response

Status Code

Description

204 No Content

Discount setup deleted successfully. Empty body.