

000 054
 001 055
 002 056
 003 057
 004 058
 005 059
 006 060
 007 061
 008 062
 009 063
 010 064
 011 065
 012 066
 013 067
 014 068
 015 069
 016 070
 017 071
 018 072
 019 073
 020 074
 021 075
 022 076
 023 077
 024 078
 025 079
 026 080
 027 081
 028 082
 029 083
 030 084
 031 085
 032 086
 033 087
 034 088
 035 089
 036 090
 037 091
 038 092
 039 093
 040 094
 041 095
 042 096
 043 097
 044 098
 045 099
 046 100
 047 101
 048 102
 049 103
 050 104
 051 105
 052 106
 053 107

Supplementary File to “Multi-channel Weighted Nuclear Norm Minimization for Real Color Image Denoising”

Anonymous ICCV submission

Paper ID 572

In this supplementary file, we provide:

1. The proof of the Theorem 1 in the main paper.
2. More denoising results on the 24 high quality images from the Kodak PhotoCD dataset.
3. More visual comparisons of denoised images by different methods on the real noisy images of the dataset [1].
4. More visual comparisons of denoised images by different methods on the real noisy images of the dataset [2].

1. Proof of Theorem 1.

Theorem 1. Assume that the weights in w are in a non-descending order, the sequence $\{\mathbf{X}_k\}$, $\{\mathbf{Z}_k\}$, and $\{\mathbf{A}_k\}$ generated in Algorithm 1 satisfy:

$$(a) \lim_{k \rightarrow \infty} \|\mathbf{X}_{k+1} - \mathbf{Z}_{k+1}\|_F = 0; \quad (b) \lim_{k \rightarrow \infty} \|\mathbf{X}_{k+1} - \mathbf{X}_k\|_F = 0; \quad (c) \lim_{k \rightarrow \infty} \|\mathbf{Z}_{k+1} - \mathbf{Z}_k\|_F = 0. \quad (1)$$

Proof. 1. Firstly, we prove that the sequence $\{\mathbf{A}_k\}$ generated by Algorithm 1 is upper bounded. Let $\mathbf{X}_{k+1} + \rho_k^{-1} \mathbf{A}_k = \mathbf{U}_k \Sigma_k \mathbf{V}_k^\top$ be its singular value decomposition (SVD) [3] in the $(k+1)$ -th iteration. According to Corollary 1 of [4], we can have the SVD of \mathbf{Z}_{k+1} as $\mathbf{Z}_{k+1} = \mathbf{U}_k \hat{\Sigma}_k \mathbf{V}_k^\top = \mathbf{U}_k \mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k) \mathbf{V}_k^\top$. Then we have

$$\|\mathbf{A}_{k+1}\|_F = \|\mathbf{A}_k + \rho_k (\mathbf{X}_{k+1} - \mathbf{Z}_{k+1})\|_F = \rho_k \|\rho_k^{-1} \mathbf{A}_k + \mathbf{X}_{k+1} - \mathbf{Z}_{k+1}\|_F \quad (2)$$

$$= \rho_k \|\mathbf{U}_k \Sigma_k \mathbf{V}_k^\top - \mathbf{U}_k \mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k) \mathbf{V}_k^\top\|_F = \rho_k \|\Sigma_k - \mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k)\|_F \quad (3)$$

$$= \rho_k \sqrt{\sum_i (\Sigma_k^{ii} - \mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k^{ii}))^2} \leq \rho_k \sqrt{\sum_i \left(\frac{w_i}{\rho_k}\right)^2} = \sqrt{\sum_i w_i^2}. \quad (4)$$

The inequality in the second last step can be proved as follows: given the diagonal matrix Σ_k , we define Σ_k^{ii} as the i -th element of Σ_k^{ii} . If $\Sigma_k^{ii} \geq \frac{w_i}{\rho_k}$, we have $\mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k^{ii}) = \Sigma_k^{ii} - \frac{w_i}{\rho_k} \geq 0$. If $\Sigma_k^{ii} < \frac{w_i}{\rho_k}$, we have $\mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k^{ii}) = 0 < \Sigma_k^{ii} + \frac{w_i}{\rho_k}$. After all, we have $|\Sigma_k^{ii} - \mathcal{S}_{\frac{w}{\rho_k}}(\Sigma_k^{ii})| \leq \frac{w_i}{\rho_k}$ and hence the inequality holds true. Hence, the sequence $\{\mathbf{A}_k\}$ is upper bounded.

2. Secondly, we prove that the sequence of Lagrangian function $\{\mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_k, \rho_k)\}$ is also upper bounded. Since the global optimal solution of \mathbf{X} and \mathbf{Z} in corresponding subproblems, we always have $\mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_k, \rho_k) \leq \mathcal{L}(\mathbf{X}_k, \mathbf{Z}_k, \mathbf{A}_k, \rho_k)$. Based on the updating rule that $\mathbf{A}_{k+1} = \mathbf{A}_k + \rho_k (\mathbf{X}_{k+1} - \mathbf{Z}_{k+1})$, we have $\mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_{k+1}, \rho_{k+1}) = \mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_k, \rho_k) + \langle \mathbf{A}_{k+1} - \mathbf{A}_k, \mathbf{X}_{k+1} - \mathbf{Z}_{k+1} \rangle + \frac{\rho_{k+1} - \rho_k}{2} \|\mathbf{X}_{k+1} - \mathbf{Z}_{k+1}\|_F^2 = \mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_k, \rho_k) + \frac{\rho_{k+1} + \rho_k}{2\rho_k^2} \|\mathbf{A}_{k+1} - \mathbf{A}_k\|_F^2$. Since the sequence $\{\|\mathbf{A}_k\|_F\}$ is upper bounded, the sequence $\{\|\mathbf{A}_{k+1} - \mathbf{A}_k\|_F\}$ is also upper bounded. Denote by a the upper bound of $\{\|\mathbf{A}_{k+1} - \mathbf{A}_k\|_F\}$, we have $\mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_{k+1}, \rho_{k+1}) \leq \mathcal{L}(\mathbf{X}_1, \mathbf{Z}_1, \mathbf{A}_0, \rho_0) + a \sum_{k=0}^{\infty} \frac{\rho_{k+1} + \rho_k}{2\rho_k^2} = \mathcal{L}(\mathbf{X}_1, \mathbf{Z}_1, \mathbf{A}_0, \rho_0) + a \sum_{k=0}^{\infty} \frac{\mu+1}{2\mu^k \rho_0} \leq \mathcal{L}(\mathbf{X}_1, \mathbf{Z}_1, \mathbf{A}_0, \rho_0) + \frac{a}{\rho_0} \sum_{k=0}^{\infty} \frac{1}{\mu^{k-1}}$. The last inequality holds since $\mu+1 < 2\mu$. Since $\sum_{k=0}^{\infty} \frac{1}{\mu^{k-1}} < \infty$, the sequence of Lagrangian function $\{\mathcal{L}(\mathbf{X}_{k+1}, \mathbf{Z}_{k+1}, \mathbf{A}_{k+1}, \rho_{k+1})\}$ is upper bound.

3. Thirdly, we prove that the sequences of $\{\mathbf{X}_k\}$ and $\{\mathbf{Z}_k\}$ are upper bounded. Since $\|\mathbf{W}(\mathbf{Y} - \mathbf{X})\|_F^2 + \|\mathbf{Z}\|_{w,*} = \mathcal{L}(\mathbf{X}_k, \mathbf{Z}_k, \mathbf{A}_{k-1}, \rho_{k-1}) - \langle \mathbf{A}_k, \mathbf{X}_k - \mathbf{Z}_k \rangle - \frac{\rho_k}{2} \|\mathbf{X}_k - \mathbf{Z}_k\|_F^2 = \mathcal{L}(\mathbf{X}_k, \mathbf{Z}_k, \mathbf{A}_{k-1}, \rho_{k-1}) + \frac{1}{2\rho_k} (\|\mathbf{A}_{k-1}\|_F^2 - \|\mathbf{A}_k\|_F^2)$. Thus $\{\mathbf{W}(\mathbf{Y} - \mathbf{X}_k)\}$ and $\{\mathbf{Z}_k\}$ are upper bounded, and hence the sequence $\{\mathbf{X}_k\}$ is bounded by the Cauchy-Schwarz inequality

Table 1. PSNR(dB) results of different denoising methods on 24 natural images.

Image#	$\sigma_r = 5, \sigma_g = 30, \sigma_b = 15$								
	CBM3D	MLP	TNRD	NI	NC	WNNM-1	WNNM-2	WNNM-3	MC-WNNM
1	27.25	28.06	28.62	25.00	29.55	28.16	27.95	28.15	30.20
2	29.70	31.30	32.70	27.80	29.69	32.54	31.60	31.73	34.04
3	30.34	31.98	34.07	28.02	31.93	33.91	33.68	33.52	35.55
4	29.47	31.10	32.56	27.70	32.56	32.68	31.85	31.90	34.06
5	27.31	28.59	29.35	26.14	30.00	28.83	29.00	28.91	30.05
6	28.20	29.10	29.90	26.15	28.81	29.55	29.46	29.62	31.64
7	29.73	31.60	33.46	27.22	31.63	33.09	33.29	32.86	34.24
8	27.47	28.16	28.91	25.34	30.16	29.15	29.24	29.03	29.91
9	30.07	31.63	33.55	27.86	31.54	33.19	33.20	32.95	34.53
10	29.96	31.37	33.20	27.74	33.44	32.98	33.02	32.74	34.38
11	28.73	29.85	30.87	26.98	30.16	30.45	30.14	30.21	32.10
12	30.20	31.50	33.31	27.97	31.69	33.22	32.71	32.65	34.64
13	26.18	26.69	26.98	25.14	27.97	26.49	26.42	26.62	28.30
14	27.86	29.07	29.87	26.67	29.21	29.36	29.14	29.30	31.18
15	29.91	31.58	33.13	28.04	31.17	33.22	32.34	32.36	34.27
16	29.29	30.35	31.54	27.46	32.18	31.34	31.05	31.21	33.72
17	29.50	31.09	32.52	27.81	32.80	32.09	32.00	31.85	33.61
18	27.72	28.74	29.36	26.57	28.63	28.88	28.76	28.89	30.56
19	28.98	30.18	31.35	27.25	29.79	31.34	30.77	30.95	33.10
20	30.63	31.78	33.27	27.89	29.52	33.00	32.55	32.58	34.18
21	28.50	29.58	30.54	26.86	30.99	30.02	30.03	30.03	31.69
22	28.61	29.78	30.82	27.19	30.50	30.47	29.82	30.10	32.08
23	30.60	32.66	35.06	28.17	32.82	34.72	34.37	33.94	35.16
24	27.97	28.81	29.61	26.01	30.75	29.47	29.35	29.39	30.93
Average	28.92	30.19	31.44	27.04	30.73	31.17	30.91	30.89	32.67

and triangle inequality. We can obtain that $\lim_{k \rightarrow \infty} \|\mathbf{X}_{k+1} - \mathbf{Z}_{k+1}\|_F = \lim_{k \rightarrow \infty} \rho_k^{-1} \|\mathbf{A}_{k+1} - \mathbf{A}_k\|_F = 0$ and the equation (a) is proved.

4. Then we can prove that $\lim_{k \rightarrow \infty} \|\mathbf{X}_{k+1} - \mathbf{X}_k\|_F = \lim_{k \rightarrow \infty} \|(\mathbf{W}^\top \mathbf{W} + \frac{\rho_k}{2} \mathbf{I})^{-1} (\mathbf{W}^\top \mathbf{W} \mathbf{Y} - \mathbf{W}^\top \mathbf{W} \mathbf{Z}_k - \frac{1}{2} \mathbf{A}_k) - \rho_k^{-1} (\mathbf{A}_k - \mathbf{A}_{k-1})\|_F \leq \lim_{k \rightarrow \infty} \|(\mathbf{W}^\top \mathbf{W} + \frac{\rho_k}{2} \mathbf{I})^{-1} (\mathbf{W}^\top \mathbf{W} \mathbf{Y} - \mathbf{W}^\top \mathbf{W} \mathbf{Z}_k - \frac{1}{2} \mathbf{A}_k)\|_F + \rho_k^{-1} \|\mathbf{A}_k - \mathbf{A}_{k-1}\|_F = 0$ and hence (b) is proved.

5. Finally, (c) can be proved by checking that $\lim_{k \rightarrow \infty} \|\mathbf{Z}_{k+1} - \mathbf{Z}_k\|_F = \lim_{k \rightarrow \infty} \|\mathbf{X}_k + \rho_k^{-1} \mathbf{A}_{k-1} - \mathbf{Z}_k + \mathbf{X}_{k+1} - \mathbf{X}_k + \rho_k^{-1} \mathbf{A}_{k-1} + \rho_k^{-1} \mathbf{A}_k - \rho_k^{-1} \mathbf{A}_{k+1}\|_F \leq \lim_{k \rightarrow \infty} \|\Sigma_{k-1} - \mathcal{S}_{w/\rho_{k-1}}(\Sigma_{k-1})\|_F + \|\mathbf{X}_{k+1} - \mathbf{X}_k\|_F + \rho_k^{-1} \|\mathbf{A}_{k-1} + \mathbf{A}_{k+1} - \mathbf{A}_k\|_F = 0$, where $\mathbf{U}_{k-1} \Sigma_{k-1} \mathbf{V}_{k-1}^\top$ is the SVD of the matrix $\mathbf{X}_k + \rho_{k-1} \mathbf{A}_{k-1}$. \square

2. More denoising results on the 24 high quality images from the Kodak PhotoCD dataset

In the main paper, we have given the PSNR results of the competing methods on the 24 high quality images from the Kodak PhotoCD dataset when the standard deviations of the additive white Gaussian noise (AWGN) are $\sigma_r = 40, \sigma_g = 20, \sigma_b = 30$ for R, G, B channels, respectively. Here we provide more denoising results on this dataset. In Tables ??-??, we give more PSNR results on these images when the noise standard deviations are $\sigma_r = 5, \sigma_g = 30, \sigma_b = 15$ in Table 1 and $\sigma_r = 30, \sigma_g = 10, \sigma_b = 50$ in Table 2, respectively. In Figures 5-??, we give the visual comparisons of the denoised images by different methods.

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320


321

322

323

Table 2. PSNR(dB) results of different denoising methods on 24 natural images.

	$\sigma_r = 30, \sigma_g = 10, \sigma_b = 50$								
Image#	CBM3D	MLP	TNRD	NI	NC	WNNM-1	WNNM-2	WNNM-3	MC-WNNM
1	23.38	26.49	26.50	24.82	23.59	26.40	25.60	24.76	27.81
2	25.19	30.94	30.90	26.82	27.79	30.89	29.75	29.21	30.96
3	25.39	32.03	32.09	27.52	27.41	32.20	31.17	30.39	32.89
4	24.96	30.55	30.47	27.34	27.00	30.74	29.71	29.10	31.19
5	23.29	26.65	26.73	25.72	26.67	26.74	25.98	24.68	27.60
6	24.09	27.76	27.70	26.10	26.12	27.85	26.96	26.01	29.15
7	24.89	30.70	30.72	27.17	28.07	30.91	29.94	28.87	31.37
8	23.30	26.12	26.27	25.59	26.11	26.87	26.33	24.74	27.44
9	25.20	31.35	31.31	27.74	28.33	31.30	30.45	29.44	32.08
10	25.13	31.01	31.05	27.60	28.53	31.12	30.17	29.21	31.83
11	24.54	28.79	28.82	26.72	24.40	28.73	27.79	26.94	29.60
12	25.43	31.60	31.60	27.82	29.01	31.59	30.62	29.91	32.11
13	22.50	24.71	24.73	24.96	23.36	24.70	23.85	22.86	25.96
14	23.91	27.69	27.72	26.26	23.08	27.62	26.81	25.91	28.57
15	25.45	31.09	31.05	27.36	28.49	31.29	30.21	29.46	31.39
16	24.89	29.79	29.73	27.35	27.10	29.84	28.85	28.13	31.10
17	25.12	30.26	30.24	27.15	27.54	30.11	29.35	28.43	31.08
18	23.83	27.26	27.26	26.05	26.15	27.32	26.18	25.28	28.32
19	24.63	29.40	29.39	27.06	27.41	29.78	28.87	28.05	30.53
20	26.43	31.16	31.27	26.43	26.92	31.25	30.43		31.55
21	24.24	28.26	28.27	26.66	27.18	28.22	27.45		29.29
22	24.51	29.03	29.06	26.83	27.64	29.02	27.81		29.57
23	25.55	32.87	32.75	27.60	23.75	32.58	31.46		32.34
24	23.85	27.06	27.13	25.86	27.05	27.50	26.63		28.32
Average	24.57	29.27	29.28	26.69	26.61	29.36	28.43		30.09

Figure 1. Denoised images of different methods on the image "kodim01" degraded by AWGN with different standard deviations of $\sigma_r = 40, \sigma_g = 20, \sigma_b = 30$ on R, G, B channels, respectively. The images are better to be zoomed in on screen.




Figure 2. Denoised images of different methods on the image “kodim03” degraded by AWGN with different standard deviations of $\sigma_r = 40$, $\sigma_g = 20$, $\sigma_b = 30$ on R, G, B channels, respectively. The images are better to be zoomed in on screen.




Figure 3. Denoised images of different methods on the image “kodim07” degraded by AWGN with different standard deviations of $\sigma_r = 40$, $\sigma_g = 20$, $\sigma_b = 30$ on R, G, B channels, respectively. The images are better to be zoomed in on screen.

432
433
434

486
487
488




Figure 4. Denoised images of different methods on the image ‘‘kodim09’’ degraded by AWGN with different standard deviations of $\sigma_r = 5, \sigma_g = 30, \sigma_b = 15$ on R, G, B channels, respectively. The images are better to be zoomed in on screen.

456

510

458
459
460
461

512
513
514
515




Figure 5. Denoised images of different methods on the image “kodim11” degraded by AWGN with different standard deviations of $\sigma_r = 5$, $\sigma_g = 30$, $\sigma_b = 15$ on R, G, B channels, respectively. The images are better to be zoomed in on screen.

483

537
538
539




Figure 6. Denoised images of the real noisy image “Frog” [1] by different methods. The images are better to be zoomed in on screen.





Figure 7. Denoised images of the real noisy image “Circuit” [1] by different methods. The images are better to be zoomed in on screen.

3. More visual comparisons of denoised images by different methods on the real noisy images of the dataset [1]

In this section, we give more comparisons of the state-of-the-art denoising methods on the dataset [1]. The real noisy images in dataset [1] have no “ground truth” images and hence we only compare the visual quality of the denoised images by different methods. As can be seen from Figures ??-??, our proposed method performs better than the competing methods.

4. More visual comparisons of denoised images by different methods on the real noisy images of the dataset [2]

In this section, we provide more comparisons of the proposed method with the state-of-the-art denoising methods on the 15 cropped real noisy images used in [2]. In this dataset, each scene was shot 500 times under the same camera and camera setting. The mean image of the 500 shots is roughly taken as the “ground truth”, with which the PSNR can be computed. As can be seen from Figures 14-??, in most cases, our proposed method achieves better performance than the the competing methods. This validates the effectiveness of our proposed external prior guided internal prior learning framework for real noisy image denoising.

648
649
650
651
652
653702
703
704
705
706
707
708
709
710
711
712
713
714

(a) Noisy [1] (b) CBM3D [5] (c) MLP [6] (d) TNRD [7] (e) NI [11]

(f) NC [1, 8] (g) WNNM-1 [10] (h) WNNM-2 [10] (i) WNNM-3 [10] (j) MC-WNNM

654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755

(a) Noisy [1] (b) CBM3D [5] (c) MLP [6] (d) TNRD [7] (e) NI [11]

(f) NC [1, 8] (g) WNNM-1 [10] (h) WNNM-2 [10] (i) WNNM-3 [10] (j) MC-WNNM

Figure 8. Denoised images of the real noisy image “Woman” [1] by different methods. The images are better to be zoomed in on screen.

756
757
758
759

810

760
761
762
763
764
765
766
767

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

768




Figure 10. Denoised images of a region cropped from the real noisy image “Canon 5D Mark 3 ISO 3200 2” [2] by different methods. The images are better to be zoomed in on screen.

769

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

770

850

851

852

853

854

855

856

857

858

859

860

861

862

863

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804


805

806

807

808

809



796

797

798

799

800

801

802

803

804

805

806

807

808

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809

809




864
865
866
867918
919
920
921872
873
874
875925
926
927
928886
887931
932

Figure 12. Denoised images of a region cropped from the real noisy image “Nikon D800 ISO 1600 2” [2] by different methods. The images are better to be zoomed in on screen.

888
889
890
891
892
893
894940
941
942
943
944
945
946
947
948903
904
905
906
907
908
909
910
911957
958
959
960
961
962
963
964
965912
913
914
915
916
917966
967
968
969
970
971


972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
9881026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079

Figure 14. Denoised images of a region cropped from the real noisy image “Nikon D800 ISO 6400 2” [2] by different methods. The images are better to be zoomed in on screen.

1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025

1080	References	1134
1081		1135
1082	[1] M. Lebrun, M. Colom, and J. M. Morel. The noise clinic: a blind image denoising algorithm. http://www.ipol.im/pub/ art/2015/125/ . Accessed 01 28, 2015. 1, 3, 4, 5, 6, 7, 8, 9, 10	1136
1083		1137
1084	[2] S. Nam, Y. Hwang, Y. Matsushita, and S. J. Kim. A holistic approach to cross-channel image noise modeling and its application to image denoising. <i>IEEE Conference on Computer Vision and Pattern Recognition (CVPR)</i> , pages 1683–1691, 2016. 1, 6, 8, 9, 10	1138
1085		1139
1086	[3] C. Eckart and G. Young. The approximation of one matrix by another of lower rank. <i>Psychometrika</i> , 1(3):211–218, 1936. 1	1140
1087		1141
1088	[4] S. Gu, Q. Xie, D. Meng, W. Zuo, X. Feng, and L. Zhang. Weighted nuclear norm minimization and its applications to low level vision. <i>International Journal of Computer Vision</i> , pages 1–26, 2016. 1	1142
1089		1143
1090	[5] K. Dabov, A. Foi, V. Katkovnik, and K. Egiazarian. Color image denoising via sparse 3D collaborative filtering with grouping constraint in luminance-chrominance space. <i>IEEE International Conference on Image Processing (ICIP)</i> , pages 313–316, 2007. 3, 4, 5, 6, 7, 8, 9, 10	1144
1091		1145
1092	[6] H. C. Burger, C. J. Schuler, and S. Harmeling. Image denoising: Can plain neural networks compete with BM3D? <i>IEEE Conference on Computer Vision and Pattern Recognition (CVPR)</i> , pages 2392–2399, 2012. 3, 4, 5, 6, 7	1146
1093		1147
1094	[7] Y. Chen, W. Yu, and T. Pock. On learning optimized reaction diffusion processes for effective image restoration. <i>IEEE Conference on Computer Vision and Pattern Recognition (CVPR)</i> , pages 5261–5269, 2015. 3, 4, 5, 6, 7, 8, 9, 10	1148
1095		1149
1096	[8] M. Lebrun, M. Colom, and J.-M. Morel. Multiscale image blind denoising. <i>IEEE Transactions on Image Processing</i> , 24(10):3149– 3161, 2015. 3, 4, 5, 6, 7, 8, 9, 10	1150
1097		1151
1098	[9] K. Dabov, A. Foi, V. Katkovnik, and K. Egiazarian. Image denoising by sparse 3-D transform-domain collaborative filtering. <i>IEEE Transactions on Image Processing</i> , 16(8):2080–2095, 2007. 8, 9, 10	1152
1099		1153
1100	[10] S. Gu, L. Zhang, W. Zuo, and X. Feng. Weighted nuclear norm minimization with application to image denoising. <i>IEEE Conference on Computer Vision and Pattern Recognition (CVPR)</i> , pages 2862–2869, 2014. 6, 7, 8, 9, 10	1154
1101		1155
1102	[11] Neatlab ABSoft. Neat Image. https://ni.neatvideo.com/home . 6, 7, 8, 9, 10	1156
1103		1157
1104		1158
1105		1159
1106		1160
1107		1161
1108		1162
1109		1163
1110		1164
1111		1165
1112		1166
1113		1167
1114		1168
1115		1169
1116		1170
1117		1171
1118		1172
1119		1173
1120		1174
1121		1175
1122		1176
1123		1177
1124		1178
1125		1179
1126		1180
1127		1181
1128		1182
1129		1183
1130		1184
1131		1185
1132		1186
1133		1187