PO Box 518 620 Applegate St. Philomath, OR 97370



(541) 929-5650 Fax (541) 929-5277 www.wetlabs.com

## **FLNTU Characterization Sheet**

Date: January 30, 2012 S/N: FLNTUS-860

## **Chlorophyll Scale Factor**

Chlorophyll concentration expressed in µg/l can be derived using the equation:

CHL  $(\mu g/I)$  = Scale Factor x (Output - Dark Counts)

	Analog		Digital	
Dark Counts	0.064	V	42	counts
Scale Factor (SF)	10	μg/I/V	0.0120	μg/l/count
Maximum Output	4.99	V	4130	counts
Resolution	0.5	mV	1.0	counts
Ambient temperature during calibration	22.3	℃		

## **Nephelometric Turbidity Unit (NTU) Scale Factor**

Turbidity units expressed in NTU can be derived using the equation:

NTU = Scale Factor x (Output - Dark Counts)

	Analog		Digital	
Dark Counts	0.075	V	49	counts
NTU Solution Value	3.87	V	3146	counts
Scale Factor (SF)	5	NTU/V	0.0061	NTU/count
Maximum Output	4.99	V	4130	counts
Resolution	1.0	mV	1.0	counts
Ambient temperature during calibration	22.3	℃		

FLNTUS-860.xls flntuchar

See reverse side for definition of terms.

Dark Counts: Signal output of the meter in clean water with black tape over detector.

NTU Solution Value: Signal output of the turbidity sensor when measuring a sample of interest.

**SF (CHL)**: Determined using the following equation:  $SF = x \div$  (output - dark counts), where x is the concentration of the solution used during instrument characterization. SF is used to derive instrument output concentration from the raw signal output of the fluorometer.

**SF (NTU)**: Scale factor is determined using the following equation:  $SF = xx \div (Output - Dark counts)$ , where xx is the value of a Formazin concentration. For example:  $12.2 \div (2011 - 50) = 0.0062$ .

Maximum Output: Maximum signal output the fluorometer is capable of.

**Resolution**: standard deviation of 1 minute of collected data.