



2. Using example given in lecture, shown optimal strategy gives




2a. [Pick Shortest] Choose the shortest task (that is, finish time-start time is as small as possible), discard all conflicting tasks, then recurse.

In this example I used the sorted version that goes from start to end and was able to get 5 tasks done, fifth task was shown after going through all the small tasks and finding a non conflicting task. I see this as a greedy strategy.



2b.[Pick Last Starter] Choose the task that starts last, discard all conflicting tasks, then recurse.

For this method I used a similar tactic of using a sorted list, I used lines as a guide to see when I can mark down the next task. In this example I was able to get 4 tasks. I found it not optimal since the fourth task was so large that it conflicted with the rest of the list. Because of that, if more larger tasks are introduced in a calendar, this method would be very inefficient.



A: $Y > X > Z$ X: $A > B > C$

B: $Z > X > Y$ Y: $A > C > B$

C: $Y > X > Z$ Z: $C > A > B$


3a [2pt] The matching AX, BY, CZ is not stable, find an unstable pair for this matching.

AX, CZ, A and Y prefer each other more and C and Z prefer each other more

b. Run the Gale-Shapley Algorithm


1. X offers job to A, A accepts
 - a. $[AX]$
2. Y offers job to A, A accepts new offer
 - a. $[AY]$
3. X offers job to B, B accepts offer
 - a. $[AY, BX]$
4. Z offers job to C, C accepts offer
 - a. $[AY, BX, CZ]$

4a. Picture (red text = degree, black text = vertices, red drawing = edges connecting)



4b. There is no euler tour because there are more than 2 vertices with odd degrees. There is no euler circuit because not all the vertices are even

4c. An example I used was locking one door on the top right of vertex d, this allowed there to be even degrees for both a and d, so there would only be odd degrees for f and b. I was able to use each door once shown below.



4d. By closing 3 doors, one on the bottom of d, one on the left of a, and one on the left of b, I was able to make all the degrees even. I was then able to make a euler circuit shown below.

```
>>> 1 = [[3,5,7,4,6], [5,3,1,5,3], [2,8,3,1,4], [4,5,7,2,3], [3,1,3,2,0]]
>>> numberMaze(1)
True
>>> 12 = [[1,5,7,4,6], [5,3,1,5,3], [2,8,3,1,4], [4,5,7,2,3], [3,1,3,2,0]]
>>> numberMaze(12)
False
```