
The slide features a vertical sidebar on the left with the text "DISCOVERING STATISTICS USING R" and a colorful abstract graphic. The main content area has the title "Exploring data with graphs" in a dark blue font.

Exploring data with graphs

1


The slide features a vertical sidebar on the left with the text "DISCOVERING STATISTICS USING R" and a colorful abstract graphic. The main content area has the title "Aims and Objectives" in a dark blue font. Below the title is a bulleted list. A blue callout box on the right contains a note about outdated code.

Aims and Objectives

- How to present data clearly
- Introduce *ggplot2*
 - <https://ggplot2.tidyverse.org>
- Graphs
 - Scatterplots
 - Histograms
 - Boxplots
 - Error bar charts
 - Line graphs

Code in book is outdated!
Stick to the code in the
scripts, on lecture slides,
and the ggplot2
cheatsheet.

2


The slide features a vertical sidebar on the left with the text "DISCOVERING STATISTICS USING R" and a colorful abstract graphic. The main content area has the title "The art of presenting data" in a dark blue font. Below the title is a bulleted list. The text "(Tuft 2001)" is in the bottom right corner.

The art of presenting data


- Graphs should:
 - Show the data
 - Induce the reader to think about the data
 - Avoid distorting the data
 - Present many numbers with minimum ink
 - Make large data sets coherent
 - Encourage reader to compare different pieces of data
 - Reveal data

(Tuft 2001)


3



4



5



6

DISCOVERING STATISTICS USING R

ggplot2

- In R, a plot is made up of layers

7

DISCOVERING STATISTICS USING R

ggplot2

- The anatomy of a `ggplot()` graph

8

DISCOVERING STATISTICS USING R

Scatterplots

- Anxiety and exam performance
- Participants:
 - 103 students
- Measures
 - Time spent revising (hours)
 - Exam performance (%)
 - Exam Anxiety (the EAQ, score out of 100)
 - Gender

9

DISCOVERING STATISTICS USING R

Scatterplots


- **Example of a simple scatterplot**
 - Create a graph object

```
> scatter<- ggplot(examData, aes(Anxiety, Exam))
```

- Draw scatterplot, adding geometric objects (points, lines, etc.) and titles for the axes

```
> scatter + geom_point() +  
  geom_smooth() +  
  labs(x= "Exam Anxiety",  
       y= "Exam Performance %")
```

10



11


DISCOVERING STATISTICS USING R

Scatterplots


- **Draw simple scatterplot with straight line**
 - Draw the same scatterplot but specify we want a straight red line obtained from a 'linear model' (lm)

```
> scatter + geom_point() +  
  geom_smooth(method= "lm", col= "red") +  
  labs(x= "Exam Anxiety",  
       y= "Exam Performance %")
```

12



13



14



15

DISCOVERING STATISTICS
USING R

Histograms

- **Histograms plot**
 - The score (x-axis)
 - The frequency (y-axis)

➔
Frequency distribution!

- **Histograms show**
 - The shape of the distribution
 - Central tendency
 - Skew/Kurtosis
 - Spread or variation in scores
 - Outliers

16

DISCOVERING STATISTICS
USING R

Histograms

- **Hygiene at a 3 day music festival**
- **Sample**
 - 810 concert-goers
- **Measured**
 - Standardized hygiene score, ranging from 0 to 4
 - 0= you smell like a corpse rotting up a skunk's arse
 - 4= you smell of sweet roses on a fresh spring day

17

DISCOVERING STATISTICS
USING R

Histograms

- **Example of a histogram**
 - Create the graph object (we will look at day 1 only)

```

> histoDay1<- ggplot(festivalData, aes(day1)) +
  theme(legend.position= "none")

– Draw histogram of hygiene scores on day 1
> histoDay1 + geom_histogram(binwidth= 0.4) +
  labs(x= "Hygiene (Day 1)",
       y= "Frequency")

– Alternatively, draw a density plot
> histoDay1 + geom_density() +
  labs(x= "Hygiene (Day 1)",
       y= "Density")
        
```

18

DISCOVERING STATISTICS
USING R

Boxplots

- **Boxplots are made up of a box and two whiskers**
- **The box shows**
 - The median
 - The upper and lower quartile
 - The limits within which the middle 50% of scores lie
- **The whiskers show**
 - The range of scores
 - The limits within which the top and bottom 25% of scores lie

19

DISCOVERING STATISTICS
USING R

Boxplots

- **Example of a boxplot**
 - Create the graph object (again, we look at day 1 only)

```
> boxplotDay1<- ggplot(festivalData,
                        aes(gender, day1))
```
- Draw the boxplot


```
> boxplotDay1 + geom_boxplot() +
                        labs(x= "Gender",
                           y= "Hygiene (Day 1)")
```

20

DISCOVERING STATISTICS
USING R

Error bar charts


- **The bar**
 - Usually shows the mean
- **The error bars display the precision of the mean in one of three ways**
 - The confidence interval (usually 95%)
 - The standard deviation
 - The standard error of the mean

21

DISCOVERING STATISTICS USING R

Error bar charts

- Is there such a thing as a 'chick flick'?
- Participants
 - 20 men
 - 20 women
- Half of each sample saw one of two films
 - A 'chick flick' (*Bridget Jones's Diary*)
 - Control (*Memento*)
- Outcome measure
 - Physiological arousal



22

DISCOVERING STATISTICS USING R

Error bar charts

- Example of a bar chart (1 independent variable)
 - Create the graph object:


```
> bar<- ggplot(chickFlick, aes(film, arousal))
```
 - Draw the error bar plot


```
> bar + stat_summary(fun.y= mean, geom= "bar",
                      fill= "white", col= "black")+
          stat_summary(fun.data= mean_cl_normal,
                      geom= "pointrange") +
          labs(x= "Film", y= "Mean Arousal")
```

23

DISCOVERING STATISTICS USING R

Error bar charts

- Example bar chart (2 independent variables, 1 graph)
 - Create the graph object:


```
> bar<- ggplot(chickFlick, aes(film, arousal,
                                fill= gender))
```
 - Draw the error bar plot


```
> bar + stat_summary(fun.y= mean, geom= "bar",
                      position= "dodge") +
          stat_summary(fun.data= mean_cl_normal,
                      geom= "errorbar", position=
                      position_dodge(width= 0.90),
                      width= 0.2) +
          labs(x= "Film", y= "Mean Arousal", fill=
                "Gender")
```

24

DISCOVERING STATISTICS USING R

Error bar charts

- **Example bar chart (2 independent variables, 2 graphs)**
 - Create the graph object:


```
> bar<- ggplot(chickFlick, aes(film, arousal, fill= film))
```
 - Draw the error bar plot



```
> bar + stat_summary(fun.y= mean, geom= "bar") +
  stat_summary(fun.data= mean_cl_normal,
    geom= "errorbar", width= 0.2)+
  facet_wrap(~ gender) +
  labs(x= "Film", y= "Mean Arousal") +
  theme(legend.position= "none")
```

25

DISCOVERING STATISTICS USING R

Line graphs

- **How to cure hiccups?**
- **Participants**
 - 15 hiccup sufferers
- **Each tries four interventions (in random order)**
 - Baseline
 - Tongue-pulling manoeuvres
 - Massage of the carotid artery
 - Digital rectal massage
- **Outcome measure**
 - Number of hiccups in the minute after each procedure



Top Hiccup Cures

1. Surprise nut triangle
2. Spoonful of honey shot of rum: repeat 12 times
3. Savage blow to solar plexus
4. Put gas station air hose in mouth, pinch nose
5. Artificial esophagus implant
6. Prayer
7. Complain about hiccups

26

DISCOVERING STATISTICS USING R

Line graphs

- **Example line graph (1 independent variable)**
 - Create the graph object


```
> line<- ggplot(hiccups, aes(Intervention_Factor, Hiccups))
```
 - Draw the line graph



```
> line + stat_summary(fun.y= mean, geom= "point")+
  stat_summary(fun.y= mean, geom= "line",
    aes(group= 1), col= "red",
    linetype= "dashed") +
  stat_summary(fun.data= mean_cl_boot,
    geom= "errorbar", width=0.2)+
  labs(x= "Intervention", y= "Mean Number of Hiccups")
```

27

DISCOVERING STATISTICS
USING R

Line graphs

- **Is text-messaging bad for your grammar?**
- **Participants:**
 - 50 children
- **Children split into two groups**
 - Text-messaging allowed
 - Text-messaging forbidden
- **Each child measures at two points in time**
 - Baseline
 - 6 months later
- **Outcome measure**
 - Percentage score on a grammar test



28

DISCOVERING STATISTICS
USING R

Line graphs

- **Example line graph (2 independent variables)**
 - Create the graph object

```
> line<- ggplot(textMessages, aes(Time,
                                     Grammar_Score, col= Group))
```

- Draw the line graph

```
> line + stat_summary(fun.y= mean, geom= "point")+
  stat_summary(fun.y= mean, geom= "line",
               aes(group= Group)) +
  stat_summary(fun.data= mean_cl_boot,
               geom= "errorbar", width=
                 0.2) +
  labs(x= "Time", y= "Mean Grammar Score",
       col= "Group")
```

29


DISCOVERING STATISTICS
USING R

Rest of afternoon and tomorrow morning...

- **Practical**
 - Continue with Chapter 3
 - Selecting/subsetting and restructuring dataframes
 - Read § 4.1, “Cramming Sam’s Tips” and “What Have I discovered about statistics?”
 - Explore ggplot2 website:
 - <https://ggplot2.tidyverse.org>
 - Do self-tests scattered through Chapter 4
 - Solve Smart Alex’s Task 2

30

DISCOVERING STATISTICS
USING R



Errata

- **ggplot2 has been drastically updated:**
 - ‘`opts()`’ is replaced with ‘`themes()`’
- R’s Souls’ Tip 4.3

To override default colours of bars:

```
+ scale_fill_manual("Gender", values= c("Female"=
                                         "blue", "Male"= "green"))
```

To override default colours of points/lines:

```
+ scale_colour_manual("Gender", values= c("Female"=
                                           "blue", "Male"= "green"))
```

31
