COMPUTER SCIENCE MENTORS 61A

August 31-September 2, 2022

Intro to Python

```
>>> "cs61a"
'cs61a'
>>> x = 3
>>> x
>>> x = print("cs61a")
cs61a
>>> X
None
>>> print (print (print ("cs61a")))
cs61a
None
None
```

return x + 1

1. What Would Python Display?

>>> 3

>>> f1(2) + f1(2 + 3)

>>> **def** f1(x):

>>> f1(3)

```
>>> def f2(y):
          return y / 0
  >>> f2(4)
  ZeroDivisionError: division by zero
  >>> def f3(x, y):
  ... if x > y:
                    return x
           elif x == y:
                    return x + y
         else:
                    return y
  >>> f3(1, 2)
  >>> f3(5, 5)
  >>> 1 or 2 or 3
  >>> 1 or 0 or 3
  >>> 4 and (2 or 1/0)
  >>> 0 or (not 1 and 3)
  False
  >>> (2 or 1/0) and (False or (True and (0 or 1)))
2. For the following expressions, simplify the operands in the order of evaluation of the entire expression
  Example: add(3, mul(4, 5))
  Order of Evaluation: add(3, mul(4, 5)) \rightarrow add(3, 20) \rightarrow 23
   (a) add(1, mul(2, 3))
      add(1, mul(2, 3))
      add(1, 6)
   (b) add(mul(2, 3), add(1, 4))
```

2 CSM 61A Spring 2022

```
add(mul(2, 3), add(1, 4))
add(6, add(1, 4))
add(6, 5)
11

(c) max(mul(1, 2), add(5, 6), 3, mul(mul(3, 4), 1), 7)

max(mul(1, 2), add(5, 6), 3, mul(mul(3, 4), 1), 7)
max(2, add(5, 6), 3, mul(mul(3, 4), 1), 7)
max(2, 11, 3, mul(mul(3, 4), 1), 7)
max(2, 11, 3, mul(12, 1), 7)
max(2, 11, 3, 12, 7)
12
```

2 Control

1. Write a function that returns True if a number is divisible by 4 and False otherwise.

```
def is_divisible_by_4 (num):
    return num % 4 == 0
```

2. Write a function find_max that takes in three numbers, x, y, z, and returns the maximum of the provided values. Assume that x, y, and z are unique. Do not use Python's built-in max function.

```
def find_max(x, y, z):
    def find_max(x, y, z):
        if x > y and x > z:
            return x
        elif y > x and y > z:
            return y
        else:
            return z
```

3. Implement pow_of_two, which prints all the positive integer powers of two less than or equal to n in ascending order. This function should return None.

Follow up question: What would you change about your solution if the question asked to print all the powers of two **strictly less than** n?

```
def pow_of_two(n):
    11 11 11
    >>> pow_of_two(6)
    2
    4
    >>> result = pow of two(16)
    2
    4
    8
    16
    >>> result is None
    True
    11 11 11
    curr = 1
    while curr <= n:</pre>
        print (curr)
        curr *= 2 # equivalent to curr = curr * 2
```

Since we are multiplying curr by 2 on each iteration of the while loop, curr holds values that are powers of 2. Notice that since there is no return statement in this function, when Python reaches the end of the function, it automatically returns None.

The answer to the follow up question is that the condition of our while loop would change to curr < n. Walk through the code for pow_of_two(16) with both of the conditions to see why they produce different outputs!

Another way you could have written this function is by using **pow** or the ** operator. That solution would look something like this where you would keep track of the exponent itself:

```
exponent = 0
while (2 ** exponent) <= n:
    print(2 ** exponent)
    exponent += 1</pre>
```

4 CSM 61A Spring 2022

4. Complete the function fact_limit, which calculates factorials up to a specified limit. Specifically, fact_limit takes in two positive integers, n and limit, and calculates the product of n, n-1, n-2, etc., working downward until it attains the greatest product that doesn't exceed limit. If there is no product less than or equal to limit, fact_limit should return 1.

Hint: The output of fact_limit is always less than or equal to limit.

```
def fact_limit(n, limit):
   >>> fact_limit(5, 20)
   20 \# 5 * 4 = 20, but 5 * 4 * 3 = 60 > 20
   >>> fact_limit(5, 200)
   120 \# 5 * 4 * 3 * 2 * 1 = 120 < 200
   >>> fact_limit(5, 3)
   1 # no partial product is less than 3
   if _____:
   product = _____
    = n - 1
   while ____:
          ____ = ____
   return _____
def fact_limit(n, limit):
   if n > limit:
       return 1
   product = n
   n = n - 1
```

while product * n <= limit and n > 0:

product = product * n

n = n - 1return product