LAMBDAS, CURRYING, AND ENVIRONMENTS

COMPUTER SCIENCE MENTORS 61A

September 14, 2026 - September 18, 2026

1 Expressions and Truth Values

1.
```
def quick_maths(man, free):
    print(man)
    if man % 2 == 0 and free:
        return quick_maths(man + 2, not free)
    else:
        man -= 1
        if man == 3:
            print(man)
        else:
            return man
big_shaq = 2
```

Expression	Interactive Output
`print(quick_maths(big_shaq, True))`	

2 Lambda Expressions and Function Forms

1. What do lambda expressions do?

Created by Cadence Loh and Rajoshi Basu. feedback form!
Provided by CSM 61A contributors under CC BY 4.0/3-clause BSD.

2. Rewrite each function in the requested equivalent form. Preserve the function's parameters and behavior; only change whether it is written with **`def`** or **`lambda`**. For your reference, a **`lambda`** assignment assigns a lambda function to a variable.

   (a) Rewrite the following **`def`** as a lambda assignment.

   ```
   def square(x):
       return x * x
   ```

   (b) Rewrite the following lambda assignment using **`def`**.

   ```
   subtract = lambda x, y: x - y
   ```

   (c) Rewrite this zero-argument function as a lambda assignment.

   ```
   def greeting():
       return 'Hello, world!'
   ```

3 Currying and Zero-Argument Functions

1. Fill in the blanks (*without using any numbers in the first blank*) such that the entire expression evaluates to `9`.

   ```
   (lambda x: lambda y: ____________________)(_____)(lambda z: z*z)()
   ```

4 Environment Diagrams with Lambdas

1. Give the environment diagram and console output that result from running the following code.

```
x = 20
def foo(y):
    x = 5
    def bar():
        return lambda y: x - y
    return bar

y = foo(7)
z = y()
print(z(2))
```

2. Draw the environment diagram that results from running the code below.

```
def dream1(f):
    def dream2(secret):
        mind = f(secret)
        kick = lambda x: mind()
        return kick(2)
    return dream2

inception = lambda secret: lambda: secret
real = dream1(inception)(42)
```

5 Basic Function Implementation

1. Write a higher-order function that passes the following doctests.

   Challenge: Write the function body in one line.

```
def mystery(f, x):
    """
    >>> from operator import add, mul
    >>> a = mystery(add, 3)
    >>> a(4) # add(3, 4)
    7
    >>> a(12)
    15
    >>> b = mystery(mul, 5)
    >>> b(7) # mul(5, 7)
    35
    >>> b(1)
    5
    >>> c = mystery(lambda x, y: x * x + y, 4)
    >>> c(5)
    21
    >>> c(7)
    23
    """
```

2. Implement `make_skipper`, which takes in a number `n` and outputs a function. When this function takes in a number `x`, it prints out all the numbers between `0` and `x`, skipping every `n`th number.

```
def make_skipper(n):
    """
    >>> a = make_skipper(2)
    >>> a(5)
    1
    3
    5
    """
```