

SEQUENCES, CONTAINERS, OBJECTS, & LINKED LISTS Meta

COMPUTER SCIENCE MENTORS 61A

September 28, 2026 – October 2, 2026

Example Timeline

- **This is a menu of problems, not a requirement to finish the worksheet.** Individual suggested times do not add up to one hour. Choose or skip problems based on your students, and give each mini-lecture immediately before its section.
- Check-in and icebreaker [5 min]. Ask what students would like more practice with: tracing expressions, choosing a representation, or writing code.
- Sequences: selected parts of Q1–Q2, then Q3 or Q4 [15 min]. Choose Q3 for nested loops or Q4 for filtering and comprehensions. Q5 is extra practice.
- Containers: Q6 or Q7 [10 min]. Choose Q6 for strings, counting, and dictionary construction or Q7 to connect dictionary comprehensions to higher-order functions.
- Objects and abstraction: Q8, then selected parts of Q9 [8 min]. Connect the ADT discussion to constructing dataclass instances, reading fields, and interpreting defaults.
- Linked lists: selected parts of Q10, then Q11 or Q12 [17 min]. Choose Q11 for construction or Q12 for processing an existing linked list. Supply the dataclass definition and focus on its interface. The iterative version of Q11 is extra practice.
- Wrap-up and questions [5 min]. Have students describe the interface of one representation in their own words.

Teaching Goals

- Keep emphasizing abstraction: what information does a value represent, and which operations does its interface support? Have students name intermediate values and their types before evaluating nested expressions.
- Let students predict, discuss with a partner, and explain their reasoning before running code. For implementation problems, establish an example and a plan before filling in blanks.
- Q1 practices indexing, slicing, concatenation, and nested-list access. Across compound data, focus on reading values and constructing results; defer mutation, sharing, and cycles. Local assignments and integer counters remain useful tools for iteration.
- **Type hints throughout:** Before solving, have students read the annotations aloud. A tuple annotation lists the types at each position; `list[int]` describes integer elements; `dict[str, int]` describes string keys and integer values. The arrow describes a function's return type. In linked-list annotations, `T` is the element type and `LinkedList[T]` also permits `()`. Annotations document expected types; Python does not automatically enforce them.
- Q6 and Q7 construct dictionaries with comprehensions. Have students identify the key and value for one input before reading the whole expression. In Q7 and Q12, `Callable` describes the argument and return types of a function parameter.
- The sequence overview and Q2 introduce tuples and their operations. Q10–Q12 cover linked-list structure, construction, traversal, and processing.

- Q13 is optional tree-recursion practice: split the possibilities into taking one donut of the current flavor or using none of that flavor. Ask students why these two counts are added.

1 Sequences

Sequence Overview

Sequences are ordered data structures that have length and support element selection. Here are some common types of sequences you'll be dealing with in this class:

- Lists: `[1, [2], 'a', lambda x: 5]`
- Tuples: `(1, (2,), 'a', lambda x: 5)`
- Strings: `'Hello World!'`

While each type of sequence is different, they all share a common interface for manipulating and accessing their data:

- **Item selection:** Use square brackets to select an element at an index:

```
(3, 1, 2)[0] # returns 3
"Hello"[-1] # returns "o"
```

- **Length:** The built-in `len` function returns the length of a sequence:

```
len((1, 2)) # returns 2
```

- **Concatenation:** Sequences can be concatenated with the `+` operator, which returns a *new* sequence:

```
[1, 2] + [3, 4] # returns [1, 2, 3, 4]
```

- **Membership:** The `in` operator tests for sequence membership:

```
1 in (1, 2, 3) # returns True
5 not in (1, 2, 3) # returns True
"apple" in "snapple" # returns True
```

Membership in Strings vs. Lists and Tuples: As a short aside, while the `in` operator works the same for lists and tuples, checking if an element is contained within the list/tuple container, the `in` operator instead for strings checks for direct substrings rather than the existence of distinct elements within the string.

- **Looping:** Sequences can be looped through with `for` loops:

```
>>> for x in [1, 2, 3]:
...     print(x)
1
2
3
```

- **Aggregation:** Common built-in functions—including `sum`, `min`, and `max`—can take sequences and aggregate them into a single value:

```
max((3, 4, 5)) # returns 5
```

- **Slicing:** Slicing is a way to create a copy of all or part of a sequence. The general syntax for slicing a sequence `seq` is as follows:

```
seq[<start index>:<end index>:<step size>]
```

This evaluates to a new sequence that includes every element starting at `<start index>` and up to and *excluding* `<end index>` in `seq`, taking steps of size `<step size>`.

If we do not supply `<start index>` or `<end index>`, it will start at the beginning of the sequence and include every element up to and including the end of the sequence.

```

>>> lst = [1, 2, 3, 4, 5]
>>> lst[2:]
[3, 4, 5]
>>> lst[:3]
[1, 2, 3]
>>> lst[::-1]
[5, 4, 3, 2, 1]
>>> lst[1:2]
[2, 4]

```

List comprehensions create a new list by processing an iterable, such as a list, tuple, string, or range. The syntax for a list comprehension is

```
[<expression> for <element> in <sequence> if <condition>]
```

We could equivalently write the following:

```

lst = []
for <element> in <sequence>:
    if <condition>:
        lst = lst + [<expression>]

```

The **if** <condition> filter statement is optional. The following list comprehension doubles each odd element of [1, 2, 3, 4]:

```

>>> [i * 2 for i in [1, 2, 3, 4] if i % 2 != 0]
[2, 6]

```

Equivalent in **for** loop syntax:

```

lst = []
for i in [1, 2, 3, 4]:
    if i % 2 != 0:
        lst = lst + [i * 2]

```

A lot of information in this guide is not the full and complete picture of how Python works, but students don't need to know that. Often a little misdirection is necessary to improve initial knowledge acquisition before a more complete picture is painted later on. I would just be sure to mention the nature of sequences: a loose umbrella (not a strict definition like a class) that encompasses many different data types.

If students are confused consider bringing up specific examples of sequences. Reading rules on a page is often not actually that instructive.

Sequence Practice

1. What would Python display? Run the statements in order. For nested expressions, work from the innermost expression outward.

```

>>> a = [1, 2, 3]
>>> a

```

```
[1, 2, 3]
```

```
>>> a[2]
```

```
3
```

```
>>> a[-1]
```

```
3
```

```
>>> a[1:]
```

```
[2, 3]
```

```
>>> a[:2]
```

```
[1, 2]
```

```
>>> a + [4, 5]
```

```
[1, 2, 3, 4, 5]
```

```
>>> a
```

```
[1, 2, 3]
```

```
>>> nested = [1, 2, 3, 4, [5, 6]]  
>>> nested[4]
```

```
[5, 6]
```

```
>>> nested[4][0]
```

```
5
```

```
>>> nested[3:5]
```

```
[4, [5, 6]]
```

Teaching Tips

Suggested Time: 6–8 min; Difficulty: Easy

- **Indexing:** Indices start at zero; negative indices count from the end. Ask students to predict the type of each result before its value.
- **Slicing:** Include the start index and exclude the stop index. An omitted bound extends to the corresponding end of the list.
- **Concatenation:** The expression `a + [4, 5]` produces a list value; evaluating it does not change the value of `a`.
- **Nested access:** First evaluate `nested[4]`, then select index zero from that result. Focus on the elements and the operation at each step.

2. **Tuples.** What would Python display? Run these statements in order. If a statement causes an error, identify the error and continue with the next statement. For `(3,)` and `(3)`, also name the type.

Creating tuples

```
>>> t: tuple[int, str, float, bool, None] = (  
...     3, "csm", 2.5, True, None  
... )  
>>> t
```

```
(3, 'csm', 2.5, True, None)
```

```
>>> 4, 5, 6, 7
```

```
(4, 5, 6, 7)
```

```
>>> (3,)
```

```
(3,)
```

```
Type: tuple.
```

```
>>> (3)
```

```
3
```

```
Type: int.
```

```
>>> ()
```

```
>>> len(())
```

```
()
```

```
0
```

Slicing and converting

```
>>> t[1:4]
```

```
('csm', 2.5, True)
```

```
>>> t[::-1]
```

```
(None, True, 2.5, 'csm', 3)
```

```
>>> list(t)
```

```
[3, 'csm', 2.5, True, None]
```

```
>>> list("csm")
```

```
>>> list(())
```

```
['c', 's', 'm']
```

```
[]
```

Combining tuples

```
>>> (4, 5) + (6, 7)
```

```
(4, 5, 6, 7)
```

```
>>> (3,) * 3
```

```
>>> (3) * 3
```

```
(3, 3, 3)
```

```
9
```

Dictionary keys

```
>>> locations = {(4, 5): "CSM"}
```

```
>>> locations[(4, 5)]
```

```
'CSM'
```

```
>>> locations[[4, 5]]
```

```
TypeError
```

```
>>> locations[(4, [5])]
```

`TypeError`

Suggested Time: 8–10 min; Difficulty: Easy–Medium

- Ask students to read the annotation on `t`: it describes a five-element tuple, with the type of each position listed in order. The annotation does not convert values or enforce their types at runtime.
 - A comma creates a tuple: parentheses usually group expressions. The empty tuple is written `()`; one item needs a trailing comma.
 - Tuples can hold different data types. Slicing returns a tuple; **list** builds a list from the elements of an iterable.
 - Tuple addition concatenates and multiplication repeats elements; neither operation changes the original tuple. Briefly describe tuples as immutable sequences; focus here on reading and combining values.
 - Dictionary keys must be hashable. A tuple can be a key only when all its elements are hashable. Lists are unhashable, including a list nested inside a tuple. Use the last example as a follow-up challenge.
3. Write a function `duplicate_list`, which takes in a list of positive integers and returns a new list with each element `x` in the original list duplicated `x` times.

```
def duplicate_list(lst: list[int]) -> list[int]:
    """
    >>> duplicate_list([1, 2, 3])
    [1, 2, 2, 3, 3, 3]
    >>> duplicate_list([5])
    [5, 5, 5, 5, 5]
    """
    _____

    for _____:
        for _____:
            _____

    _____

    new_list = []
    for x in lst:
        for i in range(x):
            new_list = new_list + [x]
    return new_list
```

Teaching Tips

1. Read the signature before solving: `list[int]` describes a list of integers, and `-> list[int]`

describes the expected return type. Type hints do not enforce types at runtime.

2. If students have trouble arriving at the solution, walk through the intuition of nested for loops and discuss what each loop represents. For example, the first loop represents iterating over each element of the list and the second one represents repeating that element.
3. This is a good problem to emphasize how we can format our logic and approach to problems based on the skeleton code.

Suggested Time: 7 min; Difficulty: Medium Explain what each loop represents: the outer loop selects an element, and the inner loop repeats it. Connect `range(x)` to exactly `x` repetitions.

4. Write a function that takes in a list `nums` and returns a new list with only the primes from `nums`. Assume that `is_prime(n)` is defined. You may use a `while` loop, a `for` loop, or a list comprehension.

```
def all_primes(nums: list[int]) -> list[int]:
```

```
    result = []
    for i in nums:
        if is_prime(i):
            result = result + [i]
    return result
```

```
    # Alternative using a list comprehension:
    return [x for x in nums if is_prime(x)]
```

Teaching Tips

1. Students may be very familiar with list comprehensions at this point, so don't spend too much time going over this question if your students don't need it
2. If they are stuck doing it with list comprehensions, state that one can approach it with a for loop
3. Might help to go through how to convert from a for/while loop to a list comprehension
4. If students are struggling with list comprehensions, it might be a good idea to explain that the entire list comprehension returns a list, instead of just acting like a for loop.

Suggested Time: 5 min; Difficulty: Easy Treat `is_prime` as a provided abstraction. Focus on filtering a sequence, then compare the loop and comprehension solutions already supplied in the bank.

5. Fill in the functions below according to the doctests.

```
def gen_list(n: int) -> list[list[int]]:
    """
    Returns a nested list structure of n elements where the
    ith element is a list from 0 (inclusive) to i (exclusive).
    >>> gen_list(3)
    [[0], [0, 1], [0, 1, 2]]
    >>> gen_list(5)
    [[0], [0, 1], [0, 1, 2], [0, 1, 2, 3], [0, 1, 2, 3, 4]]
    """
    return _____
```

For an additional challenge, try out the following:

```
def gen_increasing(n: int) -> list[list[int]]:
    """
    Returns a nested list structure of n elements where the
    ith element of each list is one more than the previous
    element (even if the previous is in a prior sublist).
    >>> gen_increasing(3)
    [[0], [1, 2], [3, 4, 5]]
    >>> gen_increasing(5)
    [[0], [1, 2], [3, 4, 5], [6, 7, 8, 9], [10, 11, 12, 13,
    14]]
    """
    return _____
```

Hint: You can sum ranges. E.g. `sum(range(3))` gives us $0 + 1 + 2 = 3$.

```
def gen_list(n: int) -> list[list[int]]:
    return [[i for i in range(j+1)] for j in range(n)]

def gen_increasing(n: int) -> list[list[int]]:
    return [[i for i in range(sum(range(j+1)), sum(range(j+1)) + j+1)] for
            j in range(n)]
```

An alternate solution for `gen_increasing` is shown below:

```
def gen_increasing(n: int) -> list[list[int]]:
    return [[i + sum(range(j + 1)) for i in range(j + 1)] for j in
            range(n)]
```

Suggested Time: 7 min; add 5 min for the challenge; Difficulty: Medium Build one inner list before reasoning about the outer comprehension. The doctests number the elements starting at one. In the challenge, `sum(range(j + 1))` counts how many values earlier sublists contain. The wrapped final doctest output is one list, not separate outputs.

2 Containers and Dictionaries

6. Write `count_t`, which returns the number of lowercase "t" characters in `word`. Then use it to construct a dictionary mapping each word in `words` to its count.

```
def count_t(word: str) -> int:
```

```
    """
```

```
    >>> count_t("tatter")
```

```
    3
```

```
    >>> count_t("tree")
```

```
    1
```

```
    >>> count_t("")
```

```
    0
```

```
    """
```

```
    _____
```

```
    for _____:
```

```
        if _____:
```

```
            _____
```

```
    _____
```

```
def count_t(word: str) -> int:
```

```
    count = 0
```

```
    for c in word:
```

```
        if c == 't':
```

```
            count += 1
```

```
    return count
```

Complete the dictionary comprehension. Its result should be `{'tatter': 3, 'tree': 1}`.

```
words = ["tatter", "tree"]
```

```
counts: dict[str, int] = {
```

```
    _____: _____ for word in words
```

```
}
```

```
counts: dict[str, int] = {
```

```
    word: count_t(word) for word in words
```

```
}
```

Teaching Tips

Suggested Time: 7 min; Difficulty: Easy

- **Read the types:** The function takes a string and returns an integer. The dictionary has string keys and integer values.
- **Plan the loop:** Start at zero, traverse the characters, count each lowercase 't', and return the total.

- **Construct the dictionary:** Identify the `key: value` pair and the iterable. Each word is a key; its count is the associated value. The expression produces a dictionary.
 - **Connect the two stages:** Ask what `count_t(word)` returns for one word before evaluating the whole comprehension. Updating the local integer count does not alter the input string.
7. Complete `snapshot`. It takes a function from integers to integers and a list of integer inputs. Return a dictionary whose keys are those inputs and whose values are the corresponding outputs of the function. Use a dictionary comprehension.

```
from collections.abc import Callable

def snapshot(
    f: Callable[[int], int], snap_inputs: list[int]
) -> dict[int, int]:
    """
    >>> snapshot(lambda x: x**2, [1, 2, 3])
    {1: 1, 2: 4, 3: 9}
    >>> snapshot(lambda x: x + 1, [])
    {}
    """
    return {
        _____: _____
        for _____
    }
```

```
def snapshot(
    f: Callable[[int], int], snap_inputs: list[int]
) -> dict[int, int]:
    return {x: f(x) for x in snap_inputs}
```

Teaching Tips

Suggested Time: 7 min; Difficulty: Easy–Medium

- **Read the function type:** In `Callable[[int], int]`, the bracketed list gives the parameter types and the final type describes the return value. Here `f` accepts one integer and returns one.
- **Connect to HOFs:** The argument is a function, not the result of calling it. Evaluate `f(x)` separately for each input.
- **Choose key and value:** Each input `x` is a key; its output `f(x)` is the value. The comprehension constructs the complete result, with no separate dictionary-update step.
- **Explain the name:** The dictionary records a function's behavior on a finite selection of inputs: a snapshot of its behavior.

3 Objects and Data Abstraction

8. (a) What is an **Abstract Data Type**?

An abstract data type describes the information a value represents and the operations we can use with it, without requiring users to know how those operations are implemented. For example, a session record can provide a topic, room, and duration through named attributes.

(b) What is the relationship between a class and an ADT?

A class is one way to implement an ADT. A dataclass can bundle a session's information into fields such as `topic`, `room`, and `minutes`. Calling `Session("Recursion", 310)` constructs an instance, and reading `s.room` accesses its room. Code using this interface need not know how the fields are stored. The class's definition implements the representation; the meaning and supported operations form the abstraction.

Teaching Tips

Suggested Time: 3–4 min; Difficulty: Conceptual

- **Connect to functions:** Using a function without inspecting its body is analogous to using a compound value through its interface.
- **Make the distinction concrete:** A dataclass provides a convenient implementation; the abstraction is the meaning of the data and what its interface lets us do. Use the session-record example in the solution.

9. **Session records.** What would Python display after executing the following definitions? Read the field annotations before tracing.

```
from dataclasses import dataclass

@dataclass
class Session:
    topic: str
    room: int
    minutes: int = 60

morning = Session("Recursion", 310)
afternoon = Session("Sequences", 205, 45)

>>> morning.topic

'Recursion'

>>> morning.minutes

60
```

```
>>> afternoon.room
```

```
205
```

```
>>> afternoon.minutes
```

```
45
```

```
>>> morning.minutes + afternoon.minutes
```

```
105
```

```
>>> morning
```

```
Session(topic='Recursion', room=310, minutes=60)
```

```
>>> Session(room=220, topic="Linked lists").topic
```

```
'Linked lists'
```

Teaching Tips

Suggested Time: 6–8 min; Difficulty: Easy

- **Fields and types:** `topic` describes text, while `room` and `minutes` describe integers. Annotations communicate expected types.
- **Construction:** `@dataclass` supplies a constructor from the declared fields. Positional arguments follow field order; keyword arguments name the fields explicitly.
- **Defaults:** Omitting `minutes` uses 60. Supplying 45 uses that value for the constructed session.
- **Access and display:** Dot notation reads one field. The generated representation names the class and its fields. Focus on constructing and reading instances; students do not need to implement special methods for this exercise.

4 Linked Lists

For the following questions, use this dataclass-based linked list. A `LinkedList[T]` is either a `Link[T]` or the empty tuple `()`. The type variable `T` describes the element type.

```
from __future__ import annotations
from dataclasses import dataclass

type LinkedList[T] = Link[T] | tuple[()]

@dataclass
class Link[T]:
    first: T
    rest: LinkedList[T] = ()

    def __str__(self) -> str:
        return format_link(self)

def format_link[T](s: Link[T]) -> str:
    string = '(' + str(s.first)
    remaining = s.rest
    while isinstance(remaining, Link):
        string += ' ' + str(remaining.first)
        remaining = remaining.rest
    assert remaining == (), 'Not a valid linked list'
    return string + ')'
```

Construct a list with `Link(1, Link(2))`. Read its elements with `first` and `rest`. At the end, `rest` is `()`, which has no `first` or `rest` attributes. **print** uses parentheses around the elements; entering a `Link` at the prompt shows the dataclass representation with field names.

Teaching the interface: Establish construction, field access, and the empty case first. Treat `format_link` as supplied display behavior; students need not implement it. In the questions, reason about element values and shorter lists. If using diagrams, draw the sequence structure without asking students to distinguish shared nodes from equal-valued nodes.

This definition uses Python 3.12 or later. The future import also supports these annotations on Python 3.12–3.13. Reference: [Composing Programs](#), [Compound Data](#).

10. What would Python display? Run these statements in order. If a statement causes an error, identify the error and continue.

```
>>> a = Link(1, Link(2, Link(3)))
>>> a.first
```

1

```
>>> a.rest.first
```

2

```

>>> a.rest.rest.first

3

>>> a.rest.rest.rest

()

>>> isinstance(a.rest, Link)

True

>>> isinstance(a.rest.rest.rest, Link)

False

>>> a.rest.rest.rest.first

AttributeError: 'tuple' object has no attribute 'first'

>>> a.rest.rest

Link(first=3, rest=())

>>> Link(1, Link(2))

Link(first=1, rest=Link(first=2, rest=()))

>>> print(a)

(1 2 3)

```

Teaching Tips

Suggested Time: 6–8 min; Difficulty: Easy

- **Follow the structure:** Each `rest` skips one element. Name the resulting value before taking another attribute.
- **Recognize the base case:** `()` is an empty linked list, not a `Link` instance. It has no `first` or `rest`.

- **Read the representations:** The dataclass representation shows `first=` and `rest=`; `print` uses the supplied formatter to show the sequence as `(1 2 3)`. Both describe the same element sequence.

11. Write a function `linkify` that, given a list `lst`, returns a linked list with the same values. You may assume that there will be no nested lists.

Try writing this function both recursively and iteratively.

```
def linkify_rec[T](lst: list[T]) -> LinkedList[T]:
    """
    >>> lst = [0, 1, 2, 3]
    >>> print(linkify_rec(lst))
    (0 1 2 3)
    >>> linkify_rec([])
    ()
    """
    if _____:
        _____
    else:
        _____
```

```
def linkify_iter[T](lst: list[T]) -> LinkedList[T]:
```

```
    _____
    for _____:
        _____
    _____
```

```
def linkify_rec[T](lst: list[T]) -> LinkedList[T]:
    if not lst:
        return ()
    else:
        return Link(lst[0], linkify_rec(lst[1:]))

def linkify_iter[T](lst: list[T]) -> LinkedList[T]:
    retVal: LinkedList[T] = ()
    for elem in lst[::-1]:
        retVal = Link(elem, retVal)
    return retVal
```

Teaching Tips

Suggested Time: 9 min recursive; add 5 min iterative; Difficulty: Medium

- **Read the types:** The type variable `T` represents the input element type, which is preserved in the output linked list.
 - **Use the recursive leap of faith:** Identify the base case, smaller input, and how to build the answer. The recursive call returns a linked list for the remaining Python list; empty input returns `()`.
 - **Build iteratively:** Process the input from right to left, placing each element at the front of the result. This preserves the input order. Use the recursive version first and the iterative version as additional practice.
12. Write a function `combine_two`, which takes in a linked list of integers `lnk` and a two-argument function `fn`. It returns a new linked list where every two elements of `lnk` have been combined using `fn`.

```
from collections.abc import Callable
def combine_two(
    lnk: LinkedList[int], fn: Callable[[int, int], int]
) -> LinkedList[int]:
    """
    >>> from operator import add, mul
    >>> lnk1 = Link(1, Link(2, Link(3, Link(4))))
    >>> print(combine_two(lnk1, add))
    (3 7)
    >>> lnk2 = Link(2, Link(4, Link(6)))
    >>> print(combine_two(lnk2, mul))
    (8 6)
    >>> combine_two(), add
    ()
    """
    if _____:

        return _____
    elif _____:

        return _____
    combined = _____

    return _____
```

```
def combine_two(
    lnk: LinkedList[int], fn: Callable[[int, int], int]
) -> LinkedList[int]:
    if not isinstance(lnk, Link):
        return ()
    elif not isinstance(lnk.rest, Link):
        return Link(lnk.first)
    combined = fn(lnk.first, lnk.rest.first)
    return Link(combined, combine_two(lnk.rest.rest, fn))
```

Teaching Tips

Suggested Time: 10 min; Difficulty: Medium

- **Function type:** `Callable[[int, int], int]` describes two integer arguments and an integer result. Connect to HOFs.
- **Base cases:** Separate empty and one-element inputs. Use `isinstance` to distinguish a node from `()`.
- **Recursive step:** Combine two values, recurse on the remaining list, and construct the result. Retain an unpaired last value.

5 Optional Extension: Tree-Recursive Counting

13. Gabe's Donut shop has an unlimited supply of f different flavors of donuts. Adit wants to buy a box containing d donuts. Complete the skeleton for the function `donut`, which determines the number of possible ways there are for Adit to select his d donuts from the f flavors. You may assume that d and f are non-negative integers.

Hint: Does order matter?

```
def donut(d: int, f: int) -> int:
    """
    >>> donut(12, 1)
    1
    >>> donut(12, 2)
    13
    >>> donut(12, 12)
    1352078
    >>> donut(0, 0)
    1
    """
    if _____:

        return _____

    if _____:

        return _____

    return _____

def donut(d: int, f: int) -> int:
    if d == 0:
        return 1
    if f == 0:
        return 0
    return donut(d - 1, f) + donut(d, f - 1)
```

Suppose the flavors are numbered 1 through f . Because order does not matter, we're going to say that Adit fills up his donut box starting with flavor number f and working down to flavor number 1. Under this scheme, Adit has a choice to make: does he want a donut of flavor number f , or does he not want one? If he does initially take a donut of flavor number f , then the number of ways to select the remaining $d - 1$ slots of the box is `donut(d - 1, f)`. If he does not want a donut of flavor number f , then he has d slots left in the box and $f - 1$ flavors to fill them with, making the number of ways to make the selection `donut(d, f - 1)`. Since he must make the choice one way or the other, the total number of ways to fill up the box is `donut(d - 1, f) + donut(d, f - 1)`.

If your students are confused on why the doctest `donut(0, 0)` returns 1, you can think about it this way:

if you want 0 donuts and they have no flavors, then there is one action you can take, do nothing and don't purchase donuts

A big concept within tree recursion counting problems is this idea that we can use some sort of “choice” to break our problem down into smaller subproblems. I would emphasize this heavily to my students. Here, the choice is whether or not Adit takes a certain flavor.

In this case, we have deliberately neglected to provide several base cases in the doc tests. While a good exam problem would include these doctests, they are often not provided, and students should be able to deduce the bases cases by either 1) mathematical maturity or 2) deduction from test inputs. In the latter case, they could for example note that `donut(1, 1) == donut(0, 1) + donut(1, 0)` and use this to help figure out what `donut` should return at these base cases.

Suggested Time: 10 min; Difficulty: Medium Taking a donut decreases the number of remaining slots; excluding a flavor decreases the available flavors. These cases do not overlap, so add their counts. Have students describe what each recursive call counts before filling in the code. A box with zero donuts is one completed choice, which explains the successful base case. Connect to earlier practice with `mario_number`: add the counts of separate choices. Ask how this differs from `make_change`, which chooses the minimum rather than counting all possibilities.