CSM 61C Spring 2019

Control and Pipelines

Mentoring 8: March 10, 2019

1 Sequential vs. Pipelined

1.1 Assume you have a RISC-V processor that has the following execution times:

IF	ID	EX	MEM	WB
100 ps	150 ps	300 ps	400 ps	250 ps

(a) In an unpipelined processor, what is the maximum clock rate possible?

(b) In a pipelined processor, what is the maximum clock rate possible?

(c) Suppose we add some hardware that shortens the ALU processing time to 250 ns. Does this change the maximum clock rate in an unpipelined processor? In a pipelined processor?

1.2 Fill in the timing diagram for the following code snippet assuming a pipelined processor (the first row has been filled in for you):

Time	1	2	3	4	5	6	7	8	9
sw									
addi									
add									
lw									

```
sw   s1, 0(s0)
addi  t0, t1, 8
add   s2, s0, s1
lw   t2, 0(t3)
```

How many cycles did the pipelined processor take? How many would an unpipelined processor take?

2 More Pipelines (Spring 2016 MT2 Q4)

2.1 Consider the following code segment:

```
Loop: lw    t1, 0(t2)
srl   t1, t1, 16
sw    t1, 0(t2)
addi  t2, t2, -4
sub   t4, t3, t2
bne   t4, 0, Loop
End:  sll   x0, x0, x0
```

Assume that originally `t3 = t2 - 196`.

Assume a standard 5 stage pipeline with no forwarding. Register file writes happen before reads, in the same clock cycle. Comparator logic begins at the end of the decode stage. We do not have a branch delay slot. Fill in the corresponding pipeline stages (F, D, E, M, W) at the appropriate times in the table below.

If the instruction requires a stall, write the stage again in the table. For example, if an instruction starts at cycle 2 but needs two stalls for the execute stage, then you would write F D E E E M W for cycles 2 - 8.

Inst/Cycle	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
`lw t1 0(t2)`																			
`srl t1 t1 16`																			
`sw t1 0(t2)`																			
`addi t2 t2 -4`																			
`sub t4 t3 t2`																			
`bne t4 0 Loop`																			

2.2 How many cycles does this loop take to fully execute (from the first lw to the `End` label)?

2.3 Now assume the pipeline has 1 delayed branch slot and standard forwarding hardware. Also, reordering of instructions is allowed to minimize stalls. Write out the reordered sequence of instructions that achieves a minimal number of stalls needed.

2.4 How many cycles does this loop take to fully execute (from the lw to the `End` label)?

3 Pipelining Hazards

We construct a different five-stage pipelined CPU by swapping the execute and the memory read stages. Note that there is now only indirect addressing for the load word and store word.



3.1 Assume that this pipeline resolves control hazards by pipeline stalls. How many cycles is it stalled on a control hazard?

3.2 Should the pipeline stall for data hazards from load instructions? Give an example, fill in the corresponding pipeline stages, and explain your idea briefly in one or two sentences.

Instr/Cycle	1	2	3	4	5	6	7	8	9	10	11	12	13