

Jericho Down Mixer Guide

Plain-English help for combining microphones and app audio into one safe program mix for output and recording.

Mixer Signal Flow

Each input is captured, processed by its mic settings, adjusted by the mixer strip, combined into the program mix, protected by the master controls, then sent to output and/or recording.

Main Mixer Areas

Area	What It Does	When To Touch It
Master bar	Controls the final program mix level, stereo/mono mode, auto normalize, limiter, and limiter ceiling.	Use it after the individual mics feel balanced. Keep limiter on for safety.
Output spectrum	Shows the program mix frequency shape.	Use it to see low rumble, harsh peaks, or missing presence in the final mix.
Program output 3D	Shows the final output as a GPU-backed rolling 3D waveform.	Use it as a confidence view that the program mix is alive and moving.
Channel strips	Each vertical strip represents one mixer input with name, route, mute, fader, meter, and clip light.	Use these for normal live mixing. Rename mics so they make sense at a glance.
Selected Input panel	Detailed tools for the selected strip: sync, meter, mute, solo, invert, reset, input gain, pan, and delay.	Use it when one input needs more than a simple fader move.
Output Routing	Chooses where the program mix is sent and shows actual routing, meters, limiter reduction, and feedback risk.	Use it before feeding speakers, headphones, a virtual cable, or another app.
Recording	Records program mix, selected processed mic, or selected raw backup.	Use program mix for the finished service. Use raw backup when you want rescue audio.
CoreAudio App Mix	Shows app sessions on the selected output with app-level mute, volume, and activity meters.	Use it when a music player, browser, or other app is too loud or should be muted.

Controls You Will Use Most

Control	Plain-English Meaning	Good Starting Point
Master volume	Final level after all channels are mixed.	Start at 100 percent. Raise only if the whole mix is quiet.
Stereo / Mono	Stereo keeps left/right placement. Mono sends the same combined signal to both sides.	Use Stereo for normal output. Use Mono for simple church PA feeds or single-channel destinations.
Normalize	Automatically lifts or trims the program mix toward a steady target.	Keep on unless you are doing manual gain staging.
Limiter	Stops sudden peaks from clipping the output.	Keep on. It is the final safety net.
Ceiling	The maximum output level allowed by the limiter.	Use -1 dB for safety. Lower it if downstream gear clips.
Mute	Silences that channel without changing its level setting.	Use for inputs not currently needed.
Fader	Main volume for a mic or source in the mix.	Start at 100 percent, then balance by ear.
Input gain	Pre-mix trim for one selected input.	Use small moves. Lower it if that input clips.
Pan	Places one input left or right in the stereo program mix.	Keep speech centered. Use gentle pan only for music or stereo spacing.
Solo	Lets you check one input without permanently changing mute states.	Use briefly while troubleshooting. Turn off before live output.
Invert	Flips polarity to help with cancellation between nearby mics.	Leave off unless two mics sound thin together but normal alone.
Delay	Adds milliseconds of delay to align late or early sources.	Use only when a USB/headset mic or distant mic is audibly out of time.

Normal Live Setup Workflow

Step	What To Do
1. Name the strips	Rename Mic 1, Mic 2, and so on to Pastor, Vocal 1, Piano, Room, or whatever matches the service.
2. Confirm routes	Check the route text under each name so device and channel choices match the real microphone.
3. Set individual levels	Talk or sing at real volume. Move each fader until the mix feels balanced. Watch clip lights.
4. Use selected-input tools	Solo one mic to troubleshoot, add input gain if needed, pan if appropriate, invert only for phase problems, and delay only for timing alignment.
5. Check the program graphs	The spectrum and 3D graph should show the combined program output, not ten separate busy lines.
6. Route or record	Choose the output device and recording source. Program mix is the normal finished output. Raw backup is for rescue.

Output, Recording, and Confidence Checks

Program mix means the finished mix after all active channels, faders, pan, delay, normalize, and limiter. This is what you normally send to speakers, a virtual cable, or a recording.

Selected mic means only the currently selected input after its processing. Use it when you need to record or inspect one microphone.

Selected mic raw backup means the current input before processing. Use it as safety audio when you may want to reprocess later.

The Mixer spectrum and 3D output graph are confidence views for the program output. If they are alive but the speaker is silent, the problem is likely routing or the playback device. If they are flat, the program mix itself is not receiving signal.

Problem Solver

Problem	Try This First
No sound to speakers	Check Output Routing, selected playback device, SEND PROGRAM MIX, master volume, and whether all channels are muted.
Recording is silent	Check Recording Source, REC button, save location, and whether the selected source has signal.
One mic is late	Select that strip and add a small Delay value until speech lines up.
Two mics sound thin together	Select one of them and try Invert. If it gets fuller, leave it on.
Mix clips	Lower the loud channel first. Then lower master volume or limiter ceiling if needed.
Feedback risk appears	Lower speaker volume, move mics away from speakers, cut narrow problem frequencies, or mute open mics.
Music app is too loud	Use CoreAudio App Mix to lower that app before it hits the program mix.