# Computer-Aided VLSI System Design Lab2: Waveform Debugging

TA: 黃佳穎 r13943003@ntu.edu.tw

#### Introduction

In this lab, you will learn:

- 1. How to dump FSDB waveform file through VCS simulator
- 2. Waveform debugging by nWave
- 3. SDF annotation for gate-level simulation after synthesis


## **Data Preparation**

- 1. Upload your files (Lab2.tar) to your work directory.
- 2. Decompress Lab2.tar with the following command:

3. Lab2 files are shown as below:

Files/Folder	Description
Lab2_alu.v	RTL code of ALU
Lab2_test_alu.v	Testbench for ALU
Lab2_alu_run.f	File list for RTL simulation
Lab2_alu_s.v	Gate-level netlist of ALU
Lab2_alu_run_s.f	File list for gate-level simulation
Lab2_alu_s.sdf	SDF file for gate-level timing annotation

4. The circuit diagram of the ALU used for this lab is illustrated as follows:



5. Enter Lab2 directory:

cd lab2

## **Environment Setup**

1. Source the default **cshrc** file:

```
source /usr/cad/synopsys/CIC/vcs.cshrc
source /usr/spring_soft/CIC/verdi.cshrc
```

## Lab 2.1. Generating the VCD & FSDB Waveforms

#### Value Change Dump (VCD) format:

- Indigenously supported by most simulators
- Using ASCII text for waveform recording (larger file size)

```
$dumpfile("filename.vcd");
$dumpvars;
```

#### Fast Signal Database (FSDB) format:

- Defined by Verdi debugging system
- More compact format and smaller file size

```
$fsdbDumpfile("filename.fsdb");
$fsdbDumpvars;
```

1. Run the RTL simulation using VCS:

```
vcs -full64 Lab2_test_alu.v Lab2_alu.v +v2k -R
or
```

```
vcs -full64 -f Lab2_alu_run.f +v2k -R
```

2. You would only see the text telling you "congratulations" but not knowing what's going on inside the circuit. Now we would like to generate VCD file.

Please open the testbench Lab2\_test\_alu.v. Add following lines in the initial block in testbench to generate vcd file:

```
$dumpfile("Lab2_alu.vcd");
$dumpvars;
```

3. Now re-run the simulation. Note we should add "-debug\_access+all" to enable vcd file dumping:

```
vcs -full64 -f Lab2_alu_run.f +v2k -R -debug_access+all
```

- 4. Please check if there exists a file called "Lab2\_alu.vcd"
- 5. Now we would like to generate FSDB file. Please open the testbench again.

6. Add the following lines in the initial block in Lab2\_test\_alu.v. You can also remove the two lines added in step 2:

```
$fsdbDumpfile("Lab2_alu.fsdb");
$fsdbDumpvars;
```

7. Now re-run the simulation. Note we should add "-debug\_access+all" to enable FSDB file dumping:

```
vcs -full64 -f Lab2_alu_run.f +v2k -R -debug_access+all
```

8. Please check if there exists a file called "Lab2 alu.fsdb"

## Lab 2.2. Using nWave for Waveform Debugging


1. Start nWave. "&" enables you to use the terminal while nWave is running in the background:

```
nWave &
```


2. Open the VCD file we obtained. VCD file will be translated to FSDB file, you can either open the VCD file using GUI or run:

```
nWave Lab2_alu.vcd &
```


3. Choose the signals we are interested in.



4. View the waveform:



- 5. Change the radix and sign representation (for alu\_out, inputA and inputB):
  - "Waveform" "Set Radix" "Decimal"
  - "Waveform" "Set Notation" "Signed 2's Complement"



### Lab 2.3. Gate-Level Simulation

1. After synthesizing Lab2\_alu.v, we can derive the gate-level netlist file "Lab2\_alu\_s.v", which is already provided in this lab.

Try this command for gate-level simulation:

```
vcs -full64 +v2k -R +neg_tchk -debug_access+all Lab2_test_alu.v Lab2_alu_s.v
/home/raid7_2/course/cvsd/CBDK_IC_Contest_v2.5/Verilog/tsmc13_neg.v
```

or

```
vcs -full64 -f Lab2_alu_run_s.f +v2k +neg_tchk -R -debug_access+all
```

2. You will see a lot of warnings about "timing violation." The reason is that the simulator does not know about the propagation delay of each gate. Hence, the simulator cannot combine the delay information with "tsmc13\_neg.v" to check if your design can run at the clock frequency defined in the testbench.

Please open the testbench Lab2\_test\_alu.v and uncomment this line:

```
$sdf_annotate("Lab2_alu_s.sdf", my_alu);
```


This line annotates the timing information (.sdf) of the netlist.

- 3. Save the modified testbench and re-run step 1.
- 4. During the simulation, there is no timing violation anymore.
- 5. Open the waveform file to see how different it is between RTL waveform and gate-level waveform.

## **Checkpoints**

Please check with TAs before leaving this lab to make sure the following goals are accomplished and to get credits.

- 1. Please generate the waveform files.
- 2. Open nWave and take the snapshots of alu\_out, clk, inputA and inputB.



- 3. Fix the timing violations in gate-level simulation.
- 4. Take a snapshot after passing gate-level simulation.

# **Submission**

- 1. Due Tuesday, Sep. 30, 20:10. No delay is allowed.
- 2. Selected students need to take snapshots of the results shown in the previous section, record them into a PDF file, and submit it to NTU COOL.

Title: studentID\_lab2 (E.g. r13943003\_lab2.pdf)