HELIOS Framework

User & Developer Reference Manual

Heavy Ion Linac Intelligent Orchestration

Autonomous, Safety-First Accelerator Control & Commissioning Platform

HELIOS Collaboration

Chong Shik Park (cspark7701@gmail.com)

October 13, 2026

Contents

1 System Overview and Architecture **2**
- 1.1 Introduction . . . 2
- 1.2 Agent Taxonomy and Roles . . . 2
- 1.3 Graduated Autonomy Levels . . . 3

2 Installation and Environment Setup **4**
- 2.1 Prerequisites . . . 4
- 2.2 External Simulators and Control Tools . . . 4

3 Operator Interfaces and CLI **5**
- 3.1 Interactive Operator Console . . . 5
- 3.2 Real-Time Web Dashboard . . . 5
- 3.3 Commissioning Shift Reporting . . . 5
- 3.4 Tamper-Evident Audit Verification . . . 5

4 Accelerator Physics and Beam Dynamics **6**
- 4.1 Multi-Species and Multi-Charge-State (MCS) Dynamics . . . 6
- 4.2 Beam-Based Alignment (BBA) and Dispersion-Free Steering (DFS) . . . 6
- 4.3 Maximum Entropy (MENT) Phase Space Tomography . . . 6

5 LinkML Ontology and Knowledge Graph **7**

6 Verification and Test Suite **8**

Chapter 1

System Overview and Architecture

1.1 Introduction

HELIOS (**HE**avy ion **L**inac **I**ntelligent **O**rchestration) is a distributed multi-agent artificial intelligence framework engineered for commissioning, operating, and optimizing heavy-ion linear accelerators (LEBT, RFQ, MEBT, SCL, and HEBT).

Aligned directly with the **Plan-First** paradigm established by the Lawrence Berkeley National Laboratory (LBNL) Osprey architecture, HELIOS enforces strict separation of concerns between optimization heuristics, digital twin simulation validations, deterministic safety gatekeepers, and hardware control layers.

1.2 Agent Taxonomy and Roles

The framework partitions operational responsibilities among specialized autonomous agents:

1. **Master Orchestrator Agent (`HELIOS-Orchestrator`)**: Decomposes high-level physicist directives into formal execution plans, manages multi-agent coordination, and interfaces with human operators.

2. **Physics and Simulation Agent (`HELIOS-Physics`)**: Manages the digital twin model, executes ANL TRACK and LBNL IMPACT-Z simulations, and evaluates deep neural surrogate models.

3. **Diagnostics and Telemetry Agent (`HELIOS-Diagnostics`)**: Ingests real-time signals from Beam Position Monitors (BPMs), Beam Loss Monitors (BLMs), and wire scanners; evaluates beam transmission and detects operational anomalies.

4. **Tuning and Optimization Agent (`HELIOS-Tuner`)**: Executes algorithmic optimization including response-matrix SVD orbit correction, multi-objective Bayesian Optimization, and Reinforcement Learning continuous control.

5. **Safety and Verification Agent (`HELIOS-Safety`)**: Serves as a deterministic gatekeeper enforcing hard software limits, slew-rate constraints, cryo-quench margins, and instant rollback stacks.

6. **Control and Hardware Interface Agent (`HELIOS-Control`)**: Interfaces with the live control system via EPICS Channel Access (CA) and pvAccess (PVA) with atomic readback verification.

1.3 Graduated Autonomy Levels

HELIOS implements five graduated operational autonomy levels for human-in-the-loop gating:

Level	Name	Description	Operator Role
0	Advisory	Passive telemetry monitoring & anomaly alerts	Manual action only
1	Assisted	Pre-flight verified plans generated	Mandatory approval per setpoint
2	Supervised	Automated tuning within tight envelopes	Supervisory abort authority
3	Bounded Auto	Closed-loop optimization within boundaries	Passive monitoring
4	Fully Auto	Self-driving linac domain commissioning	Goal-setting oversight only

Table 1.1: Operational Autonomy Levels in HELIOS.

Chapter 2

Installation and Environment Setup

2.1 Prerequisites

HELIOS requires Python 3.10 or higher (recommended: Python 3.11 in Conda).

```
# Clone repository
git clone https://github.com/cspark/helios.git
cd helios

# Create and activate conda environment
conda create -n helios python=3.11 -y
conda activate helios

# Install dependencies in editable mode
pip install -e ".[dev,ml,dashboard,ontology]"
```

2.2 External Simulators and Control Tools

- **ANL TRACK**: Heavy-ion ray-tracing and multi-charge state tracking code executed via Wine 64-bit (`wine64 track.exe`).
- **LBNL IMPACT-Z**: 3D space-charge Particle-in-Cell (PIC) simulation managed through `lume-impact`.
- **EPICS Base**: Channel Access and pvAccess tools (`p4p`, `pyepics`) for live communication with accelerator IOCs.

Chapter 3

Operator Interfaces and CLI

HELIOS provides an ergonomic command-line interface implemented via Typer and Rich.

3.1 Interactive Operator Console

Launch the conversational operator assistant:

```
helios chat
```

The console accepts natural language goals (e.g. *"Correct horizontal orbit in MEBT and verify quench margins on SCL1 cavity 02"*), decomposing them into formal Osprey execution plans.

3.2 Real-Time Web Dashboard

Start the FastAPI and WebSocket visualization dashboard:

```
helios dashboard --host 0.0.0.0 --port 8000
```

Open `http://localhost:8000` to inspect live BPM orbits, cavity resonance states, radiation loss heatmaps, and approve human-in-the-loop plans.

3.3 Commissioning Shift Reporting

Compile electronic logbook reports:

```
helios report --facility "RAON SCL1" --output shift_report.md
```

3.4 Tamper-Evident Audit Verification

Verify SHA-256 cryptographic hash chaining across all recorded Process Variable writes:

```
helios audit --verify
```

Chapter 4

Accelerator Physics and Beam Dynamics

4.1 Multi-Species and Multi-Charge-State (MCS) Dynamics

Heavy-ion linacs frequently accelerate multi-charge state beams simultaneously (e.g., $^{238}U^{33+}$ and $^{238}U^{34+}$). The magnetic rigidity $B\rho$ is given by:

$$B\rho = \frac{p}{q} = \frac{\gamma m_0 \beta c}{q} \tag{4.1}$$

The module `helios.physics.species` models isotopic distributions and composite beam envelopes across charge fractions.

4.2 Beam-Based Alignment (BBA) and Dispersion-Free Steering (DFS)

Beam offsets relative to quadrupole magnetic centers are computed via strength modulation ΔK_1:

$$\Delta x_{\text{BPM}} = R_{12} \cdot (\Delta K_1 L) \cdot (x_{\text{beam}} - x_{\text{quad}}) \tag{4.2}$$

Dispersion-Free Steering (DFS) solves the stacked linear system via weighted SVD:

$$\min_{\Delta\theta} \left(\|R_{\text{orbit}} \Delta\theta + x_0\|^2 + w^2 \|R_{\text{disp}} \Delta\theta + \eta_0\|^2 \right) \tag{4.3}$$

4.3 Maximum Entropy (MENT) Phase Space Tomography

The `helios.physics.halo` module implements iterative Maximum Entropy (MENT) reconstruction of 2D transverse phase-space (x, x') distributions from 1D profile projections. The Wangler-Crump halo parameter H is evaluated as:

$$H = \frac{\langle r^4 \rangle}{2\langle r^2 \rangle^2} - 1.0 \tag{4.4}$$

providing automatic warnings when beam halo risks cryomodule chamber scraping.

Chapter 5

LinkML Ontology and Knowledge Graph

HELIOS formally defines its accelerator domain using the **LinkML** standard (`helios/ontology/helios_schem`

- **Schema Classes**: Defines `BeamlineElement`, `MagneticElement`, `Quadrupole`, `RFCavityElement`, `BeamPositionMonitor`, and `LinacLatticeModel`.
- **W3C RDF / Turtle OWL Exporter**: Serializes digital twins into Linked Open Data knowledge graphs with upstream and downstream connection topology.
- **Topology Navigator**: The `BeamlineKnowledgeGraph` enables spatial and causal queries along the beamline (e.g., locating nearest upstream correctors).

Chapter 6

Verification and Test Suite

HELIOS includes an automated test suite verifying all 29 development phases:

```
pytest
```

The suite validates 98 tests covering lattice physics, neural surrogates, EPICS communication, RL environments, fault recovery, LinkML schemas, and end-to-end commissioning harnesses with 100% passing status.