Septum loss and jitter transfer in a matched booster-to-storage-ring transfer line

Chong Shik Park

Department of Accelerator Science and Center for Accelerator Research,
Korea University, Sejong, 30019 Republic of Korea
Corresponding author: kuphy@korea.ac.kr

October 15, 2026

Abstract

In a booster-to-storage-ring transfer line whose ends are matched to fixed optics, the quadrupoles cannot change the beam size at the line's ends. We show for a 21.8 m, 4 GeV line of the Korea Light Source design that the limiting restriction is the injection-septum blade, 1.48 mm from the injected beam in the geometry of a companion nonlinear-kicker study, and that its nominal clearance is independent of the quadrupole settings. What the optics do control is where booster shot jitter arrives: with matched ends the exit jitter depends only on the horizontal phase advance, which exchanges position jitter at the blade for angle jitter at the injection kicker. After trajectory correction, which reduces the loss from 10% to 1.6%, this jitter sets the remaining blade loss. A Gaussian loss model agrees with tracking within 1% and serves as a design objective. Matched solutions reach only a 200–232 degree phase-advance interval; a setting at its edge cuts the tracked loss on fresh machines from 2.32 to 0.66% at 13% more exit-angle jitter, whereas lowering the vertical peak beta by 45% gives no resolved change, and the mean minimum clearance used earlier cannot see either result. A dispersion-free exit is feasible, widens the reachable interval and lowers the predicted loss a further 65-fold. Aperture dimensions other than the blade, and the error levels, are declared assumptions.

Keywords: transfer line; injection septum; beam loss; betatron phase advance; booster jitter; trajectory correction

1 Introduction

Diffraction-limited storage rings require control of the distribution delivered to their injection region [1]. The Korea Light Source (KLS) design provides a 4 GeV context [2, 3]. A booster-to-storage-ring (BTS) line must deliver the booster beam through the injection septum, whose blade sits millimetres from the injected beam, with stable position and angle at the injection point. Published transfer-line studies treat these as distinct tasks. SLS 2.0 separates quadrupole-scan beam characterisation from position and angle control and identifies septum restrictions [4]. ESRF–EBS rematching includes injection-region fields and mechanical constraints [5]. Sirius studies distinguish injector stages and incoming beam-size effects [6], and MAX IV pulsed-sextupole injection addresses ring capture [7].

A common design heuristic is to lower the peak beta functions inside the line to gain aperture margin. We ask what the quadrupoles can actually change at the restriction that limits the line. Two facts organise the answer. First, the optics at both ends are fixed by the boundary match, so every restriction outside the quadrupole section, including the septa, has a nominal clearance that no quadrupole setting changes. Second, the same boundary match reduces the transfer of booster jitter to a single parameter, the horizontal phase advance, which decides whether

the jitter arrives at the septum blade as position or at the injection kicker as angle. We model the line with element-wise apertures and the blade geometry of a companion nonlinear-kicker (NKM) study, correct its trajectory as in commissioning, use a Gaussian loss probability validated by tracking as the design observable, and test the resulting settings on independently seeded machines. The article ends at the line exit and claims no ring capture or kicker transparency. Standard optimisation is used without algorithmic novelty claims.

2 Parametric model and physical observables

2.1 Boundaries, coordinates and source limitations

The Accelerator Toolbox (AT)/pyAT model [8, 9] contains 36 elements over 21.789 m, from marker m1 to marker m4 downstream of sept_ex. It has nine 0.2 m quadrupoles in three triplets, three main bends, an extraction kicker and two model septa (Fig. 1). Local coordinates are $(x, p_x, y, p_y, \delta, ct)$ with positions/path length in m, normalized canonical momenta approximately angles in rad, and $\delta = \Delta p/p_0$ dimensionless. The six design bend angles are $+7.5, +88.5, -111.701, +176, -111.701, +88.5$ mrad; reference geometry is held fixed when fields or particle momenta change.




Figure 1: Configured BTS element sequence drawn with Accelerator Toolbox synoptic plotting. Red symbols are quadrupoles and blue blocks are dipoles; blank intervals are drifts. Dotted lines mark the markers m1–m4 of the earlier four-station aperture model. The path coordinate follows the reference trajectory; this is not a surveyed mechanical layout.

Table 1: Configured entrance and exit targets. The exit values are the injected beam at the injection-septum exit used by the companion NKM study; their derivation from the ring optics is not documented in the source. A dispersion-free exit is examined in Section 4.4.

Observable	m1 entrance	m4 target
β_x, β_y [m]	7.560000, 12.269000	2.336495, 4.256241
α_x, α_y [1]	1.523100, −1.654700	−0.016335, 0.017772
D_x [m], D'_x [1]	0.276200, −0.065700	0.080868, 0.047472

Entrance and target functions (Table 1) are inherited configured values. The exit m4 is the injection-septum exit: the companion NKM study uses exactly these values as its injected beam and transports it 2.26 m to the kicker. The nonzero exit dispersion (80.9 mm, 47.5 mrad) is inherited from the configuration, not derived from the ring, whose dispersion at the injection kicker is about 0.3 mm; we therefore also examine a dispersion-free exit. Quadrupole family bounds, bore radius, pole-field limit, the 60 m beta screening ceiling and square aperture limits are modelling assumptions, not verified hardware specifications. The legacy MAD-X line has ten active quadrupoles, different drift/bend/edge definitions and an unused additional quadrupole

definition. It is not an equivalent independent lattice; our independent validation implements the identical AT sequence analytically.

The original model placed four square apertures at markers m1–m4 (19.35 mm at the line ends, 30 mm at two interior markers) and none on the magnets. That four-station model and its hypothetical internal restrictions, studied in the earlier revision, are documented in the Supplement; this article uses the element-wise restrictions of Section 2.3.

2.2 Beam covariance and clearance

The new study uses the booster horizontal design input $\epsilon_x = 7.67$ nm rad and $\sigma_\delta = 0.106\%$ [3]. The vertical input $\epsilon_y = 0.767$ nm rad is an assumed 10% ratio. Betatron coordinates and momentum are independent untruncated Gaussians before dispersion is added; initial transverse coupling is zero and $ct = 0$ for this RF-free single pass. The transverse blocks of the complete covariance are

$$\Sigma_{u,\mathrm{bet}} = \epsilon_u \begin{pmatrix} \beta_u & -\alpha_u \\ -\alpha_u & (1+\alpha_u^2)/\beta_u \end{pmatrix}, \qquad \Sigma_0 = \Sigma_{\mathrm{bet}} + \sigma_\delta^2 \mathbf{d}\mathbf{d}^\mathsf{T}, \tag{1}$$

where $\mathbf{d} = (D_x, D_x', D_y, D_y', 1, 0)^\mathsf{T}$. Rolls can generate coupling downstream. Full covariance transport, $\Sigma_s = M_s \Sigma_0 M_s^\mathsf{T}$, retains that coupling and momentum correlation. A local affine map gives the centroid $\bar{\mathbf{z}}_s = M_s \bar{\mathbf{z}}_0 + \mathbf{b}_s$.

For each aperture plane with lower/upper edges a_-, a_+, we define

$$c_u(s) = \min[a_+ - \bar{u}(s), \bar{u}(s) - a_-] - 5\sqrt{\Sigma_{uu}(s)}, \qquad c_{\min} = \min_{s \in \mathrm{stations}, u \in \{x,y\}} c_u(s). \tag{2}$$

Five sigma is a declared projected coverage metric, not complete containment of an unbounded Gaussian. Beta reduction in m must not be called a clearance increase in m. Historical optics-only ensembles use a separate conservative 100/10 nm rad, 0.11% beam configuration and are not pooled with this study.

At 4 GeV the rigidity is approximately 13.34256 T m. For K in m^{-2}, $G = K(B\rho)$ in T/m and $B_{\mathrm{pole}} = |G|r$ in T. Assumed bounds are $|K| \le 2.5$ for q11/q33 and $|K| \le 3$ for the other quadrupoles. With the assumed 19.35 mm bore, the respective maxima are 33.356/40.028 T/m and 0.645/0.775 T, below the assumed 1.2 T screening limit. This calculation checks model consistency, not magnet engineering feasibility.

2.3 Element-wise restrictions

Every element carries its own aperture (Table 2); magnets are sliced (four slices per quadrupole, eight per bend or septum) so that interior envelopes are checked. The only restriction with a source is the injection-septum blade. In the companion NKM study the injected beam leaves the septum at $x = -19.478$ mm, with the stored-beam edge at -16 mm and a 2 mm blade, i.e. 1.478 mm from the blade's outer face, chosen there as three rms sizes plus 1 mm. We place the blade at $x = +1.478$ mm along the whole injection septum and at the line end, on the side facing the stored beam. All other dimensions are declared assumptions and are swept. Bend chambers are taken as curved: the sagitta of the reference arc over its chord is 30.8 mm in b2 and 19.5 mm in b1/b3, so a straight chamber would need that much extra width. Clearances (Eq. 2) are evaluated at every aperture, with the projected halfwidth of a round aperture reduced by the other plane's centroid.

2.4 Errors, jitter and trajectory correction

Static machine errors are independent Gaussian quadrupole gradient errors (0.1% rms), x/y offsets (100 micrometres), rolls (0.5 mrad) and dipole field errors (0.05%). Each shot adds booster

Table 2: Element-wise aperture model (halfwidths; for the injection septum, a_x is the blade distance on the $+x$ side and the outer wall is at -8.5 mm). Only the blade position follows a source; all other values are assumptions.

Region	Shape	a_x [mm]	a_y [mm]	Basis
Drifts	round	19.350	19.35	assumed, equal to bore
Quadrupoles q11–q33	round	19.350	19.35	assumed bore
Extraction kicker	rect.	15.000	10.00	assumed
Extraction septum	rect.	7.500	5.00	assumed; swept
Bends b1–b3 (curved)	rect.	30.000	10.00	assumed; gap swept
Injection septum	one-sided	1.478	5.00	blade from companion

jitter at m1: entrance beta factors (5%), centroid position 0.5 mm, angle 0.2 mrad and momentum 0.1%, the latter carried by the entrance dispersion. These levels are modelling assumptions, identical to the earlier revision and to the booster jitter of the companion NKM study; their sensitivity is examined in Section 4.5.

Static trajectory errors are corrected as in commissioning. Combined horizontal and vertical thin correctors are placed before q11, q21, q31 and the injection septum, and monitors after each quadrupole and at the line end. Each machine's monitor readings of the zero-input trajectory include a static 50 micrometre rms error (offset and calibration residual). The kicks minimise the weighted readings (end monitor weight 3) with the response of the error-free model line, Tikhonov-regularised and limited to ± 1 mrad, in two passes. The correction uses no knowledge of the actual errors and does not act on shot jitter. After the first run this declared layout was amended, with a corrector before b3 and a monitor at the injection-septum entrance (Section 4.2); both layouts are reported. Every machine is evaluated uncorrected and corrected on identical particles.

3 Physical criterion, validation and comparison protocol

3.1 Active restrictions and boundary-fixed clearances

The two end stations sit where the optics are fixed by boundary data: the entrance Twiss functions and dispersion are inputs, and every admissible setting matches the exit to its target. For a centred nominal beam the clearance there is therefore $c_u = a - 5\sqrt{\epsilon_u \beta_u + D_u^2 \sigma_\delta^2}$ with the boundary values of Table 1, for every quadrupole setting K that satisfies the match. With $a = 19.35$ mm this gives 17.455/18.865 mm at the entrance and 18.555/19.064 mm at the exit (x/y), exactly the values found numerically for both settings in the four-station model (Supplement). The two interior stations have 30 mm halfwidths and could limit only if a five-sigma size exceeded about 12.5 mm, which no matched setting approaches. In this four-station model the nominal minimum clearance is thus analytically independent of K: the "saturation" of the minimum is a consequence of placing restrictions only where the optics are fixed, not a finding about the optics. Under errors, the only K-dependent part of the end-station clearances is the response of the centroid at the exit to errors and jitter. The same holds for any restriction upstream of q11 or downstream of q33: there the optics are fixed by the boundary data, so only the trajectory response can depend on K.

At a single symmetric active station away from $\bar{u} = 0$, the local sensitivity is

$$\frac{\partial c_u}{\partial K_j} = -\operatorname{sgn}(\bar{u}) \frac{\partial \bar{u}}{\partial K_j} - \frac{5}{2\sigma_u} \frac{\partial \Sigma_{uu}}{\partial K_j}. \tag{3}$$

Switching restrictions or crossing zero centroid makes this expression piecewise. In an uncoupled plane $\Sigma_{uu} = \epsilon_u \beta_u + D_u^2 \sigma_\delta^2$; our coupled calculation retains the complete covariance. Reducing

beta controls one size contribution, not necessarily dispersion or orbit sensitivity. We export these variances and centroids separately, adding variances rather than RMS sizes.

3.2 Jitter transfer between matched ends

Because both ends are matched, the horizontal transfer matrix from m1 to m4 is

$$M_x = B_4 R(\mu_x) B_1^{-1}, \qquad B = \begin{pmatrix} \sqrt{\beta} & 0 \\ -\alpha/\sqrt{\beta} & 1/\sqrt{\beta} \end{pmatrix}, \tag{4}$$

with $R(\mu_x)$ a rotation by the horizontal phase advance and $B_{1,4}$ the boundary Twiss values of Table 1. A shot centroid at m1 with covariance J (position 0.5 mm, angle 0.2 mrad) therefore reaches the exit with covariance $M_x J M_x^{\mathsf{T}}$ plus the momentum term $\sigma_{\delta,j}^2 \mathbf{d}_4 \mathbf{d}_4^{\mathsf{T}}$, which is the same for every matched setting. The quadrupoles influence the exit jitter only through μ_x. Over a full period the exit position spread ranges from 0.26 to 0.95 mm and the angle spread from 0.12 to 0.41 mrad, in opposite phase (Fig. 4, left): a matched line can move booster jitter between position, which the septum blade sees, and angle, which the injection kicker sees, but cannot remove it. Steered static errors add a small residual (Section 4.2).

3.3 Loss-based observable and design

For a Gaussian projection with centroid $\bar{u}$ and rms size σ at an aperture with edges $a_\pm$, the lost fraction is

$$P = \Phi\left(\frac{a_- - \bar{u}}{\sigma}\right) + \Phi\left(\frac{\bar{u} - a_+}{\sigma}\right), \tag{5}$$

with Φ the standard normal distribution function. Per shot, the line loss is bracketed by the largest single-aperture P and the union bound; we report the former as the prediction. When the centroid is itself Gaussian, as for linearly transported jitter, the shot-averaged lost fraction is Eq. (5) with the summed covariance of beam and jitter. This makes a smooth, loss-relevant objective. The loss-based setting minimises the logarithm of the largest shot-averaged P on the error-free line, subject to the six exit equalities, horizontal peak beta ≤ 60 m (16 subdivisions, checked at 64) and the strength bounds, with SLSQP (200 iterations, tolerance 10^{-10}) from the reference, the refined low-beta setting and the best member of a bounded multistart pool. The setting is frozen before a fresh test on 200 steered machines (seeds 92001–92004), evaluated with tracked particles.

3.4 Accuracy and spatial observation resolution

Exact independent hard-edge maps are checked against AT tracking at every element boundary. The original ten-step integrator misses its 2×10^{-6} nominal maximum-entry tolerance. Twenty/forty/eighty steps give discrepancies 2.53×10^{-7}, 1.58×10^{-8} and 9.89×10^{-10}; new studies use forty. Transverse symplectic discrepancy is 1.22×10^{-15}, without a longitudinal six-dimensional certificate. Translations, rolls and fixed-geometry dipole-field perturbations are exercised independently. Momentum errors enter particle δ without double rescaling magnet fields.

The original affine error maps omit chromatic derivatives about displaced trajectories. Comparing all 600 original shots with AT Jacobians expanded about the actual centroid changes station clearances by up to 78.43 micrometres, but shifts the paired mean by only -0.155 micrometres. Eight reference and three alternative active-station classifications change. The original mean 14.61 micrometres and interval $[-17.91, +48.32]$ become 14.45 and $[-17.88, +48.10]$; the unresolved-benefit conclusion persists. New comparisons use centred AT maps. Moment probes are uncensored by aperture limits, so propagated moments describe the incoming distribution rather than a survivor-biased subset.

Representative simultaneous-error cases compare probe steps 10^{-6}–10^{-8} and forty/eighty integration steps. Their clearance changes are below 5×10^{-6} micrometres. Product Gauss–Hermite quadrature at orders three, five and seven propagates the unrestricted Gaussian through nonlinear AT; five/seven convergence is negligible on the checked cases. Centred-linear versus nonlinear-moment discrepancy is at most 0.606 micrometres on four original extreme or representative shots and 0.6858 micrometres on two new machines for every regime/design. These finite-case checks are smaller than the reported effect intervals and illustrative 0.1 mm decision scale; they are not universal error bounds or Gaussian loss-tail certificates. Intentional scraping verifies first-loss accounting. Detailed checks are supplied in the supplement/evidence.

Spatial observation is refined independently of integration steps. Exact maps sample each finite element at 8, 16, 32 and 64 subdivisions, applying bend edges only once. Original reference boundary peaks 31.44/50.75 m become 31.63/51.27 m; old low-beta peaks 33.58/28.18 m become 33.77/28.50 m. Reoptimizing vertical peak beta on sixteen subdivisions converges in 34 SLSQP iterations. The resulting 64-subdivision peaks are 33.79/28.44 m; changes from 32 subdivisions are below 0.00035 m. These are spatially converged sampled maxima, not exact analytical extrema or a global optimum. q32 remains at its assumed lower bound -3 m^{-2}.

4 Results

4.1 Active restrictions of the element-wise line

Figure 2 shows the reference and refined low-beta optics, and Fig. 3 the nominal five-sigma clearance at every aperture. The active restriction is the injection-septum channel at the blade: 0.648 mm at the septum entrance and 0.683 mm at its exit, identical for both settings because the septum lies downstream of q33. The next restrictions are the extraction septum (4.44 mm vertically, 5.73 mm horizontally), again upstream of every quadrupole. The closest interior restriction is the vertical gap of b2, with 9.12 and 9.32 mm for the reference and low-beta settings. Sweeping the bend half-gap (7.5–12.5 mm) or the extraction-septum halfwidth (5–10 mm) does not change the minimum; the blade distance sets it directly (0.17, 0.648, 1.17 and 2.17 mm for 1, 1.478, 2 and 3 mm). In nominal terms the interior optics, including the 45% lower vertical beta peak, therefore change only clearances of order 9 mm or more; whatever the quadrupoles can do for the limiting restriction must act through the response of the trajectory to errors and jitter.

4.2 Trajectory correction

Table 3 compares the uncorrected and corrected lines on 200 machines with three shots of 2 000 particles each (seeds 91001–91004); every setting and steering variant sees the same machines, shots and particles. Without correction the static errors displace the exit centroid by 1.2 mm rms, and 10.08% of the particles are lost, almost all on the blade. The declared correction layout (correctors before q11, q21, q31 and the septum) reduces the exit position spread to 691 micrometres and the loss to 2.39%, but its last corrector, 1 m upstream of the exit, buys position with angle: the exit-angle spread grows from 364 to 535 microradians. We therefore amended the layout after this first run, adding a corrector before b3 and a monitor at the septum entrance so that position and angle at the septum are both measured and steered; the amendment is recorded in the protocol and the declared layout is reported alongside. With it the exit spreads are 683 micrometres and 337 microradians, the loss falls to 1.60% (1.56% for the low-beta setting), and the rms kick is 89 microradians. All later results use the amended layout.

Two observations matter for the design question. First, after correction the exit centroid spread, about 0.68 mm and 0.34 mrad, is that of the booster jitter alone, and it sets the remaining blade loss. Second, the mean minimum clearance does not rank the variants by loss: the uncorrected line has the largest mean clearance (0.584 mm against 0.528 mm) and six times the loss, because a static offset away from the one-sided blade raises the mean while offsets towards it are lost.




Figure 2: Reference and refined low-beta profiles drawn with Accelerator Toolbox linear-optics plotting, using the entrance Twiss parameters and 64 spatial subdivisions per finite element. The exit match remains fixed; the vertical improvement also changes horizontal transport.




Figure 3: Nominal five-sigma clearance at every aperture of the element-wise line (logarithmic scale), horizontal (top) and vertical (bottom), for the reference and refined low-beta settings. The two settings coincide at both septa; they differ only where clearances exceed 9 mm. Design beam, no errors.

Table 3: Steering on 200 machines (3 shots, 2 000 particles each). $\bar{c}_{\min}$ is the mean minimum five-sigma clearance, Lost the tracked particle-loss fraction, Predicted the mean Gaussian loss probability of the most loss-prone aperture, Blocks the number of machines with any observed loss, and x_{rms}, x'_{rms} the rms exit centroid over shots.

Setting	Steering	$\bar{c}_{\min}$ [mm]	Lost [%]	Predicted [%]	Blocks	x_{rms} [mm]	x'_{rms} [mrad]
Ref.	none	0.584	10.08	10.04	74	1.20	0.36
Low beta	none	0.556	10.01	10.01	79	1.20	0.38
Ref.	declared	0.469	2.39	2.38	54	0.69	0.54
Low beta	declared	0.453	2.44	2.44	54	0.68	0.54
Ref.	amended	0.528	1.60	1.61	49	0.68	0.34
Low beta	amended	0.523	1.56	1.57	42	0.67	0.35

The Gaussian loss prediction, by contrast, agrees with the tracked loss within 0.6% (relative) in every row. The reference and low-beta settings are indistinguishable in every column.

4.3 Reachable phase advance and the loss-based setting

Bounded least-squares matching from 360 random starts finds 349 matched settings within the strength bounds. Their horizontal phase advance spans only 200.2–232.0 degrees: the exit match, with its dispersion targets and the bend layout, pins μ_x to an interval in which booster jitter falls largely on the exit position. The reference (211.8 degrees) and low-beta (210.8 degrees) settings lie near its middle. Within the interval the predicted shot-averaged blade loss varies by more than a factor of ten (Fig. 4, right) and decreases monotonically towards the lower edge.

The loss-based search ends at that edge, $\mu_x = 200.2$ degrees. All three SLSQP starts reach the 200-iteration limit; only the start from the best pool member is feasible, and it improves that member by 1.0%. The setting is therefore a feasible point at the boundary of the reachable interval, not a certified optimum. Its predicted shot-averaged loss is 0.27% against 1.28% for the reference, because its exit position jitter is 506 instead of 643 micrometres (Table 4).

Table 4: Frozen settings and their fresh test (200 steered machines, 3 shots, 2 000 particles each). μ_x: horizontal phase advance; $\hat{\beta}$: larger peak beta; $\sigma_{x,j}$, $\sigma_{x',j}$: exit jitter from Eq. (4); $\bar{P}$: shot-averaged loss on the error-free line; Lost and Pred.: tracked and predicted loss on the test machines; Blocks: machines with any loss.

Setting	μ_x [deg]	$\hat{\beta}$ [m]	$\sigma_{x,j}$ [mm]	$\sigma_{x',j}$ [mrad]	$\bar{P}$ [%]	Lost [%]	Pred. [%]	Blocks
Ref.	211.8	51.3	0.643	0.327	1.28	2.32	2.34	59
Low beta	210.8	33.8	0.631	0.331	1.16	2.15	2.16	55
Loss-based	200.2	48.1	0.506	0.368	0.27	0.66	0.66	32

On the fresh machines the tracked loss is 2.32%, 2.15% and 0.66% for the reference, low-beta and loss-based settings, each within 1% of its prediction. The loss-based setting changes the loss by -1.66 percentage points against the reference (pointwise 95% machine-cluster interval [-2.42, -0.99]), a factor of 3.5; low beta changes it by -0.17 [-0.38, +0.02], unresolved. Its mean minimum clearance changes by only -0.013 mm [-0.030, +0.005], also unresolved: the quantity used in the earlier revision cannot see this loss reduction. The price is an exit angle jitter larger by 13% (368 against 327 microradians), which the injection kicker must accept. The loss is concentrated in shots whose entrance jitter is two to three standard deviations: the five worst of the 200 reference test machines contribute 39% of its loss, the worst losing 51% per shot on average. The machine-cluster intervals account for this heavy tail, and the population mean differs between independently seeded populations (Section 4.5).




Figure 4: Left: rms exit position (solid, mm) and angle (dashed, mrad) jitter from Eq. (4) versus horizontal phase advance, with the reachable intervals for the configured exit (blue) and a dispersion-free exit (orange; its momentum term differs slightly). Right: predicted shot-averaged blade loss of every matched solution (grey) and of the three settings (circles), with the tracked loss on steered test machines (crosses), which also include static residuals.

4.4 Exit target and dispersion

At m4 the configured target gives the injected beam an rms divergence of 76 microradians: 57 from the betatron emittance and 50 from $D'_x\sigma_\delta$. The 0.1% shot energy jitter adds a centroid angle of 47 microradians and a position of 81 micrometres rms. Both terms are fixed by the target, the same for every matched setting, and absent for a dispersion-free exit.

Matching the same Twiss functions with $D_x = D'_x = 0$ at m4 is feasible within the strength bounds: all 115 solutions from 120 bounded random starts keep both peak betas below 60 m (smallest larger peak 26.3 m). The dispersion-free target also widens the reachable phase advance to 187.7–214.2 degrees (Fig. 4), which includes phases where booster jitter falls mainly on the exit angle. The best of these solutions ($\mu_x = 187.7$ degrees, peak betas 31.4/48.2 m) has a shot-averaged blade loss of 4.1×10^{-5}, 65 times below the loss-based setting with the configured target. Its exit jitter is 350 micrometres and 394 microradians, and the beam divergence falls to 57 microradians. These numbers are analytic, from the same Gaussian model whose predictions agreed with tracking within 1% above; the dispersion-free settings were not tracked on test machines.

The exit target is thus the BTS design quantity with the largest leverage on injection. Removing the exit dispersion lowers the injected beam's divergence by a quarter and lets the line put booster jitter where the septum blade does not see it, but the angle jitter, 394 microradians against 327 for the reference, then arrives at the injection kicker. In the companion study the kicker's 80% angular acceptance is 0.44 mrad, and booster angle jitter is the only significant driver of capture among the sampled errors; whether the trade favours the blade or the kicker must be decided with the ring, not within the line.

4.5 Sensitivity to the assumed error levels

The 0.5 mrad rms quadrupole roll is large for a transfer line, and 0.1% rms shot energy jitter is at the high end of booster performance. Table 5 repeats the steered evaluation with rolls of 0.1, 0.2 and 0.5 mrad and energy jitter of 0.05 and 0.1% on another 200 independently seeded machines (analytic loss and clearance, no particle tracking). The roll level changes the predicted loss by at most 0.000 percentage points: rolls couple a small part of the horizontal motion into the vertical

plane, whose restrictions keep several millimetres of clearance, and leave the horizontal blade loss unchanged. Halving the energy jitter lowers the reference loss from 1.47% to 1.44%, because its 81 micrometre exit contribution is small compared with the betatron jitter. The ranking of the settings is the same at every level. On this population the loss-based setting is 8.4 times below the reference, against 3.5 on the tracked test population: the size of the gain depends on the sampled machines, as expected for a heavy-tailed loss, while its sign does not.

Table 5: Sensitivity of the steered line to the roll and energy-jitter levels: mean predicted loss and mean minimum five-sigma clearance on 200 machines with three shots each (seeds 93001–93004; analytic, not tracked).

Roll	$\sigma_{\delta,j}$	Predicted loss [%]			$\bar{c}_{\min}$ [mm]	
[mrad]	[%]	Ref.	Low beta	Loss-based	Ref.	Loss-based
0.1	0.05	1.44	1.34	0.18	0.516	0.511
0.1	0.10	1.47	1.38	0.18	0.515	0.509
0.2	0.05	1.44	1.34	0.18	0.516	0.511
0.2	0.10	1.47	1.38	0.18	0.515	0.509
0.5	0.05	1.44	1.34	0.18	0.516	0.511
0.5	0.10	1.47	1.38	0.18	0.515	0.509

5 Discussion and conclusions

In a BTS line matched at both ends, the beam size at the ends is fixed and so is the nominal clearance of every restriction outside the quadrupole section. With the companion blade geometry the injection septum is that restriction, and it limits the line by an order of magnitude more than any interior aperture. Lowering the interior peak beta, the usual design heuristic, therefore changes only clearances of several millimetres and, on fresh steered machines, leaves the loss unchanged.

The quadrupoles act on the loss through the trajectory. Static errors are removed by correction, provided the steering controls angle as well as position at the septum: a layout that corrected position alone traded it for exit-angle error. What remains is booster shot jitter, and for matched ends its arrival at the exit depends only on the horizontal phase advance. The line chooses whether the jitter appears as position at the blade or as angle at the injection kicker, but it cannot remove it. For the configured exit, matched solutions reach only a 32 degree interval of phase advance, and the best setting in it reduces the blade loss 3.5-fold at 13% more angle jitter. A dispersion-free exit widens the interval and lowers the predicted loss much further, again at the cost of angle jitter. The choice between blade loss and injection-angle jitter belongs to the injection design as a whole: for the companion kicker, whose 80% angular acceptance is 0.44 mrad, exit-angle jitter of 0.33–0.39 mrad is of the same order, so the trade must be evaluated with ring capture, and the booster's angle stability bounds what either choice can achieve.

Two methodological points carry over. The mean minimum five-sigma clearance used in the earlier revision does not rank settings by loss: it rewards static offsets away from a one-sided restriction and is blind to the jitter tail. A Gaussian loss probability from the propagated centroid and covariance agrees with tracked losses within 1%, is smooth, and can be optimised directly. The phase-advance view also gives a quick test for any matched transfer line: compute μ_x, read off where the booster jitter lands, and compare with the restriction and the kicker acceptance.

All aperture dimensions except the blade position, the corrector and monitor layout, the steering amendment and the error levels are declared assumptions; sweeps and a sensitivity study bound their influence on these conclusions. The loss is heavy-tailed over machines and its population mean varies between independently seeded populations, while the ranking of settings does not. The dispersion-free results are analytic. This paper neither certifies real transmission

nor derives construction tolerances, ring capture or kicker transparency; the earlier four-station analysis and historical statistics are preserved in the supplement.

Statements and Declarations

Funding. Funding information will be supplied by the author before submission.

Competing interests. The author declares no competing interests.

Acknowledgments. Author-supplied acknowledgments are pending before submission.

Author contribution. Chong Shik Park is responsible for scientific interpretation and final article approval; final approval is pending.

Generative assistance. Generative AI assistance (OpenAI Codex and Anthropic Claude through Claude Code) was used for software, numerical execution, literature checking and manuscript drafting beyond copy editing, as in the companion NKM study. The author must validate and approve the final work.

Data and code availability. A local referee attachment supplies selected raw data, configurations, source snapshots, environment identities, hashes and reproduction commands. It has not been publicly deposited or sent to a journal; reviewer delivery and final availability wording remain author actions.

A Evidence and supplementary material

The round-three study (element-wise apertures, steering, phase-advance pools, loss-based setting, fresh test, exit target and sensitivity) is in results/bts_journal_campaign_r3_20261015, one directory per stage, each with its configuration, source hashes and the protocol declared before the campaigns (round3_protocol.json, including the recorded steering amendment). The supplement preserves the four-station study, historical matching/optical statistics, block-loss inference and numerical limitations. Reviewed and original campaign identities, all previous reports, new frozen designs, station decompositions and point-by-point responses are included in the local attachment. The separate nominal phase-space diagnostic supplies initial and final particle coordinates, geometric slopes, seed and generating-source identity. Each numerical stage records source hashes and uses a fresh result directory. The first invalid shared-aperture run is retained as a failure record, not selected evidence. Technical validation does not imply journal acceptance.

References

[1] R. Hettel. DLSR design and plans: an international overview. *J. Synchrotron Rad.*, 21:843–855, 2014. https://doi.org/10.1107/S1600577514011515.

[2] J. Kim, G. Jang, J. Kim, J. Lee, and J. Seok. The Korea-4GSR storage ring lattice design. In *Proc. 16th Int. Particle Accelerator Conf. (IPAC'25)*, pages 789–792, Taipei, Taiwan, 2025. https://doi.org/10.18429/JACoW-IPAC2025-MOPS089.

[3] Y. Lee, E.-S. Kim, S. H. Park, S. Shin, and J. Kim. Study on beam injection and ramping efficiency for Korea-4GSR booster synchrotron. In *Proc. 15th Int. Particle Accelerator Conf. (IPAC'24)*, pages 1025–1028, Nashville, TN, USA, 2024. paper TUPC12; https://doi.org/10.18429/JACoW-IPAC2024-TUPC12.

[4] J. Kallestrup and V. Schlott. Beam control and characterization of the new SLS 2.0 booster-to-ring transfer line. In *Proc. IPAC'25*, 2025. https://proceedings.jacow.org/ipac2025/pdf/TUPM056.pdf.

[5] ESRF. EBS Storage Ring Technical Report. Technical report, 2018. Accessed 13 October 2026; pp. 285–286, Fig. 9.19; https://www.esrf.fr/files/live/sites/www/files/com%20photos/About%20Us/EBS-TECHREPORT-reduced.pdf.

[6] X. R. Resende, M. B. Alves, F. H. de Sá, L. Liu, A. C. S. Oliveira, and J. V. Quentino. Sirius injection optimization. In *Proc. IPAC'22*, pages 2672–2674, 2022. https://proceedings.jacow.org/ipac2022/papers/thpopt038.pdf.

[7] S. C. Leemann. Pulsed sextupole injection for Sweden's new light source MAX IV. *Phys. Rev. ST Accel. Beams*, 15:050705, 2012. https://doi.org/10.1103/PhysRevSTAB.15.050705.

[8] A. Terebilo. Accelerator modeling with MATLAB accelerator toolbox. In *Proc. 2001 Particle Accelerator Conf. (PAC'01)*, pages 3203–3205, Chicago, IL, USA, 2001. paper RPAH314.

[9] W. Rogers, N. Carmignani, L. Farvacque, and B. Nash. pyAT: A python build of accelerator toolbox. In *Proc. 8th Int. Particle Accelerator Conf. (IPAC'17)*, pages 3855–3857, Copenhagen, Denmark, 2017. https://doi.org/10.18429/JACoW-IPAC2017-THPAB060.