

```
str1 ++ str2
```

Any two lists can be concatenated this way.  
Strings are just lists of characters.

$\neq$  and unary not

```
if bool then expr1 else expr2
```

The `else` clause is required, to ensure an interesting result for the whole `if` expression.

... strict.

`:t expr` shows a value's type in `ghci`.

`:set +t` makes it permanent for that session.

The optional type declaration and the function declaration.

```
module MyMath where
```

```
  my_max :: Integer -> Integer -> Integer
```

```
  my_max x y = if x > y then x else y
```

- Multiple function definitions using pattern-matching parameters.
- Guards.



Delay the equals sign, splitting up the argument lists.

```
func args  
    | boolean1 = ...  
    | boolean2 = ...
```

`otherwise` is an alias for `true`, often used as the last guard.

Tuples use round parens, lists use brackets.

You can do it explicitly with parens and parameters, or with the dot notation:

```
composedFunc arg = secondToApply (firstToApply arg)  
composedFunc = secondToApply . firstToApply
```

length coll

[start ..]	--infinite list
[start .. end]	--default increment of 1
[start, second .. end]	--uses second to show increment

```
[expr | genOrFilter1, ..., genOrFilterN]
```

Filters are boolean expressions.

Generator form:

```
bindingForm <- collection
```

\param1 ... paramN -> body

You can append an indented `where` clause.



Just don't give a function all its arguments. No special syntax is required.

```
data NewType = Val1 | Val2 | ... | ValN
```

```
type NewType = OldType
```

```
type NewType = (Type1, ..., TypeN)
```

```
type NewType = [SomeType]
```

**Add** deriving (Show) to the end of the constructor.  
k

They are interpreted as type variables.

A collection of function signatures that any instance of the class (a **type** not an object) must support.

```
let var1 = expr1  
    ...  
    var2 = expr2  
in result-expr
```

... a way of composing functions.

... sequential execution, control structures, managing i/o, the  
Maybe monad.