

Comp 324/424 - Client-side Web Design

Spring Semester 2017 - Week 11

Dr Nick Hayward

Contents

- Server-side considerations
- Data storage
 - *Redis*
 - *MongoDB - Part I*
- Data visualisation
 - *intro*
 - *types*

Server-side considerations - data storage

intro

- tested Node.js, created a server for hosting our files and routes with ExpressJS
 - *read JSON from the server*
 - *updated our JSON on the server-side*
- works well as long as we do not need to restart, repair, update etc our server
- data lost with restart etc...
- need to consider a persistent data storage
 - *independent from the application*
- NoSQL options such as Redis and MongoDB
- integration with Node.js

Server-side considerations - data storage

SQL or NoSQL

- common database usage and storage
 - *often thought solely in terms of SQL, or structured query language*
- SQL used to query data in a relational format
- relational databases, for example MySQL or PostgreSQL, store their data in tables
 - *provides a semblance of structure through rows and cells*
 - *easily cross-reference, or relate, rows across tables*
- a relational structure to map authors to books, players to teams...
 - *thereby dramatically reducing redundancy, required storage space...*
- improvement in storage capacities, access...
 - *led to shift in thinking, and database design in general*
- started to see introduction of non-relational databases
 - *often referred to simply as **NoSQL***
- with NoSQL DBs
 - *redundant data may be stored*
 - *such designs often provide increased ease of use for developers*
- some NoSQL examples for specific use cases
 - *eg: fast reading of data more efficient than writing*
 - *specialised DB designs*

Server-side considerations - data storage

Redis - intro

- Redis provides an excellent example of NoSQL based data storage
- designed for fast access to frequently requested data
- improvement in performance often due to a reduction in perceived reliability
 - *due to in-memory storage instead of writing to a disk*
- able to flush data to disk
 - *performs this task at given points during uptime*
 - *for majority of cases considered an in-memory data store*
- stores this data in a **key-value** format
 - *similar in nature to standard object properties in JavaScript*
- Redis often a natural extension of conventional data structures
- Redis is a good option for quick access to data
 - *optionally caching temporary data for frequent access*

Server-side considerations - data storage

Redis - installation

- On OS X, use the Homebrew package manager to install Redis

```
brew install redis
```

- Windows port maintained by the Microsoft Open Tech Group - Redis
 - or use Windows package manager - <https://chocolatey.org/>
- for Linux - download, extract, and compile Redis

```
$ wget http://download.redis.io/releases/redis-3.0.5.tar.gz
$ tar xzf redis-3.0.5.tar.gz
$ cd redis-3.0.5
$ make
```

Server-side considerations - data storage

Redis - server and CLI

- start the Redis server with the following command,

```
redis-server
```

- interact with our new server directly using the CLI tool,

```
redis-cli
```

- store some data in Redis using the set command
 - create a new key for *notes*, and then set its value to *0*
 - if value is set, Redis returns *OK*

```
set notes 0
```

- retrieve a value using the get command
 - returns our set value of *0*

```
get notes
```

Image - Client-side and server-side computing

```
Drs-MacBook-Air-2:~ ancientlives$ redis-cli
127.0.0.1:6379> set notes 0
OK
127.0.0.1:6379> get notes
"0"
127.0.0.1:6379> █
```

Redis CLI - set and get

Server-side considerations - data storage

Redis - server and CLI

- also manipulate existing values for a given key
 - eg: *increment and decrement a value, or simply delete a key*
- increment key notes value by 1

```
incr notes
```

- decrement key notes value by 1

```
decr notes
```

- we can then increment or decrement by a specified amount

```
// increment by 10
incrby notes 10
// decrement by 5
decrby notes 5
```

- delete our key

```
// single key deletion
del notes
// multiple keys deletion
del notes notes2 notes3
```

Image - Client-side and server-side computing

```
Drs-MacBook-Air-2:~ ancientlives$ redis-cli
127.0.0.1:6379> set notes 0
OK
127.0.0.1:6379> get notes
"0"
127.0.0.1:6379> incr notes
(integer) 1
127.0.0.1:6379> incr notes
(integer) 2
127.0.0.1:6379> get notes
"2"
127.0.0.1:6379> decr notes
(integer) 1
127.0.0.1:6379> get notes
"1"
127.0.0.1:6379> incrby notes 10
(integer) 11
127.0.0.1:6379> get notes
"11"
127.0.0.1:6379> decrby notes 5
(integer) 6
127.0.0.1:6379> get notes
"6"
```

Redis CLI - increment and decrement

Server-side considerations - data storage

Redis and Node.js setup

- test Redis with our Node.js app
- new test app called 424-node-redis1

```
| - 424-node-redis1
|   | - app
|   |   | - assets
|   | - node_modules
|   - package.json
| - server.js
```

- create new file, `package.json` to track project
 - eg: *dependencies, name, description, version...*

Server-side considerations - data storage

Redis and Node.js - package.json

```
{
  "name": "424-node-redis1",
  "version": "1.0.0",
  "description": "test app for node and redis",
  "main": "server.js",
  "dependencies": {
    "body-parser": "^1.14.1",
    "express": "^4.13.3",
    "redis": "^2.3.0"
  },
  "author": "ancientlives",
  "license": "ISC"
}
```

- we can write the `package.json` file ourselves or use the interactive option

```
npm init
```

- then add extra dependencies, eg: Redis, using

```
npm install redis --save
```

- use `package.json` to help with app management and abstraction...

Server-side considerations - data storage

Redis and Node.js - set notes value

- add Redis to our earlier test app
- import and use Redis in the `server.js` file

```
...  
var express = require("express"),  
    http = require("http"),  
    bodyParser = require("body-parser"),  
    jsonApp = express(),  
    redis = require("redis");  
...
```

- create client to connect to Redis from Node.js

```
//create client to connect to Redis  
redisConnect = redis.createClient();
```

- then use Redis, for example, to store access total for notes on server

```
redisConnect.incr("notes");
```

- check Redis command line for change in notes value

```
get notes
```

Server-side considerations - data storage

Redis and Node.js - get notes value

- now set the counter value for our notes
 - *add our counter to the application to record access count for notes*
- use the get command with Redis to retrieve the incremented values for the notes key

```
redisConnect.get("notes", function(error, notesCounter) {  
    //set counter to int of value in Redis or start at 0  
    notesTotal.notes = parseInt(notesCounter,10) || 0;  
});
```

- get accepts two parameters - error and return value
- Redis stores values and strings
 - *convert string to integer using `parseInt()`*
 - *two parameters - return value and `base-10` value of the specified number*
- value is now being stored in a global variable `notesTotal`
 - *declared in `server.js`*

```
var express = require("express"),  
    http = require("http"),  
    bodyParser = require("body-parser"),  
    jsonApp = express(),  
    redis = require("redis"),  
    notesTotal = {};
```

Server-side considerations - data storage


Redis and Node.js - get notes value

- store notes counter value in Redis
- create new route in `server.js`
 - *monitor the returned JSON for the counter*

```
//json get route
jsonApp.get("/notesTotal.json", function(req, res) {
  res.json(notesTotal);
});
```

- start using it with our application
 - *load by default, within event handler...*
- render to DOM
- store as a internal log record
- link to create note event handler...
- DEMO - 424-node-redis I

Image - Client-side and server-side computing



Server-side considerations - data storage

MongoDB - intro

- MongoDB is another example of a NoSQL based data store
 - *a database that enables us to store our data on disk*
- unlike MySQL, for example, it is not in a relational format
- MongoDB is best characterised as a **document-oriented** database
- conceptually may be considered as storing objects in collections
- stores its data using the BSON format
 - *consider similar to JSON*
 - *use JavaScript for working with MongoDB*

Server-side considerations - data storage

MongoDB - document oriented

- SQL database, data is stored in tables and rows
- MongoDB, by contrast, uses **collections** and **documents**
- comparison often made between a collection and a table
- **NB:** a document is quite different from a table
- a document can contain a lot more data than a table
- a noted concern with this document approach is duplication of data
- one of the trade-offs between NoSQL (MongoDB) and SQL
- SQL - goal of data structuring is to normalise as much as possible
- thereby avoiding duplicated information
- NoSQL (MongoDB) - provision a data store, as easy as possible for the application to use

Server-side considerations - data storage

MongoDB - BSON

- BSON is the format used by MongoDB to store its data
- effectively, JSON stored as binary with a few notable differences
 - eg: *ObjectId* values - data type used in MongoDB to uniquely identify documents
 - created automatically on each document in the database
 - often considered as analogous to a primary key in a SQL database
- *ObjectId* is a large pseudo-random number
- for nearly all practical occurrences, assume number will be unique
- might cease to be unique if server can't keep pace with number generation...
- other interesting aspect of *ObjectId*
 - they are partially based on a timestamp
 - helps us determine when they were created

Server-side considerations - data storage

MongoDB - general hierarchy of data

- in general, MongoDB has a three tiered data hierarchy

1. database

- *normally one database per app*
- *possible to have multiple per server*
- *same basic role as DB in SQL*

2. collection

- *a grouping of similar pieces of data*
- *documents in a collection*
- *name is usually a noun*
- *resembles in concept a table in SQL*
- *documents do not require the same schema*

3. document

- *a single item in the database*
- *data structure of field and value pairs*
- *similar to objects in JSON*
- *eg: an individual user record*

Server-side considerations - data storage

MongoDB - install and setup

- install on Linux
- install on Mac OS X
 - again, we can use **Homebrew** to install MongoDB

```
// update brew packages  
brew update  
  
// install MongoDB  
brew install mongodb
```

- then follow the above OS X install instructions to set paths...
- install on Windows

Server-side considerations - data storage

MongoDB - a few shell commands

- issue following commands at command line to get started - OS X etc

```
// start MongoDB server - terminal window 1
mongod

// connect to MongoDB - terminal window 2
mongo
```

- switch to, create a new DB (if not available), and drop a current DB as follows

```
// list available databases
show dbs

// switch to specified db
use 424db1

// show current database
db

// drop current database
db.dropDatabase();
```

- DB is not created permanently until data is created and saved
 - *insert a record and save to current DB*
- only permanent DB is the local test DB, until new DBs created...

Server-side considerations - data storage

MongoDB - a few shell commands

- add an initial record to a new 424db1 database.

```
// select/create db
use 424db1

// insert data to collection in current db
db.notes.insert({
...   "travelNotes": [{
...     "created": "2015-10-12T00:00:00Z",
...     "note": "Curral das Freiras..."
...   }]
... })
```

- our new DB 424db1 will now be saved in Mongo
- we've created a new collection, notes

```
// show databases
show dbs

// show collections
show collections
```

Server-side considerations - data storage

MongoDB - test app

- now create a new test app for use with MongoDB
- create and setup app as before
 - *eg: same setup pattern as Redis test app*
- add **Mongoose** to our app
 - *use to connect to MongoDB*
 - *helps us create a schema for working with DB*
- update our `package.json` file
 - *add dependency for Mongoose*

```
// add mongoose to app and save dependency to package.json  
npm install mongoose --save
```

- test server and app as usual from app's working directory

```
node server.js
```


Server-side considerations - data storage

MongoDB - Mongoose schema

- use **Mongoose** as a type of bridge between Node.js and MongoDB
- works as a client for MongoDB from Node.js applications
- serves as a useful data modeling tool
 - *represent our documents as objects in the application*
- a data model
 - *object representation of a document collection within data store*
 - *helps specify required fields for each collection's document*
 - *known as a schema in Mongoose, eg: `NoteSchema`*

```
var NoteSchema = mongoose.Schema({  
  "created": Date,  
  "note": String  
});
```

- using schema, build a model
 - *by convention, use first letter uppercase for name of data model object*

```
var Note = mongoose.model("Note", NoteSchema);
```

- now start creating objects of this model type using JavaScript

```
var funchalNote = new Note({  
  "created": "2015-10-12T00:00:00Z",  
  "note": "Curral das Freiras..."  
});
```

- then use the Mongoose object to interact with the MongoDB
 - *using functions such as `save` and `find`*

Server-side considerations - data storage

MongoDB - test app

- with our new DB setup, our schema created
 - *now start to add notes to our DB, 424db1, in MongoDB*
- in our `server.js` file
 - *need to connect Mongoose to 424db1 in MongoDB*
 - *define our schema for our notes*
 - *then model a note*
 - *use model to create a note for saving to 424db1*

```
...  
  
//connect to 424db1 DB in MongoDB  
mongoose.connect('mongodb://localhost/424db1');  
  
//define Mongoose schema for notes  
var NoteSchema = mongoose.Schema({  
  "created": Date,  
  "note": String  
});  
  
//model note  
var Note = mongoose.model("Note", NoteSchema);  
  
...
```

Server-side considerations - data storage

MongoDB - test app

- then update app's post route to save note to 424db1

```
//json post route - update for MongoDB
jsonApp.post("/notes", function(req, res) {
  var newNote = new Note({
    "created":req.body.created,
    "note":req.body.note
  });
  newNote.save(function (error, result) {
    if (error !== null) {
      console.log(error);
      res.send("error reported");
    } else {
      Note.find({}, function (error, result) {
        res.json(result);
      })
    }
  });
});
```

Server-side considerations - data storage

MongoDB - test app

- update our app's get route for serving these notes


```
//json get route - update for mongo
jsonApp.get("/notes.json", function(req, res) {
  Note.find({}, function (error, notes) {
    //add some error checking...
    res.json(notes);
  });
});
```

- modify buildNotes () function in json_app.js to get return correctly

```
...
//get travelNotes
var $travelNotes = response;
...
```

- now able to enter, save, read notes for app
- notes data is stored in the 424db1 database in MongoDB
- notes are loaded from DB on page load
- notes are updated from DB for each new note addition
- DEMO - 424-node-mongo I

Image - Client-side and server-side computing



Data visualisation

intro - part I

- data visualisation - study of how to visually communicate and analyse data
- covers many disparate aspects
 - *including infographics, exploratory tools, dashboards...*
- already some notable definitions of data visualisation
- one of the better known examples,

"Data visualisation is the representation and presentation of data that exploits our visual perception in order to amplify cognition."

(Kirk, A. "Data Visualisation: A successful design process." Packt Publishing. 2012.)

- several variants of this general theme exist
 - *the underlying premise remains the same*
- simply, data visualisation is a visual representation of the underlying data
- visualisation aims to impart a better understanding of this data
 - *by association, its relevant context*

Data visualisation

intro - part 2

- an inherent flip-side to data visualisation
- without a correct understanding of its application
 - *it can simply impart a false perception, and understanding, on the dataset*
- run the risk of creating many examples of standard **areal unit** problem
 - *perception often based on creator's base standard and potential bias*
- inherently good at seeing what we want to see
- without due care and attention visualisations may provide false summations of the data

Data visualisation

types - part I

- many different ways to visualise datasets
 - *many ways to customise a standard infographic*
- some standard examples that allow us to consider the nature of visualisations
 - *infographics*
 - *exploratory visualisations*
 - *dashboards*
- perceived that data visualisation is simply a variation between
 - *infographics, exploratory tools, charts, and some data art*

I. infographics

- *well suited for representing large datasets of contextual information*
- *often used in projects more inclined to exploratory data analysis,*
- *tend to be more interactive for the user*
- *data science can perceive infographics as improper data visualisation because*
- *they are designed to guide a user through a story*
- *the main facts are often already highlighted*
- **NB:** *such classifications often still only provide tangible reference points*

Data visualisation

types - part 2

2. exploratory visualisations

- *more interested in the provision of tools to explore and interpret datasets*
- *visualisations can be represented either static or interactive*
- *from a user perspective these charts can be viewed*
- *either carefully*
- *simply become interactive representations*
- *both perspectives help a user discover new and interesting concepts*
- *interactivity may include*
- *option for the user to filter the dataset*
- *interact with the visualisation via manipulation of the data*
- *modify the resultant information represented from the data*
- *often perceived as more objective and data oriented than other forms*

3. dashboards

- *dense displays of charts*
- *represent and understand a given issue, domain...*
- *as quickly and effectively as possible*
- *examples of dashboards*
- *display of server logs, website users, business data...*

Data visualisation

Dashboards - intro

- dashboards are dense displays of charts
- allow us to represent and understand the key **metrics** of a given issue
 - *as quickly and effective as possible*
 - *eg: consider display of server logs, website users, and business data...*
- one definition of a dashboard is as follows,

"A dashboard is a visual display of the most important information needed to achieve one or more objective; consolidated and arranged on a single screen so the information can be monitored at a glance."

Few, Stephen. Information Dashboard Design: The Effective Visual Communication of Data. O'Reilly Media. 2006.

- dashboards are visual displays of information
 - *can contain text elements*
 - *primarily a visual display of data rendered as meaningful information*

Data visualisation

Dashboards - intro

- information needs to be consumed quickly
- often simply no available time to read long annotations or repeatedly click controls
- information needs to be visible, and ready to be consumed
- dashboards are normally presented as a complementary environment
- an option to other tools and analytical/exploratory options
- design issues presented by dashboards include effective distribution of available space
- compact charts that permit quick data retrieval are normally preferred
- dashboards should be designed with a purpose in mind
- generalised information within a dashboard is rarely useful
- display most important information necessary to achieve their defined purpose
- a dashboard becomes a central view for collated data
- represented as meaningful information

Data visualisation

Dashboards - good practices

- to help promote our information
 - *need to design the dashboard to fully exploit available screen space*
- need to use this space to help users absorb as much information as possible
- some visual elements more easily perceived and absorbed by users than others
- some naturally convey and communicate information more effectively than others
- such attributes are known as **pre-attentive attributes of visual perception**
- for example,
 - *colour*
 - *form*
 - *position*

Data visualisation

Dashboards - visual perception

■ pre-attentive attributes of visual perception

1. Colour

- *many different colour models currently available*
- *most useful relevant to dashboard design is the HSL model*
- *this model describes colour in terms of three attributes*
 - *hue*
 - *saturation*
 - *lightness*
- *perception of colour often depends upon context*

2. Form

- *correct use of length, width, and general size can convey quantitative dimensions*
- *each with varying degrees of precision*
- *use the Laws of Prägnanz to manipulate groups of similar shapes and designs*
- *thereby easily grouping like data and information for the user*

3. Position


- *relative positioning of elements helps communicate dashboard information*
- *laws of Prägnanz teach us*
- *position can often infer a perception of relationship and similarity*
- *higher items are often perceived as being better*
- *items on the left of the screen traditionally seen first by a western user*

Data visualisation

Building a dashboard


- need to clearly determine the questions that need to be answered
 - *given the information collated and presented within the dashboard*
- need to ensure that any problems can be detected on time
- be certain why we actually need a dashboard for the current dataset
- then begin to collect the requisite data to help us answer such questions
 - *data can be sourced from multiple, disparate datasets*
- chosen visualisations help us tell this story more effectively
- present it in a manner appealing to our users
- need to consider information visualisations familiar to our users
 - *helps reduce any potential user's cognitive overload*
- carefully consider organisation of data and information
- organise the data into logical units of information
 - *helps present dashboard information in a meaningful manner*
- dashboard sections should be organised
 - *to help highlight and detect any underlying or prevailing issues*
 - *then present them to the user*

Image - Google Analytics




Dashboard - Google Analytics

Image - Yahoo Flurry



Dashboard - Yahoo Flurry

Image - Mint



Dashboard - Mint

Demos

Redis

- `424-node-redis l`

MongoDB

- `424-node-mongo l`

References

- Chocolatey for Windows
 - *Chocolatey package manager for Windows*
- Homebrew for OS X
 - *Homebrew - the missing package manager for OS X*
- Kirk, A. *Data Visualisation: A successful design process*. Packt Publishing. 2012.
- MongoDB
 - *MongoDB - For Giant Ideas*
 - *MongoDB - Getting Started (Node.js driver edition)*
 - *MongoDB - Getting Started (shell edition)*
- Mongoose
 - *MongooseJS Docs*
- Node.js
 - *Node.js home*
 - *Node.js - download*
 - *ExpressJS*
 - *ExpressJS body-parser*
- Redis
 - *redis.io*
 - *redis commands*
 - *redis - npm*
 - *try redis*
 - *Windows support*
- W3 Selector API