

Comp 324/424 - Client-side Web Design

Spring Semester 2017 - Week 8

Dr Nick Hayward

Contents

- DEV Week presentation and demo
- DEV Week peer review
- AJAX and JSON

DEV Week presentation and demo...

brief presentation or demonstration of current project work

- ~ 5 to 10 minutes per group
- analysis of work conducted so far
 - *eg: during semester & DEV week*
- presentation, demonstration, or video overview...
 - *outline current state of web app*
 - *show prototypes and designs*
 - *explain what works & does not work*
 - *anything else considered relevant to your research or development...*

DEV Week peer review

- take notes for each presentation
- complete peer review per project presentation
 - *individually, **NOT** as a group*
- peer review **MUST** be completed this week
 - *part of this week's assignment*
- collated, anonymised results sent to each group
- carefully review peer review results
 - *consider modifications, updates...*

AJAX and JSON - part I

intro

- AJAX is a simple way to load data
 - *often new or updated data*
 - *into a current page without having to refresh the browser window*
- common form of data for work with AJAX is JSON
- many common usage scenarios and examples for AJAX
 - *autocomplete in forms*
 - *live filtering of search queries*
 - *real-time updates for content and data streams*
- also use AJAX to help us load data behind the scenes
 - *preparing content for our users before a specific request is received*
 - *helps to speed up page responses and data load times*
- AJAX uses an asynchronous model for processing requests
- user can continue to perform various tasks, queries, and work
 - *whilst the browser itself continues to load data*
- inherent benefit of AJAX should include
 - *a more responsive site, intuitive usage and interface experience*

AJAX and JSON - part 2

asynchronous model

- traditional synchronous model normally stops a page
 - *until it has loaded and processed a requested script*
- AJAX enables a browser to request data from the server
 - *without this synchronous pause in usage*
- AJAX's **asynchronous processing model**
 - *often known as **non-blocking***
 - *allows a page to load data and process user's interactions*
- server responds with the requested data
 - *an event will be fired by the browser*
 - *event can then call a function to process the data*
 - *often JSON, XML, or simply HTML*
- browser will use an **XMLHttpRequest** object to help handle these AJAX requests
- browser will not wait for a response

JSON and jQuery - get a file - part I

initial setup

- try some AJAX with a JSON file

```
{  
  "country": "France",  
  "city": "Marseille"  
}
```

- save this content to our docs/json/trips.json file
- run on a server, local or remote
 - browser security restrictions for JavaScript
 - local server such as XAMPP, Python's SimpleHTTPServer, Node.js...

```
python -m SimpleHTTPServer 8080
```

- initially use the `getJSON()` function to test reading this content

```
$.getJSON("docs/json/trips.json", function(trip) {  
  console.log(trip);  
});
```

- console output is expected JSON object

```
Object { country: "France", city: "Marseille" }
```

JSON and jQuery - get a file - part 2

test with site

- now use this return object to load our data as required within a site

```
//overall app logic and loader...
function loadJSON() {
  "use strict";

  $.getJSON("docs/json/trips.json", function(trip) {
    //element for trip data
    var $tripData = $("

");
    //add some content from json to element
    $tripData.html(trip.city + ", " + trip.country);
    //append content to .note-output section
    $(".note-output").append($tripData);
  });
};

$(document).ready(loadJSON);


```

- DEMO - AJAX I - AJAX - demo I

JSON and jQuery - get a file - part 3

array for trips...

- need to store multiple trips
 - *multiple countries, multiple cities, and so on...*
- need to work with JSON arrays
 - *update `trips.json` file for cities*

```
{  
  "cities": [  
    {  
      "name": "Marseille",  
      "region": "Provence-Alpes-Côte d'Azur"  
    },  
    {  
      "name": "Paris",  
      "region": "Île-de-France"  
    }  
  ]  
}
```

JSON and jQuery - get a file - part 4

load an array for trips...

- update JavaScript to load array and set data as required

```
//overall app logic and loader...
function loadJSON() {
  "use strict";

  $.getJSON("docs/json/trips.json", function(trips) {
    //element for trip data
    var $cityData = $("

");

    //iterate over cities array - trips.cities...
    var $cities = trips.cities;
    $cities.forEach(function (item) {
      var $city = $("- ");
      $city.html(item.name + " in the region of " + item.region);
      $cityData.append($city);
    })
    //append list to .note-output
    $(".note-output").append($cityData);
  });
};

$(document).ready(loadJSON);

```

- DEMO - AJAX 2 - AJAX - demo 2

Demos

AJAX

- DEMO 1 - AJAX - demo 1
- DEMO 2 - AJAX - demo 2

References - JS & Libraries

- jQuery
 - *jQuery*
 - *jQuery API*
 - *jQuery - .getJSON()*
- Lint options
 - *JSLint - JavaScript Validator*
 - *JSONLint - JSON Validator*
- MDN
 - *MDN - JS*
 - *MDN - JS Objects*
- W3
 - *W3 - JS Object*