

Comp 125 - Visual Information Processing

Spring Semester 2018 - week 10 - monday

Dr Nick Hayward

Fun exercise - using CSS to style HTML

using the provided HTML5 template, `index.html`

- create a new directory for your application
 - e.g. *fun-application*
- add the HTML file to this application directory
- create a new CSS stylesheet for this application
 - e.g. *style.css*
- add the following to the application's HTML file
 - a `<link>` to your CSS stylesheet
 - a `<title>` for the application
 - any other suitable metadata
- then, add the following structure to this HTML page
 - header and heading
 - image and title - any image is fine...
 - brief information about the image
 - a link to further information on the image
 - e.g. a photo of the Great Pyramid might link to an article on Wikipedia &c.
 - a `<table>` with data on the image, its content &c.
 - `<footer>` for information about the site, its developer, copyright information &c.
- add appropriate styling using the CSS stylesheet, e.g.
 - font colour, font size, font-family &c.
 - correct use of the box model for the content, e.g.
 - image and title
 - any textual data
 - links
 - custom styling for general structure and aesthetics
 - aesthetics and design are your own choice

Assignment must be submitted by Monday 26th March 2018 at 2.30pm using either GitHub or a private message to the course TA, Catherine, on Slack.

n.b. correct use of semantic elements is required.

Fun exercise - using CSS to style HTML

sample HTML5 template

```
<!DOCTYPE html>
<html>
  <head>
    <meta charset="UTF-8">
    <title>Demo 1</title>
  </head>
  <body>
    <h3>Our first web page</h3>

  </body>
</html>
```

CSS Basics - cascading rules - part I

- CSS, or cascading style sheets, employs a set of **cascading** rules
- rules applied by each browser as a ruleset conflict arises
 - e.g. issue of **specificity**

```
p {  
  color: blue;  
}  
p.p1 {  
  color: red;  
}
```

- the more specific rule, the class, will take precedence
- issue of possible duplication in rulesets

```
h3 {  
  color: black;  
}  
  
h3 {  
  color: blue;  
}
```

- **cascading** rules state the later ruleset will be the one applied
 - blue heading instead of black...

CSS Basics - cascading rules - part 2

- simple styling and rulesets can quickly become compounded and complicated
- different styles, in different places, can interact in complex ways
- a powerful feature of CSS
 - *can also create issues with logic, maintenance, and design*
- three primary sources of style information that form this cascade
 1. default styles applied by the browser for a given markup language
 - *e.g. colours for links, size of headings...*
 2. styles specific to the current user of the document
 - *often affected by browser settings, device, mode...*
 3. styles linked to the document by the designer
 - *external file, embedded, and as inline styles per element*

CSS Basics - cascading rules - part 3

- basic cascading nature creates the following pattern
 - *browser's style will be default*
 - *user's style will modify the browser's default style*
 - *styles of the document's designer modify the styles further*

CSS Basics - inheritance

- CSS includes inheritance for its styles
- descendants will inherit properties from their ancestors
- style an element
 - *descendants of that element within the DOM inherit that style*

```
body {  
  background: blue;  
}  
  
p {  
  color: white;  
}
```

- p is a descendant of body in the DOM
 - *inherits background colour of the body*
- this characteristic of CSS is an important feature
 - *helps to reduce redundancy and repetition of styles*
- useful to maintain outline of document's DOM structure
- most styles follow this pattern but not all
- margin, padding, and border rules for block-level elements **not inherited**

CSS Basics - fonts - part I

- fonts can be set for the body or within an element's specific ruleset
- we need to specify our font-family,

```
body {  
  font-family: "Times New Roman", Georgia, Serif;  
}
```

- value for the font-family property specifies preferred and fall-back fonts
 - *Times New Roman*, then the browser will try *Georgia* and *Serif*
 - " " - quotation marks for names with spaces...

n.b. " " added due to CSS validator requesting this standard - it's believed to be a legacy error with the validator...

CSS Basics - fonts - part 2

- useful to be able to modify the size of our fonts as well

```
body {  
  font-size: 100%;  
}  
  
h3 {  
  font-size: x-large;  
}  
  
p {  
  font-size: larger;  
}  
  
p.p1 {  
  font-size: 1.1em;  
}
```

- set base font size to 100% of font size for a user's web browser
- scale our other fonts relative to this base size
 - CSS absolute size values, such as *x-large*
 - font sizes relative to the current context, such as *larger*
 - *em* are meta-units, which represent a multiplier on the current font-size
 - relative to current element for required font size
 - 1.5em of 12px is effective 18px
- em font-size scales according to the base font size
 - modify base font-size, em sizes adjust
- try different examples at
 - [W3 Schools - font-size](#)

Demo - CSS Fonts

- [Demo - CSS Fonts](#)
- [JSFiddle - CSS Fonts](#)

CSS Basics - fonts - part 3

- rem unit for font sizes
- size calculated against root of document

```
body {  
  font-size: 100%;  
}  
  
p {  
  font-size: 1.5rem;  
}
```

- element font-size will be root size * rem size
 - e.g. body font-size is currently 16px
 - rem will be 16 * 1.5

References

- MDN - CSS
- CSS documentation
- cascade and inheritance
- fonts
- W3Schools - CSS
- CSS
- fonts